



MPE Test Report

Report No.: STS2512395H01

Issued for

Curv Group LLC

860 Bonnie Ln, Elk Grove Village, IL 60007, USA

Product Name: SmartCharge power bank

Brand Name: STATIK

Model Name: PUP-0430-V2

Series Model(s): PUP-0430-V2-BLK, PUP-0430-V2-WHT,
PUP-0430-V2-ORG, PUP-0430-V2-CLR

FCC ID: 2AMNT-PUP-0430

Test Standard: FCC CFR 47 part 1, 1.1310

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST RESULT CERTIFICATION**

Applicant's Name: Curv Group LLC
Address: 860 Bonnie Ln, Elk Grove Village, IL 60007, USA
Manufacturer's Name: Curv Group LLC
Address: 860 Bonnie Ln, Elk Grove Village, IL 60007, USA

Product Description

Product Name: SmartCharge power bank
Brand Name: STATIK
Model Name: PUP-0430-V2
Series Model(s): PUP-0430-V2-BLK, PUP-0430-V2-WHT, PUP-0430-V2-ORG,
PUP-0430-V2-CLR
Standards: FCC CFR 47 part 1, 1.1310
Test Procedure: KDB 680106 D01 Wireless Power Transfer v04

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test.....:

Date of receipt of test item: 18 Dec. 2025

Date of performance of tests...: 18 Dec. 2025 to 22 Dec. 2025

Date of Issue.....: 22 Dec. 2025

Test Result.....: **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)



Authorized Signatory :

Bovey Yang

(Bovey Yang)

**Table of Contents****Page**

1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACTORY	5
1.2 MEASUREMENT UNCERTAINTY	5
1.3 GENERAL DESCRIPTION OF THE EUT	6
1.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	8
1.6 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	8
2. COIL SPECIFICATIONS	9
2.1 COIL SIZE	9
2.2 LOCATION(S) – COIL TO THE OUTER SURFACE OF THE ENCLOSURE(S)	9
3. MAXIMUM PERMISSIBLE EXPOSURE	10
3.1 MEASURING STANDARD	10
3.2 REQUIREMENTS	10
3.3 TEST PROCEDURE	12
3.4 TEST SETUP	12
3.5 TEST RESULTS	13
3.6 MAXIMUM PERMISSIBLE EXPOSURE	15



Revision History

Rev.	Issue Date	Report No.	Effect Page	Contents
00	22 Dec. 2025	STS2512395H01	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainly
1	H-filed	$\pm 0.83\text{dB}$
2	E-filed	$\pm 0.91\text{dB}$



1.3 GENERAL DESCRIPTION OF THE EUT

Product Name	SmartCharge power bank
Brand	STATIK
Model Number	PUP-0430-V2
Series Model(s)	PUP-0430-V2-BLK, PUP-0430-V2-WHT, PUP-0430-V2-ORG, PUP-0430-V2-CLR
Model Difference	All models are identical except for the model names and appearance of the color, the test model is PUP-0430-V2.
Equipemnt Category	Non-ISM frequency
Antenna Type	loop coil antenna
Operating frequency	115-205kHz; 300-350kHz
Modulation Type	ASK
Power Rating	AC Input: 100~240V AC 50Hz/60Hz 0.3A(Max) TYPE-C Input: DC 5V/3A, 9V/2A, 12V/1.5 PD 18W Max TYPE-C output: DC5V/3A, 9V/2.22A, 12V/1.67A, Max 20W USB output: DC5V/3A, 9V/2A, 10V/2.25A, 12V/1.5A, Max 22.5W TYPE-C cable output: DC5V/3A, 9V/2.22A, 12V/1.67A, MAX 20W Type-C Cable 2 Output: DC5V/2A In charging AC, the product outputs 5V/2A at a maximum of 10W. In charging TYPE-C, the product output 5V/2A at a maximum of 10W. Multiple simultaneously outputs: 5V/3A Max
Adapter	N/A
Battery	10000mAh, @3.85V, 38.5Wh
Wireless charging power	15W Max(2.5W Max For Apple watch)
Hardware version number	N/A
Software version number	N/A
Connecting I/O Port(s)	Please refer to the Note 1.

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	NOTE
1	N/A	N/A	Coil	N/A	Antenna

The EUT antenna is Coil Antenna. No antenna other than that furnished by the responsible party shall be used with the device.



1.4 DESCRIPTION OF THE TEST MODES

Equipment under test was operated during the measurement under the following conditions:

Test Mode	Description	
Mode 1	AC Adapter + EUT + Load(10W, 115-205kHz) (Battery Status: < 1%)	Record
Mode 2	AC Adapter + EUT + Load(10W, 115-205kHz) (Battery Status: < 50%)	Record
Mode 3	AC Adapter + EUT + Load(10W, 115-205kHz) (Battery Status: < 99%)	Record
Mode 4	AC Adapter + EUT + Load(2.5W, 300-350kHz) (Battery Status: < 1%)	Record
Mode 5	AC Adapter + EUT + Load(2.5W, 300-350kHz) (Battery Status: < 50%)	Record
Mode 6	AC Adapter + EUT + Load(2.5W, 300-350kHz) (Battery Status: < 99%)	Record
Mode 7	USB Input + EUT + Load(10W, 115-205kHz) (Battery Status: < 1%)	Record
Mode 8	USB Input + EUT + Load(10W, 115-205kHz) (Battery Status: < 50%)	Record
Mode 9	USB Input + EUT + Load(10W, 115-205kHz) (Battery Status: < 99%)	Record
Mode 10	USB Input + EUT + Load(2.5W, 300-350kHz) (Battery Status: < 1%)	Record
Mode 11	USB Input + EUT + Load(2.5W, 300-350kHz) (Battery Status: < 50%)	Record
Mode 12	USB Input + EUT + Load(2.5W, 300-350kHz) (Battery Status: < 99%)	Record
Mode 13	EUT + Load(15W, 115-205kHz) (Battery Status: < 1%)	Record
Mode 14	EUT + Load(15W, 115-205kHz) (Battery Status: < 50%)	Pre-tested
Mode 15	EUT + Load(15W, 115-205kHz) (Battery Status: < 99%)	Pre-tested
Mode 16	EUT + Load(2.5W, 300-350kHz) (Battery Status: < 1%)	Record
Mode 17	EUT + Load(2.5W, 300-350kHz) (Battery Status: < 50%)	Pre-tested
Mode 18	EUT + Load(2.5W, 300-350kHz) (Battery Status: < 99%)	Pre-tested
Mode 19	Test the EUT in idle mode.	Pre-tested
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		



1.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Electric and Magnetic field Probe - Analyzer	Narda	EHP-200A	180ZX10220	2025.02.22	2026.02.21

1.6 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Adapter	ZTC	NB-A515A	N/A
E-2	Load	N/A	N/A	N/A
C-1	DC cable	N/A	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	0.8m	N/A


Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.

2. COIL SPECIFICATIONS

Item	Parameter
Input inductance:	L1: 6.9uH±10%
Material of enclosure(s):	Silk wrapped wire
Number of turns:	Transmitter 1: 12turns

2.1 COIL SIZE




Unit: mm

A	B	C	D2	E	H	I
43.5±1.0	13.5±0.5	0.8±0.05	50±3	4±2	2.8MAX	8±0.5

2.2 LOCATION(S) – COIL TO THE OUTER SURFACE OF THE ENCLOSURE(S)

Unit: mm

Front A	Rear B	Left C	Right D	Top E	Bottom F
20	20	30	30	2	35





3. MAXIMUM PERMISSIBLE EXPOSURE

3.1 MEASURING STANDARD

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1091 RF exposure is calculated. According KDB680106 D01: KDB 680106 D01 Wireless Power Transfer v04.

3.2 REQUIREMENTS

According to the item 3 of KDB 680106 D01v04:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

- (1) Mobile Device and Portable Device Configurations
- (2) Equipment Authorization Procedures for Devices Operating at Frequencies Below 4 MHz
- (3) The aggregate H-field strengths anywhere at or beyond 20 cm surrounding the device.

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6



Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density

Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03


Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

Note 4: The aggregate H-field strengths at 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

3.3 TEST PROCEDURE


- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (2cm increments from 0 ~ 20 cm for all sides for portable mode, 15 cm from all sides and 20 cm from the top for mobile mode) which is between the edge of the charger and the geometric edge of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E, F) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.
- 5) According to the requirements if KDB 680106 D01 v04, If the center of the probe sensing element is located more than 5mm from the probe outer surface, the field strengths need to be estimated through modeling for those positions that are not reachable. (The sensitive elements are located approximately 18.5 mm below the external surface specified in user manual of MAGPy-8H3D+E3D)
- 6) Use Biot-Savart Law, the value of 0 cm can be estimated through the results of 2 cm, according to the formula:

Top & Bottom Side:



$$B = \frac{\mu_0 * I * N * R^2}{2 * (R^2 + x^2)^{3/2}}$$

Front, left, right & rear Side:



$$B = \frac{\mu_0 * I * N}{2 * x}$$

Remark:

B: H-field (Unit:T)

μ_0 : Space permeability = $4 * \pi * 10^{-7}$


I (Unit: A): The current element passing through a radiated coil


R: Radius of radiated coil, according to the coil specification: R=0.015m

X: The distance from the sensing elements of the probe to the edge of the radiated coil (the dimensions of EUT and load are take into account), (Unit: m)

N: Turns of the radiated coil, according to the coil specification: N=15.

3.4 TEST SETUP





3.5 TEST RESULTS

The EUT does comply with item 3 KDB680106 D01 v04.



- (1) Power transfer frequency is less than 1 MHz.

Yes, The working frequency is 115kHz-205kHz and 300-350kHz.

- (2) Output power from each primary coil is less than or equal to 15 watts.

Yes, The maximum output power is 15 watts.

- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter(i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)

Yes, The maximum permitted load is placed in physical contact with the transmitter.

- (4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions)

No, the EUT is Portable condition assessment.

- (5) (5)The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios(i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.

Yes, The H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit ; coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.

- (6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time. as per design conditions, if the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered then those cases must be tested as well, For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.

Yes, For systems with single radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time.



3.6 MAXIMUM PERMISSIBLE EXPOSURE

For Mobile Mode: We measured the distance of 20cm, 22cm and 24cm, and recorded the test data of the worst 20cm.

115kHz-205kHz:

Mode 1:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 1%	Top	1.142	0.124
20cm	< 1%	Bottom	0.959	0.066
20cm	< 1%	Left	0.891	0.116
20cm	< 1%	Right	0.879	0.108
20cm	< 1%	Front	0.477	0.017
20cm	< 1%	Rear	0.446	0.028
Limit			614	1.63

Mode 2:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 50%	Top	1.066	0.111
20cm	< 50%	Bottom	0.964	0.046
20cm	< 50%	Left	0.827	0.114
20cm	< 50%	Right	0.835	0.098
20cm	< 50%	Front	0.437	0.017
20cm	< 50%	Rear	0.418	0.015
Limit			614	1.63

Mode 3:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 99%	Top	1.064	0.114
20cm	< 99%	Bottom	0.911	0.063
20cm	< 99%	Left	0.809	0.118
20cm	< 99%	Right	0.767	0.119
20cm	< 99%	Front	0.402	0.035
20cm	< 99%	Rear	0.383	0.022
Limit			614	1.63



Mode 7:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 1%	Top	1.150	0.121
20cm	< 1%	Bottom	0.951	0.058
20cm	< 1%	Left	0.889	0.113
20cm	< 1%	Right	0.868	0.106
20cm	< 1%	Front	0.484	0.018
20cm	< 1%	Rear	0.447	0.018
Limit			614	1.63

Mode 8:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 50%	Top	1.063	0.112
20cm	< 50%	Bottom	0.957	0.048
20cm	< 50%	Left	0.819	0.103
20cm	< 50%	Right	0.829	0.111
20cm	< 50%	Front	0.426	0.014
20cm	< 50%	Rear	0.404	0.021
Limit			614	1.63

Mode 9:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 99%	Top	1.053	0.113
20cm	< 99%	Bottom	0.917	0.068
20cm	< 99%	Left	0.819	0.126
20cm	< 99%	Right	0.768	0.124
20cm	< 99%	Front	0.391	0.022
20cm	< 99%	Rear	0.389	0.038
Limit			614	1.63



300kHz-350kHz

Mode 4:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 1%	Top	1.143	0.118
20cm	< 1%	Bottom	0.963	0.043
20cm	< 1%	Left	0.882	0.123
20cm	< 1%	Right	0.876	0.121
20cm	< 1%	Front	0.480	0.007
20cm	< 1%	Rear	0.441	0.018
Limit			614	1.63

Mode 5:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 50%	Top	1.054	0.107
20cm	< 50%	Bottom	0.960	0.043
20cm	< 50%	Left	0.823	0.107
20cm	< 50%	Right	0.825	0.099
20cm	< 50%	Front	0.437	0.007
20cm	< 50%	Rear	0.405	0.014
Limit			614	1.63

Mode 6:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 99%	Top	1.060	0.118
20cm	< 99%	Bottom	0.909	0.055
20cm	< 99%	Left	0.814	0.118
20cm	< 99%	Right	0.766	0.114
20cm	< 99%	Front	0.401	0.028
20cm	< 99%	Rear	0.384	0.028
Limit			614	1.63



Mode 10:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 1%	Top	1.149	0.114
20cm	< 1%	Bottom	0.961	0.069
20cm	< 1%	Left	0.889	0.109
20cm	< 1%	Right	0.873	0.118
20cm	< 1%	Front	0.475	0.014
20cm	< 1%	Rear	0.447	0.036
Limit			614	1.63

Mode 11:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 50%	Top	1.064	0.116
20cm	< 50%	Bottom	0.956	0.045
20cm	< 50%	Left	0.834	0.103
20cm	< 50%	Right	0.836	0.108
20cm	< 50%	Front	0.434	0.018
20cm	< 50%	Rear	0.406	0.024
Limit			614	1.63

Mode 12:

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 99%	Top	1.055	0.111
20cm	< 99%	Bottom	0.912	0.052
20cm	< 99%	Left	0.817	0.121
20cm	< 99%	Right	0.776	0.118
20cm	< 99%	Front	0.405	0.015
20cm	< 99%	Rear	0.375	0.038
Limit			614	1.63

Note: All test modes were pre-tested, but we only recorded the worst case in this report.



Mode 13

Note: <1%, 50%, >95% load all have been tested, only worse case Max load (<1%) is reported.

H-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, ... 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (A/m)

Battery < 1% (Worst case)

Test Distance (cm)	Test Position A (A/m)	Test Position B (A/m)	Test Position C (A/m)	Test Position D (A/m)	Test Position E (A/m)	Test Position F (A/m)	Limit (A/m)
6	0.135	0.105	0.133	0.136	0.047	0.058	1.63
8	0.125	0.1	0.125	0.132	0.021	0.024	
10	0.125	0.089	0.125	0.125	0.014	0.015	
12	0.116	0.079	0.116	0.121	0.011	0.013	
14	0.116	0.063	0.112	0.114	0.009	0.012	
16	0.108	0.054	0.11	0.107	0.008	0.01	
18	0.105	0.049	0.099	0.109	0.007	0.008	
20	0.103	0.04	0.096	0.099	0.005	0.008	

Use the Biot-Sacart Law to estimated the results of 6cm through 8cm

Test position	Measure Value (A/m)	Estimated Value (A/m)	Agreement Ratio	Limits
A	0.135	0.150	10.75%	30%
B	0.105	0.120	13.91%	30%
C	0.133	0.147	10.77%	30%
D	0.136	0.156	14.39%	30%
E	0.047	0.045	-3.97%	30%
F	0.058	0.042	-28.37%	30%

Use the Biot-Sacart Law to estimated the results of 8cm through 10cm

Test position	Measure Value (A/m)	Estimated Value (A/m)	Agreement Ratio	Limits
A	0.125	0.145	16.39%	30%
B	0.1	0.104	3.59%	30%
C	0.125	0.144	15.15%	30%
D	0.132	0.144	9.04%	30%
E	0.021	0.026	23.77%	30%
F	0.024	0.024	-0.36%	30%

As the model is sufficient, the value of 4cm can be estimated through the results of 6 cm

Test position	Estimated Value (A/m)	Limits (A/m)
A	0.168	1.63
B	0.131	
C	0.162	
D	0.166	
E	0.126	
F	0.113	



As the model is sufficient, the value of 2cm can be estimated through the results of 4 cm

Test position	Estimated Value (A/m)	Limits (A/m)
A	0.222	1.63
B	0.173	
C	0.207	
D	0.212	
E	0.444	
F	0.259	

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

Test position	Estimated Value (A/m)	Limits (A/m)
A	0.328	1.63
B	0.255	
C	0.286	
D	0.293	
E	1.241	
F	0.761	



Mode 16

Note: <1%, 50%, >95% load all have been tested, only worse case Max load (<1%) is reported.

H-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, ... 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (A/m)

Battery < 1% (Worst case)

Test Distance (cm)	Test Position A (A/m)	Test Position B (A/m)	Test Position C (A/m)	Test Position D (A/m)	Test Position E (A/m)	Test Position F (A/m)	Limit (A/m)
6	0.139	0.101	0.134	0.134	0.047	0.059	1.63
8	0.13	0.102	0.122	0.128	0.021	0.024	
10	0.123	0.087	0.125	0.125	0.014	0.016	
12	0.117	0.08	0.112	0.12	0.011	0.013	
14	0.114	0.064	0.109	0.115	0.009	0.011	
16	0.108	0.055	0.104	0.109	0.008	0.009	
18	0.106	0.055	0.099	0.108	0.006	0.008	
20	0.108	0.04	0.101	0.096	0.005	0.007	

Use the Biot-Sacart Law to estimated the results of 6cm through 8cm

Test position	Measure Value (A/m)	Estimated Value (A/m)	Agreement Ratio	Limits
A	0.139	0.155	11.86%	30%
B	0.101	0.122	20.79%	30%
C	0.134	0.144	7.30%	30%
D	0.134	0.151	12.58%	30%
E	0.047	0.045	-3.97%	30%
F	0.059	0.042	-29.58%	30%

Use the Biot-Sacart Law to estimated the results of 8cm through 10cm

Test position	Measure Value (A/m)	Estimated Value (A/m)	Agreement Ratio	Limits
A	0.13	0.143	10.13%	30%
B	0.102	0.101	-0.72%	30%
C	0.122	0.144	17.98%	30%
D	0.128	0.144	12.45%	30%
E	0.021	0.026	23.77%	30%
F	0.024	0.026	6.29%	30%

As the model is sufficient, the value of 4cm can be estimated through the results of 6 cm

Test position	Estimated Value (A/m)	Limits (A/m)
A	0.173	1.63
B	0.126	
C	0.163	
D	0.163	
E	0.126	
F	0.115	



As the model is sufficient, the value of 2cm can be estimated through the results of 4 cm


Test position	Estimated Value (A/m)	Limits (A/m)
A	0.229	1.63
B	0.166	
C	0.208	
D	0.208	
E	0.444	
F	0.263	

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

Test position	Estimated Value (A/m)	Limits (A/m)
A	0.338	1.63
B	0.245	
C	0.289	
D	0.289	
E	1.241	
F	0.774	

MPE Setup photo

0cm



20cm



※※※※※END OF THE REPORT※※※※※