



Produkte  
Products

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                              |                                                                                                                                                                                                                                                                      |                                |                                              |                                         |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|----------------------------------------------|-----------------------------------------|
| <b>Prüfbericht - Nr.: 14049619 001</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                              |                                                                                                                                                                                                                                                                      | Seite 1 von 15<br>Page 1 of 15 |                                              |                                         |
| <i>Test Report No.:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                              |                                                                                                                                                                                                                                                                      |                                |                                              |                                         |
| <b>Auftraggeber:</b><br><i>Client:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                              | SHANTOU PENGXIANG TOYS CO., LTD<br>Pengxiang Building, Ganxia Road,<br>Bumei Industrial Zone, Chenghai District,<br>Shantou, China                                                                                                                                   |                                |                                              |                                         |
| <b>Gegenstand der Prüfung:</b><br><i>Test Item:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                              | Short Range Device - Radio Control Toy Transmitter (2.4GHz)                                                                                                                                                                                                          |                                |                                              |                                         |
| <b>Bezeichnung:</b><br><i>Identification:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Please refer to "Models" on<br>page 6        | <b>Serien-Nr.:</b><br><i>Serial No.:</i>                                                                                                                                                                                                                             | Engineering sample             |                                              |                                         |
| <b>Wareneingangs-Nr.:</b><br><i>Receipt No.:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                               | A000623094-001                               | <b>Eingangsdatum:</b><br><i>Date of Receipt:</i>                                                                                                                                                                                                                     | 28.06.2017                     |                                              |                                         |
| <b>Zustand des Prüfgegenstandes bei Anlieferung:</b><br><i>Condition of test item at delivery:</i>                                                                                                                                                                                                                                                                                                                                                                                             |                                              | Test sample is not damaged and suitable for testing.                                                                                                                                                                                                                 |                                |                                              |                                         |
| <b>Prüfört:</b><br><i>Testing Location:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                              | TÜV Rheinland Hong Kong Ltd.<br>3/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong<br>Global United Technology Services Co., Ltd.<br>2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, China |                                |                                              |                                         |
| <b>Prüfgrundlage:</b><br><i>Test Specification:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                              | FCC Part 15 Subpart C<br>ANSI C63.10-2013                                                                                                                                                                                                                            |                                |                                              |                                         |
| <b>Prüfergebnis:</b><br><i>Test Results:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                              | Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.<br>The above mentioned product was tested and <b>passed</b> .                                                                                                           |                                |                                              |                                         |
| <b>Prüflaboratorium:</b><br><i>Testing Laboratory:</i>                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                              | TÜV Rheinland Hong Kong Ltd.<br>3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong                                                                                                                                           |                                |                                              |                                         |
| <b>geprüft/ tested by:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                              | <b>kontrolliert/ reviewed by:</b>                                                                                                                                                                                                                                    |                                |                                              |                                         |
| <div style="display: flex; justify-content: space-between;"> <div> 11.07.2017<br/>Kevin Wong<br/>Project Manager </div> <div>  </div> </div>                                                                                                                                                                                                                                                                |                                              | <div style="display: flex; justify-content: space-between;"> <div> 11.07.2017<br/>Benny Lau<br/>Senior Project Manager </div> <div>  </div> </div>                              |                                |                                              |                                         |
| <b>Datum</b><br><i>Date</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <b>Name/Stellung</b><br><i>Name/Position</i> | <b>Unterschrift</b><br><i>Signature</i>                                                                                                                                                                                                                              | <b>Datum</b><br><i>Date</i>    | <b>Name/Stellung</b><br><i>Name/Position</i> | <b>Unterschrift</b><br><i>Signature</i> |
| <b>Sonstiges:</b><br>Other Aspects                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                              | FCC ID: 2AM0Z075485806279                                                                                                                                                                                                                                            |                                |                                              |                                         |
| <b>Abkürzungen:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                              | <b>Abbreviations:</b>                                                                                                                                                                                                                                                |                                |                                              |                                         |
| P(ass) = entspricht Prüfgrundlage<br>F(ail) = entspricht nicht Prüfgrundlage<br>N/A = nicht anwendbar<br>N/T = nicht getestet                                                                                                                                                                                                                                                                                                                                                                  |                                              | P(ass) = passed<br>F(ail) = failed<br>N/A = not applicable<br>N/T = not tested                                                                                                                                                                                       |                                |                                              |                                         |
| <p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b></p> <p><i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i></p> |                                              |                                                                                                                                                                                                                                                                      |                                |                                              |                                         |

## Table of Content

|                                                                         | Page          |
|-------------------------------------------------------------------------|---------------|
| Cover Page .....                                                        | 1             |
| Table of Content .....                                                  | 2             |
| Product information.....                                                | 4             |
| Manufacturers declarations .....                                        | 4             |
| Product function and intended use .....                                 | 4             |
| Submitted documents.....                                                | 4             |
| Independent Operation Modes .....                                       | 5             |
| Related Submittal(s) Grants .....                                       | 5             |
| Remark .....                                                            | 5             |
| Test Set-up and Operation Mode.....                                     | 6             |
| Principle of Configuration Selection .....                              | 6             |
| Test Operation and Test Software .....                                  | 6             |
| Special Accessories and Auxiliary Equipment.....                        | 6             |
| Countermeasures to achieve EMC Compliance.....                          | 6             |
| Test Methodology .....                                                  | 7             |
| Radiated Emission .....                                                 | 7             |
| Field Strength Calculation.....                                         | 7             |
| Test Setup Diagram .....                                                | 8             |
| List of Test and Measurement Instruments.....                           | 9             |
| Measurement Uncertainty .....                                           | 10            |
| Results FCC Part 15 – Subpart C .....                                   | 11            |
| FCC 15.203 – Antenna Requirement 1.....                                 | Pass ..... 11 |
| FCC 15.204 – Antenna Requirement 2.....                                 | Pass ..... 11 |
| FCC 15.207 – Conducted Emission on AC Mains .....                       | N/A ..... 11  |
| Subclause 15.215 (c) – 20 dB Bandwidth.....                             | Pass ..... 12 |
| Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics..... | Pass ..... 13 |
| Subclause 15.249 (d), 15.205 – Out Of Band Radiated Emission .....      | Pass ..... 15 |
| Appendix 1 – Test protocols .....                                       | 3 pages       |
| Appendix 2 – Test setup .....                                           | 2 pages       |
| Appendix 3 – EUT External Photos .....                                  | 3 pages       |
| Appendix 4 – EUT Internal Photos .....                                  | 8 pages       |

Appendix 5 – RF exposure information ..... 2 pages

## Product information

### Manufacturers declarations

|                                         | <b>Transmitter</b>       |
|-----------------------------------------|--------------------------|
| Operating frequency range               | 2416 - 2480MHz           |
| Type of modulation                      | GFSK                     |
| Number of channels                      | 65                       |
| Type of antenna                         | Wire Antenna             |
| Power level                             | fix                      |
| Connection to public utility power line | No                       |
| Nominal voltage                         | V <sub>nom</sub> : 4.5 V |

### Product function and intended use

The equipment under test (EUT) is a radio control transmitter operating at 2.4GHz. It is powered by battery only.

The manufacturer declares that the models as listed below table are all identical in electrical, PCB layout and components used except the model number and packaging only.

FCC ID: 2AM0Z075485806279

| <b>Models</b>                                                                                                                                                                                                                                                                                                                                                                                                              | <b>Product description</b>                                         |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| S757, S767, S777, S787, S797, 9600, 9601, 9602, 9603, 9604, 9605, 9600-1, 9601-1, 9602-1, 9603-1, 9604-1, 9605-1, S626, S636, S656, S666, S676, S686, S696, 9300, 9301, 9301-1, 9302, 9303, 9303-1, 9304, 9305, S727, S737, 9500, 9501, 9502, 9503, 9504, 9505, 9200, 9201, 9201-1, 9202, 9203, 9203-1, 9204, 9205, 9800, 9801, 9801-1, 9802, 9803, 9803-1, 9804, 9805, 9900, 9901, 9901-1, 9902, 9903, 9903-1, 9904, 9905 | <b>Short Range Device - Radio Control Toy Transmitter (2.4GHz)</b> |

### Submitted documents

Circuit Diagram  
 Block Diagram  
 Bill of material  
 Technical Description  
 User manual  
 Label

## Independent Operation Modes

The basic operation modes are:

- Transmitting mode.
- Normal operation mode

For further information refer to User Manual

## Related Submittal(s) Grants

This is a single application for certification of the transmitter.

## Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- A test mode sample which can transmit continuously in the lowest, middle and highest frequency channels at its maximum power was provided by the applicant..

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- None

### Countermeasures to achieve EMC Compliance

- None

## Test Methodology

### Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.  
R = Reading of Spectrum Analyzer in dBuV.  
AF = Antenna Factor in dB.  
CF = Cable Attenuation Factor in dB.  
FA = Filter Attenuation Factor in dB.  
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.


## Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



## List of Test and Measurement Instruments

**Global United Technology Services Co., Ltd. (Registration number: 600491)**

### Radiated Emission

| Equipment                  | Manufacturer     | Type                 | Cal. Date   | Due Date    |
|----------------------------|------------------|----------------------|-------------|-------------|
| 3m Semi- Anechoic Chamber  | ZhongYu Electron | 9.0(L)*6.0(W)*6.0(H) | 03-Jul-2015 | 02-Jul-2018 |
| Control Room               | ZhongYu Electron | 6.2(L)*2.5(W)*2.4(H) | N/A         | N/A         |
| ESU EMI Test Receiver      | R&S              | ESU26                | 26-Jun-2017 | 25-Jun-2018 |
| Loop Antenna               | Zhinan           | ZN30900A             | 26-Jun-2017 | 25-Jun-2018 |
| BiConiLog Antenna          | SCHWARZBECK      | VULB9163             | 26-Jun-2017 | 25-Jun-2018 |
| Double-ridged horn antenna | SCHWARZBECK      | 9120D                | 26-Jun-2017 | 25-Jun-2018 |
| Horn Antenna               | ETS-LINDGREN     | 3160-09              | 26-Jun-2017 | 25-Jun-2018 |
| RF Amplifier               | HP               | 8347A                | 26-Jun-2017 | 25-Jun-2018 |
| RF Amplifier               | HP               | 8349B                | 26-Jun-2017 | 25-Jun-2018 |
| Broadband Preamplifier     | SCHWARZBECK      | BBV9718              | 26-Jun-2017 | 25-Jun-2018 |
| EMI Test Software          | AUDIX            | E3                   | N/A         | N/A         |
| Coaxial cable              | GTS              | N/A                  | N/A         | N/A         |
| Coaxial Cable              | GTS              | N/A                  | N/A         | N/A         |
| Thermo meter               | N/A              | N/A                  | 26-Jun-2017 | 25-Jun-2018 |

### TÜV Rheinland Hong Kong Ltd

#### Radio Test

| Equipment         | Manufacturer | Type  | Cal. Date | Due Date    |
|-------------------|--------------|-------|-----------|-------------|
| Spectrum Analyzer | R & S        | FSP30 | 15-Oct-16 | 15-Oct-2017 |

## Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions measurements is  $\pm 3.70\text{dB}$  (9kHz to 30MHz) and  $\pm 4.64\text{dB}$  (30MHz to 1000MHz) and is  $\pm 4.83\text{dB}$  (1GHz to 18GHz) and  $\pm 5.20\text{dB}$  (18GHz to 25GHz)

The estimated combined standard uncertainty for antenna conducted emission is  $\pm 2.1\text{dB}$

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for the level of confidence is approximately 95%.

## Results FCC Part 15 – Subpart C

|                                                                                                                     |                               |                        |
|---------------------------------------------------------------------------------------------------------------------|-------------------------------|------------------------|
| <b>FCC 15.203 – Antenna Requirement 1</b>                                                                           |                               | <b>Pass</b>            |
| <b>FCC Requirement:</b> No antenna other than that furnished by the responsible party shall be used with the device |                               |                        |
| <b>Results:</b>                                                                                                     | a) Antenna type:              | Fixed Integral antenna |
|                                                                                                                     | b) Manufacturer and model no: | N/A                    |
|                                                                                                                     | c) Peak Gain:                 | 0dBi                   |
| <b>Verdict:</b>                                                                                                     | Pass                          |                        |

|                                                                                                                                                                                                                                                      |                                        |             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|-------------|
| <b>FCC 15.204 – Antenna Requirement 2</b>                                                                                                                                                                                                            |                                        | <b>Pass</b> |
| <b>FCC Requirement:</b> An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator. |                                        |             |
| <b>Results:</b>                                                                                                                                                                                                                                      | Only one integral antenna can be used. |             |
| <b>Verdict:</b>                                                                                                                                                                                                                                      | N/A                                    |             |

|                                                        |  |            |
|--------------------------------------------------------|--|------------|
| <b>FCC 15.207 – Conducted Emission on AC Mains</b>     |  | <b>N/A</b> |
| There is no AC power input or output ports on the EUT. |  |            |

| <b>Subclause 15.215 (c) – 20 dB Bandwidth</b>                                                                                                                                                                                  |                         |                    |                          | <b>Pass</b>        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|--------------------|--------------------------|--------------------|
| Test Specification : ANSI C63.10 – 2013<br>Mode of operation : Tx mode<br>Port of testing : Enclosure<br>Supply voltage : 4.5VDC, 3 x 1.5V AA size new battery<br>Temperature : 23°C<br>Humidity : 50%                         |                         |                    |                          |                    |
| <b>Requirement:</b> The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated. |                         |                    |                          |                    |
| <b>Results:</b> Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.<br>For test protocols refer to Appendix 1.                         |                         |                    |                          |                    |
| <b>Frequency (MHz)</b>                                                                                                                                                                                                         | <b>20 dB left (MHz)</b> | <b>Limit (MHz)</b> | <b>20 dB right (MHz)</b> | <b>Limit (MHz)</b> |
| 2416                                                                                                                                                                                                                           | 2415.300                | > 2400             | 2416.880                 | < 2483.5           |
| 2448                                                                                                                                                                                                                           | 2447.300                | > 2400             | 2448.790                 | < 2483.5           |
| 2480                                                                                                                                                                                                                           | 2479.290                | > 2400             | 2480.680                 | < 2483.5           |

| <b>Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics</b>                                                                                                                                                                |              |                         | <b>Pass</b> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------------------------|-------------|
| Test Specification : ANSI C63.10 – 2013<br>Mode of operation : Tx mode<br>Port of testing : Enclosure<br>Frequency range : 9kHz – 25GHz<br>Supply voltage : 4.5VDC, 3 x 1.5V AA size new battery<br>Temperature : 23°C<br>Humidity : 50% |              |                         |             |
| Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.                                                                                     |              |                         |             |
| <b>Results:</b> PASS.                                                                                                                                                                                                                    |              |                         |             |
| Fundamental Frequency 2416MHz                                                                                                                                                                                                            |              | Vertical Polarization   |             |
| Freq MHz                                                                                                                                                                                                                                 | Level dBuV/m | Limit/ Detector dBuV/m  |             |
| 2415.900                                                                                                                                                                                                                                 | 87.41        | 114.0 / PK              |             |
| 2415.900                                                                                                                                                                                                                                 | 79.05        | 94.0 / AV               |             |
| Fundamental Frequency 2416MHz                                                                                                                                                                                                            |              | Horizontal Polarization |             |
| Freq MHz                                                                                                                                                                                                                                 | Level dBuV/m | Limit/ Detector dBuV/m  |             |
| 2415.880                                                                                                                                                                                                                                 | 89.82        | 114.0 / PK              |             |
| 2415.880                                                                                                                                                                                                                                 | 78.60        | 94.0 / AV               |             |
| Harmonics 2416MHz                                                                                                                                                                                                                        |              | Vertical Polarization   |             |
| Freq MHz                                                                                                                                                                                                                                 | Level dBuV/m | Limit/ Detector dBuV/m  |             |
| 4837.650                                                                                                                                                                                                                                 | 49.61        | 74.0 / PK               |             |
| 4837.650                                                                                                                                                                                                                                 | 38.18        | 54.0 / AV               |             |
| Harmonics 2416MHz                                                                                                                                                                                                                        |              | Horizontal Polarization |             |
| Freq MHz                                                                                                                                                                                                                                 | Level dBuV/m | Limit/ Detector dBuV/m  |             |
| 4832.675                                                                                                                                                                                                                                 | 53.41        | 74.0 / PK               |             |
| 4832.675                                                                                                                                                                                                                                 | 36.71        | 54.0 / AV               |             |
| 7247.350                                                                                                                                                                                                                                 | 54.51        | 74.0 / PK               |             |
| 7247.350                                                                                                                                                                                                                                 | 42.42        | 54.0 / AV               |             |
| Fundamental Frequency 2448MHz                                                                                                                                                                                                            |              | Vertical Polarization   |             |
| Freq MHz                                                                                                                                                                                                                                 | Level dBuV/m | Limit/ Detector dBuV/m  |             |
| 2447.840                                                                                                                                                                                                                                 | 86.51        | 114.0 / PK              |             |
| 2447.840                                                                                                                                                                                                                                 | 78.13        | 94.0 / AV               |             |
| Fundamental Frequency 2448MHz                                                                                                                                                                                                            |              | Horizontal Polarization |             |
| Freq MHz                                                                                                                                                                                                                                 | Level dBuV/m | Limit/ Detector dBuV/m  |             |
| 2447.920                                                                                                                                                                                                                                 | 89.78        | 114.0 / PK              |             |
| 2447.920                                                                                                                                                                                                                                 | 82.54        | 94.0 / AV               |             |

|                               |                         |                                   |                         |                         |                                   |
|-------------------------------|-------------------------|-----------------------------------|-------------------------|-------------------------|-----------------------------------|
| Harmonics 2448MHz             |                         |                                   | Vertical Polarization   |                         |                                   |
| <b>Freq<br/>MHz</b>           | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> | <b>Freq<br/>MHz</b>     | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> |
| 4896.130                      | 48.40                   | 74.0 / PK                         | 4896.130                | 37.36                   | 54.0 / AV                         |
| Harmonics 2448MHz             |                         |                                   | Horizontal Polarization |                         |                                   |
| <b>Freq<br/>MHz</b>           | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> | <b>Freq<br/>MHz</b>     | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> |
| 4895.420                      | 54.72                   | 74.0 / PK                         | 4895.520                | 43.96                   | 54.0 / AV                         |
| 7343.350                      | 58.08                   | 74.0 / PK                         | 7343.350                | 44.97                   | 54.0 / AV                         |
| Fundamental Frequency 2480MHz |                         |                                   | Vertical Polarization   |                         |                                   |
| <b>Freq<br/>MHz</b>           | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> | <b>Freq<br/>MHz</b>     | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> |
| 2479.800                      | 85.06                   | 114.0 / PK                        | 2479.800                | 76.59                   | 94.0 / AV                         |
| Fundamental Frequency 2480MHz |                         |                                   | Horizontal Polarization |                         |                                   |
| <b>Freq<br/>MHz</b>           | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> | <b>Freq<br/>MHz</b>     | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> |
| 2479.970                      | 88.46                   | 114.0 / PK                        | 2479.970                | 81.17                   | 94.0 / AV                         |
| Harmonics 2480MHz             |                         |                                   | Vertical Polarization   |                         |                                   |
| <b>Freq<br/>MHz</b>           | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> | <b>Freq<br/>MHz</b>     | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> |
| 4959.295                      | 50.05                   | 74.0 / PK                         | 4959.295                | 36.78                   | 54.0 / AV                         |
| Harmonics 2480MHz             |                         |                                   | Horizontal Polarization |                         |                                   |
| <b>Freq<br/>MHz</b>           | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> | <b>Freq<br/>MHz</b>     | <b>Level<br/>dBuV/m</b> | <b>Limit/ Detector<br/>dBuV/m</b> |
| 4959.920                      | 55.79                   | 74.0 / PK                         | 4959.920                | 41.18                   | 54.0 / AV                         |
| 7439.820                      | 54.61                   | 74.0 / PK                         | 7439.820                | 42.46                   | 54.0 / AV                         |

|                                                                                                                                                                                                                                                                                   |                     |                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-------------------------------|
| <b>Subclause 15.249 (d), 15.205 – Out Of Band Radiated Emission</b>                                                                                                                                                                                                               |                     | <b>Pass</b>                   |
| Test Specification : ANSI C63.10 – 2013<br>Mode of operation : Tx mode<br>Port of testing : Enclosure<br>Detector : Peak<br>Frequency range : 9kHz – 25GHz<br>Supply voltage : 6.0VDC, 4 x 1.5V AA size new battery<br>Temperature : 23°C<br>Humidity : 50%                       |                     |                               |
| <b>Requirement:</b> Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation. |                     |                               |
| <b>Results:</b> All three transmit frequency modes comply with the field strength limit of section 15.209. There is no spurious found below 30MHz.                                                                                                                                |                     |                               |
| Tx frequency 2416MHz Vertical Polarization                                                                                                                                                                                                                                        |                     |                               |
| <b>Freq MHz</b>                                                                                                                                                                                                                                                                   | <b>Level dBuV/m</b> | <b>Limit/ Detector dBuV/m</b> |
| 2400.000                                                                                                                                                                                                                                                                          | 45.53               | 74.0 / PK                     |
| 2400.000                                                                                                                                                                                                                                                                          | 24.27               | 54.0 / AV                     |
| Tx frequency 2416MHz Horizontal Polarization                                                                                                                                                                                                                                      |                     |                               |
| <b>Freq MHz</b>                                                                                                                                                                                                                                                                   | <b>Level dBuV/m</b> | <b>Limit/ Detector dBuV/m</b> |
| 2400.000                                                                                                                                                                                                                                                                          | 49.93               | 74.0 / PK                     |
| 2400.000                                                                                                                                                                                                                                                                          | 24.27               | 54.0 / AV                     |
| Tx frequency 2448MHz Vertical Polarization                                                                                                                                                                                                                                        |                     |                               |
| <b>Freq MHz</b>                                                                                                                                                                                                                                                                   | <b>Level dBuV/m</b> | <b>Limit/ Detector dBuV/m</b> |
| No peak found                                                                                                                                                                                                                                                                     | ---                 | 74.0 / PK                     |
| No peak found                                                                                                                                                                                                                                                                     | ---                 | 54.0 / AV                     |
| Tx frequency 2448MHz Horizontal Polarization                                                                                                                                                                                                                                      |                     |                               |
| <b>Freq MHz</b>                                                                                                                                                                                                                                                                   | <b>Level dBuV/m</b> | <b>Limit/ Detector dBuV/m</b> |
| No peak found                                                                                                                                                                                                                                                                     | ---                 | 74.0 / PK                     |
| No peak found                                                                                                                                                                                                                                                                     | ---                 | 54.0 / AV                     |
| Tx frequency 2480MHz Vertical Polarization                                                                                                                                                                                                                                        |                     |                               |
| <b>Freq MHz</b>                                                                                                                                                                                                                                                                   | <b>Level dBuV/m</b> | <b>Limit/ Detector dBuV/m</b> |
| 2483.500                                                                                                                                                                                                                                                                          | 58.47               | 74.0 / PK                     |
| 2483.500                                                                                                                                                                                                                                                                          | 29.17               | 54.0 / AV                     |
| Tx frequency 2480MHz Horizontal Polarization                                                                                                                                                                                                                                      |                     |                               |
| <b>Freq MHz</b>                                                                                                                                                                                                                                                                   | <b>Level dBuV/m</b> | <b>Limit/ Detector dBuV/m</b> |
| 2483.500                                                                                                                                                                                                                                                                          | 60.58               | 74.0 / PK                     |
| 2483.500                                                                                                                                                                                                                                                                          | 29.90               | 54.0 / AV                     |