

INTERTEK TESTING SERVICES

Analysis Report

The equipment under test (EUT) is a portable transmitter for a Toy RC Drifter And Police Car 2pk With Cones operating at 49.86MHz. The EUT is powered by one 9.0V 6F22 size batteries. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna with unique antenna connector

Antenna Gain: 0dBi

The nominal conducted output power specified: -25.0dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -27.15dBm (+/- 3dB)

Modulation Type: Pulse modulation

According to the KDB 447498:

The worst-case peak radiated emission for the EUT is 70.5dBμV/m at 3m in the frequency 49.86MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -24.73dBm

The ERP = EIRP – 2.15 = -26.88 dBm

which is within the production variation.

The maximum conducted output power specified is -22dBm = 0.006mW

The source- based time-averaging conducted output power

= 0.006* Duty Cycle mW < 0.006mW (Duty Cycle < 100%)

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

= $474 * [1 + \log(100/f(\text{MHz}))]/2$

= 308.6 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

Transmitter Duty Cycle Calculation

The duration of one cycle = 17.5362ms

Effective period of the cycle = 1.5652ms x 4 + 0.5217ms x 10 = 11.4778ms

DC = 11.4778ms / 17.5362ms = 0.6545 or 65.45%

FCC ID: 2AMPNYH002