

FCC TEST REPORT

For

DongGuan Smart-tech technology Co., LTD

Light Stream Controller

Model No.: V-20587

Additional Model No.: /

Prepared for : DongGuan Smart-tech technology Co., LTD
Address : 5th bulding Liyuan district Zhangmutou town Dongguan City
Guangdong Province China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an
District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : June 01, 2017
Number of tested samples : 1
Serial number : 1334502319
Date of Test : June 01, 2017~June 29, 2017
Date of Report : June 29, 2017

FCC TEST REPORT
FCC CFR 47 PART 15 C(15.249): 2016**Report Reference No. : LCS170601100AE**

Date of Issue : June 29, 2017

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, ChinaTesting Location/ Procedure : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name : DongGuan Smart-tech technology Co., LTD**Address : 5th bulding Liyuan district Zhangmutou town Dongguan City
Guangdong Province China**Test Specification**

Standard : FCC CFR 47 PART 15 C(15.249): 2016

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description. : Light Stream Controller

Trade Mark..... : Village Lighting Co.

Model/ Type reference : V-20587

Ratings..... : Input: AC 120V 50/60Hz 7A (Max)
Output: AC 120V 50/60Hz 7A (Max)Result : **Positive****Compiled by:**

Aking Jin/ File administrators

Supervised by:

Dick Su/ Technique principal

Approved by:

Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCS170601100AE	<u>June 29, 2017</u> Date of issue
----------------------------------	---------------------------------------

Type / Model.....	: V-20587
EUT.....	: Light Stream Controller
Applicant.....	: DongGuan Smart-tech technology Co., LTD
Address.....	: 5th bulding Liyuan district Zhangmutou town Dongguan City Guangdong Province China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: DongGuan Smart-tech technology Co., LTD
Address.....	: 5th bulding Liyuan district Zhangmutou town Dongguan City Guangdong Province China
Telephone.....	: /
Fax.....	: /
Factory.....	: DongGuan Smart-tech technology Co., LTD
Address.....	: 5th bulding Liyuan district Zhangmutou town Dongguan City Guangdong Province China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
-------------	----------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Revision	Issue Date	Revisions	Revised By
00	June 29, 2017	Initial Issue	Gavin Liang

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	6
1.1. DESCRIPTION OF DEVICE (EUT)	6
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	6
1.3. EXTERNAL I/O CABLE	6
1.4. DESCRIPTION OF TEST FACILITY	6
1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
1.6. MEASUREMENT UNCERTAINTY	7
1.7. DESCRIPTION OF TEST MODES	7
2. TEST METHODOLOGY	8
2.1. EUT CONFIGURATION	8
2.2. EUT EXERCISE	8
2.3. GENERAL TEST PROCEDURES	8
3. SYSTEM TEST CONFIGURATION	9
3.1. JUSTIFICATION	9
3.2. EUT EXERCISE SOFTWARE	9
3.3. SPECIAL ACCESSORIES	9
3.4. BLOCK DIAGRAM/SCHEMATICS.....	9
3.5. EQUIPMENT MODIFICATIONS	9
3.6. TEST SETUP	9
4. SUMMARY OF TEST RESULTS	10
5. TEST RESULT	11
5.1. RADIATED EMISSION MEASUREMENT.....	11
5.2. 20 DB BANDWIDTH MEASUREMENT.....	21
5.3. AC POWER LINE CONDUCTED EMISSIONS	23
5.4. ANTENNA REQUIREMENTS	26
6. LIST OF MEASURING EQUIPMENTS.....	27
7. TEST SETUP PHOTOGRAPHS OF EUT	28
8. EXTERIOR PHOTOGRAPHS OF THE EUT.....	28
9. INTERIOR PHOTOGRAPHS OF THE EUT	28

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: Light Stream Controller
Model Number	: V-20587
Model Declaration	: /
Test Model	: V-20587
Hardware version	: V2.0
Software version	: V2.6
Power Supply	: Input: AC 120V 50/60Hz 7A (Max) Output: AC 120V 50/60Hz 7A (Max)
Bluetooth Function	: Supported BT 4.0
Operation frequency	: 2402MHz-2480MHz
Channel Spacing	: 2MHz
Modulation Type	: GFSK
Bluetooth Version	: 4.0 (Support only BLE)
Channel Number	: 40 Channels
Antenna Type	: Internal PCB Antenna
Antenna Gain	: 2.0dBi (Max.)
2.4G Function	
Frequency Range	: 5 channels hopping from 2402.00-2480.00MHz (See section 1.7)
Modulation Type	: FSK
Antenna Type	: External SMA Antenna
Antenna Gain	: 2.0dBi (Max.)
Extreme temp. Tolerance	: -10°C to +40°C

1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
Antenna Port	1	N/A

1.4. Description of Test Facility

CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	±3.10dB	(1)
	30MHz~200MHz	±2.96dB	(1)
	200MHz~1000MHz	±3.10dB	(1)
	1GHz~26.5GHz	±3.80dB	(1)
	26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	±1.63dB	(1)
Power disturbance	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Pre-test AC conducted emission at both power adapter and charge from PC mode, recorded worst case.

Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, which was determined to be 2.4GHz mode (Low Channel).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be 2.4GHz mode(Low Channel).

All test modes were tested, only the result of the worst case was recorded in the report.

Channel List & Frequency

Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	2411	3	2444
1	2422	4	2455
2	2433	---	---

Mode of Operations	Transmitting Frequency (MHz)
FSK	2411
	2433
	2455
For Conducted Emission	
Test Mode	TX Mode
For Radiated Emission	
Test Mode	TX Mode

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (RFstar Smart Studio 7) provided by application.

3.3. Special Accessories

No.	Equipment	Manufacturer	Model No.	Serial No.	Length	shielded/ unshielded	Notes
1	PC	Lenovo	Ideapad	A131101550	/	/	DOC
2	Power adapter	Lenovo	CPA-A090	36200414	1.00m	unshielded	DOC

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart C		
FCC Rules	Description of Test	Result
§15.205(a), §15.209(a), §15.249(a), §15.249(c)	Radiated Emissions Measurement	Compliant
§15.205, §15.249(d)	Emissions at Restricted Band	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant

5. TEST RESULT

5.1. Radiated Emission Measurement

5.1.1. Standard Applicable

1. According to §15.249 (d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Frequencies(MHz)	Field Strength(microvolts/meter)	Measurement Distance(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

2. According to §15.249 (a): Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental		Field strength of harmonics	
	millivolts/meter	dBuV/m	microvolts/meter	dBuV/m
902-928 MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25 GHz	250	108	2500	68

As shown in §15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth

5.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB/VB 200Hz/1KHz for QP/Average
Start ~ Stop Frequency	150kHz~30MHz / RB/VB 9kHz/30KHz for QP/Average
Start ~ Stop Frequency	30MHz~1000MHz / RB/VB 120kHz/1MHz for QP

5.1.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.


Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


5.1.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);
 Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Results of Radiated Emissions (9 KHz~30MHz)

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	Low Channel

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dB)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.1.7. Results of Radiated Emissions (30MHz~1GHz)

Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	Low Channel

Low Channel
Horizontal:



pol: HORIZONTAL


	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	37.81	4.84	0.38	13.02	18.24	40.00	-21.76	QP
2	45.38	2.75	0.41	13.53	16.69	40.00	-23.31	QP
3	143.83	8.71	0.71	8.22	17.64	43.50	-25.86	QP
4	176.27	9.36	0.73	9.42	19.51	43.50	-23.99	QP
5	272.28	6.57	1.04	12.43	20.04	46.00	-25.96	QP
6	368.11	13.31	1.22	14.49	29.02	46.00	-16.98	QP

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20dB below the official limit are not reported

Vertical:



pol:

VERTICAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	47.99	4.99	0.35	13.37	18.71	40.00	-21.29	QP
2	88.34	8.70	0.68	11.37	20.75	43.50	-22.75	QP
3	128.11	10.87	0.67	9.22	20.76	43.50	-22.74	QP
4	207.85	8.78	0.86	10.82	20.46	43.50	-23.04	QP
5	285.98	5.37	1.00	12.79	19.16	46.00	-26.84	QP
6	416.18	9.20	1.17	15.39	25.76	46.00	-20.24	QP

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported

Note:

- 1). Pre-scan all modes and recorded the worst case results in this report (Low Channel). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 2). Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

5.1.7. Results of Radiated Emissions (Above 1GHz)

Field Strength Of Fundamental						
Frequency (MHz)	Pol.	Measure Result (PK, dBuV/m)	Measure Result (AVG, dBuV/m)	Peak Limit (dBuV/m)	AVG Limit (dBuV/m)	Result
2411	H	84.62	80.62	114	94	Pass
2411	V	83.26	80.32	114	94	Pass

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4822.11	45.44	33.06	35.04	3.94	47.40	74	-26.60	Peak	Horizontal
4822.13	34.43	33.06	35.04	3.94	36.39	54	-17.61	Average	Horizontal
4822.11	44.37	33.06	35.04	3.94	46.33	74	-27.67	Peak	Vertical
4822.13	34.51	33.06	35.04	3.94	36.47	54	-17.53	Average	Vertical

Field Strength Of Fundamental						
Frequency (MHz)	Pol.	Measure Result (PK, dBuV/m)	Measure Result (AVG, dBuV/m)	Peak Limit (dBuV/m)	AVG Limit (dBuV/m)	Result
2433	H	85.62	81.89	114	94	Pass
2433	V	84.26	82.05	114	94	Pass

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4866.13	42.81	33.16	35.15	3.96	44.78	74	-29.22	Peak	Horizontal
4866.15	34.08	33.16	35.15	3.96	36.05	54	-17.95	Average	Horizontal
4866.13	44.41	33.16	35.15	3.96	46.38	74	-27.62	Peak	Vertical
4866.16	35.98	33.16	35.15	3.96	37.95	54	-16.05	Average	Vertical

Field Strength Of Fundamental						
Frequency (MHz)	Pol.	Measure Result (PK, dBuV/m)	Measure Result (AVG, dBuV/m)	Peak Limit (dBuV/m)	AVG Limit (dBuV/m)	Result
2455	H	87.65	84.65	114	94	Pass
2455	V	88.11	85.21	114	94	Pass

Freq. MHz	Reading Level dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4910.10	44.30	33.26	35.14	3.98	46.40	74	-27.60	Peak	Horizontal
4910.13	34.01	33.26	35.14	3.98	36.11	54	-17.89	Average	Horizontal
4910.11	42.21	33.26	35.14	3.98	44.31	74	-29.69	Peak	Vertical
4910.13	34.80	33.26	35.14	3.98	36.90	54	-17.10	Average	Vertical



Notes:

1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
3. No emission was be recorded above 18GHz means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


5.1.8. Results for Restricted Band Edge Testing

GFSK						
Freq. MHz	Reading Level dBm	Antenna Gain dBi	Measured E dBuV/m	Limit dBuV/m	Margin dB	Remark
2310.000	-51.937	2.0	45.293	74	-28.707	Peak
2310.000	-62.962	2.0	34.268	54	-19.732	Average
2390.000	-51.278	2.0	45.952	74	-28.048	Peak
2390.000	-62.720	2.0	34.510	54	-19.490	Average
2483.500	-49.400	2.0	47.830	74	-26.170	Peak
2483.500	-62.391	2.0	34.839	54	-19.161	Average
2500.000	-51.061	2.0	46.169	74	-27.831	Peak
2500.000	-62.355	2.0	34.875	54	-19.125	Average


Test plot of Band Edge (Conducted)



Low Channel / 2411MHz - Peak



Low Channel / 2411MHz - Average



High Channel / 2455MHz - Peak

High Channel / 2455MHz - Average

5.2. 20 DB BANDWIDTH MEASUREMENT

5.2.1. Limit


No Limit

5.2.2. Test Procedures

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set to the maximum power setting and enable the EUT transmit continuously.
- D. For 20dB bandwidth measurement, use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW/VBW=30 KHz/ 100KHz; Sweep = auto; Detector function = peak; Trace = max hold.

5.2.3. Test Setup Layout



5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.5. Test Result of 20 dB Bandwidth Measurement


Temperature	25°C	Humidity	60%
Test Engineer	Jayden Zhuo	Configurations	2.4G (FSK)

Test Mode	Channel	Frequency (MHz)	20dB Bandwidth (KHz)	Limits	Verdict
GFSK	Low	2411	746.6	Non-specified	PASS
	Middle	2433	822.9		
	High	2455	826.1		


Remark:

1. Test results including cable loss;
2. please refer to following plots;


20 dB Bandwidth Measurement



Low Channel-2411MHz



Middle Channel-2433MHz



High Channel-2455MHz

5.3. AC Power line conducted emissions


5.3.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

* Decreasing linearly with the logarithm of the frequency


5.3.2 Block Diagram of Test Setup



5.3.3 Test Results


PASS

The test data please refer to following page.

AC Conducted Emission of power adapter @ AC 120V/60Hz (worst case)


	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuA	dB	dB	dBuA	dBuA	dB	
1	0.27	23.18	9.60	0.03	42.81	61.12	-18.31	QP
2	0.27	2.13	9.60	0.03	21.76	51.11	-29.35	Average
3	0.56	30.09	9.62	0.04	49.75	56.00	-6.25	QP
4	0.56	9.78	9.62	0.04	29.44	46.00	-16.56	Average
5	1.18	19.43	9.63	0.05	39.11	56.00	-16.89	QP
6	1.18	-0.16	9.63	0.05	19.52	46.00	-26.48	Average
7	1.63	18.11	9.63	0.05	37.79	56.00	-18.21	QP
8	1.63	-1.36	9.63	0.05	18.32	46.00	-27.68	Average
9	3.16	17.60	9.64	0.06	37.30	56.00	-18.70	QP
10	3.16	-4.92	9.64	0.06	14.78	46.00	-31.22	Average
11	6.56	20.63	9.68	0.07	40.38	60.00	-19.62	QP
12	6.56	1.81	9.68	0.07	21.56	50.00	-28.44	Average

Remarks: 1. Measured = Reading +Cable Loss.
2. The emission levels that are 20dB below the official limit are not reported.




	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuA	dB	dB	dBuA	dBuA	dB	
1	0.23	20.29	9.63	0.03	39.95	62.61	-22.66	QP
2	0.23	0.67	9.63	0.03	20.33	52.61	-32.28	Average
3	0.59	29.37	9.63	0.04	49.04	56.00	-6.96	QP
4	0.59	11.28	9.63	0.04	30.95	46.00	-15.05	Average
5	1.15	21.28	9.63	0.05	40.96	56.00	-15.04	QP
6	1.15	0.98	9.63	0.05	20.66	46.00	-25.34	Average
7	2.27	18.05	9.64	0.05	37.74	56.00	-18.26	QP
8	2.27	-4.84	9.64	0.05	14.85	46.00	-31.15	Average
9	6.59	21.02	9.67	0.07	40.76	60.00	-19.24	QP
10	6.59	1.34	9.67	0.07	21.08	50.00	-28.92	Average
11	10.85	11.86	9.69	0.08	31.63	60.00	-28.37	QP
12	10.85	-7.06	9.69	0.08	12.71	50.00	-37.29	Average

Remarks: 1. Measured = Reading +Cable Loss.
2. The emission levels that are 20dB below the official limit are not reported.

AC Conducted Emission of power adapter @ AC 240V/60Hz (worst case)

	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuA	dB	dB	dBuA	dBuA	dB	
1	0.31	24.14	9.63	0.03	43.80	59.88	-16.08	QP
2	0.31	1.36	9.63	0.03	21.02	49.88	-28.86	Average
3	0.57	31.06	9.63	0.04	50.73	56.00	-5.27	QP
4	0.57	8.36	9.63	0.04	28.03	46.00	-17.97	Average
5	0.89	21.47	9.63	0.05	41.15	56.00	-14.85	QP
6	0.89	0.27	9.63	0.05	19.95	46.00	-26.05	Average
7	1.98	20.80	9.64	0.05	40.49	56.00	-15.51	QP
8	1.98	-1.93	9.64	0.05	17.76	46.00	-28.24	Average
9	3.51	18.74	9.65	0.06	38.45	56.00	-17.55	QP
10	3.51	-2.87	9.65	0.06	16.84	46.00	-29.16	Average
11	6.59	21.22	9.67	0.07	40.96	60.00	-19.04	QP
12	6.59	3.10	9.67	0.07	22.84	50.00	-27.16	Average

Remarks: 1. Measured = Reading +Cable Loss.
2. The emission levels that are 20dB below the official limit are not reported.



	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuA	dB	dB	dBuA	dBuA	dB	
1	0.37	21.12	9.61	0.03	40.76	58.52	-17.76	QP
2	0.37	1.58	9.61	0.03	21.22	48.52	-27.30	Average
3	0.61	29.77	9.63	0.04	49.44	56.00	-6.56	QP
4	0.61	8.25	9.63	0.04	27.92	46.00	-18.08	Average
5	0.83	21.02	9.63	0.04	40.69	56.00	-15.31	QP
6	0.83	0.97	9.63	0.04	20.64	46.00	-25.36	Average
7	1.95	19.81	9.63	0.05	39.49	56.00	-16.51	QP
8	1.95	-1.26	9.63	0.05	18.42	46.00	-27.58	Average
9	3.42	17.71	9.65	0.06	37.42	56.00	-18.58	QP
10	3.42	-3.19	9.65	0.06	16.52	46.00	-29.48	Average
11	6.63	18.54	9.69	0.07	38.30	60.00	-21.70	QP
12	6.63	2.04	9.69	0.07	21.80	50.00	-28.20	Average

Remarks: 1. Measured = Reading +Cable Loss.
2. The emission levels that are 20dB below the official limit are not reported.

5.4. Antenna Requirements

5.4.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

5.4.2 Antenna Connected Construction

5.4.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.4.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 2.0dBi, and the antenna is an External PCB antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

5.4.2.3. Results: Compliance.

6. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal Date	Due Date
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	June 17, 2017	June 16, 2018
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	July 16, 2016	July 15, 2017
Signal analyzer	Agilent	N9020A	MY50510140	9kHz~26.5GHz	October 27, 2016	October 27, 2017
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	June 17, 2017	June 16, 2018
LISN (Support Unit)	EMCO	3819/2NM	9703-1839	9KHz-30MHz	June 17, 2017	June 16, 2018
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	June 17, 2017	June 16, 2018
ISN	SCHAFFNER	ISN ST08	21653	9KHz-30MHz	June 17, 2017	June 16, 2018
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30M-18GHz 3m	June 17, 2017	June 16, 2018
Amplifier	SCHAFFNER	COA9231A	18667	9kHz-2GHz	June 17, 2017	June 16, 2018
Amplifier	Agilent	8449B	3008A02120	1GHz-26.5GHz	July 16, 2016	July 15, 2017
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz-40GHz	July 16, 2016	July 15, 2017
Loop Antenna	R&S	HFH2-Z2	860004/001	9k-30MHz	June 17, 2017	June 16, 2018
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	30MHz-1GHz	June 09, 2017	June 08, 2018
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	June 09, 2017	June 08, 2018
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz-40GHz	June 09, 2017	June 08, 2018
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	June 17, 2017	June 16, 2018
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz-40GHz	June 17, 2017	June 16, 2018
Power Meter	R&S	NRVS	100444	DC-40GHz	June 17, 2017	June 16, 2018
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	June 17, 2017	June 16, 2018
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	June 17, 2017	June 16, 2018
AC Power Source	HPC	HPA-500E	HPA-9100024	AC 0~300V	June 17, 2017	June 16, 2018
DC power Source	GW	GPC-6030D	C671845	DC 1V-60V	June 17, 2017	June 16, 2018
Temp. and Humidify Chamber	Giant Force	GTH-225-20-S	MAB0103-00	N/A	June 17, 2017	June 16, 2018
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	June 17, 2017	June 16, 2018
RF CABLE-2m	JYE Bao	RG142	CB)35-2m	20MHz-1GHz	June 17, 2017	June 16, 2018
EMC Test Software	Audix	E3	N/A	N/A	N/A	N/A

Note: All equipment through GRGT EST calibration

7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----