




Test report No:
2630595R.701B

FCC TEST REPORT

Product Name	KEY ASSEMBLY LOCK CYLINDER
Trademark	VW
Model and /or type reference	KEY ASSEMBLY LOCK CYLINDER
FCC ID	2AMR2F03H00G056
Applicant's name / address	United Automotive Electronic Systems Co., Ltd. No. 555, Rongqiao Road, Pudong New Area, Shanghai
Test method requested, standard	CFR 47, FCC Part 15 C ANSI C63.10: 2020
Verdict Summary	IN COMPLIANCE
Testedby (name / position & signature)	Tim Cao / Project Manager 
Approved by (name / position & signature)	Frank He / Technical Manager 
Date of issue	2026-04-13
Report Version	V1.0
Report template No	Template_FCC 15.231-RF-V1.0

INDEX

	page
General conditions	4
Environmental conditions	4
Possible test case verdicts	5
Abbreviations	5
Document History	6
Remarks and Comments.....	6
Used Equipment	7
Uncertainty	8
1 General Information.....	9
2 Description of Test Setup	10
3 Verdict summary section	11
3.1 Standards.....	11
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	11
3.3 Overview of results.....	12
3.4 Test Facility.....	13
4 Test Results.....	14
4.1 Field strength of fundamental	14
4.1.1 Limit	14
4.1.2 Test Setup.....	15
4.1.3 Test Procedure.....	15
4.2 Field strength of spurious emissions	16
4.2.1 Limit	16
4.2.2 Test Setup.....	18
4.2.3 Test Procedure.....	18
4.3 DTS Bandwidth	19
4.3.1 Limit	19
4.3.2 Test Setup.....	19
4.3.3 Test Procedure.....	19
4.4 Duration Time.....	20
4.4.1 Limit	20
4.4.2 Test Setup.....	20
4.4.3 Test Procedure.....	20
5 Test setup photo and EUT Photo.....	21
Appendix A-TEST DATA: Field strength of fundamental	22



Appendix B-TEST DATA: Field strength of spurious emissions	24
Appendix C-TEST DATA: 20dB Bandwidth.....	28
Appendix D-TEST DATA: Duration Time	29

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Mar. 20, 2026
Date (start test)	Mar. 23, 2026
Date (finish test)	Apr. 10, 2026

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2630595R.701B	V1.0	Initial issue of report.	2026-04-13

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with CFR 47, FCC Part 15 C, ANSI C63.10:2020.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, it is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1 General Description of the Item(s);

USED EQUIPMENT

Radiated Emission(9kHz-1GHz) / AC3

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100176	2026.03.23	2027.03.22	4.42 SP3	N/A
Loop Antenna	R&S	HFH2-Z2E	101149	2025.04.16	2026.04.15	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	AC3-TH	2025.06.17	2026.06.16	N/A	N/A
EMI V3(test software)	DEKRA	N/A	N/A	N/A	N/A	N/A	N/A

Radiated Emission (1GHz-40GHz) / AC5

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EXA Spectrum Analyzer	Keysight	N9020B	MY60112218	2025.09.20	2026.09.19	A.31.05	N/A
Pre-Amplifier	Tonscond	PA0118-43	JSPA21029	2025.07.02	2026.07.01	N/A	N/A
DRG Horn	ETS-Lindgren	3117	00123988	2025.11.24	2026.11.23	N/A	N/A
Filter Switch Box	MVE	MSW-F196	C070001S	2026.03.15	2027.03.14	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	HB05-TH	2025.06.17	2026.06.16	N/A	N/A
Cable	Lair Microwave	LA800-NMNWM-6.5M	502201001001	2026.03.15	2027.03.14	N/A	N/A
Cable	Lair Microwave	LA800-NMNWM-1.2M	202201003001	2026.03.15	2027.03.14	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	3

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%. The uncertainties comply with the standard required as below.

Test item	Uncertainty
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~200MHz: 3.50 dB 300MHz~1GHz: 3.60 dB Vertical: 30MHz~200MHz: 3.60 dB 300MHz~1GHz: 3.50 dB
Radiated Emission(1GHz~26.5GHz)	Horizontal: 1GHz~18GHz: 5.00 dB Vertical: 1GHz~18GHz: 4.80 dB
Occupied Bandwidth	$\pm 1\text{kHz}$
Time	$\pm 0.5\text{s}$

1 GENERAL INFORMATION

Product Name..... :	KEY ASSEMBLY LOCK CYLINDER
Model No. :	KEY ASSEMBLY LOCK CYLINDER
Trademark. :	VW
Manufacturer..... :	Changhui Auto Electric (Huangshan) Joint-stock Company
Manufacturer Address..... :	Xikou Town, Xiuning County, Huangshan City, Anhui Province, China.
Wireless specification..... :	SRD
Operating frequency range(s)..... :	434.42MHz
Type of Modulation..... :	FSK/ASK
Number of channel..... :	1
Power Supply..... :	3Vdc
Antenna Type	Onboard metal antenna

Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

2 DESCRIPTION OF TEST SETUP

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
N/A	N/A	N/A	N/A
Software	Type / Version	Manufacturer	Supplied by
N/A	N/A	N/A	N/A

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
FCC CFR Title 47 Part 15 Subpart C Section 15.231	2024	Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.
ANSI C63.10	2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

Requirement – Test case	Basic standard(s)	Verdict	Remark
Field strength of fundamental	FCC 15.231(b)(1)	PASS	Test data please refer to appendix
Field strength of spurious emissions	FCC 15.231(b)(1)(2),FCC 15.209	PASS	
20dB Bandwidth	FCC 15.231(c)	PASS	
Duration Time	FCC 15.231(a)(1)	PASS	

3.4 Test Facility

USA : FCC Designation Number: CN1199

4 TEST RESULTS

4.1 Field strength of fundamental

VERDICT: PASS

4.1.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.231	
Fundamental frequency (MHz)	Field strength of fundamental (μ V/m)	Field strength of fundamental (dB μ V/m)
40.66-40.70	2250	67.04
70-130	1250	61.93
130-174	1250-3750	61.93-71.48 ¹⁾
174-260	3750	71.48
260-470	3750-12500	71.48-81.93 ¹⁾
Above 470	12500	81.93

Note 1) : Linear interpolations

The field intensity in micro-volts per meter can then be determined by the following equation: $FI(V/m) = 10FI(dBV/m) / 20$ The FCC specified emission limits were calculated according the EUT operating frequency and obtained by following linear interpolation equations:

For fundamental frequency:

$$f_{EUT} : \text{EUT Operating Frequency Emission Limit (V/m)} = [f_{EUT}(\text{MHz}) - 260(\text{MHz})] \times \{ [12500(\text{V/m}) - 3750(\text{V/m})] / [470(\text{MHz}) - 260(\text{MHz})] \} + 3750(\text{V/m})$$

Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209 limit in the table below has to be followed.

Note:


(1) The tighter limit applies at the band edges.

(2) Emission level (dBuV/m)=20log Emission level (uV/m)


Fundamental frequency	Field strength of Fundamental
433.66 MHz	AV: 80.82 dBuV/m at 3m distance
	PK:100.82 dBuV/m at 3m distance
434.18 MHz	AV: 80.83 dBuV/m at 3m distance
	PK:100.83 dBuV/m at 3m distance

4.1.2 Test Setup

30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



4.1.3 Test Procedure

	References Rule	Chapter	Description
☒	ANSI C63.10	11.12	Emissions in restricted frequency bands
☒	☒ ANSI C63.10	11.12.1	Radiated emission measurements
☒	☒ ANSI C63.10	11.12.2.7	Radiated spurious emission test
☒	☒ ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☒	☒ ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☒	☒ ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.2 Field strength of spurious emissions**VERDICT: PASS****4.2.1 Limit**

Standard			FCC 15.231(b)(1)(2)
Fundamental frequency (MHz)	Field strength of spurious emission (μ V/m)	Field strength of spurious emission (dB μ V/m)	
40.66-40.70	225	47.04	
70-130	125	41.93	
130-174	125-375	41.93-51.48 _(Note 1)	
174-260	375	51.48	
260-470	375-1250	51.48-61.93 _(Note 1)	
Above 470	1250	61.93	

Note 1: Linear interpolations

The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

Intentional radiators operating under the provisions of this section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in §15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

FCC 15.209			
Frequency (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88-216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)

Note 2: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 3: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

RSS-Gen section 8.9

General field strength limits at frequencies above 30MHz

Frequency (MHz)	Field strength (μ V/m at 3m)
30 -88	100
88-216	150
216 - 960	200
Above 960	500


General field strength limits at frequencies below 30MHz

Frequency	Magnetic Field strength(H-Field) (μ A/m)	Measurement distance (m)
9 -490 kHz	6.37/F (F in kHz)	300
490 -1705 kHz	63.7/F (F in kHz)	30
1.705 – 30 MHz	0.08	30


Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector

4.2.2 Test Setup

30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



4.2.3 Test Procedure


	References Rule	Chapter	Description
☒	ANSI C63.10	11.12	Emissions in restricted frequency bands
☒	ANSI C63.10	11.12.1	Radiated emission measurements
☒	ANSI C63.10	11.12.2.7	Radiated spurious emission test
☒	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☒	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.3 DTS Bandwidth

VERDICT: PASS

4.3.1 Limit	
Standard	FCC 15.231(c)
The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.	
Standard	RSS-Gen Issue5 (6.7)
For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).	

4.3.2 Test Setup




4.3.3 Test Procedure			
	Reference Rule	Chapter	Description
☒	ANSI C63.10	6.9	Occupied bandwidth tests
☒	ANSI C63.10	6.9.2	Occupied bandwidth—relative measurement procedure
☒	ANSI C63.10	6.9.3	Occupied bandwidth—power bandwidth (99%) measurement procedure

4.4 Duration Time**VERDICT: PASS****4.4.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.247 (b)(3)

(1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.


4.4.2 Test Setup**4.4.3 Test Procedure**

1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT.
2. Set the EUT to proper test channel.
3. Single scan the transmission, and read the transmission time.

5 TEST SETUP PHOTO AND EUT PHOTO


Remark: The test setup photo and EUT Photo please see appendix.

Appendix A-TEST DATA: Field strength of fundamental
Operating



Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	434.40	63.3	79.88	16.570	-	-	PK	Horizo	NA

Operating




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	434.40	49.4	65.93	16.570	-	-	PK	Vertic	NA

Note 1:
We have evaluated three orthogonal positions (X , Y , Z) and the position with the highest emission level(X Axis) was recorded and shown in the report.

Appendix B-TEST DATA: Field strength of spurious emissions

Operating

Test Graph




Data List

NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	1737.58	56.3	34.52	-21.740	74.00	39.48	PK	Horizo	PASS
2	1738.11	51.4	29.63	-21.730	54.00	24.37	AV	Horizo	PASS
3	5212.91	51.4	43.46	-7.940	74.00	30.54	PK	Horizo	PASS
4	5213.98	46.4	38.45	-7.940	54.00	15.55	AV	Horizo	PASS
5	5647.13	49.0	42.71	-6.320	74.00	31.29	PK	Horizo	PASS
6	5647.66	44.4	38.11	-6.310	54.00	15.89	AV	Horizo	PASS
7	6082.41	48.7	43.53	-5.140	74.00	30.47	PK	Horizo	PASS
8	6082.94	41.2	36.07	-5.130	54.00	17.93	AV	Horizo	PASS
9	6516.63	47.1	43.85	-3.260	74.00	30.15	PK	Horizo	PASS
10	6517.16	43.3	40.06	-3.260	54.00	13.94	AV	Horizo	PASS
11	6950.84	48.2	45.61	-2.580	74.00	28.39	PK	Horizo	PASS
12	6950.84	43.0	40.37	-2.580	54.00	13.63	AV	Horizo	PASS
13	7383.99	47.4	46.00	-1.360	74.00	28.00	PK	Horizo	PASS
14	7385.06	43.5	42.15	-1.350	54.00	11.85	AV	Horizo	PASS
15	10425.64	45.5	47.15	1.660	74.00	26.85	PK	Horizo	PASS
16	10427.24	41.3	42.94	1.660	54.00	11.06	AV	Horizo	PASS

Operating

Test Graph




Data List

NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	1711.41	58.5	36.44	-22.020	74.00	37.56	PK	Vertic	PASS
2	1711.94	53.5	31.48	-22.010	54.00	22.52	AV	Vertic	PASS
3	5213.44	52.0	44.06	-7.940	74.00	29.94	PK	Vertic	PASS
4	5213.98	48.3	40.33	-7.940	54.00	13.67	AV	Vertic	PASS
5	6081.88	43.4	38.31	-5.130	54.00	15.69	AV	Vertic	PASS
6	6082.41	49.6	44.49	-5.140	74.00	29.51	PK	Vertic	PASS
7	6516.09	49.5	46.25	-3.260	74.00	27.75	PK	Vertic	PASS
8	6517.16	44.8	41.56	-3.260	54.00	12.44	AV	Vertic	PASS
9	7385.06	49.1	47.78	-1.350	74.00	26.22	PK	Vertic	PASS
10	7385.59	44.8	43.45	-1.340	54.00	10.55	AV	Vertic	PASS
11	8254.02	43.0	41.28	-1.670	54.00	12.72	AV	Vertic	PASS
12	8254.56	47.4	45.76	-1.670	74.00	28.24	PK	Vertic	PASS
13	8688.77	46.9	45.86	-1.000	74.00	28.14	PK	Vertic	PASS
14	8689.31	41.3	40.32	-1.000	54.00	13.68	AV	Vertic	PASS
15	10425.64	45.0	46.63	1.660	74.00	27.37	PK	Vertic	PASS
16	10426.17	39.8	41.44	1.660	54.00	12.56	AV	Vertic	PASS

Operating

Test Graph




Data List

NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	49.64	13.3	28.22	14.900	40.00	11.78	PK	Horizo	PASS
2	96.45	14.9	26.89	12.010	43.50	16.61	PK	Horizo	PASS
3	247.52	14.6	27.74	13.150	46.00	18.26	PK	Horizo	PASS
4	351.80	14.4	29.81	15.420	46.00	16.19	PK	Horizo	PASS
5	723.79	15.4	36.32	20.880	46.00	9.68	PK	Horizo	PASS
6	868.81	21.0	43.41	22.400	46.00	2.59	PK	Horizo	PASS

Operating

Test Graph



Data List

NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	30.49	22.3	35.19	12.930	40.00	4.81	PK	Vertic	PASS
2	75.35	21.8	31.72	9.880	40.00	8.28	PK	Vertic	PASS
3	108.33	16.8	29.05	12.270	43.50	14.45	PK	Vertic	PASS
4	187.87	13.8	24.75	10.970	43.50	18.75	PK	Vertic	PASS
5	284.63	13.3	27.09	13.760	46.00	18.91	PK	Vertic	PASS
6	645.95	15.6	35.61	20.000	46.00	10.39	PK	Vertic	PASS


Note:

1. Level = Reading + Factor(Probe+Cable-Amp).
2. Margin = Limit – level
3. The test frequency range, 9kHz~30MHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report.
4. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.
5. As the radiated emission was performed, so conducted emission was not tested.
6. We have evaluated three orthogonal positions (X , Y , Z) and the position with the highest emission level(X Axis) was recorded and shown in the report.

Appendix C-TEST DATA: 20dB Bandwidth

Mode Test Freq. (MHz)	99% Occupied Bandwidth (kHz)	20dB Occupied Bandwidth (kHz)	Limit (kHz)	Result
434.42	92.94	98.58	Within band	Pass

Appendix D-TEST DATA: Duration Time



The End