



FCC LISTED, REGISTRATION
NUMBER: 720267

ISED LISTED REGISTRATION
NUMBER 4621A-2

Informe de ensayo nº:
Test report No:

NIE: 54090RRF.002

Test report

USA FCC Part 15.247, 15.209

CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

Identificación del objeto ensayado.....: Identification of item tested	Wireless electronic device with integrated locking system for light weapon
Marca Trademark	Radetec
Modelo y/o referencia tipo Model and /or type reference	Lock Attached Component (LAC) for AR-15
Other identification of the product	FCC ID: 2AMSYLACP0141 IC: 23746-LACP0141
Final HW version	1.0
Final SW version	1.0
Características Features	Not provided data
Solicitante Applicant	RADE TECNOLOGÍAS, S.L. Av. Diagonal Plaza, 14 Nave 61, 50197 Zaragoza (Spain)
Método de ensayo solicitado, norma.....: Test method requested, standard	USA FCC Part 15.247 10-1-17 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 10-1-17 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 4 (November 2014). Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Resultado.....: Summary	IN COMPLIANCE
Aprobado por (nombre / cargo y firma) Approved by (name / position & signature)	A. Llamas RF Lab. Manager 
Fecha de realización Date of issue	2018-04-23
	Firmado digitalmente por ALEJANDRO LLAMAS RODRIGUEZ Fecha: 2018.04.23 17:16:06 +02'00'

Formato de informe No.: Report template No	
	FDT08_20

Index

Competences and guarantees.....4

General conditions.....4

Uncertainty4

Usage of samples.....5

Test sample description5

Identification of the client5

Testing period.....5

Environmental conditions.....6

Remarks and comments.....7

Testing verdicts8

Appendix A – Test results.9

Competences and guarantees

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

DEKRA Testing and Certification is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: ISED 4621A-2.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification internal document PODT000.

Usage of samples

Samples undergoing test have been selected by: **the client**

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
54090/037	Wireless electronic device with integrated locking system for light weapon	Lock Attached Component (LAC) for AR-15	---	2018-02-21
54090/047	Battery	NP-BX1	---	2018-02-21

1. Sample S/01 has undergone following test(s).
All radiated tests indicated in appendix A.

Sample S/02 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
54090/051	Wireless electronic device with integrated locking system for light weapon	Lock Attached Component (LAC) for AR-15	---	2018-03-01

1. Sample S/02 has undergone following test(s).
All conducted tests indicated in appendix A.

Test sample description

The test sample consists of a device embedded in the firearm with an integrated locking device that enables the locking to be activated wirelessly and remotely.

The device is designed for the AR-15 platform. The system is designed to ensure that the shooting range instructor user has full control over all the weapons of the range.

Identification of the client

RADE TECNOLOGÍAS, S.L.

Av. Diagonal Plaza, 14 Nave 61, 50197 Zaragoza (Spain)

Testing period

The performed test started on 2018-02-22 and finished on 2018-03-02.

The tests have been performed at DEKRA Testing and Certification.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω
Normal site attenuation (NSA)	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
Field homogeneity	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar
Shielding effectiveness	> 100 dB
Electric insulation	> 10 kΩ
Reference resistance to earth	< 1 Ω

Remarks and comments

1; The tests have been performed by the technical personnel: Carlos Alberto Contreras.

2: Used instrumentation:

Conducted Measurements

		Last Cal. date	Cal. due date
1.	Spectrum analyser Rohde & Schwarz FSV40	2017/07	2019/07
2.	Power supply DC 30 V/ 5 A U8002A KEYSIGHT TECHNOLOGIES	---	---
3.	Digital Multimeter Fluke 179	2017/05	2018/05

Radiated Measurements

		Last Cal. date	Cal. due date
1.	Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2.	BiconicalLog antenna ETS LINDGREN 3142E	2017/07	2020/04
3.	Multi Device Controller EMCO 2090	N.A.	N.A.
4.	Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2016/11	2019/11
5.	Broadband Horn antenna 18-40 GHz SCHWARZBECK BBHA 9170	2017/03	2020/03
6.	EMI Test Receiver R&S ESU 40	2016/03	2018/03
7.	Spectrum analyser Rohde & Schwarz FSV40	2017/07	2019/07
8.	RF pre-amplifier 30 MHz-6 GHz BONN BLNA 0360-01N	2017/07	2018/07
9.	RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-3A	2017/05	2018/05

Testing verdicts

Not applicable	N/A
Pass	P
Fail	F
Not measured	N/M

FCC PART 15.247 / RSS-247 PARAGRAPH		VERDICT			
		NA	P	F	NM
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a)	6 dB Bandwidth		P		
Section 15.247 Subclause (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain		P		
Section 15.247 Subclause (d) / RSS-247 5.5	Emission limitations conducted (Transmitter)		P		
Section 15.247 Subclause (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)		P		
Section 15.247 Subclause (e) / RSS-247 5.2. (b)	Power spectral density		P		
Section 15.247 Subclause (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)		P		

Appendix A – Test results.

INDEX

TEST CONDITIONS	11
Occupied Bandwidth	13
Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a). 6 dB Bandwidth	15
Section 15.247 Subclause (b) / RSS-247 5.4. (d). Maximum output power and antenna gain	17
Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter)	19
Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)	21
Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density	23

TEST CONDITIONS

Power supply (V):

$V_{\text{nominal}} = 3.6 \text{ Vdc}$

Type of power supply = Internal battery.

Type of antenna: Internal antenna.

Declared Gain for antenna: +0.5 dBi.

TEST FREQUENCIES:

Lowest channel: 911.72 MHz

Highest channel: 918.20 MHz

The test set-up was made in accordance to the general provisions of FCC DTS Measurement 558074 D01 DTS Meas Guidance v04 dated 04/05/2017.

The sample was used to configure the EUT to continuously transmit at a specified output power in all channels.

CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is directly connected to the spectrum analyzer.



RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-10 GHz (1 GHz-18 GHz Double ridge horn antenna).


For radiated emissions in the range 1 GHz-10 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission.


It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

Radiated measurements setup $f < 1$ GHz



Radiated measurements setup $f > 1$ GHz




Occupied Bandwidth

RESULTS


(see next plots).

	Lowest frequency 911.72 MHz	Highest frequency 918.2 MHz
99% bandwidth (kHz)	587.333	556.533
-26 dBc bandwidth (kHz)	697.200	649.333
Measurement uncertainty (kHz)	<±0.23	

Lowest Channel



Highest channel



Section 15.247 Subclause (a) (2) / RSS-247 5.2. (a). 6 dB Bandwidth

SPECIFICATION

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS


6 dB Bandwidth (see next plots).

	Lowest frequency 911.72 MHz	Highest frequency 918.2 MHz
6 dB Spectrum bandwidth (KHz)	562.400	553.000
Measurement uncertainty (kHz)	<±1.03	


Verdict: PASS

6 dB BANDWIDTH.

Lowest Channel



Highest channel



Section 15.247 Subclause (b) / RSS-247 5.4. (d). Maximum output power and antenna gain

SPECIFICATION

For systems using digital modulation in the 902-928 MHz band: 1 watt (30 dBm).
The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

RESULTS

The maximum peak conducted output power was measured using the method according to point 9.1.1. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

MAXIMUM OUTPUT POWER. See next plots.


Declared Gain for antenna: +0.5 dBi.

	Lowest frequency 911.72 MHz	Highest frequency 918.2 MHz
Maximum conducted power (dBm)	11.11	11.11
Maximum EIRP power (dBm)	11.61	11.61
Measurement uncertainty (dB)	<±1.20	


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

Lowest Channel



Highest Channel



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations conducted (Transmitter)

SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

RESULTS:

Reference Level Measurement

	Lowest frequency 911.72 MHz	Highest frequency 918.2 MHz
Reference Level Measurement (dBm)	10.99	10.99
Measurement uncertainty (dB)	<±1.20	


RESULTS:

Lowest frequency 911.72 MHz	Limit (dBm)
All peaks are more than 20 dB below the limit.	-9.01

Highest frequency 918.20 MHz	Limit (dBm)
All peaks are more than 20 dB below the limit.	-9.01


Verdict: PASS

Lowest Channel



Note: The peak shown in the plot above the limit is the carrier frequency.

Highest channel



Note: The peak shown in the plot above the limit is the carrier frequency.

Section 15.247 Subclause (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)


SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

RESULTS:

1. LOW FREQUENCY SECTION CONDUCTED.

See next plot.




Measurement uncertainty (dB)	< ±1.20
------------------------------	---------

Verdict: PASS

2. HIGH FREQUENCY SECTION. CONDUCTED.

See next plot.



Measurement uncertainty (dB)	< ±1.20
------------------------------	---------

Verdict: PASS

Section 15.247 Subclause (e) / RSS-247 5.2. (b) Power spectral density

SPECIFICATION

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

The maximum power spectral density level in the fundamental emission was measured using the method PKPSD (Peak PSD) according to point 10.2. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v04 dated 05/04/2017.


Power spectral density (see next plots).

	Lowest frequency 911.72 MHz	Highest frequency 918.2 MHz
Power spectral density (dBm)	7.83	7.83
Measurement uncertainty (dB)	<±1.20	


Verdict: PASS

Power spectral density.

Lowest Channel



Highest channel



Section 15.247 Subclause (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-10 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz-1000 MHz.

No radiated spurious signals were detected at less than 20 dB respect to the limit for both the lowest and highest operating channels.

Frequency range 1 GHz-10 GHz.

The results in the next tables show the maximum measured levels in the 1-10 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB μ V/m at 3 m) are measured with AVG detector for checking compliance with the average limit.

1.1. CHANNEL LOWEST (911.72 MHz). Out-of-band spurious emissions in the 1-10 GHz range.

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
1.82335	V	Peak	46.42	± 4.87
2.73565	H	Peak	46.22	± 4.87
3.64735	H	Peak	46.35	± 4.87
4.55965	H	Peak	46.85	± 4.87
5.47045	H	Peak	46.81	± 4.87
6.38065	H	Peak	50.97	± 4.87
7.29205	V	Peak	46.22	± 4.87
8.20375	H	Peak	44.97	± 4.87


1.2. CHANNEL HIGHEST (918.20 MHz). Out-of-band spurious emissions in the 1-10 GHz range.

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB μ V/m)	Measurement Uncertainty (dB)
1.83625	V	Peak	44.39	± 4.87
2.75455	H	Peak	47.20	± 4.87
3.67195	H	Peak	45.55	± 4.87
4.59145	H	Peak	45.89	± 4.87
5.51005	H	Peak	45.41	± 4.87
6.42625	H	Peak	49.16	± 4.87
7.34425	H	Peak	44.18	± 4.87
8.26255	V	Peak	45.97	± 4.87

Verdict: PASS


FREQUENCY RANGE 30 MHz-1000 MHz.

CHANNEL LOWEST



Note: The carrier was attenuated using a Notch filter.


CHANNEL HIGHEST



Note: The carrier was attenuated using a Notch filter.

FREQUENCY RANGE 1 GHz to 10 GHz.

CHANNEL LOWEST



CHANNEL HIGHEST

