

Compatible Electronics
1050 Lawrence Drive, Newbury Park , CA 91320

Power Density Based 20 separation distance (cm)

914.9	Frequency (MHz)
19.04	Power to Antenna (dBm)
1.8	Antenna gain (dBi)

FCC

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

0.024
Power Density (mW/cm²)

Canada **FCC**
0.277 0.609933 Limit (mW/cm²)
0.253 0.586 Margin
0.087 0.040 MPE Ratio

(General Population)

Device FCC ID 2AMUGLR1110TRK
Date 10/29/2020
Prepared By Reynald Ramirez

Canada

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

Compatible Electronics
 1050 Lawrence Drive, Newbury Park , CA 91320

Power Density Based 20 separation distance (cm)

2480	Frequency (MHz)
6.369	Power to Antenna (dBm)
-0.5	Antenna gain (dBi)

FCC

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

0.024
 Power Density (mW/cm2)

Canada FCC

0.547 1 Limit (mW/cm2)

0.523 0.976 Margin

0.044 0.024 MPE Ratio

(General Population)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Device FCC ID 2AMUGLR1110TRK

Date 10/29/2020

Prepared By Reynald Ramirez

Canada

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}
Note: f is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

Compatible Electronics
1050 Lawrence Drive, Newbury Park , CA 91320

MPE Ratio of simultaneous operation based on highest power density compared to the **FCC** limits

Device FCC ID	2AMUGLR1110TRK
Date	10/29/2020
Prepared By	R. Ramirez

e.i.r.p			
19.04	0.04	Ratio 1	900 MHz
6.396	0.024	Ratio 2	2.4 GHz
		Ratio 3	
	0.064	Total	Ratio Must be <=1

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modeled, or measured field strengths or power density.

447498 D01

0.936 Remaining

Compatible Electronics
1050 Lawrence Drive, Newbury Park , CA 91320

MPE Ratio of simultaneous operation based on highest power density compared to the **ISED** limits

Device FCC ID	2AMUGLR1110TRK
Date	10/29/2020
Prepared By	R. Ramirez

e.i.r.p			
19.04	0.087	Ratio 1	900 MHz
6.396	0.044	Ratio 2	2.4 GHz
		Ratio 3	
	0.131	Total	Ratio Must be <=1

0.869 Remaining

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modeled, or measured field strengths or power density.

447498 D01