



Radio Test Report

Report No.:STS2512072W01

Issued for

Chengdu Meross Technology Co.,Ltd.

No.201 & 202, 2F, Building 8, No.99 Tianhua 1st Road (Tianfu Software Park B), Gaoxin District, Chengdu, Sichuan, China

Product Name: Smart Presence Sensor

Brand Name: meross, Refoss, Flysocks, Meross Smart, RefossSmart

Model Name: MS605

Series Model(s): MS600, MS615, MS620, MS625

FCC ID: 2AMUU-MS605

Test Standards: FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name..... : Chengdu Meross Technology Co.,Ltd.
Address : No.201 & 202, 2F, Building 8, No.99 Tianhua 1st Road (Tianfu Software Park B), Gaoxin District, Chengdu, Sichuan, China
Manufacturer's Name : Chengdu Meross Technology Co., Ltd.
Address : No.201 & 202, 2F, Building 8, No.99 Tianhua 1st Road (Tianfu Software Park B), Gaoxin District, Chengdu, Sichuan, China

Product Description

Product Name : Smart Presence Sensor
Brand Name : meross, Refoss, Flysocks, Meross Smart, RefossSmart
Model Name : MS605
Series Model(s) : MS600, MS615, MS620, MS625

Test Standards : FCC Part15.247

Test Procedure : ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the IC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test..... :

Date of receipt of test item : 10 Dec. 2025

Date (s) of performance of tests..... : 10 Dec. 2025 ~ 08 Jan. 2026

Date of Issue..... : 08 Jan. 2026

Test Result..... : **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	7
1.1 TEST FACTORY	8
1.2 MEASUREMENT UNCERTAINTY	8
2. GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF THE EUT	9
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	10
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.6 EQUIPMENTS LIST	12
3. EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.2 TEST PROCEDURE	14
3.3 TEST SETUP	14
3.4 EUT OPERATING CONDITIONS	14
3.5 TEST RESULTS	14
4. RADIATED EMISSION MEASUREMENT	15
4.1 RADIATED EMISSION LIMITS	15
4.2 TEST PROCEDURE	17
4.3 TEST SETUP	18
4.4 EUT OPERATING CONDITIONS	18
4.5 FIELD STRENGTH CALCULATION	19
4.6 TEST RESULTS	20
5. DUTY CYCLE	41
5.1 TEST STANDARD	41
5.2 TEST PROCEDURE	41
5.3 DEVIATION FROM STANDARD	41
5.4 TEST SETUP	41
5.6 TEST RESULTS	41
6. CONDUCTED SPURIOUS & BAND EDGE EMISSION	42
6.1 LIMIT	42
6.2 TEST PROCEDURE	42
6.3 TEST SETUP	42



Table of Contents	Page
6.4 EUT OPERATION CONDITIONS	42
6.5 TEST RESULTS	42
7. POWER SPECTRAL DENSITY TEST	43
7.1 LIMIT	43
7.2 TEST PROCEDURE	43
7.3 TEST SETUP	43
7.4 EUT OPERATION CONDITIONS	43
7.5 TEST RESULTS	43
8. BANDWIDTH TEST	44
8.1 LIMIT	44
8.2 TEST PROCEDURE	44
8.3 TEST SETUP	44
8.4 EUT OPERATION CONDITIONS	44
8.5 TEST RESULTS	44
9. PEAK OUTPUT POWER TEST	45
9.1 LIMIT	45
9.2 TEST PROCEDURE	45
9.3 TEST SETUP	45
9.4 EUT OPERATION CONDITIONS	45
9.5 TEST RESULTS	45
10. ANTENNA REQUIREMENT	46
10.1 STANDARD REQUIREMENT	46
10.2 EUT ANTENNA	46
APPENDIX 1-TEST DATA	47
DUTY CYCLE	47
MAXIMUM PEAK CONDUCTED OUTPUT POWER	51
-6DB BANDWIDTH	55
OCCUPIED CHANNEL BANDWIDTH	59
MAXIMUM POWER SPECTRAL DENSITY LEVEL	63
BAND EDGE	67
CONDUCTED RF SPURIOUS EMISSION	72



Table of Contents

Page

APPENDIX 2- EUT TEST PHOTO

79

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	08 Jan. 2026	STS2512072W01	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

Note:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.751\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.888\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.48\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 2.52\text{dB}$
5	All emissions, radiated 1G-18GHz	$\pm 3.48\text{dB}$
6	All emissions, radiated >18GHz	$\pm 4.18\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.48\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.52\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.6\%$
10	Power Spectral Density, conducted	$\pm 1.214\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart Presence Sensor	
Brand Name	meross, Refoss, Flysocks, Meross Smart, RefossSmart	
Model Name	MS605	
Series Model(s)	MS600, MS615, MS620, MS625	
Model Difference	Only different in model name	
Product Description	The EUT is a Smart Presence Sensor	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Configuration:	LE(Support 1M PHY, 2M PHY)
	Number Of Channel:	40
	Antenna Type:	Integrated
	Antenna Gain (dBi)	1.5
Channel List	Please refer to the Note 3.	
Power Rating	Input: 3VDC (Battery: CR123A)	
Adapter	N/A	
Battery	Model: CR123A Brand: N/A Rated Voltage: 3V	
Hardware version number	N/A	
Software version number	N/A	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Worst Mode	Description	Data/Modulation
Mode 1	TX CH00(2402MHz)	1M PHY /GFSK
Mode 2	TX CH19(2440MHz)	1M PHY /GFSK
Mode 3	TX CH39(2480MHz)	1M PHY /GFSK

Worst Mode	Description	Data/Modulation
Mode 4	TX CH00(2402MHz)	2M PHY /GFSK
Mode 5	TX CH19(2440MHz)	2M PHY /GFSK
Mode 6	TX CH39(2480MHz)	2M PHY /GFSK

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

(2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/60Hz is shown in the report.

2.3 TEST SOFTWARE AND POWER LEVEL


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
BLE(With 2M PHY)	BLE_1M PHY	GFSK	1.5	2	PUTTY
	BLE_2M PHY	GFSK		2	




2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



RF Conducted Test



2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Notebook	DELL	Inspiron 3501	N/A
C-1	Serial port board	XES	WTYZK	N/A
C-2	USB Cable	MI	RYEW3A	N/A

Item	Equipment	Mfr/Brand	Length	Note
C-2	Shielded	NO	150cm	N/A

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Pre-Amplifier(0.1M-3GHz)	EM	EM330	060665	2025.02.22	2026.02.21
Pre-Amplifier(1 G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18 G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2025.02.22	2026.02.21
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2027.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBEC K	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Filter Box	BALUN Technology	SU319E	BL-SZ1530051	N/A	N/A
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENG ENG	DPS-305AF	17064939	2025.09.22	2026.09.21
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2025.02.22	2026.02.21
Power Meter	Keysight	U2021XA	MY56120038	2025.09.23	2026.09.22
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
Temperature& Humidity test chamber	Safety test	AG80L	171200018	2025.02.22	2026.02.21
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	MW	MTS 8310_2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “*” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.5 TEST RESULTS

Note: product is battery operated and conducted emission test is not applicable.



4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2475 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

Please refer to section 3.4 of this report.



4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



4.6 TEST RESULTS

(Between 9KHz – 30 MHz)

Temperature:	23.4°C	Relative Humidity:	60%
Test Voltage:	DC 3V	Polarization:	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



(30MHz -1000MHz)

1M PHY


Temperature:	23.4°C	Relative Humidity:	60%
Test Voltage:	DC 3V	Phase:	Horizontal
Test Mode:	Mode 1/2/3 (Mode 3 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	95.9600	58.40	-20.67	37.73	43.50	-5.77	peak
2	155.1300	58.81	-18.63	40.18	43.50	-3.32	peak
3	239.5200	56.73	-18.10	38.63	46.00	-7.37	peak
4	288.0200	50.78	-15.26	35.52	46.00	-10.48	peak
5	431.5800	49.41	-10.13	39.28	46.00	-6.72	peak
6	799.2100	39.78	-2.04	37.74	46.00	-8.26	peak

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.

80.0 dBuV/m






Temperature:	23.4°C	Relative Humidity:	60%
Test Voltage:	DC 3V	Phase:	Vertical
Test Mode:	Mode 1/2/3 (Mode 3 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	71.7100	60.67	-24.56	36.11	40.00	-3.89	peak
2	119.2400	55.90	-18.38	37.52	43.50	-5.98	peak
3	143.4900	57.22	-18.23	38.99	43.50	-4.51	peak
4	239.5200	54.54	-18.10	36.44	46.00	-9.56	peak
5	431.5800	45.21	-10.13	35.08	46.00	-10.92	peak
6	800.1800	36.33	-2.05	34.28	46.00	-11.72	peak

Remark:

1. $\text{Margin} = \text{Result} (\text{Result} = \text{Reading} + \text{Factor}) - \text{Limit}$
2. $\text{Factor} = \text{Antenna factor} + \text{Cable attenuation factor (cable loss)} - \text{Amplifier gain}$
3. All modes have been tested, only show the worst case.






2M PHY

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 3V	Phase:	Horizontal
Test Mode:	Mode 4/5/6 (Mode 4 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	71.7100	53.82	-24.56	29.26	40.00	-10.74	peak
2	119.2400	55.63	-18.38	37.25	43.50	-6.25	peak
3	156.1000	58.57	-18.66	39.91	43.50	-3.59	peak
4	198.7800	59.58	-21.12	38.46	43.50	-5.04	peak
5	431.5800	48.36	-10.13	38.23	46.00	-7.77	peak
6	800.1800	38.72	-2.05	36.67	46.00	-9.33	peak

Remark:

1. Margin = Result (Result = Reading + Factor) - Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain
3. All modes have been tested, only show the worst case.






Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 3V	Phase:	Vertical
Test Mode:	Mode 4/5/6 (Mode 4 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	71.7100	60.74	-24.56	36.18	40.00	-3.82	peak
2	119.2400	56.34	-18.38	37.96	43.50	-5.54	peak
3	143.4900	56.55	-18.23	38.32	43.50	-5.18	peak
4	239.5200	55.25	-18.10	37.15	46.00	-8.85	peak
5	480.0800	43.99	-8.65	35.34	46.00	-10.66	peak
6	799.2100	38.41	-2.04	36.37	46.00	-9.63	peak

Remark:

1. $\text{Margin} = \text{Result} (\text{Result} = \text{Reading} + \text{Factor}) - \text{Limit}$
2. $\text{Factor} = \text{Antenna factor} + \text{Cable attenuation factor (cable loss)} - \text{Amplifier gain}$
3. All modes have been tested, only show the worst case.





(1GHz-25GHz) Spurious emission Requirements

1M PHY

Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
Low Channel (GFSK/2402 MHz)								
2061.00	49.79	0.83	74	-24.21	Peak	324.2	Horizontal	Pass
2061.00	33.54	0.83	54	-20.46	AV	324.2	Horizontal	Pass
2662.50	52.20	3.98	74	-21.80	Peak	158.4	Horizontal	Pass
2662.50	38.28	3.98	54	-15.72	AV	158.4	Horizontal	Pass
4960.00	46.69	-5.99	74	-27.31	Peak	56.8	Horizontal	Pass
4960.00	40.64	-5.99	54	-13.36	AV	56.8	Horizontal	Pass
7437.25	50.51	-1.53	74	-23.49	Peak	40.9	Horizontal	Pass
7437.25	42.57	-1.53	54	-11.43	AV	40.9	Horizontal	Pass
10676.75	51.39	1.31	74	-22.61	Peak	21.9	Horizontal	Pass
10676.75	40.80	1.31	54	-13.20	AV	21.9	Horizontal	Pass
14414.00	54.87	6.89	74	-19.13	Peak	290.7	Horizontal	Pass
14414.00	44.50	6.89	54	-9.50	AV	290.7	Horizontal	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
2060.70	48.72	0.78	74	-25.28	Peak	324.6	Horizontal	Pass
2060.70	32.74	0.78	54	-21.26	AV	324.6	Horizontal	Pass
2662.18	50.58	3.95	74	-23.42	Peak	159.1	Horizontal	Pass
2662.18	36.48	3.95	54	-17.52	AV	159.1	Horizontal	Pass
4959.55	46.04	-6.03	74	-27.96	Peak	57.0	Horizontal	Pass
4959.55	38.67	-6.03	54	-15.33	AV	57.0	Horizontal	Pass
7437.04	49.99	-1.55	74	-24.01	Peak	41.2	Horizontal	Pass
7437.04	40.75	-1.55	54	-13.25	AV	41.2	Horizontal	Pass
10676.29	49.41	1.27	74	-24.59	Peak	22.2	Horizontal	Pass
10676.29	39.30	1.27	54	-14.70	AV	22.2	Horizontal	Pass
14413.69	53.12	6.86	74	-20.88	Peak	291.0	Horizontal	Pass
14413.69	43.71	6.86	54	-10.29	AV	291.0	Horizontal	Pass




High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
2060.73	49.04	0.80	74	-24.96	Peak	324.7	Horizontal	Pass
2060.73	31.88	0.80	54	-22.12	AV	324.7	Horizontal	Pass
2662.04	50.83	3.94	74	-23.17	Peak	158.8	Horizontal	Pass
2662.04	36.58	3.94	54	-17.42	AV	158.8	Horizontal	Pass
4959.79	45.63	-6.02	74	-28.37	Peak	57.0	Horizontal	Pass
4959.79	39.58	-6.02	54	-14.42	AV	57.0	Horizontal	Pass
7436.96	49.41	-1.57	74	-24.59	Peak	41.5	Horizontal	Pass
7436.96	42.00	-1.57	54	-12.00	AV	41.5	Horizontal	Pass
10676.51	50.35	1.27	74	-23.65	Peak	22.2	Horizontal	Pass
10676.51	39.97	1.27	54	-14.03	AV	22.2	Horizontal	Pass
14413.58	53.30	6.84	74	-20.70	Peak	291.0	Horizontal	Pass
14413.58	43.31	6.84	54	-10.69	AV	291.0	Horizontal	Pass




1GHz-18GHz-H

RF_FCC Test Case_FCC 15C 1GHz-18GHz



18GHz-26GHz-H

100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19392.000	50.10	1.54	51.64	54.00	-2.36	peak
2	20632.000	49.37	2.35	51.72	54.00	-2.28	peak
3	22032.000	47.56	3.45	51.01	54.00	-2.99	peak
4	23280.000	48.01	3.92	51.93	54.00	-2.07	peak
5	24544.000	46.64	4.76	51.40	54.00	-2.60	peak
6	25768.000	45.97	5.74	51.71	54.00	-2.29	peak




Low Channel (GFSK/2402 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1784.00	53.76	-0.69	74	-20.24	Peak	305.7	Vertical	Pass
1784.00	50.09	-0.69	54	-3.91	AV	305.7	Vertical	Pass
2663.50	59.40	3.98	74	-14.60	Peak	82.1	Vertical	Pass
2663.50	46.88	3.98	54	-7.12	AV	82.1	Vertical	Pass
4960.00	44.85	-5.99	74	-29.15	Peak	90.7	Vertical	Pass
4960.00	38.22	-5.99	54	-15.78	AV	90.7	Vertical	Pass
7440.00	49.46	-1.51	74	-24.54	Peak	85.4	Vertical	Pass
7440.00	41.62	-1.51	54	-12.38	AV	85.4	Vertical	Pass
10800.50	51.53	2.04	74	-22.47	Peak	345.1	Vertical	Pass
10800.50	40.81	2.04	54	-13.19	AV	345.1	Vertical	Pass
13910.75	54.67	7.33	74	-19.33	Peak	316.4	Vertical	Pass
13910.75	44.19	7.33	54	-9.81	AV	316.4	Vertical	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1783.62	53.00	-0.76	74	-21.00	Peak	306.2	Vertical	Pass
1783.62	49.13	-0.76	54	-4.87	AV	306.2	Vertical	Pass
2663.10	58.44	3.93	74	-15.56	Peak	82.8	Vertical	Pass
2663.10	45.45	3.93	54	-8.55	AV	82.8	Vertical	Pass
4959.72	44.22	-6.03	74	-29.78	Peak	91.0	Vertical	Pass
4959.72	36.66	-6.03	54	-17.34	AV	91.0	Vertical	Pass
7439.56	48.87	-1.56	74	-25.13	Peak	86.0	Vertical	Pass
7439.56	41.09	-1.56	54	-12.91	AV	86.0	Vertical	Pass
10800.21	50.10	2.00	74	-23.90	Peak	345.3	Vertical	Pass
10800.21	39.20	2.00	54	-14.80	AV	345.3	Vertical	Pass
13910.39	53.90	7.31	74	-20.10	Peak	317.0	Vertical	Pass
13910.39	43.04	7.31	54	-10.96	AV	317.0	Vertical	Pass



High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1783.68	51.90	-0.72	74	-22.10	Peak	306.1	Vertical	Pass
1783.68	49.25	-0.72	54	-4.75	AV	306.1	Vertical	Pass
2663.29	58.67	3.95	74	-15.33	Peak	82.6	Vertical	Pass
2663.29	45.18	3.95	54	-8.82	AV	82.6	Vertical	Pass
4959.66	42.85	-6.04	74	-31.15	Peak	91.3	Vertical	Pass
4959.66	36.41	-6.04	54	-17.59	AV	91.3	Vertical	Pass
7439.79	48.29	-1.54	74	-25.71	Peak	85.6	Vertical	Pass
7439.79	40.52	-1.54	54	-13.48	AV	85.6	Vertical	Pass
10800.29	49.55	1.99	74	-24.45	Peak	345.4	Vertical	Pass
10800.29	39.37	1.99	54	-14.63	AV	345.4	Vertical	Pass
13910.47	53.12	7.31	74	-20.88	Peak	316.6	Vertical	Pass
13910.47	42.52	7.31	54	-11.48	AV	316.6	Vertical	Pass

1GHz-18GHz-V


RE_FCC Test Case_FCC 15C 1GHz-18GHz





18GHz-26GHz-V

100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18392.000	49.60	2.35	51.95	54.00	-2.05	peak
2	19168.000	50.25	1.65	51.90	54.00	-2.10	peak
3	21424.000	49.26	2.89	52.15	54.00	-1.85	peak
4	22248.000	48.81	3.67	52.48	54.00	-1.52	peak
5	23616.000	47.49	4.25	51.74	54.00	-2.26	peak
6	25560.000	46.22	5.67	51.89	54.00	-2.11	peak

Note:

1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor.

2) The frequency above 18GHz emission of peak points that show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



2M PHY

Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
Low Channel (GFSK/2402 MHz)								
1911.50	48.29	-0.13	74	-25.71	Peak	49.3	Horizontal	Pass
1911.50	35.09	-0.13	54	-18.91	AV	49.3	Horizontal	Pass
2664.50	56.69	3.98	74	-17.31	Peak	129.6	Horizontal	Pass
2664.50	42.81	3.98	54	-11.19	AV	129.6	Horizontal	Pass
4803.00	44.79	-7.12	74	-29.21	Peak	99.5	Horizontal	Pass
4803.00	36.67	-7.12	54	-17.33	AV	99.5	Horizontal	Pass
7206.25	52.07	-1.90	74	-21.93	Peak	89.8	Horizontal	Pass
7206.25	44.11	-1.90	54	-9.89	AV	89.8	Horizontal	Pass
9609.75	52.09	0.57	74	-21.91	Peak	103.6	Horizontal	Pass
9609.75	42.05	0.57	54	-11.95	AV	103.6	Horizontal	Pass
14419.50	54.36	6.85	74	-19.64	Peak	303.6	Horizontal	Pass
14419.50	43.83	6.85	54	-10.17	AV	303.6	Horizontal	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1911.09	46.78	-0.19	74	-27.22	Peak	50.0	Horizontal	Pass
1911.09	33.36	-0.19	54	-20.64	AV	50.0	Horizontal	Pass
2664.14	55.36	3.95	74	-18.64	Peak	130.3	Horizontal	Pass
2664.14	40.97	3.95	54	-13.03	AV	130.3	Horizontal	Pass
4802.63	44.19	-7.17	74	-29.81	Peak	100.0	Horizontal	Pass
4802.63	35.41	-7.17	54	-18.59	AV	100.0	Horizontal	Pass
7205.75	50.20	-1.92	74	-23.80	Peak	90.3	Horizontal	Pass
7205.75	43.56	-1.92	54	-10.44	AV	90.3	Horizontal	Pass
9609.25	50.21	0.52	74	-23.79	Peak	104.1	Horizontal	Pass
9609.25	40.23	0.52	54	-13.77	AV	104.1	Horizontal	Pass
14419.21	52.43	6.81	74	-21.57	Peak	304.3	Horizontal	Pass
14419.21	42.99	6.81	54	-11.01	AV	304.3	Horizontal	Pass




High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1911.22	47.20	-0.16	74	-26.80	Peak	50.0	Horizontal	Pass
1911.22	33.16	-0.16	54	-20.84	AV	50.0	Horizontal	Pass
2664.27	55.60	3.94	74	-18.40	Peak	129.8	Horizontal	Pass
2664.27	41.38	3.94	54	-12.62	AV	129.8	Horizontal	Pass
4802.62	43.21	-7.15	74	-30.79	Peak	99.9	Horizontal	Pass
4802.62	36.06	-7.15	54	-17.94	AV	99.9	Horizontal	Pass
7205.97	50.21	-1.92	74	-23.79	Peak	90.1	Horizontal	Pass
7205.97	43.21	-1.92	54	-10.79	AV	90.1	Horizontal	Pass
9609.35	50.40	0.55	74	-23.60	Peak	103.9	Horizontal	Pass
9609.35	40.05	0.55	54	-13.95	AV	103.9	Horizontal	Pass
14419.22	53.08	6.81	74	-20.92	Peak	304.2	Horizontal	Pass
14419.22	43.13	6.81	54	-10.87	AV	304.2	Horizontal	Pass




1GHz-18GHz-H

RF_FCC Test Case_FCC 15C 1GHz-18GHz



18GHz-26GHz-H

100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19056.000	50.38	1.72	52.10	54.00	-1.90	peak
2	20768.000	49.94	2.46	52.40	54.00	-1.60	peak
3	22032.000	48.56	3.45	52.01	54.00	-1.99	peak
4	23208.000	48.22	3.85	52.07	54.00	-1.93	peak
5	23888.000	47.72	4.52	52.24	54.00	-1.76	peak
6	25600.000	46.06	5.68	51.74	54.00	-2.26	peak




Low Channel (GFSK/2402 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1129.00	50.04	-1.71	74	-23.96	Peak	133.0	Vertical	Pass
1129.00	33.16	-1.71	54	-20.84	AV	133.0	Vertical	Pass
2654.50	59.10	3.98	74	-14.90	Peak	90.6	Vertical	Pass
2654.50	45.66	3.98	54	-8.34	AV	90.6	Vertical	Pass
4803.00	44.82	-7.12	74	-29.18	Peak	111.2	Vertical	Pass
4803.00	37.14	-7.12	54	-16.86	AV	111.2	Vertical	Pass
7203.50	50.29	-1.90	74	-23.71	Peak	91.0	Vertical	Pass
7203.50	41.57	-1.90	54	-12.43	AV	91.0	Vertical	Pass
9604.25	52.84	0.57	74	-21.16	Peak	0.0	Vertical	Pass
9604.25	43.28	0.57	54	-10.72	AV	0.0	Vertical	Pass
13952.00	54.88	7.85	74	-19.12	Peak	58.6	Vertical	Pass
13952.00	44.76	7.85	54	-9.24	AV	58.6	Vertical	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1128.67	49.32	-1.77	74	-24.68	Peak	133.4	Vertical	Pass
1128.67	32.51	-1.77	54	-21.49	AV	133.4	Vertical	Pass
2654.07	57.35	3.95	74	-16.65	Peak	91.0	Vertical	Pass
2654.07	44.18	3.95	54	-9.82	AV	91.0	Vertical	Pass
4802.71	42.87	-7.16	74	-31.13	Peak	111.4	Vertical	Pass
4802.71	36.10	-7.16	54	-17.90	AV	111.4	Vertical	Pass
7203.25	49.05	-1.94	74	-24.95	Peak	91.4	Vertical	Pass
7203.25	40.33	-1.94	54	-13.67	AV	91.4	Vertical	Pass
9603.79	51.55	0.55	74	-22.45	Peak	0.5	Vertical	Pass
9603.79	42.56	0.55	54	-11.44	AV	0.5	Vertical	Pass
13951.68	52.96	7.82	74	-21.04	Peak	59.1	Vertical	Pass
13951.68	44.07	7.82	54	-9.93	AV	59.1	Vertical	Pass



High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1128.58	48.25	-1.76	74	-25.75	Peak	133.6	Vertical	Pass
1128.58	32.34	-1.76	54	-21.66	AV	133.6	Vertical	Pass
2654.19	58.25	3.96	74	-15.75	Peak	91.0	Vertical	Pass
2654.19	44.26	3.96	54	-9.74	AV	91.0	Vertical	Pass
4802.58	43.88	-7.14	74	-30.12	Peak	111.6	Vertical	Pass
4802.58	36.53	-7.14	54	-17.47	AV	111.6	Vertical	Pass
7203.09	49.27	-1.93	74	-24.73	Peak	91.7	Vertical	Pass
7203.09	40.43	-1.93	54	-13.57	AV	91.7	Vertical	Pass
9604.01	51.24	0.53	74	-22.76	Peak	0.4	Vertical	Pass
9604.01	41.52	0.53	54	-12.48	AV	0.4	Vertical	Pass
13951.74	54.38	7.81	74	-19.62	Peak	58.9	Vertical	Pass
13951.74	43.05	7.81	54	-10.95	AV	58.9	Vertical	Pass

1GHz-18GHz-V


RE_FCC Test Case_FCC 15C 1GHz-18GHz





18GHz-26GHz-V

100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18728.000	50.46	2.03	52.49	54.00	-1.51	peak
2	20184.000	49.95	1.96	51.91	54.00	-2.09	peak
3	21368.000	49.07	2.86	51.93	54.00	-2.07	peak
4	23256.000	47.76	3.89	51.65	54.00	-2.35	peak
5	24224.000	47.44	4.66	52.10	54.00	-1.90	peak
6	25560.000	46.22	5.67	51.89	54.00	-2.11	peak


Note:

- 1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor.
- 2) The frequency above 18GHz emission of peak points that show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.




4.6 TEST RESULTS (Restricted Bands Requirements)

1M PHY
GFSK-Low
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2369.500	39.32	0.66	39.98	54.00	-14.02	peak
2	2390.000	38.30	0.81	39.11	54.00	-14.89	peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2365.000	40.14	0.62	40.76	54.00	-13.24	peak
2	2390.000	36.45	0.81	37.26	54.00	-16.74	peak

GFSK-High
Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	42.87	1.02	43.89	54.00	-10.11	peak
2	2485.975	41.56	1.02	42.58	54.00	-11.42	peak


Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	41.83	1.02	42.85	74.00	-11.15	peak
2	2486.925	45.57	1.03	46.60	74.00	-7.40	peak




2M PHY
GFSK-Low
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.000	39.56	0.77	40.33	54.00	-13.67	peak
2	2390.000	38.42	0.81	39.23	54.00	-14.77	peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2381.100	39.07	0.75	39.82	54.00	-14.18	peak
2	2390.000	37.61	0.81	38.42	54.00	-15.58	peak

GFSK-High
Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	45.21	1.02	46.23	54.00	-7.77	peak
2	2484.200	43.33	1.03	44.36	54.00	-9.64	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.51	1.02	40.53	54.00	-13.47	peak
2	2484.225	49.52	1.03	50.55	54.00	-3.45	peak



5. DUTY CYCLE

5.1 TEST STANDARD

Please refer to ANSI C63.10-2020 Section 11.6

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Zero
RB	set RBW to the largest available value
VB	$VBW \geq RBW$.
Detector	Peak
Trace	Clear Write
Sweep Time	Auto

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



6. CONDUCTED SPURIOUS & BAND EDGE EMISSION

6.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

6.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

6.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

6.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

6.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



7. POWER SPECTRAL DENSITY TEST

7.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	$\leq 8 \text{ dBm}$ (RBW $\geq 3 \text{ KHz}$)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

7.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



8. BANDWIDTH TEST

8.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

8.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq$ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

8.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



9. PEAK OUTPUT POWER TEST

9.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

9.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW $\geq$ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq$ [3 $\times$ RBW].
- Set span $\geq$ [3 $\times$ RBW].
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

9.3 TEST SETUP



9.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

9.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is Integrated Antenna. It comply with the standard requirement.


**APPENDIX 1-TEST DATA****Duty Cycle**

Condition	Mode	Frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	0	0	100	0	0
NVNT	BLE 1M	2440	0	0	100	0	0
NVNT	BLE 1M	2480	0	0	100	0	0
NVNT	BLE 2M	2402	0	0	100	0	0
NVNT	BLE 2M	2440	0	0	100	0	0
NVNT	BLE 2M	2480	0	0	100	0	0






Duty Cycle NVNT BLE 1M 2480MHz




Duty Cycle NVNT BLE 2M 2402MHz






Duty Cycle NVNT BLE 2M 2440MHz




Duty Cycle NVNT BLE 2M 2480MHz







Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	0.23	<=30	Pass
NVNT	BLE 1M	2440	0.95	<=30	Pass
NVNT	BLE 1M	2480	1.11	<=30	Pass
NVNT	BLE 2M	2402	0.56	<=30	Pass
NVNT	BLE 2M	2440	0.31	<=30	Pass
NVNT	BLE 2M	2480	0.06	<=30	Pass












-6dB Bandwidth

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	0.6856	≥ 0.5	Pass
NVNT	BLE 1M	2440	0.677	≥ 0.5	Pass
NVNT	BLE 1M	2480	0.688	≥ 0.5	Pass
NVNT	BLE 2M	2402	1.331	≥ 0.5	Pass
NVNT	BLE 2M	2440	1.233	≥ 0.5	Pass
NVNT	BLE 2M	2480	1.092	≥ 0.5	Pass












Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	BLE 1M	2402	1.0637
NVNT	BLE 1M	2440	1.0391
NVNT	BLE 1M	2480	1.0658
NVNT	BLE 2M	2402	2.1373
NVNT	BLE 2M	2440	2.1408
NVNT	BLE 2M	2480	2.1064












Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	-13.3	≤ 8	Pass
NVNT	BLE 1M	2440	-11.81	≤ 8	Pass
NVNT	BLE 1M	2480	-11.97	≤ 8	Pass
NVNT	BLE 2M	2402	-14.14	≤ 8	Pass
NVNT	BLE 2M	2440	-14.53	≤ 8	Pass
NVNT	BLE 2M	2480	-14.95	≤ 8	Pass













Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-50.31	<=-20	Pass
NVNT	BLE 1M	2480	-53.86	<=-20	Pass
NVNT	BLE 2M	2402	-29.22	<=-20	Pass
NVNT	BLE 2M	2480	-47.34	<=-20	Pass















Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-42.81	<=-20	Pass
NVNT	BLE 1M	2440	-43.89	<=-20	Pass
NVNT	BLE 1M	2480	-42.37	<=-20	Pass
NVNT	BLE 2M	2402	-37.36	<=-20	Pass
NVNT	BLE 2M	2440	-35.84	<=-20	Pass
NVNT	BLE 2M	2480	-37.06	<=-20	Pass
















APPENDIX 2- EUT TEST PHOTO

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

*****END OF THE REPORT*****