

1 Cover Page

RF Exposure REPORT

Application No.: SHEM2007000791CR
FCC ID: 2AMVQ-WK31
IC: 22969-WK31
Applicant: Hangzhou Virtual And Reality Technology Co.,LTD.
Address of Applicant: Room 901,Building 6,No.1818-2,West Wenyi Road,Yuhang Street,Yuhang District, Hangzhou, Zhejiang Province
Manufacturer: Hangzhou Virtual And Reality Technology Co.,LTD.
Address of Manufacturer: Room 901,Building 6,No.1818-2,West Wenyi Road,Yuhang Street,Yuhang District, Hangzhou, Zhejiang Province


Equipment Under Test (EUT):

EUT Name: Foot Sensor
Model No.: WK311
Trade mark: KATVR
Standard(s) : FCC Rules 47 CFR §2.1093
 KDB447498 D01 General RF Exposure Guidance v06
 RSS-102 Issue 5 March 2019 Amendment 1

Date of Receipt: 2020-07-13
Date of Test: 2020-07-15 to 2020-09-18
Date of Issue: 2020-09-19

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Eric Lin
EMC Lab Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300

中国·江苏·昆山市留学院创业园伟业路10号 邮编 215300

t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn

t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com

Revision Record			
Version	Description	Date	Remark
00	Original	2020-09-19	/

Authorized for issue by:				
		Damon Zhou		
		Damon Zhou / Project Engineer		
		Eric Lin		
		Eric Lin / Reviewer		



2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T.	4
3.2 DETAILS OF E.U.T.....	4
3.3 TEST LOCATION.....	5
3.4 TEST FACILITY	5
4 TEST STANDARDS AND LIMITS	6
4.1 FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS	6
4.2 IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS	7
5 MEASUREMENT AND CALCULATION.....	8
5.1 MAXIMUM TRANSMIT POWER.....	8
5.2 RF EXPOSURE CALCULATION.....	8

3 General Information

3.1 General Description of E.U.T.

Power supply:	DC 3.7V by Rechargeable battery
Serial Number:	KSK11B50001
Firmware Version:	V2.0.0

3.2 Details of E.U.T.

Antenna Gain:	2.1dBi
Antenna Type:	PCB Antenna
Bluetooth Version:	V4.2 LE
Channel Spacing:	2MHz
Modulation Type:	GFSK
Data Rate:	1Mbps
Number of Channels:	40
Operation Frequency:	2402MHz to 2480MHz

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888

Fax: +86 512 5737 0818

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L4354)**

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC (Designation Number: CN1172)**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory.

Designation Number: CN1172.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development (ISED) Canada as an accredited testing laboratory.

CAB Identifier: CN0072.

- **VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max power of channel})/(\text{min test separation distance})]*[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion. For 2.4G band device, the limit of worse case is

$$P_{\text{max}} \leq 7.5 * D_{\text{min}} / \sqrt{f} = 7.5 * 5 / \sqrt{2.480} = 23.810 \text{ mW}$$

4.2 IC Radiofrequency radiation exposure limits

According to RSS-102 section 2.5.1, SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance

MHz	5	10	15	20	25	30	35	40	45	50	mm
≤300	71	101	132	162	193	223	254	284	315	345	mW
450	52	70	88	106	123	141	159	177	195	213	
835	17	30	42	55	67	80	92	105	117	130	
1900	7	10	18	34	60	99	153	225	316	431	
2450	4	7	15	30	52	83	123	173	235	309	
3500	2	6	16	32	55	86	124	170	225	290	
5800	1	6	15	27	41	56	71	85	97	106	

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power. For controlled use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation are multiplied by a factor of 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5. If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.

The practical use condition for this device is as a limb-worn accessories. So the applicable limit is 10-g extremity SAR

For 2.4G band device, the limit is $P_{\max} \leq 2.5 \times 4 = 10 \text{ mW}$

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report KSEM200700079101.

Test Data:

Test Mode	Test Channel	Power[dBm]	Peak Power (mW)
BLE	2402	4.88	3.08
BLE	2440	4.06	2.55
BLE	2480	4.12	2.58

5.2 RF Exposure Calculation

The Max Conducted Peak Output Power is 3.08mW. The best case gain of the antenna is 2.1dBi.

2.1dBi logarithmic terms convert to numeric result is nearly 1.62

According to the formula. calculate the EIRP test result:

$$\text{EIRP} = P \times G = 3.08\text{mW} \times 1.62 = 4.99\text{mW} < 10 \text{ mW} < 23.810\text{mW}$$

So the SAR report is not required.

--End of the Report--