TEST REPORT

FCC ID: 2AMY3-8T9-422L

Product: Tablet PC

Model No.: Acer One 8 T9-422L

Trade Mark: Acer

Report No.: WSCT-A2LA-R&E230300002A-LE

Issued Date: 13 April 2023

Issued for:

Acer India Pvt Ltd.
Embassy Heights 6th Floor, No. 13, Magrath Road, (Next to Hosmat Hospital), Bangalore-560 025, India.

Issued By:

World Standardization Certification & Testing Group(Shenzhen) Co.,Ltd.
Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China
TEL: +86-755-26996192
FAX: +86-755-86376605

Note: *The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group(Shenzhen) Co., Ltd. This report must not be used by the client to claim product certification, approval, or any agency of the U.S. Government.*

TABLE OF CONTENTS

1. Test Certification 3
2. Test Result Summary 4
3. EUT Description 5
4. Genera Information 6
4.1. TEST ENVIRONMENT AND MODE 6
4.2. DESCRIPTION OF SUPPORT UNITS 6
5. Facilities and Accreditations 7
5.1. FACILITIES 7
5.2. ACCREDITATIONS 7
5.3. MEASUREMENT UNCERTAINTY 8
5.4. MEASUREMENT INSTRUMENTS 9
6. Test Results and Measurement Data 10
6.1. ANTENNA REQUIREMENT 10
6.2. CONDUCTED EMISSION 11
6.3. CONDUCTED OUTPUT POWER 14
6.4. EMISSION BANDWIDTH 20
6.5. POWER SPECTRAL DENSITY 26
6.6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION MEASUREMENT 32
6.7. RADIATED SPURIOUS EMISSION MEASUREMENT 43

1. Test Certification

Product:	Tablet PC
Model No.:	Acer One 8 T9-422L
Trade Mark:	Acer
Applicant:	**Acer India Pvt Ltd.**
Address:	Embassy Heights 6th Floor, No. 13, Magrath Road, (Next to Hosmat Hospital), Bangalore-560 025, India.
Manufacturer:	**Acer India Pvt Ltd.**
Address:	Embassy Heights 6th Floor, No. 13, Magrath Road, (Next to Hosmat Hospital), Bangalore-560 025, India.
Factory:	**Acer India Pvt Ltd.**
Address:	RS No. 38/2, Sedarapet Village, Villianur Commune, Pondicherry – 605111.
Date of Test:	12 January 2023 to 15 March 2023
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 KDB 558074 D01 DTS Meas Guidance v04

The above equipment has been tested by World Standardization Certification & Testing Group(Shenzhen)Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: Wang Xiang **(Wang Xiang)**

Checked By: **(Qin Shuiquan)**

Approved By: **(Liu Fuxin)**

Date: 13 April 2023

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	1§5.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

Note:

1. PASS: Test item meets the requirement.

2. Fail: Test item does not meet the requirement.

3. N/A: Test case does not apply to the test object.

4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product:	Tablet PC
Model No.:	Acer One 8 T9-422L
Trade Mark:	Acer
Operation Frequency:	2402MHz~2480MHz
Channel Separation:	2MHz
Number of Channel:	40
Modulation Technology:	GFSK
Antenna Type:	Integral Antenna
Antenna Gain:	2.16dBi
Rechargeable Li-Polymer Battery:	Model: GFL 1100100 1ICP4/100/100 Nominal Voltage: 3.8V Rated capacity: 5100mAh/19.38Wh Limited Charge Voltage: 4.35V
Adapter:	Model: BSY01J3050200UU Input: 100-240V~50/60Hz 0.3A Output:5.0V⎓2.0A 10.0W
Remark:	N/A.

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
…	…	…	…	…	…	…	…
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz
Remark: Channel 0, 19 & 39 have been tested.							

4. Genera Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) with Fully-charged battery.
The sample was placed (0.1m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Adapter	BSY01J3050200UU	/	/	ADAPTER

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group(Shenzhen) CO., LTD**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2. ACCREDITATIONS

CNAS - Registration Number: L3732

China National Accreditation Service for Conformity Assessment, The test firm Registration Number: L3732

FCC - Designation Number: CN1303

World Standardization Certification & Testing Group(Shenzhen) CO., LTD. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Designation Number: CN1303.

A2LA - Certificate Number: 5768.01

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA).Certification Number: 5768.01

5.3. Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission Test	±3.2dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(<1GHz)	±4.7dB
5	All emissions, radiated(>1GHz)	±4.7dB
6	Temperature	±0.5°C
7	Humidity	±2.0%

5.4. MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
Test software	--	EZ-EMC	CON-03A	-	-
Test software	--	MTS8310	-	-	-
EMI Test Receiver	R&S	ESCI	100005	11/05/2022	11/04/2023
LISN	AFJ	LS16	16010222119	11/05/2022	11/04/2023
LISN(EUT)	Mestec	AN3016	04/10040	11/05/2022	11/04/2023
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	11/05/2022	11/04/2023
Coaxial cable	Megalon	LMR400	N/A	11/05/2022	11/04/2023
GPIB cable	Megalon	GPIB	N/A	11/05/2022	11/04/2023
Spectrum Analyzer	R&S	FSU	100114	11/05/2022	11/04/2023
Pre Amplifier	H.P.	HP8447E	2945A02715	11/05/2022	11/04/2023
Pre-Amplifier	CDSI	PAP-1G18-38	--	11/05/2022	11/04/2023
Bi-log Antenna	SUNOL Sciences	JB3	A021907	11/05/2022	11/04/2023
9*6*6 Anechoic	--	--	--	11/05/2022	11/04/2023
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	11/05/2022	11/04/2023
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	11/05/2022	11/04/2023
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	11/05/2022	11/04/2023
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	11/05/2022	11/04/2023
Loop Antenna	EMCO	6502	00042960	11/05/2022	11/04/2023
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	11/05/2022	11/04/2023
Power meter	Anritsu	ML2487A	6K00003613	11/05/2022	11/04/2023
Power sensor	Anritsu	MX248XD	--	11/05/2022	11/04/2023
Spectrum Analyzer	Keysight	N9010B	MY60241089	11/05/2022	11/04/2023

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The Bluetooth antenna is a Integral Antenna. it meets the standards, and the best case gain of the antenna is 2.16dBi.	

6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2014
Frequency Range:	150 kHz to 30 MHz
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto
Limits:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Test Setup:



Test Mode:	Charging + Transmitting Mode
Test Procedure:	1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2014 on conducted measurement.
Test Result:	PASS

6.2.2. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1580	51.40	10.41	61.81	65.56	-3.75	QP
2		0.1980	20.55	10.41	30.96	53.69	-22.73	AVG
3		0.2060	48.01	10.41	58.42	63.36	-4.94	QP
4		0.2580	45.19	10.42	55.61	61.49	-5.88	QP
5		0.3140	43.87	10.43	54.30	59.86	-5.56	QP
6		0.3140	14.54	10.43	24.97	49.86	-24.89	AVG
7		0.3860	38.03	10.45	48.48	58.15	-9.67	QP
8		0.4140	17.36	10.45	27.81	47.57	-19.76	AVG
9		1.0260	16.22	10.51	26.73	46.00	-19.27	AVG
10		3.3740	20.83	10.67	31.50	46.00	-14.50	AVG
11		3.4860	37.46	10.67	48.13	56.00	-7.87	QP
12		5.2140	14.67	10.69	25.36	50.00	-24.64	AVG

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1539	51.27	10.41	61.68	65.78	-4.10	QP
2		0.1700	49.69	10.41	60.10	64.96	-4.86	QP
3		0.1980	21.72	10.41	32.13	53.69	-21.56	AVG
4		0.2140	46.20	10.41	56.61	63.04	-6.43	QP
5		0.2620	45.14	10.42	55.56	61.36	-5.80	QP
6		0.2779	14.77	10.43	25.20	50.88	-25.68	AVG
7		0.3620	40.32	10.44	50.76	58.68	-7.92	QP
8		0.4220	14.11	10.45	24.56	47.41	-22.85	AVG
9		0.4740	36.70	10.46	47.16	56.44	-9.28	QP
10		0.7460	15.88	10.49	26.37	46.00	-19.63	AVG
11		3.5340	16.94	10.68	27.62	46.00	-18.38	AVG
12		7.9740	5.57	10.75	16.32	50.00	-33.68	AVG

Note1:

Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = Antenna factor + Cable loss
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)
Q.P. =Quasi-Peak AVG =average
** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

6.3. Conducted Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074
Limit:	30dBm
Test Setup:	
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04. 2. Set spectrum analyzer as following: a) Set the RBW ≥ DTS bandwidth. b) Set VBW ≥ 3 × RBW. c) Set span ≥ 3 x RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.
Test Result:	PASS

6.3.2. Test Data

BLE 1M			
Test channel	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
Lowest	-10.77	30.00	PASS
Middle	-10.16	30.00	PASS
Highest	-10.97	30.00	PASS

BLE 2M			
Test channel	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
Lowest	-7.97	30.00	PASS
Middle	**-7.31**	30.00	PASS
Highest	-8.11	30.00	PASS

Test plots as follows:

BLE 1M

Lowest channel



Middle channel

Highest channel



BLE 2M

Lowest channel



Middle channel



Highest channel



6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074
Limit:	>500kHz
Test Setup:	
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test data

BLE 1M

Test channel	6dB Emission Bandwidth (kHz)		
	BT LE mode	Limit	Result
Lowest	0.668	>500k	PASS
Middle	0.677	>500k	
Highest	0.655	>500k	

BLE 2M

Test channel	6dB Emission Bandwidth (kHz)		
	BT LE mode	Limit	Result
Lowest	1.137	>500k	PASS
Middle	1.133	>500k	
Highest	1.241	>500k	

Test plots as follows:

BLE 1M

Lowest channel



Middle channel



Highest channel



BLE 2M

Lowest channel

Middle channel

Highest channel



6.5. Power Spectral Density

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v04 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): 3 kHz ≤ RBW ≤ 100 kHz. Video bandwidth VBW ≥ 3 x RBW. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW) 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

6.5.2. Test Instruments

RF Test Room				
Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
Spectrum Analyzer	R&S	FSU	200054	Sep. 27, 2018
RF cable (9kHz-26.5GHz)	TCT	RE-06	N/A	Sep. 27, 2018
Antenna Connector	TCT	RFC-01	N/A	Sep. 27, 2018

Note: *The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).*

6.5.3. Test data

Test channel	Power Spectral Density (dBm/3kHz)		
	BLE 1M	Limit	Result
Lowest	-23.55	8 dBm/3kHz	PASS
Middle	-22.91	8 dBm/3kHz	
Highest	-23.77	8 dBm/3kHz	

Test channel	Power Spectral Density (dBm/3kHz)		
	BLE 2M	Limit	Result
Lowest	-26.1	8 dBm/3kHz	PASS
Middle	-25.41	8 dBm/3kHz	
Highest	-26.22	8 dBm/3kHz	

Test plots as follows:

BLE 1M

Lowest channel



Middle channel



Highest channel



BLE 2M

Lowest channel



Middle channel



Highest channel



6.6. Conducted Band Edge and Spurious Emission Measurement

6.6.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	
Test Mode:	Refer to item 4.1
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS

Report No.: WSCT-A2LA-R&E230300002A-LE

Test Data

Band Edge

BLE 1M

Band Edge (Low channel)



Band Edge (Low channel)



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.402 2 GHz	-8.152 dBm			
2	N	1	f	2.400 0 GHz	-59.80 dBm			
3	N	1	f	2.400 0 GHz	-59.80 dBm			
4	N	1	f	2.332 8 GHz	-57.68 dBm			
5								
6								

Band Edge (High channel)



Band Edge (High channel)



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.480 0 GHz	-8.164 dBm			
2	N	1	f	2.483 5 GHz	-59.35 dBm			
3	N	1	f	2.500 0 GHz	-60.07 dBm			
4	N	1	f	2.498 7 GHz	-56.57 dBm			
5								
6								

BLE 2M

Band Edge (Low channel)

Band Edge (Low channel)



Band Edge (High channel)



Band Edge (High channel)



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.480 0 GHz	-9.423 dBm			
2	N	1	f	2.483 5 GHz	-60.16 dBm			
3	N	1	f	2.500 0 GHz	-60.09 dBm			
4	N	1	f	2.486 2 GHz	-57.09 dBm			
5								
6								

Conducted RF Spurious Emission

BLE 1M

Low channel



Low channel



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.401 7 GHz	-8.979 dBm			
2	N	1	f	25.727 1 GHz	-49.23 dBm			
3	N	1	f	4.924 3 GHz	-54.22 dBm			
4	N	1	f	7.194 5 GHz	-54.75 dBm			
5	N	1	f	9.758 6 GHz	-54.52 dBm			
6								

Middle channel



Middle channel



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.439 7 GHz	-8.456 dBm			
2	N	1	f	25.726 2 GHz	-49.19 dBm			
3	N	1	f	5.016 9 GHz	-54.66 dBm			
4	N	1	f	7.173 4 GHz	-53.38 dBm			
5	N	1	f	9.858 3 GHz	-54.53 dBm			
6								

High channel



High channel



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.480 2 GHz	-8.583 dBm			
2	N	1	f	26.194 7 GHz	-48.63 dBm			
3	N	1	f	5.138 7 GHz	-53.58 dBm			
4	N	1	f	7.515 7 GHz	-54.41 dBm			
5	N	1	f	9.850 4 GHz	-54.06 dBm			
6								

BLE 2M

Low channel

Low channel



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.402 6 GHz	-10.23 dBm			
2	N	1	f	26.327 1 GHz	-48.60 dBm			
3	N	1	f	4.998 4 GHz	-53.51 dBm			
4	N	1	f	7.225 4 GHz	-54.66 dBm			
5	N	1	f	9.691 6 GHz	-54.86 dBm			
6								

Middle channel



Middle channel



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.439 7 GHz	-9.362 dBm			
2	N	1	f	26.287 4 GHz	-48.09 dBm			
3	N	1	f	4.812 2 GHz	-54.41 dBm			
4	N	1	f	7.349 0 GHz	-54.88 dBm			
5	N	1	f	9.780 7 GHz	-54.02 dBm			
6								

High channel



High channel



	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.480 2 GHz	-11.99 dBm			
2	N	1	f	26.233 5 GHz	-49.39 dBm			
3	N	1	f	5.121 9 GHz	-54.74 dBm			
4	N	1	f	7.324 2 GHz	-54.82 dBm			
5	N	1	f	9.780 7 GHz	-53.52 dBm			
6								

6.7. Radiated Spurious Emission Measurement

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2014
Frequency Range:	9 kHz to 25 GHz
Measurement Distance:	3 m
Antenna Polarization:	Horizontal & Vertical
Operation mode:	Refer to item 4.1

Receiver Setup:

Frequency	Detector	RBW	VBW	Remark
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

Limit:

Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(KHz)	300
0.490-1.705	24000/F(KHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
Above 1GHz	500	3	Average
	5000	3	Peak

Test setup:

For radiated emissions below 30MHz



30MHz to 1GHz



Above 1GHz



Test Procedure:

1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.1 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

	2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥RBW; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for f 1 GHz for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test mode:	Refer to section 4.1 for details
Test results:	PASS

Note: Freq. = Emission frequency in MHz
Reading level (dBμV) = Receiver reading
Corr. Factor (dB) = Attenuation factor + Cable loss
Level (dBμV) = Reading level (dBμV) + Corr. Factor (dB)
Limit (dBμV) = Limit stated in standard
Margin (dB) = Level (dBμV) – Limits (dBμV)

6.7.2. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		30.9619	23.94	4.43	28.37	40.00	-11.63	QP
2		56.7917	30.10	-5.83	24.27	40.00	-15.73	QP
3		89.9047	31.51	-5.92	25.59	43.50	-17.91	QP
4		158.1123	38.49	-5.63	32.86	43.50	-10.64	QP
5		248.5519	42.38	-4.79	37.59	46.00	-8.41	QP
6	*	455.9058	38.41	0.06	38.47	46.00	-7.53	QP

Vertical:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		30.9619	23.94	4.43	28.37	40.00	-11.63	QP
2		80.6442	34.61	-7.10	27.51	40.00	-12.49	QP
3		158.1123	38.49	-5.63	32.86	43.50	-10.64	QP
4	*	248.5519	43.38	-4.79	38.59	46.00	-7.41	QP
5		386.6338	38.90	-1.14	37.76	46.00	-8.24	QP
6		952.0937	25.32	6.45	31.77	46.00	-14.23	QP

Note1:
Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = Antenna factor + Cable loss - Amplifier factor.
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)

Above 1GHz

Freq. (MHz)	Low channel: 2402MHz						
	Ant.Pol	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4804	V	60.92	39.77	74	54	-13.08	-14.23
7206	V	58.36	40.07	74	54	-15.64	-13.93
4804	H	59.99	40.20	74	54	-14.01	-13.80
7206	H	59.64	40.64	74	54	-14.36	-13.36

Freq. (MHz)	Middle channel: 2440MHz						
	Ant.Pol	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4880	V	60.91	41.60	74	54	-13.09	-12.40
7320	V	58.61	39.32	74	54	-15.39	-14.68
4880	H	59.92	40.12	74	54	-14.08	-13.88
7320	H	59.02	40.02	74	54	-14.98	-13.98

Freq. (MHz)	High channel: 2480 MHz						
	Ant.Pol	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
4960	V	59.33	40.23	74	54	-14.67	-13.77
7440	V	58.54	40.61	74	54	-15.46	-13.39
4960	H	59.85	39.24	74	54	-14.15	-14.76
7440	H	58.60	39.60	74	54	-15.40	-14.40

Note:

1. *All emissions not reported were more than 20dB below the specified limit or in the noise floor.*
2. *Emission Level= Reading Level+Probe Factor +Cable Loss.*
3. *Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*

Restricted Bands Requirements

Test result for GFSK Mode（the worst case）

Frequency	Reading	Correct Factor	Emission Level	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel							
2390	60.20	-8.76	51.44	74	22.56	H	PK
2390	54.33	-8.76	45.57	54	8.43	H	AV
2390	61.59	-8.73	52.86	74	21.14	V	PK
2390	54.66	-8.73	45.93	54	8.07	V	AV
High Channel							
2483.5	63.47	-8.76	54.71	74	19.29	H	PK
2483.5	54.70	-8.76	45.94	54	8.06	H	AV
2483.5	63.11	-8.73	54.38	74	19.62	V	PK
2483.5	57.77	-8.73	49.04	54	4.96	V	AV

*******END OF REPORT*******