Certificate # 2951.01

TEST REPORT

Applicant	ONANOFF LIMITED
Address	RM 424, Sino Ind. Plaza, 9 Kai Cheung Road, Kowloon Bay, Kowloon, Hong Kong SAR.

Manufacturer or Supplier	ONANOFF LIMITED
Address	RM 424, Sino Ind. Plaza, 9 Kai Cheung Road, Kowloon Bay, Kowloon, Hong Kong SAR.
Product	BuddyPhones Cosmos+
Brand Name	BuddyPhones
Model	BT-BP-COSMOSP
Additional Model & Model Difference	N/A
Date of tests	Jul. 22, 2021 ~ Sep. 01, 2021

the tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Sep. 09, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at https://www.cps.bureauveritas.com/terms-conditions and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4
1 SUMMARY OF TEST RESULTS 5
2 MEASUREMENT UNCERTAINTY 5
3 GENERAL INFORMATION 6
3.1 GENERAL DESCRIPTION OF EUT 6
3.2 DESCRIPTION OF TEST MODES 7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST 8
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 10
3.4 DESCRIPTION OF SUPPORT UNITS 10
4 TEST TYPES AND RESULTS 11
4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT 11
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 11
4.1.2 TEST INSTRUMENTS 12
4.1.3 TEST PROCEDURES 13
4.1.4 DEVIATION FROM TEST STANDARD 14
4.1.5 TEST SETUP 14
4.1.6 EUT OPERATING CONDITIONS 15
4.1.7 TEST RESULTS 16
4.2 NUMBER OF HOPPING FREQUENCY USED 24
4.2.1 LIMIT OF HOPPING FREQUENCY USED 24
4.2.2 TEST SETUP 24
4.2.3 TEST INSTRUMENTS 24
4.2.4 TEST PROCEDURES 25
4.2.5 DEVIATION FROM TEST STANDARD 25
4.2.6 TEST RESULTS 25
4.3 DWELL TIME ON EACH CHANNEL 28
4.3.1 LIMIT OF DWELL TIME USED 28
4.3.2 TEST SETUP 28
4.3.3 TEST INSTRUMENTS 28
4.3.4 TEST PROCEDURES 28
4.3.5 DEVIATION FROM TEST STANDARD 29
4.3.6 TEST RESULTS 29

4.4 CHANNEL BANDWIDTH 32
4.4.1 LIMITS OF CHANNEL BANDWIDTH 32
4.4.2 TEST SETUP 32
4.4.3 TEST INSTRUMENTS 32
4.4.4 TEST PROCEDURE 32
4.4.5 DEVIATION FROM TEST STANDARD 32
4.4.6 EUT OPERATING CONDITION 32
4.4.7 TEST RESULTS 33
4.5 HOPPING CHANNEL SEPARATION 37
4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION 37
4.5.2 TEST SETUP 37
4.5.3 TEST INSTRUMENTS 37
4.5.4 TEST PROCEDURES 37
4.5.5 DEVIATION FROM TEST STANDARD 37
4.5.6 TEST RESULTS 38
4.6 CONDUCTED OUTPUT POWER 42
4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 42
4.6.2 TEST SETUP 42
4.6.3 TEST INSTRUMENTS 42
4.6.4 TEST PROCEDURES 42
4.6.5 DEVIATION FROM TEST STANDARD 42
4.6.6 EUT OPERATING CONDITION 43
4.6.7 TEST RESULTS 43
4.7 OUT OF BAND EMISSION MEASUREMENT 45
4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 45
4.7.2 TEST INSTRUMENTS 45
4.7.3 TEST PROCEDURE 45
4.7.4 DEVIATION FROM TEST STANDARD 45
4.7.5 EUT OPERATING CONDITION 45
4.7.6 TEST RESULTS 45
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 50
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 51

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2107WDG0326-1	Original release	Sep. 09, 2021

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	N/A	Powered by battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GMHz	3.82dB
	1GHz ~ 18GHz	4.94dB
	18GHz ~ 40GHz	5.07dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	BuddyPhones Cosmos+
MODEL NO.	BT-BP-COSMOSP
ADDITIONAL MODELS	N/A
FCC ID	2AN2MBUDDYPHONESCMP
POWER SUPPLY	DC 3.7V from battery or DC 5V from USB host unit
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, π/4 DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
PEAK OUTPUT POWER	2.723mW (Max. Measured)
ANTENNA TYPE	Chip Antenna, 3.45dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB Cable: Unshielded, Detachable, 105cm Aux in Cable: Unshielded, Detachable, 120cm

NOTES:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2107WDG0326-1) for detailed product photo.
4. When the EUT in charging mode that BT function can't working.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports
The worst case was found when positioned on X axis for radiated emission.
Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	Powered by Fully Battery with Bluetooth link

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	27deg. C, 56%RH	DC 3.7V From Fully Battery	Jelly
RE≥1G	27deg. C, 56%RH	DC 3.7V From Fully Battery	Jelly
PLC	-	-	-
APCM	25deg. C, 60%RH	DC 3.7V From Fully Battery	Vincent

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247
KDB 558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessory or support units.

4 TEST TYPES AND RESULTS

4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTES:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 07,22
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	May 09, 22
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 29,22
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Mar. 13,22
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	May 29,22
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 29,22
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	May 09, 22
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	May 22,22
Test Software	ADT	ADT_Radiated_V 7.6.15.9.2	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	May 08,22
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Mar. 13,22
Test Software	ADT	ADT_Radiated_V 7.6.15.9.2	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A

NOTES:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above1GHz if tested.
4. The FCC Site Registration No. is 749762.

4.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the center of the loop shall be 1m above the ground.

g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTES:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup



Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.

b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

c. The necessary accessories enable the EUT in full functions.

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	239.86	25.76 QP	46.00	-20.24	1.00 H	263	44.33	-18.57
2	350.22	28.27 QP	46.00	-17.73	1.00 H	276	43.66	-15.39
3	389.09	24.96 QP	46.00	-21.04	1.00 H	286	39.10	-14.14
4	476.14	25.26 QP	46.00	-20.74	1.00 H	295	37.10	-11.84
5	679.78	21.27 QP	46.00	-24.73	1.00 H	304	29.37	-8.10
6	751.28	23.28 QP	46.00	-22.72	1.00 H	314	29.53	-6.25

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	239.86	17.52 QP	46.00	-28.48	1.00 V	215	36.09	-18.57
2	350.22	25.16 QP	46.00	-20.84	1.00 V	125	40.55	-15.39
3	476.14	26.22 QP	46.00	-19.78	1.00 V	56	38.06	-11.84
4	**532.10**	**34.93 QP**	**46.00**	**-11.07**	**1.00 V**	**34**	**45.60**	**-10.67**
5	623.81	21.29 QP	46.00	-24.71	1.00 V	325	29.73	-8.44
6	681.33	21.80 QP	46.00	-24.20	1.00 V	234	29.89	-8.09

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	40.69 PK	74.00	-33.31	1.00 H	126	40.15	0.54
2	2390.00	29.85 AV	54.00	-24.15	1.00 H	126	29.31	0.54
3	*2402.00	94.37 PK			1.00 H	126	93.79	0.58
4	*2402.00	92.91 AV			1.00 H	126	92.33	0.58
5	4804.00	43.02 PK	74.00	-30.98	1.00 H	0	37.71	5.31
6	4804.00	35.42 AV	54.00	-18.58	1.00 H	0	30.11	5.31
7	#7206.00	48.09 PK	74.00	-25.91	1.00 H	0	38.39	9.70
8	#7206.00	39.65 AV	54.00	-14.35	1.00 H	0	29.95	9.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	39.54 PK	74.00	-34.46	1.00 V	50	39.00	0.54
2	2390.00	28.57 AV	54.00	-25.43	1.00 V	50	28.03	0.54
3	*2402.00	89.57 PK			1.00 V	50	88.99	0.58
4	*2402.00	87.36 AV			1.00 V	50	86.78	0.58
5	4804.00	42.68 PK	74.00	-31.32	1.00 V	0	37.37	5.31
6	4804.00	35.21 AV	54.00	-18.79	1.00 V	0	29.90	5.31
7	#7206.00	45.85 PK	74.00	-28.15	1.00 V	0	36.15	9.70
8	#7206.00	39.01 AV	54.00	-14.99	1.00 V	0	29.31	9.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	96.04 PK			1.00 H	69	95.31	0.73
2	*2441.00	94.27 AV			1.00 H	69	93.54	0.73
3	4882.00	47.51 PK	74.00	-26.49	1.00 H	0	42.12	5.39
4	4882.00	37.26 AV	54.00	-16.74	1.00 H	0	31.87	5.39
5	7323.00	50.28 PK	74.00	-23.72	1.00 H	0	40.50	9.78
6	7323.00	40.85 AV	54.00	-13.15	1.00 H	0	31.07	9.78
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	90.36 PK			1.00 V	177	89.63	0.73
2	*2441.00	88.54 AV			1.00 V	177	87.81	0.73
3	4882.00	45.26 PK	74.00	-28.74	1.00 V	0	39.87	5.39
4	4882.00	36.69 AV	54.00	-17.31	1.00 V	0	31.30	5.39
5	7323.00	49.62 PK	74.00	-24.38	1.00 V	0	39.84	9.78
6	7323.00	40.25 AV	54.00	-13.75	1.00 V	0	30.47	9.78

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	95.62 PK			1.00 H	158	94.75	0.87
2	*2480.00	93.15 AV			1.00 H	158	92.28	0.87
3	2483.50	43.22 PK	74.00	-30.78	1.00 H	158	42.33	0.89
4	2483.50	37.96 AV	54.00	-16.04	1.00 H	158	37.07	0.89
5	4960.00	45.25 PK	74.00	-28.75	1.00 H	0	39.76	5.49
6	4960.00	36.69 AV	54.00	-17.31	1.00 H	0	31.20	5.49
7	7440.00	49.68 PK	74.00	-24.32	1.00 H	0	39.82	9.86
8	7440.00	40.28 AV	54.00	-13.72	1.00 H	0	30.42	9.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	90.68 PK			1.00 V	74	89.81	0.87
2	*2480.00	88.69 AV			1.00 V	74	87.82	0.87
3	2483.50	42.20 PK	74.00	-31.80	1.00 V	74	41.31	0.89
4	2483.50	37.21 AV	54.00	-16.79	1.00 V	74	36.32	0.89
5	4960.00	44.57 PK	74.00	-29.43	1.00 V	0	39.08	5.49
6	4960.00	35.69 AV	54.00	-18.31	1.00 V	0	30.20	5.49
7	7440.00	48.87 PK	74.00	-25.13	1.00 V	0	39.01	9.86
8	7440.00	40.06 AV	54.00	-13.94	1.00 V	0	30.20	9.86

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.25 PK	74.00	-29.75	1.00 H	121	43.71	0.54
2	2390.00	33.96 AV	54.00	-20.04	1.00 H	121	33.42	0.54
3	*2402.00	99.67 PK			1.00 H	121	98.80	0.87
4	*2402.00	97.34 AV			1.00 H	121	96.47	0.87
5	4804.00	45.26 PK	74.00	-28.74	1.00 H	0	39.95	5.31
6	4804.00	37.96 AV	54.00	-16.04	1.00 H	0	32.65	5.31
7	#7206.00	50.27 PK	74.00	-23.73	1.00 H	0	40.57	9.70
8	#7206.00	41.18 AV	54.00	-12.82	1.00 H	0	31.48	9.70
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	42.57 PK	74.00	-31.43	1.00 V	230	42.03	0.54
2	2390.00	32.16 AV	54.00	-21.84	1.00 V	230	31.62	0.54
3	*2402.00	91.42 PK			1.00 V	230	90.55	0.87
4	*2402.00	88.67 AV			1.00 V	230	87.80	0.87
5	4804.00	44.17 PK	74.00	-29.83	1.00 V	0	38.86	5.31
6	4804.00	36.96 AV	54.00	-17.04	1.00 V	0	31.65	5.31
7	#7206.00	48.67 PK	74.00	-25.33	1.00 V	0	38.97	9.70
8	#7206.00	40.29 AV	54.00	-13.71	1.00 V	0	30.59	9.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	100.74 PK			1.00 H	53	100.01	0.73
2	*2441.00	98.67 AV			1.00 H	53	97.94	0.73
3	4882.00	43.85 PK	74.00	-30.15	1.00 H	0	38.46	5.39
4	4882.00	36.59 AV	54.00	-17.41	1.00 H	0	31.20	5.39
5	7440.00	49.75 PK	74.00	-24.25	1.00 H	0	39.89	9.86
6	7440.00	41.17 AV	54.00	-12.83	1.00 H	0	31.31	9.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	89.67 PK			1.00 V	114	88.94	0.73
2	*2441.00	87.31 AV			1.00 V	114	86.58	0.73
3	4882.00	43.36 PK	74.00	-30.64	1.00 V	0	37.97	5.39
4	4882.00	35.96 AV	54.00	-18.04	1.00 V	0	30.57	5.39
5	7440.00	48.64 PK	74.00	-25.36	1.00 V	0	38.78	9.86
6	7440.00	40.31 AV	54.00	-13.69	1.00 V	0	30.45	9.86

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	100.37 PK			1.00 H	123	99.50	0.87
2	*2480.00	98.25 AV			1.00 H	123	97.38	0.87
3	2483.50	61.37 PK	74.00	-12.63	1.00 H	123	60.48	0.89
4	**2483.50**	**43.57 AV**	**54.00**	**-10.43**	**1.00 H**	**123**	**42.68**	**0.89**
5	4960.00	45.58 PK	74.00	-28.42	1.00 H	0	40.09	5.49
6	4960.00	36.69 AV	54.00	-17.31	1.00 H	0	31.20	5.49
7	7440.00	49.62 PK	74.00	-24.38	1.00 H	0	39.76	9.86
8	7440.00	42.21 AV	54.00	-11.79	1.00 H	0	32.35	9.86
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	90.57 PK			1.00 V	84	89.70	0.87
2	*2480.00	87.69 AV			1.00 V	84	86.82	0.87
3	2483.50	57.41 PK	74.00	-16.59	1.00 V	84	56.52	0.89
4	2483.50	40.17 AV	54.00	-13.83	1.00 V	84	39.28	0.89
5	4960.00	43.37 PK	74.00	-30.63	1.00 V	0	37.88	5.49
6	4960.00	35.10 AV	54.00	-18.90	1.00 V	0	29.61	5.49
7	7440.00	48.62 PK	74.00	-25.38	1.00 V	0	38.76	9.86
8	7440.00	40.66 AV	54.00	-13.34	1.00 V	0	30.80	9.86

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.2.2 TEST SETUP



4.2.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	N/A
Power Sensor	Keysight	U2021XA	MY55060018	May 09, 22
Power Meter	Anritsu	ML2495A	1139001	Feb. 24,22
Power Sensor	Anritsu	MA2411B	1531155	Feb. 24,22
Digital Multimeter	FLUKE	15B	A1220010DG	N/A
Humid & Temp Programmable Tester	Haida	HD-225T	110807201	Nov. 03,21
Oscilloscope	Agilent	DSO9254A	MY51260160	Aug. 10,22
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Feb. 24,22
Signal Generator	Agilent	N5183A	MY50140980	Aug. 10,22
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Sep. 04,21
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Keysight	E3642A	MY56146098	N/A

NOTES:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.2.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on Max Hold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were completed.

4.2.5 DEVIATION FROM TEST STANDARD

No deviation.

4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
0.01 dBm
2.40200 GHz
Marker 2 [T1]
0.34 dBm
2.44200 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
0.98 dBm
2.44300 GHz
Marker 2 [T1]
-1.92 dBm
2.48000 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

8DPSK


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
1.07 dBm
2.40200 GHz
Marker 2 [T1]
0.70 dBm
2.44200 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.42142 GHz
4.2 MHz/
Span 42 MHz


RBW 100 kHz
VBW 300 kHz
SWT 1.09 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-0.19 dBm
2.44300 GHz
Marker 2 [T1]
0.55 dBm
2.48000 GHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4634 GHz
4.2 MHz/
Span 42 MHz

4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.3.2 TEST SETUP



10dB ATTENUATION PAD

4.3.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.3.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	17	107.44	0.444	47.703	400	PASS
DH3	79	31.6	5	16	101.12	1.696	171.500	400	PASS
DH5	79	31.6	5	17	107.44	3.072	330.060	400	PASS

8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	17	107.44	0.450	48.348	400	PASS
3DH3	79	31.6	5	17	107.44	1.700	182.650	400	PASS
3DH5	79	31.6	5	17	107.44	3.008	323.180	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK

DH1





DH3





DH5





8DPSK

3DH1





3DH3





3DH5





4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.4.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.93
39	2441	0.94
78	2480	0.94

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-19.00 dBm
2.44054 GHz
Delta 2 [T1]
0.00 dB
940.00 kHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 0.99 dBm
D2 -19.01 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.441 GHz
300 kHz/
Span 3 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-19.32 dBm
2.47954 GHz
Delta 2 [T1]
0.00 dB
940.00 kHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 0.67 dBm
D2 -19.33 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.48 GHz
300 kHz/
Span 3 MHz

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.26
39	2441	1.26
78	2480	1.26

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-19.02 dBm
2.44036 GHz
Delta 2 [T1]
0.00 dB
1.26 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 0.97 dBm
D2 -19.03 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.441 GHz
300 kHz/
Span 3 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.05 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
-19.35 dBm
2.47936 GHz
Delta 2 [T1]
0.00 dB
1.26 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
D1 0.64 dBm
D2 -19.36 dBm
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
F1
F2
Center 2.48 GHz
300 kHz/
Span 3 MHz

4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.5.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.93	0.620	PASS
39	2441	1.00	0.94	0.627	PASS
78	2480	1.00	0.94	0.627	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
0.99 dBm
2.44100 GHz
Delta 2 [T2]
0.01 dB
1.00 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
0.68 dBm
2.47900 GHz
Delta 2 [T1]
0.00 dB
1.00 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.26	0.840	PASS
39	2441	1.00	1.26	0.840	PASS
78	2480	1.00	1.26	0.840	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0



CH 39


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T1]
0.98 dBm
2.44100 GHz
Delta 2 [T2]
0.28 dB
1.00 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4415 GHz
250 kHz/
Span 2.5 MHz

CH 78


RBW 30 kHz
VBW 100 kHz
SWT 1.06 ms
[T1] MP VIEW
[T2] MP VIEW
Marker 1 [T2]
0.66 dBm
2.47900 GHz
Delta 2 [T1]
0.02 dB
1.00 MHz
Ref 11 dBm
Att 20 dB
Offset 1 dB
11
0
-10
-20
-30
-40
-50
-60
-70
-80
-89
Center 2.4795 GHz
250 kHz/
Span 2.5 MHz

4.6 CONDUCTED OUTPUT POWER

4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 0.125W.

4.6.2 TEST SETUP



10dB ATTENUATION
PAD

4.6.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	1.40	1.380	0.125	PASS
39	2441	1.67	1.469	0.125	PASS
78	2480	1.66	1.466	0.125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	4.09	2.564	0.125	PASS
39	**2441**	**4.35**	**2.723**	**0.125**	**PASS**
78	2480	4.29	2.685	0.125	PASS

AVERAGE OUTPUT POWER(FOR REFERENCE)

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.34	1.081
39	2441	0.58	1.143
78	2480	0.39	1.094

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.73	1.183
39	**2441**	**0.98**	**1.253**
78	2480	0.93	1.239

4.7 OUT OF BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.7.2 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.7.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation.

4.7.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK

Low Channel





High Channel





8DPSK

Low Channel





High Channel





GFSK

Hopping on Low Channel





Hopping on High Channel





8DPSK

Hopping on Low Channel





Hopping on High Channel





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---