



承认书

APPROVAL SHEET

封样版本 Sample Version 2.0

Southstar		
FICTION	DQE	R&D
Customer		
PUR	QC	R&D

Manufacturers: SHENZHEN SOUTH STAR TECHNOLOGY CO., LTD
Office address: 803, Tianshu block, Xinggang tongchuanghui, No. 6099,
Bao'an Avenue,
Xinhe community, Fuhai street, Bao'an District, Shenzhen
Production address: No. 3, Chigang Nanfang 1st Road, Humen Town, Dongguan
City,
Guangdong Province
Tel: 0755-27474071 Fax: 0755-29976316
[Http://www.southstar-tech.com](http://www.southstar-tech.com)



History

Version	Date	Change Description	remark
1.0	2024.04.16	First edition	
2.0	2024.05.25	Drawing update	



目录

1. 概述 (summarize)	5
2. 天线图片 (Antenna picture)	6
3. 调试 (Tuning)	6
3.1 测试仪器 (Test instrument)	6
3.2 测试环境及方式 (Test environment and method)	6
4. 工程图纸 (Engineering drawing)	7
5. 天线装配图 (Antenna assembly drawing)	8
6. 测试数据 (Test data)	9-10


1. summarize

This report mainly describes the antenna performance of SOUTHSTAR for Stone Technology's Vivian project. The Vivian project prototype uses a frequency band ranging from 2400 MHZ to 2500 MHZ

. 电性能Electrical Characteristics	
Frequency 频率	2400MHz~2500 MHz
VSWR 电压驻波比	<2
Efficiency 效率	>50%
Impedance 阻抗	50 Ohm
Polarization 极化	Linear
Gain 增益	2.11dBi
Bandwidth 带宽	100MHz (Min)
Return loss 回波损耗	10dB (Min)
Maximum Power 最大功率	1W
Radiation 辐射	Omni directional
. 材料&物理性能Material & Mechanical Characteristics	
射频材料 Material of Radiator	PCB Black
射频线类型 Cable Type	1.13 Black
接头类型 Connector Type	Primary terminal
重量 weight	
. 环境 Environmental	
工作温度 Operation Temperature	- 30 °C ~ + 65 °C
存放温度 Storage Temperature	- 40 °C ~ + 70 °C



2. Vivian WIFI antenna photo





South
star SHENZHEN SOUTH STAR TECHNOLOGY CO., LTD

3 Test Equipment & Conditions


1. NetWork Analyzers:

Keysight E5071C

2. Comprehensive tester:

CMW500 、MT8000A、MT8862A

3. 3D Chamber Test System:



Name	Parameter	Method	Standard no		
Antenna performance	Radiation efficiency	IEEE Standard Test Procedures for Antenna	ANSI/IEEE Std 149. 2021		
Equipment	Manufacturer	Model No.	Serial NO.	Last Cal.	Due Date
Network Analyzer	Keysight	E5071C	MY47003143	2024. 04. 13	2025. 04. 12
Antenna	southstar	WIFI	N12-8165-ROA		
Chamber	SUNYIELD	MULTI-PROBE OTA MEASUREMENT SYSTEM			



深圳市南斗星科技有限公司

SHENZHEN SOUTH STAR TECHNOLOGY CO.,LTD

5. antenna assembly picture:

please refer to internal photo.



深圳市南斗星科技有限公司

SHENZHEN SOUTH STAR TECHNOLOGY CO.,LTD


6. test date

1. Antenna pattern

E5071C Network Analyzer


1 Active Ch/Trace 2 Response 3 Stimulus 4 Mkr/Analysis 5 Instr State

► Tr1 S11 Log Mag 5.000dB/ Ref 0.000dB [F2 Del]




Tr2 S11 Smith (R+jX) Scale 1.000U [F2]

>1	2.400000	GHZ	53.067	Ω	8.8957	Ω	589.92	pH
2	2.412000	GHZ	52.054	Ω	9.4222	Ω	621.72	pH
3	2.450000	GHZ	47.483	Ω	10.830	Ω	703.55	pH
4	2.483000	GHZ	45.898	Ω	12.155	Ω	779.13	pH
5	2.500000	GHZ	44.930	Ω	12.184	Ω	775.67	pH



Tr3 S11 SWR 1.000/ Ref 1.000 [F2]

>1	2.400000	GHZ	1.2002
2	2.412000	GHZ	1.2082
3	2.450000	GHZ	1.2569
4	2.483000	GHZ	1.3062
5	2.500000	GHZ	1.3201



1 Start 1 MHz

IFBW 70 kHz

Stop 3 GHz C?

2. antenna gain

Frequency (MHz)	Efficiency (%)	Gain(dBi)
2400	60.82	1.87
2410	63.17	1.82
2420	64.92	1.89
2430	66.13	2.06
2440	65.43	2.11
2450	64.53	2.03
2460	63.89	1.93
2470	63.98	2.02
2480	64.92	1.90
2490	64.68	1.94
2500	63.54	1.93
均值:	64.18	1.95

3. Directional diagram

