

测试报告 (Test report)



客户名称(CN)		项目名称(RN)	
测试频段 Test frequency band	2.4G	天线类型 antenna form	
射频工程师 (RF)		结构工程师 (ME)	
日期(Date)	2025/08/19	制表人 Watchmaker	

目录 Directory list

- 一、报告版本提要 (Summary of the report version)
- 二、天线实物图 (Physical diagram of the antenna)
- 三、天线匹配电路 (Antenna matching circuit)
- 四、驻波比、回波损耗 (Standing wave ratio, return loss)
- 五、增益、效率、辐射方向图 (Gain, efficiency, radiation pattern)

一、报告版本提要 (Summary of the report version)

版本 Version number	日期 Date	内容概况 Content Overview
V1.0	2025/08/19	初始版本


二、天线实物图 (Physical diagram of the antenna)




三、天线匹配电路 (Antenna matching circuit)

Element	E1	E2	E3	
Value	/	/	/	

未修改匹配电路。






四、天线驻波比、回波损耗 (Standing wave ratio, return loss)



五、增益、效率、辐射方向图 (Gain, efficiency, radiation pattern)

Frequency ID	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
Frequency (MHz)	2400	2405	2410	2415	2420	2425	2430	2435	2440	2445	2450	2455	2460	2465	2470	2475	2480	2485	2490	2495	2500
Efficiency (dBi)	-1.81	-1.70	-1.65	-1.61	-1.53	-1.46	-1.44	-1.45	-1.45	-1.47	-1.52	-1.62	-1.74	-1.85	-1.91	-1.97	-2.00	-1.99	-1.92	-1.85	-1.82
Gain (dBi)	2.56	2.61	2.64	2.65	2.70	2.75	2.77	2.70	2.64	2.56	2.44	2.25	2.08	1.90	1.81	1.73	1.74	1.77	1.80	1.85	1.87
Efficiency (%)	65.84	67.63	68.46	69.04	70.35	71.47	71.84	71.67	71.54	71.22	70.44	68.92	67.03	65.31	64.42	63.55	63.14	63.27	64.20	65.36	65.71
Directivity (dB)	4.37	4.31	4.29	4.26	4.23	4.21	4.20	4.15	4.10	4.04	3.96	3.87	3.82	3.75	3.72	3.69	3.74	3.76	3.72	3.70	3.69
Peak Gain Position (Theta)	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	75.00	90.00	90.00	90.00	90.00	90.00	90.00
Peak Gain Position (Phi)	255.00	255.00	255.00	255.00	255.00	255.00	255.00	255.00	255.00	255.00	255.00	255.00	255.00	255.00	120.00	255.00	255.00	255.00	255.00	255.00	255.00
Efficiency ThetaPol (%)	59.63	61.47	62.51	63.33	64.78	66.06	66.64	66.74	66.82	66.65	66.04	64.76	63.06	61.46	60.67	59.95	59.65	59.79	60.76	61.99	62.43
Efficiency PhiPol (%)	6.21	6.16	5.95	5.71	5.58	5.41	5.21	4.93	4.71	4.58	4.40	4.16	3.97	3.84	3.74	3.60	3.49	3.48	3.43	3.37	3.28
Upper Hem. Efficiency (%)	39.57	40.46	40.87	41.31	42.32	43.34	43.92	44.20	44.47	44.51	44.14	43.15	41.78	40.39	39.44	38.46	37.83	37.63	38.01	38.65	38.89
Lower Hem. Efficiency (%)	26.27	27.17	27.59	27.73	28.03	28.13	27.92	27.46	27.07	26.72	26.30	25.77	25.25	24.92	24.98	25.09	25.31	25.64	26.19	26.71	26.82
T90(H)角度	3.25	3.21	3.19	3.13	3.06	3.05	2.91	2.88	2.77	2.71	2.70	2.75	2.74	2.75	2.84	2.89	2.96	2.93	2.84	2.78	2.71
Gain 15deg (dBi)																					
E1(XZ)波瓣宽度	74.00	69.00	68.00	66.00	67.00	66.00	67.00	68.00	69.00	70.00	55.00	56.00	54.00	55.00	71.00	71.00	70.00	70.00	69.00	69.00	69.00
E1(XZ)前后比	4.82	5.19	5.46	5.71	5.86	6.01	6.04	6.10	6.15	6.19	6.28	6.40	6.63	6.70	6.97	7.24	7.34	7.35	7.35	7.28	7.25
E2(YZ)波瓣宽度	37.00	38.00	38.00	39.00	40.00	40.00	41.00	42.00	44.00	45.00	48.00	48.00	50.00	50.00	48.00	48.00	47.00	48.00	49.00	49.00	50.00
E2(YZ)前后比	10.15	10.33	10.41	10.33	10.38	10.32	10.23	10.27	10.30	10.22	10.26	10.52	10.72	10.80	11.06	10.82	10.55	10.16	10.11	10.16	10.30
最大增益外轴比(P)	15.35	15.97	16.99	18.11	18.69	19.48	20.67	21.44	21.97	22.32	23.54	23.50	23.74	24.76	18.31	15.72	15.61	15.63	16.08	16.47	17.02
顶点(Theta=0)轴轴比(P)	3.80	4.85	6.34	7.18	7.86	8.15	8.86	9.05	9.39	9.71	9.77	9.44	9.35	9.74	10.25	10.25	10.21	11.20	12.39	14.53	13.95
角10度最差(大)轴轴比(P)	30.89	30.23	47.93	46.53	54.28	59.10	55.12	57.56	53.61	58.42	58.17	55.01	59.39	59.23	67.06	55.88	80.35	59.01	57.62	58.73	56.97
Hc(XY)波瓣宽度	258.00	337.00	339.00	346.00	354.00	356.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00	360.00
Hc(XY)前后比	0.34	0.28	0.29	0.23	0.20	0.23	0.14	0.16	0.15	0.08	0.08	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
左旋圆极化效率(%)	35.31	36.11	35.97	35.90	36.17	36.41	36.28	36.07	35.80	35.72	35.50	35.12	34.51	33.95	33.81	33.52	33.41	33.42	33.58	33.82	33.56
右旋圆极化效率(%)	30.53	31.52	32.49	33.13	34.18	35.05	35.56	35.60	35.73	35.50	34.94	33.80	32.52	31.35	30.61	30.03	29.73	29.85	30.61	31.54	32.15





原装进口法国 SATIMO 公司 StarLab 3D 实验室,能精确快速的测试手机、平板电脑和笔记本等通信终端产品的 TRP、TIS、效率、增益、苹果图、方向图等参数数据。

The StarLab 3D laboratory of the original imported French SATIMO Company can accurately and quickly test the parameter data such as TRP, TIS, efficiency, gain, Apple chart and pattern of communication terminal products such as mobile phones, tablet computers and laptops.