TESTING LABORATORY
CERTIFICATE#4323.01

FCC PART 15.247
TEST REPORT

For

M5Stack Technology Co.,Ltd

106,1st Floor,Building 1,Bright Technology Park,88 Zhuguang North Road,XiliTaoyuan Street,Nanshan District,Shenzhen,Guangdong,China

FCC ID: 2AN3WM5STICKCPLUS

Report Type:	**Product Type:**
Original Report	M5StickC PLUS

Test Engineer:	Lee Li
Report Number:	RSHD200602001-00C
Report Date:	2020-07-09
Reviewed By:	Oscar Ye EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliant Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EUT EXERCISE SOFTWARE 6
SPECIAL ACCESSORIES 6
EQUIPMENT MODIFICATIONS 6
SUPPORT EQUIPMENT LIST AND DETAILS 7
EXTERNAL I/O CABLE 7
BLOCK DIAGRAM OF TEST SETUP 7
SUMMARY OF TEST RESULTS **9**
TEST EQUIPMENT LIST **10**
FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) **11**
APPLICABLE STANDARD 11
CALCULATED FORMULARY: 11
CALCULATED DATA (WORST CASE): 11
FCC §15.203 – ANTENNA REQUIREMENT **12**
APPLICABLE STANDARD 12
ANTENNA CONNECTOR CONSTRUCTION 12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **13**
APPLICABLE STANDARD 13
EUT SETUP 13
EMI TEST RECEIVER SETUP 13
TEST PROCEDURE 14
CORRECTED FACTOR & MARGIN CALCULATION 14
TEST RESULTS SUMMARY 14
TEST DATA 14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS **19**
APPLICABLE STANDARD 19
EUT SETUP 19
EMI TEST RECEIVER SETUP 20
TEST PROCEDURE 20
CORRECTED AMPLITUDE & MARGIN CALCULATION 20
TEST RESULTS SUMMARY 20
TEST DATA 20
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST **33**
APPLICABLE STANDARD 33
TEST PROCEDURE 33
TEST DATA 33
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH **39**
APPLICABLE STANDARD 39

TEST PROCEDURE 39
TEST DATA 39

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST 45

APPLICABLE STANDARD 45
TEST PROCEDURE 45
TEST DATA 45

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....48

APPLICABLE STANDARD 48
TEST PROCEDURE 48
TEST DATA 48

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT 64

APPLICABLE STANDARD 64
TEST PROCEDURE 64
TEST DATA 64

FCC §15.247(d) - BAND EDGES TESTING 71

APPLICABLE STANDARD 71
TEST PROCEDURE 71
TEST DATA 71

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	M5Stack Technology Co.,Ltd
Product Type:	M5StickC PLUS
Tested Model:	M5StickC PLUS
Series Model:	M5StickT
Power Supply:	DC 3.7V from battery or DC 5.0V
RF Function:	Classic BT
Operating Band/Frequency:	2402-2480MHz
Channel Number:	79
Channel Separation:	1MHz
Modulation Type:	GFSK, π/4-DQPSK, 8DPSK
Antenna Type:	PIFA Antenna
Maximum Antenna Gain:	2.0dBi

Note: The model difference was explained in the attached declaration letter.

**All measurement and test data in this report was gathered from production sample serial number: 20200602001. (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-06-02)*

Objective

This test report is prepared on behalf of *M5Stack Technology Co.,Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: 2AN3WM5STICKCPLUS.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	…	…
…	…	…	…
…	…	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

Note: We test all the items for model M5StickC PLUS, but only AC Line Conducted Emissions and Spurious Emissions (below 1GHz) for model M5StickT.

EUT Exercise Software

RF test software: EspRFtestTool

GFSK, π/4-DQPSK , 8DPSK Power level: 6 .

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Notebook	GX620	D65874152
DELL	Adapter	LA65NS0-00	DF263

External I/O Cable

Cable Description	Shielding Type	Length (m)	From Port	To
USB Cable	Un-shielding	1.0	Notebook	EUT

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test（Chamber 1#）					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-11-12	2020-11-11
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2019-12-26	2022-12-25
Sonoma Instrunent	Pre-amplifier	310N	171205	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	-	-
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test（Chamber 2#）					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	6229	2019-01-11	2022-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-10-18	2022-10-17
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2019-11-12	2020-11-11
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-07-23	2020-07-22
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
M5Stack Technology Co.,Ltd	RF Cable	M5Stack Technology Co.,Ltd 01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2019-11-30	2020-11-29
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Audix	Test Software	e3	V9	--	--
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2019-08-10	2020-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	**Electric Field Strength (V/m)**	**Magnetic Field Strength (A/m)**	**Power Density (mW/cm²)**	**Averaging Time (minutes)**
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm^2);
P = power input to the antenna (in appropriate units, e.g., mW);
G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data (worst case):

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm^2)	MPE Limit (mW/cm^2)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412-2462	2.00	1.58	21.00	125.89	20	0.0396	1.0
802.11g		2.00	1.58	20.50	112.20	20	0.0353	1.0
802.11n-HT20		2.00	1.58	20.50	112.20	20	0.0353	1.0
802.11n-HT40	2422-2452	2.00	1.58	20.50	112.20	20	0.0353	1.0
BLE	2402-2480	2.00	1.58	5.50	3.55	20	0.0011	1.0
BT	2402-2480	2.00	1.58	7.50	5.62	20	0.0018	1.0

Note: 1. For the above tune up power were declared by the manufacturer.
2. Wi-Fi and BT/BLE can't transmit simultaneously.

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an internal PIFA antenna for Bluetooth, which the antenna gain is 2.0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Attenuator. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Attenuator (dB)

The "**Over Limit**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over Limit of 7dB means the emission is 7 dB above the limit. The equation for over Limit calculation is as follows:

Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	23.4~24.6℃
Relative Humidity:	49~50%
ATM Pressure:	101.1~101.3kPa

The testing was performed by Lee Li from 2020-06-09 to 2020-06-30.

EUT operation mode: Transmitting in high channel of 8DPSK mode (Worst case)

Model: M5StickC PLUS

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.152	9.50	19.82	29.32	55.91	-26.59	Average
2	0.152	31.70	19.82	51.52	65.91	-14.39	QP
3	0.199	5.60	19.82	25.42	53.67	-28.25	Average
4	0.199	27.90	19.82	47.72	63.67	-15.95	QP
5	0.415	8.20	19.74	27.94	47.55	-19.61	Average
6	0.415	14.10	19.74	33.84	57.55	-23.71	QP
7	1.276	3.80	19.82	23.62	46.00	-22.38	Average
8	1.276	9.00	19.82	28.82	56.00	-27.18	QP
9	1.593	3.29	19.85	23.14	46.00	-22.86	Average
10	1.593	8.79	19.85	28.64	56.00	-27.36	QP
11	2.066	2.80	19.78	22.58	46.00	-23.42	Average
12	2.066	8.20	19.78	27.98	56.00	-28.02	QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.151	10.20	19.82	30.02	55.96	-25.94	Average
2	0.151	30.20	19.82	50.02	65.96	-15.94	QP
3	0.200	6.30	19.82	26.12	53.62	-27.50	Average
4	0.200	26.20	19.82	46.02	63.62	-17.60	QP
5	0.367	9.70	19.78	29.48	48.56	-19.08	Average
6	0.367	15.30	19.78	35.08	58.56	-23.48	QP
7	0.454	7.70	19.75	27.45	46.80	-19.35	Average
8	0.454	11.30	19.75	31.05	56.80	-25.75	QP
9	1.269	4.90	19.82	24.72	46.00	-21.28	Average
10	1.269	11.50	19.82	31.32	56.00	-24.68	QP
11	2.750	2.70	19.47	22.17	46.00	-23.83	Average
12	2.750	9.30	19.47	28.77	56.00	-27.23	QP

Model: M5StickT

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.153	4.80	19.82	24.62	55.82	-31.20	Average
2	0.153	26.20	19.82	46.02	65.82	-19.80	QP
3	0.200	-0.10	19.82	19.72	53.62	-33.90	Average
4	0.200	20.40	19.82	40.22	63.62	-23.40	QP
5	0.258	1.60	19.82	21.42	51.51	-30.09	Average
6	0.258	14.90	19.82	34.72	61.51	-26.79	QP
7	0.327	-0.60	19.82	19.22	49.53	-30.31	Average
8	0.327	10.00	19.82	29.82	59.53	-29.71	QP
9	0.410	4.70	19.74	24.44	47.64	-23.20	Average
10	0.410	9.40	19.74	29.14	57.64	-28.50	QP
11	1.276	0.90	19.82	20.72	46.00	-25.28	Average
12	1.276	7.70	19.82	27.52	56.00	-28.48	QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.153	3.60	19.82	23.42	55.82	-32.40	Average
2	0.153	24.60	19.82	44.42	65.82	-21.40	QP
3	0.209	0.80	19.82	20.62	53.23	-32.61	Average
4	0.209	17.30	19.82	37.12	63.23	-26.11	QP
5	0.266	-1.50	19.82	18.32	51.25	-32.93	Average
6	0.266	11.80	19.82	31.62	61.25	-29.63	QP
7	0.379	1.40	19.77	21.17	48.30	-27.13	Average
8	0.379	5.30	19.77	25.07	58.30	-33.23	QP
9	0.474	-2.70	19.76	17.06	46.45	-29.39	Average
10	0.474	3.20	19.76	22.96	56.45	-33.49	QP
11	1.255	4.40	19.82	24.22	46.00	-21.78	Average
12	1.255	9.30	19.82	29.12	56.00	-26.88	QP

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV /m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The "**Margin**" column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	24.8℃
Relative Humidity:	50 %
ATM Pressure:	101.2kPa

The testing was performed by Lee Li on 2020-06-09.

EUT operation mode: Transmitting

Model: M5StickC PLUS

Spurious Emission Test:

30MHz-1GHz:
Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***high channel of 8DPSK Mode in Z-axis of orientation*** *was recorded*



Frequency (MHz)	Corrected Amplitude Quasi-peak (dBµV/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
83.96	30.64	200	H	177	-18.1	40.00	9.36
373.38	39.23	100	H	121	-9.3	46.00	6.77
453.41	38.20	100	H	114	-7.3	46.00	7.80
506.63	41.00	200	V	283	-6.1	46.00	5.00
586.78	40.48	200	H	154	-5.5	46.00	5.52
666.68	37.73	200	H	34	-3.8	46.00	8.27

Model: M5StickT

Spurious Emission Test:

30MHz-1GHz:
Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***high channel of 8DPSK Mode in Z-axis of orientation*** *was recorded*



Frequency (MHz)	Corrected Amplitude Quasi-peak (dBµV/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
83.96	33.46	200	H	179	-18.1	40.00	6.54
266.68	35.70	100	H	165	-12.1	46.00	10.30
399.93	39.82	100	H	158	-8.6	46.00	6.18
499.97	40.28	200	H	149	-6.1	46.00	5.72
586.66	41.94	100	V	270	-5.5	46.00	4.06
826.73	42.07	100	V	284	-1.0	46.00	3.93

1GHz-18GHz:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***8DPSK Mode in Z-axis of orientation*** *was recorded*

Note:
1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
   Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1064.60	---	25.55	100	V	0	-18.7	54.00	28.45
1064.60	35.37	---	100	V	0	-18.7	74.00	38.63
3201.50	---	34.70	150	H	258	-9.6	54.00	19.30
3201.50	41.01	---	150	H	258	-9.6	74.00	32.99
4804.00	---	31.06	200	V	272	-5.6	54.00	22.94
4804.00	38.95	---	200	V	272	-5.6	74.00	35.05
7300.20	---	39.22	100	H	0	0.6	54.00	14.78
7300.20	45.29	---	100	H	0	0.6	74.00	28.71
9746.50	---	40.11	200	V	314	2.0	54.00	13.89
9746.50	44.98	---	200	V	314	2.0	74.00	29.02
17796.00	---	48.68	100	V	19	8.8	54.00	5.32
17796.00	53.92	---	100	V	19	8.8	74.00	20.08

Middle Channel: 2441MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1727.60	---	27.86	200	V	191	-15.5	54.00	26.14
1727.60	35.54	---	200	V	191	-15.5	74.00	38.46
3454.80	---	34.68	200	V	307	-8.9	54.00	19.32
3454.80	40.68	---	200	V	307	-8.9	74.00	33.32
4882.00	---	33.43	150	H	0	-5.4	54.00	20.57
4882.00	40.20	---	150	H	0	-5.4	74.00	33.80
7323.00	---	38.96	100	V	160	0.7	54.00	15.04
7323.00	44.01	---	100	V	160	0.7	74.00	29.99
10384.00	---	40.01	150	V	88	2.2	54.00	13.99
10384.00	45.97	---	150	V	88	2.2	74.00	28.03
17770.50	---	47.97	100	V	85	8.8	54.00	6.03
17770.50	54.33	---	100	V	85	8.8	74.00	19.67

High Channel: 2480MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1880.60	---	27.61	150	V	358	-14.9	54.00	26.39
1880.60	33.07	---	150	V	358	-14.9	74.00	40.93
3201.50	---	34.21	200	H	59	-9.6	54.00	19.79
3201.50	41.41	---	200	H	59	-9.6	74.00	32.59
4960.00	---	33.34	100	V	190	-5.2	54.00	20.66
4960.00	41.08	---	100	V	190	-5.2	74.00	32.92
7896.90	---	39.74	200	V	176	1.6	54.00	14.26
7896.90	45.77	---	200	V	176	1.6	74.00	28.23
9826.40	---	40.73	100	V	95	2.0	54.00	13.27
9826.40	45.42	---	100	V	95	2.0	74.00	28.58
17843.60	---	48.13	200	H	57	8.8	54.00	5.87
17843.60	53.58	---	200	H	57	8.8	74.00	20.42

18GHz-25GHz:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***high channel of 8DPSK Mode in Z-axis of orientation*** *was recorded*

Horizontal



Date: 9.JUN.2020 00:31:11

Vertical



Date: 9.JUN.2020 00:45:31

Fundamental Test & Restricted Bands Emissions:

Pre-Scan with GFSK, π/4-DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case ***8DPSK Mode in Z-axis of orientation*** *was recorded*

Note:
1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
   Corrected Amplitude (dBμV /m) = Corrected Factor (dB/m) + Reading (dBμV)
   Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV /m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	---	38.35	200	H	304	-2.9	54.00	15.65
2390.00	45.90	---	200	H	304	-2.9	74.00	28.10
High Channel: 2480MHz								
2483.50	---	37.63	150	H	142	-2.4	54.00	16.37
2483.50	45.92	---	150	H	142	-2.4	74.00	28.08

Conducted Spurious Emissions at Antenna Port

BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel



BDR (GFSK): High Channel



EDR (π/4-DQPSK): Low Channel



EDR (π/4-DQPSK): Middle Channel



EDR (π/4-DQPSK): High Channel



EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a. Span: Wide enough to capture the peaks of two adjacent channels.
b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c. Video (or average) bandwidth (VBW) ≥ RBW.
d. Sweep: Auto.
e. Detector function: Peak.
f. Trace: Max hold.
g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data

Environmental Conditions

Temperature:	24.5 ℃
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Lee Li on 2020-06-15.

EUT operation mode: Transmitting

Test Result: Compliant.

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.003	0.956	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.956	Pass
	Adjacent	2442			
	High	2480	1.003	0.956	Pass
	Adjacent	2479			
EDR (π/4-DQPSK)	Low	2402	1.003	0.882	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.882	Pass
	Adjacent	2442			
	High	2480	1.003	0.882	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.003	0.878	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.878	Pass
	Adjacent	2442			
	High	2480	1.003	0.878	Pass
	Adjacent	2479			

Note: For BDR mode, Limit = 20 dB bandwidth , For EDR mode, Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel



Date: 15.JUN.2020 18:36:39

BDR (GFSK): High Channel



Date: 15.JUN.2020 18:53:46

EDR (π/4-DQPSK): Low Channel



Date: 15.JUN.2020 18:31:06

EDR (π/4-DQPSK): Middle Channel



Date: 15.JUN.2020 18:38:47

EDR (π/4-DQPSK): High Channel



Date: 15.JUN.2020 18:50:28

EDR (8DPSK): Low Channel



Date: 15.JUN.2020 18:27:59

EDR (8DPSK): Middle Channel



Date: 15.JUN.2020 18:42:55

EDR (8DPSK): High Channel



Date: 15.JUN.2020 18:47:35

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	24.7 ℃
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Lee Li on 2020-06-06.

EUT operation mode: Transmitting

Test Result: Compliant.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.956
	Middle	2441	0.956
	High	2480	0.956
EDR (π/4-DQPSK)	Low	2402	1.323
	Middle	2441	1.323
	High	2480	1.323
EDR (8DPSK)	Low	2402	1.317
	Middle	2441	1.317
	High	2480	1.317

BDR (GFSK): Low Channel



BDR (GFSK): Middle Channel



Date: 6.JUN.2020 11:35:26

BDR (GFSK): High Channel



Date: 6.JUN.2020 11:38:12

EDR (π/4-DQPSK): Low Channel



EDR(π/4-DQPSK): Middle Channel



EDR (π/4-DQPSK): High Channel



EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
c. VBW ≥ RBW.
d. Sweep: Auto.
e. Detector function: Peak.
f. Trace: Max hold.
g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data

Environmental Conditions

Temperature:	24.6 ℃
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Lee Li on 2020-06-06.

EUT operation mode: Hopping

Test Result: Compliant.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels



EDR (π/4-DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a Span: Zero span, centered on a hopping channel.
b RBW shall be ≤ channel spacing and where possible RBW should be set ≥ 1 / T, where T is the expected dwell time per channel.
c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d Detector function: Peak.
e Trace: Max hold.

Test Data

Environmental Conditions

Temperature:	24.6 ℃
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Lee Li on 2020-06-06.

EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.387	0.124	0.4	Pass
		Middle	0.387	0.124	0.4	Pass
		High	0.389	0.124	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.651	0.264	0.4	Pass
		Middle	1.651	0.264	0.4	Pass
		High	1.651	0.264	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.92	0.311	0.4	Pass
		Middle	2.91	0.310	0.4	Pass
		High	2.92	0.311	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (π/4-DQPSK)	2DH1	Low	0.401	0.128	0.4	Pass
		Middle	0.401	0.128	0.4	Pass
		High	0.401	0.128	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.663	0.266	0.4	Pass
		Middle	1.663	0.266	0.4	Pass
		High	1.663	0.266	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.930	0.313	0.4	Pass
		Middle	2.930	0.313	0.4	Pass
		High	2.930	0.313	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.401	0.128	0.4	Pass
		Middle	0.401	0.128	0.4	Pass
		High	0.401	0.128	0.4	Pass
		Note:3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.663	0.266	0.4	Pass
		Middle	1.663	0.266	0.4	Pass
		High	1.663	0.266	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.930	0.313	0.4	Pass
		Middle	2.930	0.313	0.4	Pass
		High	2.920	0.311	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				

BDR (GFSK): Pulse time, Low Channel, DH1



BDR (GFSK): Pulse time, Middle Channel, DH1



BDR (GFSK): Pulse time, High Channel, DH1



BDR (GFSK): Pulse time, Low Channel, DH3



BDR (GFSK): Pulse time, Middle Channel, DH3



BDR (GFSK): Pulse time, High Channel, DH3



BDR (GFSK): Pulse time, Low Channel, DH5



BDR (GFSK): Pulse time, Middle Channel, DH5



BDR (GFSK): Pulse time, High Channel, DH5



Date: 6.JUN.2020 16:26:27

EDR (π/4-DQPSK): Pulse time, Low Channel, 2DH1



Date: 6.JUN.2020 14:42:34

EDR (π/4-DQPSK):Pulse time, Middle Channel, 2DH1



EDR (π/4-DQPSK):Pulse time, High Channel, 2DH1



EDR (π/4-DQPSK):Pulse time, Low Channel, 2DH3



EDR (π/4-DQPSK):Pulse time, Middle Channel, 2DH3



EDR (π/4-DQPSK):Pulse time, High Channel, 2DH3



Date: 6.JUN.2020 14:53:41

EDR (π/4-DQPSK):Pulse time, Low Channel, 2DH5



Date: 6.JUN.2020 16:28:03

EDR (π/4-DQPSK):Pulse time, Middle Channel, 2DH5



EDR (π/4-DQPSK):Pulse time, High Channel, 2DH5



EDR (8DPSK): Pulse time, Low Channel, 3DH1



EDR (8DPSK): Pulse time, Middle Channel, 3DH1



EDR (8DPSK): Pulse time, High Channel, 3DH1



EDR (8DPSK): Pulse time, Low Channel, 3DH3



EDR (8DPSK): Pulse time, Middle Channel, 3DH3



Date: 6.JUN.2020 15:48:04

EDR (8DPSK): Pulse time, High Channel, 3DH3



Date: 6.JUN.2020 15:47:16

EDR (8DPSK): Pulse time, Low Channel, 3DH5



EDR (8DPSK): Pulse time, Middle Channel, 3DH5



EDR (8DPSK): Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

a. Use the following spectrum analyzer settings:
   1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
   2) RBW > 20 dB bandwidth of the emission being measured.
   3) VBW ≥ RBW.
   4) Sweep: Auto.
   5) Detector function: Peak.
   6) Trace: Max hold.

b. Allow trace to stabilize.
c. Use the marker-to-peak function to set the marker to the peak of the emission.
d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions

Temperature:	21.7 ℃
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Lee Li on 2020-06-06.

EUT operation mode: Transmitting

Test Result: Compliant.

Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	4.38	2.74	1000
	2441	4.63	2.90	1000
	2480	4.76	2.99	1000
EDR (π/4-DQPSK)	2402	6.62	4.59	125
	2441	6.86	4.85	125
	2480	6.99	5.00	125
EDR (8DPSK)	2402	7.12	5.15	125
	2441	7.24	5.30	125
	2480	7.36	5.45	125

BDR (GFSK): 2402MHz



BDR (GFSK): 2441MHz



BDR (GFSK): 2480MHz



EDR(π/4-DQPSK): 2402MHz



EDR(π/4-DQPSK): 2441MHz



EDR(π/4-DQPSK): 2480MHz



EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.8℃
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Lee Li on 2020-06-06.

EUT operation mode: Transmitting & Hopping

Test Result: Compliant.

Band Edge

BDR (GFSK): Left Side - Transmitting



BDR (GFSK): Right Side - Transmitting



EDR (π/4-DQPSK): Left Side - Transmitting



EDR (π/4-DQPSK): Right Side - Transmitting



EDR (8DPSK): Left Side - Transmitting



EDR (8DPSK): Right Side - Transmitting



BDR (GFSK): Left Side - Hopping



BDR (GFSK): Right Side- Hopping



EDR (π/4-DQPSK): Left Side- Hopping



EDR (π/4-DQPSK): Right Side- Hopping



EDR (8DPSK): Left Side- Hopping



EDR (8DPSK): Right Side- Hopping



Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******