

RF Test Report

For


Applicant name: SHENZHEN TORRAS TECHNOLOGY CO., LTD.
Address: RM1215, BLK C, Zhantao Technology BLDG, Minzhi Avenue, Minzhi ST, Longhua DIST, Shenzhen, China
EUT name: Car Mount Wireless Charger
Brand name: TORRAS
Model number: WZ2A
Series model number: N/A
FCC ID: 2AN4Y-WZ2A

Issued By

Company name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: 101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Report number: BTF251205R00101
Test standards: 47 CFR Part 15C
Test conclusion: Pass

Date of sample receipt: 2025-12-02
Test date: 2025-12-02 to 2026-05-07
Date of issue: 2026-06-24

Prepared by: 
Chris.Liu / Project engineer

Approved by: 

Ryan.CJ / EMC Manager

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2026-06-24	Original
<i>Note:</i> <i>Once the revision has been made, then previous versions reports are invalid.</i>		

Table of Contents

1 Introduction	4
1.1 Laboratory Location	4
1.2 Laboratory Facility	4
1.3 Announcement	4
2 Product Information	5
2.1 Application Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Technical Information	6
3 Summary of Test Results	7
3.1 Test Standards	7
3.2 Uncertainty of Test	7
3.3 Summary of Test Result	7
3.4 Additions to, deviations, or exclusions from the method	7
4 Test Configuration	8
4.1 Test Equipment List	8
4.2 Test Auxiliary Equipment	8
4.3 Test Modes	8
5 Evaluation Results (Evaluation)	9
5.1 Antenna requirement	9
5.1.1 Conclusion	9
6 Radio Spectrum Matter Test Results (RF)	10
6.1 Conducted Emission at AC power line	10
6.1.1 Test Data	11
6.2 20dB Occupied Bandwidth	13
6.2.1 Test Data	14
6.3 Emissions in frequency bands (below 30MHz)	16
6.3.1 Test Data	17
6.4 Emissions in frequency bands (30MHz - 1GHz)	21
6.4.1 Test Data	22
7 Test Setup Photos	24
8 EUT Constructional Details (EUT Photos)	24

1 Introduction

1.1 Laboratory Location

Test location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China
Phone number:	+86-0755-23146130
Fax number:	+86-0755-23146130

1.2 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1409**
BTF Testing Lab (Shenzhen) Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The test firm Registration No. is 695374.
- **CNAS - Registration No.: CNAS L17568**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L17568.
- **A2LA - Registration No.: 6660.01**
BTF Testing Lab (Shenzhen) Co., Ltd. is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.
- (7) All entrusted information in this report is provided by the client and has been confirmed through consultation with the client; The testing items for this report have been discussed and confirmed with the client, and our company is only responsible for the content reflected in the report.

2 Product Information

2.1 Application Information

Company name:	SHENZHEN TORRAS TECHNOLOGY CO., LTD.
Address:	RM1215, BLK C, Zhantao Technology BLDG, Minzhi Avenue, Minzhi ST, Longhua DIST, Shenzhen, China

2.2 Manufacturer Information

Company name:	SHENZHEN TORRAS TECHNOLOGY CO., LTD.
Address:	RM1215, BLK C, Zhantao Technology BLDG, Minzhi Avenue, Minzhi ST, Longhua DIST, Shenzhen, China

2.3 Factory Information

Company name:	SHENZHEN TORRAS TECHNOLOGY CO., LTD.
Address:	RM1215, BLK C, Zhantao Technology BLDG, Minzhi Avenue, Minzhi ST, Longhua DIST, Shenzhen, China

2.4 General Description of Equipment under Test (EUT)

EUT name:	Car Mount Wireless Charger
Under test model name:	WZ2A
Series model name:	N/A
Description of model name differentiation:	N/A
Hardware version:	N/A
Software version:	N/A
Ratings:	Input: 5.0V $\overline{\text{---}}$ 3.0A/9.0V $\overline{\text{---}}$ 3.0A/12.0V $\overline{\text{---}}$ 3.0A/15.0V $\overline{\text{---}}$ 3.0A Output: 25W MAX

2.5 Technical Information

Operation Frequency:	125kHz-129kHz, 340kHz-380kHz
Modulation technology:	ASK
Antenna type:	Coil Antenna

3 Summary of Test Results

3.1 Test Standards

The tests were performed according to following standards:
47 CFR Part 15C: Intentional Radiators

3.2 Uncertainty of Test

Measurement	Value
Conducted Emission for LISN (150kHz ~ 30MHz)	±2.45 dB
Occupied Channel Bandwidth	±5 %
Unwanted Emissions, conducted	±3.0 dB
The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3.3 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15C	47 CFR Part 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15C	47 CFR Part 15.207(a)	Pass
20dB Occupied Bandwidth	47 CFR Part 15C	47 CFR Part 15.215(c)	Pass
Emissions in frequency bands (below 30MHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass
Emissions in frequency bands (30MHz - 1GHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass
Remark: 1. Pass: Meet the requirements. 2. N/A: not applicable.			

3.4 Additions to, deviations, or exclusions from the method

None

4 Test Configuration

4.1 Test Equipment List

Conducted Emission at AC power line					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
EMI Receiver	Rohde & Schwarz	ESCI3	101422	2025/10/17	2026/10/16
V-LISN	Schwarzbeck	NSLK 8127	01073	2025/8/23	2026/8/22
Coaxial Switcher	Schwarzbeck	CX210	CX210	/	/
Pulse Limiter	Schwarzbeck	VTSD 9561-F	00953	/	/
Test Software	Frad	EZ_EMC	Version: EMC-CON 3A1.1+	/	/

20dB Occupied Bandwidth					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	Keysight	N9020A	MY50410020	2025/10/17	2026/10/16

Emissions in frequency bands (below 30MHz) Emissions in frequency bands (30MHz - 1GHz)					
Test Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
EMI Receiver	Rohde & Schwarz	ESCI7	101032	2025/10/17	2026/10/16
Signal Analyzer	Rohde & Schwarz	FSQ40	100010	2025/10/17	2026/10/16
Log periodic antenna	Schwarzbeck	VULB 9168	01328	2025/10/18	2026/10/17
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00059	2025/06/25	2027/06/24
Preamplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9744	00246	2025/5/26	2026/5/25
Test Software	Frad	EZ_EMC	Version: FA-03A2 RE+	/	/

4.2 Test Auxiliary Equipment

No.	Description	Manufacturer	Model	Serial Number	Certification
1	iPhone	Apple	iPhone 15 pro	/	/

4.3 Test Modes

No.	Test Modes	
TM1	EUT stand alone, standby.powered by AC input.	
TM2	Direct contact duringcharging/operating between theEUT& Mobile phone is poweredby AC input.	Using a mobile phone load (Battery Status:99%)
TM3		Using a mobile phone load (Battery Status:50%)
TM4		Using a mobile phone load (Battery Status:1%)
Remark:@125kHz-129kHz, 340kHz-380kHz(128kHz&360.000kHz)		

5 Evaluation Results (Evaluation)

5.1 Antenna requirement


Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Operating Environment:	
Temperature:	24.3 °C
Humidity:	49.7 %
Atmospheric Pressure:	1010 mbar
Test voltage:	AC 120V 60Hz

5.1.1 Conclusion

The antenna is a permanently fixed coil antenna and meets the standard requirements. Please refer to the EUT photos for the antenna.

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).		
Test Method:	ANSI C63.10-2020 + Cor.1-2023 section 6.2		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dBμV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
*Decreases with the logarithm of the frequency.			
Procedure:	Refer to ANSI C63.10-2020 + Cor.1-2023 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		
Test Setup:			
Operating Environment:			
Temperature:	24.8 °C		
Humidity:	55 %		
Atmospheric Pressure:	1010 mbar		
Test voltage:	AC 120V 60Hz		

6.1.1 Test Data


Remark: The report only reflects the test data of worst mode.

TM4 / Line: Line



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	36.12	10.20	46.32	66.00	-19.68	QP	P	
2	0.1500	21.79	10.20	31.99	56.00	-24.01	AVG	P	
3	0.2353	35.53	10.18	45.71	62.26	-16.55	QP	P	
4	0.2353	18.91	10.18	29.09	52.26	-23.17	AVG	P	
5	0.2893	23.51	10.21	33.72	50.54	-16.82	AVG	P	
6	0.2940	31.78	10.21	41.99	60.41	-18.42	QP	P	
7	0.3750	31.75	10.20	41.95	58.39	-16.44	QP	P	
8	0.4334	18.57	10.19	28.76	47.19	-18.43	AVG	P	
9	1.3064	29.17	10.24	39.41	56.00	-16.59	QP	P	
10 *	1.3064	24.47	10.24	34.71	46.00	-11.29	AVG	P	
11	2.7554	30.37	10.26	40.63	56.00	-15.37	QP	P	
12	2.7554	24.43	10.26	34.69	46.00	-11.31	AVG	P	


TM4 / Line: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	36.41	10.21	46.62	66.00	-19.38	QP	P	
2	0.1500	20.61	10.21	30.82	56.00	-25.18	AVG	P	
3	0.2328	35.80	10.21	46.01	62.35	-16.34	QP	P	
4	0.2353	20.50	10.21	30.71	52.26	-21.55	AVG	P	
5	0.2893	32.17	10.21	42.38	60.54	-18.16	QP	P	
6	0.2893	20.61	10.21	30.82	50.54	-19.72	AVG	P	
7	0.4692	28.05	10.23	38.28	56.53	-18.25	QP	P	
8	0.4692	15.15	10.23	25.38	46.53	-21.15	AVG	P	
9	1.1580	29.12	10.23	39.35	56.00	-16.65	QP	P	
10	1.1580	17.96	10.23	28.19	46.00	-17.81	AVG	P	
11	2.4674	30.17	10.26	40.43	56.00	-15.57	QP	P	
12 *	2.4674	24.84	10.26	35.10	46.00	-10.90	AVG	P	

6.2 20dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15.215(c)
Test Method:	ANSI C63.10-2020 + Cor.1-2023, section 6.9.2
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Procedure:	a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Steps a) through c) might require iteration to adjust within the specified tolerances. e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value. f) Set detection mode to peak and trace mode to max hold. g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value). h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument. i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j). j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth. k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).
Test Setup:	




Operating Environment:	
Temperature:	24.3 °C
Humidity:	49.7 %
Atmospheric Pressure:	1010 mbar
Test voltage:	AC 120V 60Hz

6.2.1 Test Data


Test Frequency (kHz)	f _L (kHz)	f _H (kHz)	20dB Bandwidth (Hz)	Limits
128.000	127.759	128.252	493	N/A
360.000	359.763	360.255	492	N/A

Remark: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 200 Hz to perform the occupied bandwidth test.

Test Plot as Follows:



6.3 Emissions in frequency bands (below 30MHz)

Test Requirement:	47 CFR Part 15.209		
Test Method:	ANSI C63.10-2020 + Cor.1-2023 section 6.4		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a)and (b)of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b)of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.		
Procedure:	ANSI C63.10-2020 + Cor.1-2023 section 6.4		
Test Setup:			
Operating Environment:			
Temperature:	24.3 °C		
Humidity:	49.7 %		


Atmospheric Pressure:	1010 mbar
Test voltage:	AC 120V 60Hz

6.3.1 Test Data

Test Frequency (MHz)	Field strength(dBuV/m)	Limits
128.000	59.67	105.44
360.000	56.73	96.47


Remark: The report only reflects the worst test data.

TM1 / Polarization: Coaxial




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	0.0100	72.99	-30.37	42.62	127.59	-84.97	peak	P
2	0.0204	76.16	-30.35	45.81	121.40	-75.59	peak	P
3	0.0263	74.67	-30.35	44.32	119.19	-74.87	peak	P
4	0.0434	73.47	-30.32	43.15	114.84	-71.69	peak	P
5	0.0874	70.37	-30.26	40.11	108.77	-68.66	peak	P
6 *	0.1290	87.70	-30.23	57.47	105.39	-47.92	peak	P

TM1 / Polarization:Parallel




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	0.0142	72.14	-30.36	41.78	124.54	-82.76	peak	P
2	0.0252	74.27	-30.35	43.92	119.56	-75.64	peak	P
3	0.0420	74.48	-30.32	44.16	115.13	-70.97	peak	P
4	0.0555	75.41	-30.30	45.11	112.71	-67.60	peak	P
5	0.0743	69.66	-30.28	39.38	110.18	-70.80	peak	P
6 *	0.1282	89.90	-30.23	59.67	105.44	-45.77	peak	P

TM1 / Polarization: Coaxial




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	0.1698	58.91	-29.88	29.03	103.00	-73.97	peak	P
2 *	0.3653	89.44	-29.43	60.01	96.35	-36.34	peak	P
3	0.6140	53.94	-28.88	25.06	71.83	-46.77	peak	P
4	0.8920	49.77	-28.25	21.52	68.56	-47.04	peak	P
5	1.4993	46.02	-26.98	19.04	64.02	-44.98	peak	P
6	12.3180	24.03	-5.26	18.77	69.50	-50.73	peak	P

TM1 / Polarization: Parallel



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	0.2720	60.91	-29.65	31.26	98.91	-67.65	peak	P
2 *	0.3602	86.18	-29.45	56.73	96.47	-39.74	peak	P
3	0.5806	51.53	-28.95	22.58	72.32	-49.74	peak	P
4	1.1812	48.63	-27.64	20.99	66.11	-45.12	peak	P
5	3.0820	42.45	-23.73	18.72	69.50	-50.78	peak	P
6	13.6590	18.05	-2.78	15.27	69.50	-54.23	peak	P

6.4 Emissions in frequency bands (30MHz - 1GHz)


Test Requirement:	47 CFR Part 15.209		
Test Method:	ANSI C63.10-2020 + Cor.1-2023 section 6.5		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a)and (b)of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b)of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.			
Procedure:	ANSI C63.10-2020 + Cor.1-2023 section 6.5		
Test Setup:			
Operating Environment:			
Temperature:	24.6 °C		
Humidity:	55 %		

Atmospheric Pressure:	1010 mbar
Test voltage:	AC 120V 60Hz

6.4.1 Test Data


Remark: The report only reflects the worst test data.

TM4 / Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	64.4331	30.64	-9.44	21.20	40.00	-18.80	peak	P
2	143.8295	58.97	-27.39	31.58	43.50	-11.92	peak	P
3 *	204.9551	61.40	-26.71	34.69	43.50	-8.81	peak	P
4	303.5437	57.05	-25.75	31.30	46.00	-14.70	peak	P
5	389.3549	55.60	-24.99	30.61	46.00	-15.39	peak	P
6	679.9600	53.37	-22.61	30.76	46.00	-15.24	peak	P

TM4 / Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	48.1625	38.95	-9.66	29.29	40.00	-10.71	QP	P
2	95.4270	60.68	-27.97	32.71	43.50	-10.79	QP	P
3	143.8295	62.79	-27.39	35.40	43.50	-8.10	QP	P
4 *	204.2377	63.54	-26.72	36.82	43.50	-6.68	QP	P
5	389.3548	53.82	-24.99	28.83	46.00	-17.17	QP	P
6	704.2261	57.89	-22.41	35.48	46.00	-10.52	QP	P

7 Test Setup Photos

Please refer to the Appendix I Test Setup Photos

8 EUT Constructional Details (EUT Photos)

Please refer to the Appendix II External Photos & Appendix III External Photos



BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

www.btf-lab.com

-- END OF REPORT --