

# TEST REPORT

**FCC ID: 2AN4YCDRZ35**

**Product: Wireless Charger**

**Model No.: CDRZ35**

**Additional Model: N/A**

**Trade Mark: TORRAS**

**Report No.: TCT180201E907**

**Issued Date: Feb. 02, 2018**

Issued for:

**SHENZHEN TORRAS TECHNOLOGY CO., LTD.  
17F, BLOCK C, ZHANTAO TECHNOLOGY BUILDING, MINZHI ROAD,  
LONGHUA DISTRICT, SHENZHEN, China**

Issued By:

**Shenzhen Tongce Testing Lab.  
1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,  
Shenzhen, Guangdong, China  
TEL: +86-755-27673339  
FAX: +86-755-27673332**

**Note:** This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

## TABLE OF CONTENTS

|                                                   |          |
|---------------------------------------------------|----------|
| <b>1. Test Certification.....</b>                 | <b>3</b> |
| <b>2. Test Result Summary .....</b>               | <b>4</b> |
| <b>3. EUT Description .....</b>                   | <b>5</b> |
| <b>4. General Information .....</b>               | <b>6</b> |
| 4.1. Test environment and mode .....              | 6        |
| 4.2. Description of Support Units .....           | 6        |
| <b>5. Facilities and Accreditations .....</b>     | <b>7</b> |
| 5.1. Facilities .....                             | 7        |
| 5.2. Location.....                                | 7        |
| 5.3. Measurement Uncertainty .....                | 7        |
| <b>6. Test Results and Measurement Data .....</b> | <b>8</b> |
| 6.1. Antenna requirement.....                     | 8        |
| 6.2. Conducted Emission .....                     | 9        |
| 6.3. Radiated Spurious Emission Measurement ..... | 13       |
| <b>Appendix A: Photographs of Test Setup</b>      |          |
| <b>Appendix B: Photographs of EUT</b>             |          |

## 1. Test Certification

|                              |                                                                                           |
|------------------------------|-------------------------------------------------------------------------------------------|
| <b>Product:</b>              | Wireless Charger                                                                          |
| <b>Model No.:</b>            | CDRZ35                                                                                    |
| <b>Additional Model No.:</b> | N/A                                                                                       |
| <b>Trade Mark:</b>           | TORRAS                                                                                    |
| <b>Applicant:</b>            | SHENZHEN TORRAS TECHNOLOGY CO., LTD.                                                      |
| <b>Address:</b>              | 17F, BLOCK C, ZHANTAO TECHNOLOGY BUILDING, MINZHI ROAD, LONGHUA DISTRICT, SHENZHEN, China |
| <b>Manufacturer:</b>         | SHENZHEN TORRAS TECHNOLOGY CO., LTD.                                                      |
| <b>Address:</b>              | 17F, BLOCK C, ZHANTAO TECHNOLOGY BUILDING, MINZHI ROAD, LONGHUA DISTRICT, SHENZHEN, China |
| <b>Date of Test:</b>         | Jan. 09, 2018 - Jan. 16, 2018                                                             |
| <b>Applicable Standards:</b> | FCC CFR Title 47 Part 15 Subpart C                                                        |

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Date:

Jan. 16, 2018

Brews Xu

Reviewed By:



Date:

Feb. 02, 2018

Beryl

Approved By:



Date:

Feb. 02, 2018

Tomsin



## 2. Test Result Summary

| Requirement                      | CFR 47 Section | Result |
|----------------------------------|----------------|--------|
| Antenna requirement              | §15.203        | PASS   |
| AC Power Line Conducted Emission | §15.207        | PASS   |
| Spurious Emission                | §15.209(a)(f)  | PASS   |

**Note:**

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

### 3. EUT Description

|                               |                             |
|-------------------------------|-----------------------------|
| <b>Product:</b>               | Wireless Charger            |
| <b>Model No.:</b>             | CDRZ35                      |
| <b>Additional Model No.:</b>  | N/A                         |
| <b>Trade Mark:</b>            | <b>TORRAS</b>               |
| <b>Operation Frequency:</b>   | 110-205KHz                  |
| <b>Number of Channel:</b>     | 20 Channels                 |
| <b>Modulation Technology:</b> | MSK                         |
| <b>Antenna Type:</b>          | Inductive loop coil Antenna |
| <b>Antenna Gain:</b>          | 0dBi                        |

#### Operation Frequency each of channel

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 1       | 0.110           | 6       | 0.135           | 11      | 0.160           | 16      | 0.185           |
| 2       | 0.115           | 7       | 0.140           | 12      | 0.165           | 17      | 0.190           |
| 3       | 0.120           | 8       | 0.145           | 13      | 0.170           | 18      | 0.195           |
| 4       | 0.125           | 9       | 0.150           | 14      | 0.175           | 19      | 0.200           |
| 5       | 0.130           | 10      | 0.155           | 15      | 0.180           | 20      | 0.205           |

## 4. Genera Information

### 4.1. Test environment and mode

| Operating Environment:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 25.0 °C                                                                                                                                  |
| Humidity:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 56 % RH                                                                                                                                  |
| Atmospheric Pressure:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1010 mbar                                                                                                                                |
| Test Mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                          |
| Engineering mode:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) with Fully-charged battery. |
| The sample was placed (0.1m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. |                                                                                                                                          |

### 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Equipment    | Model No.  | Serial No.     | FCC ID | Trade Name |
|--------------|------------|----------------|--------|------------|
| Mobile Phone | SM-G9350   | R28HA2ER3GT    | /      | SAMSUNG    |
| Adapter      | EP-TA20CBC | R37HAEY0DT1RT3 | /      | SAMSUNG    |

**Note:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 5. Facilities and Accreditations

### 5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

### 5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

### 5.3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                          | MU                        |
|-----|-------------------------------|---------------------------|
| 1   | Conducted Emission            | $\pm 2.56\text{dB}$       |
| 2   | RF power, conducted           | $\pm 0.12\text{dB}$       |
| 3   | Spurious emissions, conducted | $\pm 0.11\text{dB}$       |
| 4   | All emissions, radiated(<1G)  | $\pm 3.92\text{dB}$       |
| 5   | All emissions, radiated(>1G)  | $\pm 4.28\text{dB}$       |
| 6   | Temperature                   | $\pm 0.1^{\circ}\text{C}$ |
| 7   | Humidity                      | $\pm 1.0\%$               |

## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

**Standard requirement:**


FCC Part15 C Section 15.203

**15.203 requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

**E.U.T Antenna:**


The antenna is inductive loop coil antenna which permanently attached, and the best case gain of the antenna is 0dBi.





## 6.2. Conducted Emission

### 6.2.1. Test Specification

| Test Requirement:     | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|--------------|--|------------|---------|----------|-----------|-----------|-------|----|----|------|----|----|
| Test Method:          | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Frequency Range:      | 150 kHz to 30 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Receiver setup:       | RBW=9 kHz, VBW=30 kHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Limits:               | <table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>                                                                                                                                                                                                                                                                                                                                                                                                            | Frequency range (MHz) | Limit (dBuV) |  | Quasi-peak | Average | 0.15-0.5 | 66 to 56* | 56 to 46* | 0.5-5 | 56 | 46 | 5-30 | 60 | 50 |
| Frequency range (MHz) | Limit (dBuV)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
|                       | Quasi-peak                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Average               |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.15-0.5              | 66 to 56*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 56 to 46*             |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 0.5-5                 | 56                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 46                    |              |  |            |         |          |           |           |       |    |    |      |    |    |
| 5-30                  | 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 50                    |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Setup:           | <div><p style="text-align: center;"><b>Reference Plane</b></p><p><i>Remark:</i><br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p></div>                                                                                                                                                                                                                                                                                                                                                                                                                            |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Mode:            | Charging + Transmitting Mode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Procedure:       | <div><div>1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</div></div> |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |
| Test Result:          | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                       |              |  |            |         |          |           |           |       |    |    |      |    |    |

## 6.2.2. Test Instruments


| Conducted Emission Shielding Room Test Site (843) |                       |           |               |                 |
|---------------------------------------------------|-----------------------|-----------|---------------|-----------------|
| Equipment                                         | Manufacturer          | Model     | Serial Number | Calibration Due |
| Test Receiver                                     | R&S                   | ESPI      | 101401        | Jun. 12, 2018   |
| LISN                                              | Schwarzbeck           | NSLK 8126 | 8126453       | Sep. 27, 2018   |
| Coax cable<br>(9KHz-30MHz)                        | TCT                   | CE-05     | N/A           | Sep. 27, 2018   |
| EMI Test Software                                 | Shurple<br>Technology | EZ-EMC    | N/A           | N/A             |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.2.3. Test data

Please refer to following diagram for individual

#### Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **L1** Temperature: 25  
Limit: FCC Part 15C Conduction(QP) Power: DC 5V form adapter Humidity: 55 %

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBμV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBμV | Limit<br>dBμV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1590       | 38.69                    | 11.47                   | 50.16                    | 65.52         | -15.36     | peak     |         |
| 2   |     | 0.2174       | 38.97                    | 11.44                   | 50.41                    | 62.92         | -12.51     | peak     |         |
| 3   |     | 0.2893       | 34.10                    | 11.40                   | 45.50                    | 60.54         | -15.04     | peak     |         |
| 4   | *   | 2.1703       | 33.49                    | 11.63                   | 45.12                    | 56.00         | -10.88     | peak     |         |
| 5   |     | 3.4529       | 31.00                    | 11.17                   | 42.17                    | 56.00         | -13.83     | peak     |         |
| 6   |     | 30.0000      | 35.96                    | 10.59                   | 46.55                    | 60.00         | -13.45     | peak     |         |

#### Note:

Freq. = Emission frequency in MHz

Reading level (dBμV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBμV) = Reading level (dBμV) + Corr. Factor (dB)

Limit (dBμV) = Limit stated in standard


Margin (dB) = Measurement (dBμV) – Limits (dBμV)

Q.P. =Quasi-Peak

AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

## Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site: Phase: **N** Temperature: 25  
 Limit: FCC Part 15C Conduction(QP) Power: DC 5V form adapter Humidity: 55 %

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1544       | 40.70                    | 11.47                   | 52.17                    | 65.76         | -13.59     | peak     |         |
| 2   |     | 0.2129       | 38.70                    | 11.44                   | 50.14                    | 63.09         | -12.95     | peak     |         |
| 3   |     | 0.2849       | 35.75                    | 11.41                   | 47.16                    | 60.67         | -13.51     | peak     |         |
| 4   |     | 1.4549       | 32.66                    | 11.42                   | 44.08                    | 56.00         | -11.92     | peak     |         |
| 5   | *   | 2.3054       | 32.98                    | 11.58                   | 44.56                    | 56.00         | -11.44     | peak     |         |
| 6   |     | 29.7104      | 34.88                    | 10.60                   | 45.48                    | 60.00         | -14.52     | peak     |         |

### Note1:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard


Margin (dB) = Measurement (dBuV) – Limits (dBuV)


Q.P. =Quasi-Peak AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.


## 6.3. Radiated Spurious Emission Measurement

### 6.3.1. Test Specification

|                              |                                                                                      |                                   |                               |          |
|------------------------------|--------------------------------------------------------------------------------------|-----------------------------------|-------------------------------|----------|
| <b>Test Requirement:</b>     | FCC Part15 C Section 15.209                                                          |                                   |                               |          |
| <b>Test Method:</b>          | ANSI C63.10: 2013                                                                    |                                   |                               |          |
| <b>Frequency Range:</b>      | 9 kHz to 25 GHz                                                                      |                                   |                               |          |
| <b>Measurement Distance:</b> | 3 m                                                                                  |                                   |                               |          |
| <b>Antenna Polarization:</b> | Horizontal & Vertical                                                                |                                   |                               |          |
| <b>Operation mode:</b>       | Refer to item 4.1                                                                    |                                   |                               |          |
| <b>Receiver Setup:</b>       | Frequency                                                                            | Detector                          | RBW                           | VBW      |
|                              | 9kHz- 150kHz                                                                         | Quasi-peak                        | 200Hz                         | 1kHz     |
|                              | 150kHz- 30MHz                                                                        | Quasi-peak                        | 9kHz                          | 30kHz    |
|                              | 30MHz-1GHz                                                                           | Quasi-peak                        | 100KHz                        | 300KHz   |
|                              | Above 1GHz                                                                           | Peak                              | 1MHz                          | 3MHz     |
| <b>Limit:</b>                | Remark                                                                               |                                   |                               |          |
|                              | Quasi-peak Value                                                                     |                                   |                               |          |
|                              | Quasi-peak Value                                                                     |                                   |                               |          |
|                              | Quasi-peak Value                                                                     |                                   |                               |          |
|                              | Peak Value                                                                           |                                   |                               |          |
| <b>Test setup:</b>           | Average Value                                                                        |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |
| <b>Test setup:</b>           | Frequency                                                                            | Field Strength (microvolts/meter) | Measurement Distance (meters) |          |
|                              | 0.009-0.490                                                                          | 2400/F(KHz)                       | 300                           |          |
|                              | 0.490-1.705                                                                          | 24000/F(KHz)                      | 30                            |          |
|                              | 1.705-30                                                                             | 30                                | 30                            |          |
|                              | 30-88                                                                                | 100                               | 3                             |          |
| <b>Test setup:</b>           | 88-216                                                                               | 150                               | 3                             |          |
|                              | 216-960                                                                              | 200                               | 3                             |          |
|                              | Above 960                                                                            | 500                               | 3                             |          |
|                              |                                                                                      |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |
| <b>Test setup:</b>           | Frequency                                                                            | Field Strength (microvolts/meter) | Measurement Distance (meters) | Detector |
|                              | Above 1GHz                                                                           | 500                               | 3                             | Average  |
|                              |                                                                                      | 5000                              | 3                             | Peak     |
|                              |                                                                                      |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |
| <b>Test setup:</b>           | For radiated emissions below 30MHz                                                   |                                   |                               |          |
|                              |  |                                   |                               |          |
|                              | 30MHz to 1GHz                                                                        |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |
|                              |                                                                                      |                                   |                               |          |



Above 1GHz



## Test Procedure:

- For the radiated emission test below 1GHz:  
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:  
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               | <p>measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</p> <p>3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.</p> <p>4. Use the following spectrum analyzer settings:</p> <p>(1) Span shall wide enough to fully capture the emission being measured;</p> <p>(2) Set RBW=100 kHz for <math>f &lt; 1</math> GHz; <math>VBW \geq RBW</math>; Sweep = auto; Detector function = peak; Trace = max hold;</p> <p>(3) Set RBW = 1 MHz, VBW= 3MHz for <math>f \geq 1</math> GHz for peak measurement.</p> <p>For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. <math>VBW \geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p> |
| Test mode:    | Refer to section 4.1 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test results: | PASS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### 6.3.2. Test Instruments

| Radiated Emission Test Site (966) |                                          |            |               |                 |
|-----------------------------------|------------------------------------------|------------|---------------|-----------------|
| Name of Equipment                 | Manufacturer                             | Model      | Serial Number | Calibration Due |
| Test Receiver                     | ROHDE&SCHW<br>ARZ                        | ESVD       | 100008        | Sep. 27, 2018   |
| Spectrum Analyzer                 | ROHDE&SCHW<br>ARZ                        | FSQ        | 200061        | Sep. 27, 2018   |
| Pre-amplifier                     | EM Electronics<br>Corporation<br>CO.,LTD | EM30265    | 07032613      | Sep. 27, 2018   |
| Pre-amplifier                     | HP                                       | 8447D      | 2727A05017    | Sep. 27, 2018   |
| Loop antenna                      | ZHINAN                                   | ZN30900A   | 12024         | Sep. 27, 2018   |
| Broadband Antenna                 | Schwarzbeck                              | VULB9163   | 340           | Sep. 27, 2018   |
| Horn Antenna                      | Schwarzbeck                              | BBHA 9120D | 631           | Sep. 27, 2018   |
| Horn Antenna                      | Schwarzbeck                              | BBH 9170   | 582           | Jun. 07, 2018   |
| Antenna Mast                      | Keleto                                   | CC-A-4M    | N/A           | N/A             |
| Coax cable<br>(9KHz-1GHz)         | TCT                                      | RE-low-01  | N/A           | Sep. 27, 2018   |
| Coax cable<br>(9KHz-40GHz)        | TCT                                      | RE-high-02 | N/A           | Sep. 27, 2018   |
| Coax cable<br>(9KHz-1GHz)         | TCT                                      | RE-low-03  | N/A           | Sep. 27, 2018   |
| Coax cable<br>(9KHz-40GHz)        | TCT                                      | RE-high-04 | N/A           | Sep. 27, 2018   |
| EMI Test Software                 | Shurple<br>Technology                    | EZ-EMC     | N/A           | N/A             |

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).




## 6.3.3. Test Data

Please refer to following diagram for individual

9KHz-30MHz


9KHz-150KHz:



|                                |                               |                 |
|--------------------------------|-------------------------------|-----------------|
| Site                           | Polarization: <b>Vertical</b> | Temperature: 25 |
| Limit: FCC Part15.209(9K-150K) | Power: AC 120V/60Hz           | Humidity: 55 %  |
| EUT: Charger                   | Distance: 3m                  |                 |
| M/N: CDRZ35                    |                               |                 |
| Mode: Charging                 |                               |                 |
| Note:                          |                               |                 |

| No. | Mk. | Freq.  | Reading Level | Correct Factor | Measurement | Limit | Over   | Antenna Height | Table Degree |         |
|-----|-----|--------|---------------|----------------|-------------|-------|--------|----------------|--------------|---------|
|     |     | MHz    | dBuV          | dB             | dBuV/m      | dB/m  | dB     | cm             | degree       | Comment |
| 1   |     | 0.0154 | 38.52         | 20.96          | 59.48       | 123.8 | -64.37 | peak           |              |         |
| 2   |     | 0.0269 | 41.12         | 19.00          | 60.12       | 119.0 | -58.89 | peak           |              |         |
| 3   |     | 0.0309 | 40.32         | 19.27          | 59.59       | 117.8 | -58.22 | peak           |              |         |
| 4   |     | 0.0446 | 38.59         | 20.18          | 58.77       | 114.6 | -55.86 | peak           |              |         |
| 5   |     | 0.0810 | 38.74         | 22.65          | 61.39       | 109.4 | -48.06 | peak           |              |         |
| 6   | *   | 0.0990 | 37.56         | 23.87          | 61.43       | 107.7 | -46.28 | peak           |              |         |

150KHz-30MHz:



Site

Polarization: **Vertical**

Temperature: 25

Limit: FCC Part15.209(150K-30M)

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Wireless Charger

Distance: 3m

M/N: CDRZ35


Mode: Charging

Note:

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|-------------------------|-----------------|---------|
| 1   |     | 0.1685       | 43.98                    | 26.19                   | 70.17                      | 103.0         | -32.92     | peak                    |                 |         |
| 2   |     | 0.6578       | 31.33                    | 25.38                   | 56.71                      | 71.25         | -14.54     | peak                    |                 |         |
| 3   |     | 2.4735       | 30.74                    | 25.00                   | 55.74                      | 69.50         | -13.76     | peak                    |                 |         |
| 4   |     | 3.1730       | 31.66                    | 24.96                   | 56.62                      | 69.50         | -12.88     | peak                    |                 |         |
| 5   |     | 8.1913       | 33.14                    | 25.98                   | 59.12                      | 69.50         | -10.38     | peak                    |                 |         |
| 6   | *   | 15.7179      | 34.44                    | 25.36                   | 59.80                      | 69.50         | -9.70      | peak                    |                 |         |

## 30MHz-1GHz

Horizontal:



Site

Polarization: **Horizontal**

Temperature: 25


Limit: FCC Part 15B Class B 3M Radiation

Power:

Humidity: 55 %

| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit | Over   | Antenna Height | Table Degree |        |
|-----|-----|----------|---------------|----------------|-------------|-------|--------|----------------|--------------|--------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dB/m  | dB     | Detector       | cm           | degree |
| 1   |     | 31.6202  | 33.98         | -13.63         | 20.35       | 40.00 | -19.65 | peak           |              |        |
| 2   |     | 56.7917  | 35.92         | -13.19         | 22.73       | 40.00 | -17.27 | peak           |              |        |
| 3   |     | 98.4866  | 33.35         | -12.16         | 21.19       | 43.50 | -22.31 | peak           |              |        |
| 4   |     | 160.3456 | 45.25         | -15.17         | 30.08       | 43.50 | -13.42 | peak           |              |        |
| 5   | *   | 185.1379 | 44.67         | -13.65         | 31.02       | 43.50 | -12.48 | peak           |              |        |
| 6   |     | 543.2742 | 31.41         | -2.09          | 29.32       | 46.00 | -16.68 | peak           |              |        |

Vertical:



Site: Polarization: **Vertical** Temperature: 25  
Limit: FCC Part 15B Class B 3M Radiation Power: Humidity: 55 %

| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over   | Antenna | Table  |         |
|-----|-----|----------|---------|---------|----------|-------|--------|---------|--------|---------|
|     |     | MHz      | Level   | Factor  | ment     |       |        | Height  | Degree |         |
|     |     |          | dBuV    | dB      | dBuV/m   | dB/m  | dB     | cm      | degree | Comment |
| 1   | *   | 32.7486  | 45.77   | -13.52  | 32.25    | 40.00 | -7.75  | peak    |        |         |
| 2   |     | 53.5052  | 43.71   | -12.92  | 30.79    | 40.00 | -9.21  | peak    |        |         |
| 3   |     | 61.5618  | 42.48   | -14.04  | 28.44    | 40.00 | -11.56 | peak    |        |         |
| 4   |     | 118.1862 | 39.89   | -13.87  | 26.02    | 43.50 | -17.48 | peak    |        |         |
| 5   |     | 183.2005 | 44.13   | -13.77  | 30.36    | 43.50 | -13.14 | peak    |        |         |
| 6   |     | 541.3725 | 33.28   | -2.13   | 31.15    | 46.00 | -14.85 | peak    |        |         |

## Note:


Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

## Appendix A: Photographs of Test Setup

Product: Wireless Charger

Model: CDRZ35

Radiated Emission



### Conducted Emission





**Appendix B: Photographs of EUT**  
**Product: Wireless Charger**  
**Model: CDRZ35**  
**External Photos**













**Product: Wireless Charger**  
**Model: CDRZ35**  
**Internal Photos**









**\*\*\*\*\*END OF REPORT\*\*\*\*\***