

RF Exposure Evaluation

1 Measuring Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1091 RF exposure is calculated. According KDB680106 D01: KDB 680106 D01 Wireless Power Transfer v04.

2 Requirements

According to the item 3 of KDB 680106 D01v04:

Inductive wireless power transfer applications that meet all of the following requirements are excluded from submitting an RF exposure evaluation.

- (1) Mobile Device and Portable Device Configurations
- (2) Equipment Authorization Procedures for Devices Operating at Frequencies Below 4 MHz
- (3) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the top surface.

Limits


The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
f=Plane-wave equivalent power density
RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

3 Test Setup



4 Test Procedure

- 1) The RF exposure test was performed in anechoic chamber.
- 2) The measurement probe was placed at test distance (15 cm from all sides and 20 cm from the top) which is between the edge of the charger and the geometric center of probe.
- 3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- 4) The EUT was measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.

Remark: The EUT's test position A, B, C, D and E is valid for the E and H field measurements.



5 Equipment Approval Considerations

The EUT does comply with KDB 680106 D01 as follow table.

Requirements of section 5 of KDB 680106 D01	Yes / No	Description
Mobile Device and Portable Device Configurations	Yes	Mobile Device
Equipment Authorization Procedures for Devices Operating at Frequencies Below 4 MHz	Yse	The device operate in the frequency range113-205KHz,360 KHz (for mobile phone) and 113-205KHz(for earphone).
RF Exposure compliance may be ensured only for a minimum separation distance that is greater than 20 cm, while use conditions at smaller distances can still be considered unlikely.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface.

6 Description of the test mode

Equipment under test was operated during the measurement under the following conditions:

Test Mode	Description	
Mode 1	AC Adapter + EUT + Wireless charger receiver 1 + Wireless charger receiver 2	Record
Mode 2	AC Adapter + EUT + Wireless charger receiver 1	Pre-tested
Mode 3	AC Adapter + EUT + Wireless charger receiver 2	Pre-tested
Mode 4	Test the EUT in idle mode.	Pre-tested
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		

7 Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	Wireless charger receiver	YBZ	15W	N/A	N/A	N/A
2	Watch wireless charger receiver	YBZ	5W	N/A	N/A	N/A

8 Test Instruments list

Test Equipment	Manufacturer	Model No.	SN.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
Electric and Magnetic Field Analyzer	Narda	EHP-200A	180ZX10505	21.06.2023	20.06.2024

9 Test Result

Test Mode 1_MPE_Coil 1_Phone

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 1%	Top	15.44	0.51
15cm	< 1%	Top	15.56	0.54
15cm	< 1%	Left	14.98	0.61
15cm	< 1%	Right	15.28	0.59
15cm	< 1%	Front	15.25	0.41
15cm	< 1%	Rear	15.26	0.37
Limit			614	1.63
Margin Limit (%)			2.53%	37.42%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 50%	Top	14.73	0.32
15cm	< 50%	Top	13.93	0.33
15cm	< 50%	Left	14.33	0.39
15cm	< 50%	Right	14.15	0.26
15cm	< 50%	Front	14.00	0.24
15cm	< 50%	Rear	14.17	0.32
Limit			614	1.63
Margin Limit (%)			2.40%	23.93%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 99%	Top	14.30	0.25
15cm	< 99%	Top	13.20	0.11
15cm	< 99%	Left	13.50	0.35
15cm	< 99%	Right	14.00	0.20
15cm	< 99%	Front	14.06	0.32
15cm	< 99%	Rear	14.22	0.23
Limit			614	1.63
Margin Limit (%)			2.33%	21.47%

Test Mode 1 MPE Coil 2 Earphone

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 1%	Top	13.69	0.34
15cm	< 1%	Top	13.77	0.35
15cm	< 1%	Left	13.79	0.29
15cm	< 1%	Right	13.63	0.34
15cm	< 1%	Front	13.80	0.32
15cm	< 1%	Rear	13.66	0.39
Limit			614	1.63
Margin Limit (%)			2.25%	23.93%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 50%	Top	13.12	0.49
15cm	< 50%	Top	11.97	0.53
15cm	< 50%	Left	12.54	0.32
15cm	< 50%	Right	12.36	0.64
15cm	< 50%	Front	12.57	0.42
15cm	< 50%	Rear	12.77	0.59
Limit			614	1.63
Margin Limit (%)			2.14%	39.26%

MPE				
Test distance	Battery levels	Probe from EUT Side	E-field (V/m)	H-field (A/m)
20cm	< 99%	Top	12.54	0.35
15cm	< 99%	Top	11.31	0.42
15cm	< 99%	Left	12.04	0.46
15cm	< 99%	Right	11.95	0.49
15cm	< 99%	Front	12.23	0.24
15cm	< 99%	Rear	12.12	0.49
Limit			614	1.63
Margin Limit (%)			2.04%	30.06%

Note: All test modes were pre-tested, but we only recorded the worst case in this report.

Total exposure**MPE-based total exposure ratio (Worst case):**

E-field:

$$\text{Coil 1} + \text{Coil 2} = 0.0253 + 0.0225 = 0.0478 < 1$$

H-field:


$$\text{Coil 1} + \text{Coil 2} = 0.3742 + 0.3969 = 0.7669 < 1$$

10 Test Setup photo


Front




Left



Rear



Right



Top



End of report