



FCC RF Test Report

APPLICANT : mixi, Inc.
EQUIPMENT : Mobile Phone
BRAND NAME : RATEL
MODEL NAME : CELL
MODEL NUMBER : R1020
FCC ID : 2AN7THST-101-1
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Dec. 08, 2017 and testing was completed on Mar. 12, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID: 2AN7THST-101-1

Page Number : 1 of 29

Report Issued Date : Mar. 20, 2018

Report Version : Rev. 01

Report Template No.: BU5-FR15EWLB4 AC MA Version 1.4



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	11
3.2 Maximum Conducted Output Power Measurement	14
3.3 Power Spectral Density Measurement	15
3.4 Unwanted Emissions Measurement	18
3.5 AC Conducted Emission Measurement.....	24
3.6 Automatically Discontinue Transmission	26
3.7 Antenna Requirements.....	27
4 LIST OF MEASURING EQUIPMENT	28
5 UNCERTAINTY OF EVALUATION	29
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	
APPENDIX F. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7D0829F	Rev. 01	Initial issue of report	Mar. 20, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 8.41 dB at 47.010 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 23.50 dB at 0.150 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

mixi, Inc.

Sumitomo Fudosan Shibuya First Tower 7F, 1-2-20 Higashi, Shibuya-ku, Tokyo, 150-0011, Japan

1.2 Manufacturer

Wistron Corporation

21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist, New Taipei City 221, Taiwan R.O.C.

1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GNSS

Product Specification subjective to this standard	
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass: PIFA Antenna NFC: Coil Antenna

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	03CH10-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Single Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0


MIMO Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + NFC on + USB Cable Type C to Type C (EUT Charging from Adapter)
--------------------------------------	---

Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, utility “QRCT” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.



3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.



3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 1	Ant. 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.10	0.10	3.10	4.74	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1240001	N/A	Sep. 07, 2017	Feb. 09, 2018~ Feb. 22, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207349	300MHz~40GHz z	Sep. 07, 2017	Feb. 09, 2018~ Feb. 22, 2018	Sep. 06, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 20, 2017	Feb. 09, 2018~ Feb. 22, 2018	Jun. 19, 2018	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jan. 02, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Sep. 20, 2017	Jan. 02, 2018	Sep. 19, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Jan. 02, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 08, 2017	Jan. 02, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 19, 2017	Mar. 03, 2018~ Mar. 12, 2018	Oct. 18, 2018	Radiation (03CH10-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Mar. 03, 2018~ Mar. 12, 2018	Jul. 17, 2018	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35413&02	30MHz~1GHz	Dec. 18, 2017	Mar. 03, 2018~ Mar. 12, 2018	Dec. 17, 2018	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-132 5	1GHz ~ 18GHz	Sep. 27, 2017	Mar. 03, 2018~ Mar. 12, 2018	Sep. 26, 2018	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY532700 78	1GHz~26.5GHz	Oct. 25, 2017	Mar. 03, 2018~ Mar. 12, 2018	Oct. 24, 2018	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JAP00101800 -30-10P	160118550 004	1GHz~18GHz	Apr. 13, 2017	Mar. 03, 2018~ Mar. 12, 2018	Apr. 12, 2018	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 85	10Hz ~ 44GHz	Oct. 31, 2017	Mar. 03, 2018~ Mar. 12, 2018	Oct. 30, 2018	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Mar. 03, 2018~ Mar. 12, 2018	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Mar. 03, 2018~ Mar. 12, 2018	N/A	Radiation (03CH10-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Mar. 03, 2018~ Mar. 12, 2018	Nov. 22, 2019	Radiation (03CH10-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY532900 53	20Hz to 26.5GHz	Jan. 16, 2018	Mar. 03, 2018~ Mar. 12, 2018	Jan. 15, 2019	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 27, 2017	Mar. 03, 2018~ Mar. 12, 2018	Nov. 26, 2018	Radiation (03CH10-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.60
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.90
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Luffy Lin/Derek Hsu	Temperature:	21~25	°C
Test Date:	2018/02/09~2018/02/22	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	17.70	17.65	24.27	23.52	16.32	16.36	0.5		Pass
11a	6Mbps	2	157	5785	17.75	17.75	24.91	23.52	16.34	16.32	0.5		Pass
11a	6Mbps	2	165	5825	17.55	17.70	24.24	23.58	16.32	16.32	0.5		Pass
HT20	MCS0	2	149	5745	19.10	18.75	25.93	25.42	17.60	17.61	0.5		Pass
HT20	MCS0	2	157	5785	18.85	19.05	25.67	25.69	17.60	17.59	0.5		Pass
HT20	MCS0	2	165	5825	19.00	18.90	25.70	26.27	17.61	17.60	0.5		Pass
HT40	MCS0	2	151	5755	37.10	37.00	44.32	43.44	36.40	36.32	0.5		Pass
HT40	MCS0	2	159	5795	37.20	37.00	43.69	43.61	36.42	36.35	0.5		Pass
VHT80	MCS0	2	155	5775	76.20	76.08	87.32	85.43	76.36	76.34	0.5		Pass

TEST RESULTS DATA
Average Power Table

Band IV														
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.29	0.32	8.97	8.95		30.00	30.00	3.10	0.10	Pass
11a	6Mbps	1	157	5785	0.29	0.32	8.93	8.96		30.00	30.00	3.10	0.10	Pass
11a	6Mbps	1	165	5825	0.29	0.32	8.95	8.97		30.00	30.00	3.10	0.10	Pass
HT20	MCS0	1	149	5745	0.35	0.00	8.67	8.69		30.00	30.00	3.10	0.10	Pass
HT20	MCS0	1	157	5785	0.35	0.00	8.77	8.66		30.00	30.00	3.10	0.10	Pass
HT20	MCS0	1	165	5825	0.35	0.00	8.75	8.72		30.00	30.00	3.10	0.10	Pass
HT40	MCS0	1	151	5755	0.60	0.56	8.70	8.73		30.00	30.00	3.10	0.10	Pass
HT40	MCS0	1	159	5795	0.60	0.56	8.72	8.70		30.00	30.00	3.10	0.10	Pass
VHT20	MCS0	1	149	5745	0.35	0.30	8.77	8.76		30.00	30.00	3.10	0.10	Pass
VHT20	MCS0	1	157	5785	0.35	0.30	8.76	8.73		30.00	30.00	3.10	0.10	Pass
VHT20	MCS0	1	165	5825	0.35	0.30	8.81	8.71		30.00	30.00	3.10	0.10	Pass
VHT40	MCS0	1	151	5755	0.60	0.59	8.81	8.73		30.00	30.00	3.10	0.10	Pass
VHT40	MCS0	1	159	5795	0.60	0.59	8.74	8.81		30.00	30.00	3.10	0.10	Pass
VHT80	MCS0	1	155	5775	0.70	0.70	8.72	8.68		30.00	30.00	3.10	0.10	Pass
11a	6Mbps	2	149	5745	0.32	0.29	8.99	8.96	11.99	30.00		3.10		Pass
11a	6Mbps	2	157	5785	0.32	0.29	8.98	8.97	11.99	30.00		3.10		Pass
11a	6Mbps	2	165	5825	0.32	0.29	8.97	8.98	11.99	30.00		3.10		Pass
HT20	MCS0	2	149	5745	0.35	0.30	8.97	8.90	11.95	30.00		3.10		Pass
HT20	MCS0	2	157	5785	0.35	0.30	8.97	8.95	11.97	30.00		3.10		Pass
HT20	MCS0	2	165	5825	0.35	0.30	8.96	8.90	11.94	30.00		3.10		Pass
HT40	MCS0	2	151	5755	0.56	0.60	8.99	8.91	11.96	30.00		3.10		Pass
HT40	MCS0	2	159	5795	0.56	0.60	8.98	8.90	11.95	30.00		3.10		Pass
VHT20	MCS0	2	149	5745	0.31	0.31	8.96	8.87	11.92	30.00		3.10		Pass
VHT20	MCS0	2	157	5785	0.31	0.31	8.96	8.88	11.93	30.00		3.10		Pass
VHT20	MCS0	2	165	5825	0.31	0.31	8.91	8.81	11.87	30.00		3.10		Pass
VHT40	MCS0	2	151	5755	0.58	0.68	8.98	8.90	11.95	30.00		3.10		Pass
VHT40	MCS0	2	159	5795	0.58	0.68	8.97	8.89	11.94	30.00		3.10		Pass
VHT80	MCS0	2	155	5775	0.65	0.65	8.99	8.71	11.87	30.00		3.10		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	0.32	0.29	2.22	-5.43	-8.69	-2.42	30.00		4.74		Pass	
11a	6Mbps	2	157	5785	0.32	0.29	2.22	-5.34	-8.45	-2.33	30.00		4.74		Pass	
11a	6Mbps	2	165	5825	0.32	0.29	2.22	-5.38	-8.58	-2.37	30.00		4.74		Pass	
HT20	MCS0	2	149	5745	0.35	0.30	2.22	-5.20	-7.00	-1.77	30.00		4.74		Pass	
HT20	MCS0	2	157	5785	0.35	0.30	2.22	-4.98	-7.26	-1.97	30.00		4.74		Pass	
HT20	MCS0	2	165	5825	0.35	0.30	2.22	-5.89	-7.76	-2.53	30.00		4.74		Pass	
HT40	MCS0	2	151	5755	0.56	0.60	2.22	-8.09	-10.45	-5.08	30.00		4.74		Pass	
HT40	MCS0	2	159	5795	0.56	0.60	2.22	-8.34	-10.33	-5.10	30.00		4.74		Pass	
VHT80	MCS0	2	155	5775	0.65	0.65	2.22	-11.21	-13.65	-8.20	30.00		4.74		Pass	

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Shareef Yu	Temperature :	24~25℃
		Relative Humidity :	53~56%

EUT Information

Report NO : 7D0829
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

ENV216 Auto Test FCC Power Bar - L



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	42.5	Off	L1	19.5	23.5	66.0
0.302000	29.8	Off	L1	19.5	30.4	60.2
0.398000	30.3	Off	L1	19.5	27.6	57.9
0.494000	29.6	Off	L1	19.5	26.5	56.1
0.678000	31.9	Off	L1	19.5	24.1	56.0
1.254000	30.7	Off	L1	19.5	25.3	56.0
13.558000	31.2	Off	L1	19.7	28.8	60.0


Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	20.6	Off	L1	19.5	35.4	56.0
0.302000	23.3	Off	L1	19.5	26.9	50.2
0.398000	21.7	Off	L1	19.5	26.2	47.9
0.494000	21.5	Off	L1	19.5	24.6	46.1
0.678000	20.1	Off	L1	19.5	25.9	46.0
1.254000	20.9	Off	L1	19.5	25.1	46.0
13.558000	18.2	Off	L1	19.7	31.8	50.0

EUT Information

Report NO : 7D0829
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

ENV216 Auto Test FCC Power Bar - N



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	37.3	Off	N	19.5	28.7	66.0
0.302000	24.3	Off	N	19.5	35.9	60.2
0.678000	25.6	Off	N	19.5	30.4	56.0
1.102000	21.5	Off	N	19.5	34.5	56.0
1.438000	21.1	Off	N	19.5	34.9	56.0
3.070000	19.9	Off	N	19.5	36.1	56.0
13.558000	32.5	Off	N	19.8	27.5	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	23.8	Off	N	19.5	32.2	56.0
0.302000	19.2	Off	N	19.5	31.0	50.2
0.678000	17.1	Off	N	19.5	28.9	46.0
1.102000	16.3	Off	N	19.5	29.7	46.0
1.438000	16.6	Off	N	19.5	29.4	46.0
3.070000	15.1	Off	N	19.5	30.9	46.0
13.558000	18.4	Off	N	19.8	31.6	50.0



Appendix C. Radiated Spurious Emission

Test Engineer :	Daniel Lee, Master Huang, and J.C. Liang	Temperature :	18~22°C
		Relative Humidity :	48~53%

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5621.2	48.05	-20.15	68.2	39.73	32.22	8.64	32.54	100	119	P	H
		5659.8	48.08	-27.4	75.48	39.61	32.26	8.77	32.56	100	119	P	H
		5713.4	53.89	-55.06	108.95	45.21	32.31	8.95	32.58	100	119	P	H
		5721.6	48.75	-65.7	114.45	40	32.32	9.01	32.58	100	119	P	H
	*	5745	99.4	-	-	90.58	32.34	9.07	32.59	100	119	P	H
	*	5745	92.11	-	-	83.29	32.34	9.07	32.59	100	119	A	H
													H
													H
		5642.8	48.45	-19.75	68.2	40.06	32.24	8.7	32.55	113	190	P	V
		5680.4	49.02	-41.71	90.73	40.49	32.27	8.83	32.57	113	190	P	V
		5719.2	48.37	-62.21	110.58	39.62	32.32	9.01	32.58	113	190	P	V
		5724.6	58.29	-63	121.29	49.54	32.32	9.01	32.58	113	190	P	V
	*	5745	98.17	-	-	89.35	32.34	9.07	32.59	113	190	P	V
	*	5745	90.86	-	-	82.04	32.34	9.07	32.59	113	190	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5607.8	48.15	-20.05	68.2	39.91	32.2	8.58	32.54	100	116	P	H
		5667	48.82	-32	80.82	40.28	32.27	8.83	32.56	100	116	P	H
		5712.8	48.95	-59.84	108.79	40.27	32.31	8.95	32.58	100	116	P	H
		5722.6	47.89	-68.84	116.73	39.14	32.32	9.01	32.58	100	116	P	H
	*	5785	98.7	-	-	89.73	32.38	9.2	32.61	100	116	P	H
	*	5785	90.21	-	-	81.24	32.38	9.2	32.61	100	116	A	H
		5851.6	48.32	-70.23	118.55	39.35	32.44	9.16	32.63	100	116	P	H
		5863.2	48.4	-60.1	108.5	39.45	32.46	9.13	32.64	100	116	P	H
		5876	49.49	-54.97	104.46	40.52	32.48	9.13	32.64	100	116	P	H
		5938.8	48.72	-19.48	68.2	39.82	32.55	9.01	32.66	100	116	P	H
													H
													H
		5630.8	47.94	-20.26	68.2	39.57	32.22	8.7	32.55	107	189	P	V
		5673.2	48.94	-36.47	85.41	40.4	32.27	8.83	32.56	107	189	P	V
		5715.2	48.57	-60.89	109.46	39.89	32.31	8.95	32.58	107	189	P	V
		5723.8	47.98	-71.48	119.46	39.23	32.32	9.01	32.58	107	189	P	V
	*	5785	97.28	-	-	88.31	32.38	9.2	32.61	107	189	P	V
	*	5785	89.21	-	-	80.24	32.38	9.2	32.61	107	189	A	V
		5853.2	48.45	-66.45	114.9	39.48	32.44	9.16	32.63	107	189	P	V
		5862.8	48.09	-60.52	108.61	39.14	32.46	9.13	32.64	107	189	P	V
		5900.4	49.08	-37.28	86.36	40.15	32.5	9.07	32.64	107	189	P	V
		5931.4	50.38	-17.82	68.2	41.46	32.53	9.04	32.65	107	189	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	96.56	-	-	87.52	32.43	9.23	32.62	100	115	P	H
	*	5825	89.46	-	-	80.42	32.43	9.23	32.62	100	115	A	H
		5853.2	48.11	-66.79	114.9	39.14	32.44	9.16	32.63	100	115	P	H
		5859.8	49.52	-59.93	109.45	40.54	32.46	9.16	32.64	100	115	P	H
		5900.2	48.94	-37.57	86.51	40.01	32.5	9.07	32.64	100	115	P	H
		5926.6	48.39	-19.81	68.2	39.47	32.53	9.04	32.65	100	115	P	H
													H
													H
	*	5825	96.79	-	-	87.75	32.43	9.23	32.62	102	189	P	V
	*	5825	88.65	-	-	79.61	32.43	9.23	32.62	102	189	A	V
		5852.8	48.44	-67.38	115.82	39.47	32.44	9.16	32.63	102	189	P	V
		5874.6	48.45	-56.86	105.31	39.48	32.48	9.13	32.64	102	189	P	V
		5903	49.09	-35.35	84.44	40.16	32.5	9.07	32.64	102	189	P	V
		5929.8	49.8	-18.4	68.2	40.88	32.53	9.04	32.65	102	189	P	V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	44.41	-29.59	74	58.07	39.81	12.74	66.21	100	0	P	H
		17235	45.75	-22.45	68.2	53.99	41.02	16.76	66.02	100	0	P	H
													H
													H
		11490	44.98	-29.02	74	58.64	39.81	12.74	66.21	100	0	P	V
		17235	46.21	-21.99	68.2	54.45	41.02	16.76	66.02	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		11570	44.09	-29.91	74	57.79	39.69	12.8	66.19	100	0	P	H
		17355	45.82	-22.38	68.2	53.26	41.58	16.86	65.88	100	0	P	H
													H
													H
		11570	45.22	-28.78	74	58.92	39.69	12.8	66.19	100	0	P	V
		17355	45.27	-22.93	68.2	52.71	41.58	16.86	65.88	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	45.29	-28.71	74	59.01	39.58	12.87	66.17	100	0	P	H
		17475	45.35	-22.85	68.2	51.99	42.14	16.96	65.74	100	0	P	H
													H
													H
		11650	44.33	-29.67	74	58.05	39.58	12.87	66.17	100	0	P	V
		17475	45.55	-22.65	68.2	52.19	42.14	16.96	65.74	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5643.4	48.25	-19.95	68.2	39.86	32.24	8.7	32.55	100	119	P	H
		5670.2	49.43	-33.76	83.19	40.89	32.27	8.83	32.56	100	119	P	H
		5717.6	49.49	-60.64	110.13	40.74	32.32	9.01	32.58	100	119	P	H
		5724.6	51.58	-69.71	121.29	42.83	32.32	9.01	32.58	100	119	P	H
	*	5745	99.64	-	-	90.82	32.34	9.07	32.59	100	119	P	H
	*	5745	92.37	-	-	83.55	32.34	9.07	32.59	100	119	A	H
													H
													H
		5644	48.6	-19.6	68.2	40.21	32.24	8.7	32.55	103	190	P	V
		5687.2	49.41	-46.35	95.76	40.8	32.29	8.89	32.57	103	190	P	V
		5705.4	48.96	-57.75	106.71	40.28	32.31	8.95	32.58	103	190	P	V
		5722.2	49.95	-65.87	115.82	41.2	32.32	9.01	32.58	103	190	P	V
	*	5745	98.76	-	-	89.94	32.34	9.07	32.59	103	190	P	V
	*	5745	90.85	-	-	82.03	32.34	9.07	32.59	103	190	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5642.2	50.35	-17.85	68.2	41.96	32.24	8.7	32.55	100	116	P	H
		5681	49.49	-41.69	91.18	40.96	32.27	8.83	32.57	100	116	P	H
		5719	49.22	-61.3	110.52	40.47	32.32	9.01	32.58	100	116	P	H
		5724.2	48.51	-71.87	120.38	39.76	32.32	9.01	32.58	100	116	P	H
	*	5785	100.87	-	-	91.9	32.38	9.2	32.61	100	116	P	H
	*	5785	93.47	-	-	84.5	32.38	9.2	32.61	100	116	A	H
		5853.6	49.36	-64.63	113.99	40.37	32.46	9.16	32.63	100	116	P	H
		5863	49.62	-58.94	108.56	40.67	32.46	9.13	32.64	100	116	P	H
		5890.2	49.58	-44.34	93.92	40.62	32.5	9.1	32.64	100	116	P	H
		5940.6	48.65	-19.55	68.2	39.75	32.55	9.01	32.66	100	116	P	H
													H
													H
		5620.6	47.95	-20.25	68.2	39.63	32.22	8.64	32.54	100	195	P	V
		5668.4	48.41	-33.44	81.85	39.87	32.27	8.83	32.56	100	195	P	V
		5705.2	47.93	-58.73	106.66	39.25	32.31	8.95	32.58	100	195	P	V
		5723.2	48.01	-70.09	118.1	39.26	32.32	9.01	32.58	100	195	P	V
	*	5785	97.87	-	-	88.9	32.38	9.2	32.61	100	195	P	V
	*	5785	90.57	-	-	81.6	32.38	9.2	32.61	100	195	A	V
		5850	49	-73.2	122.2	40.03	32.44	9.16	32.63	100	195	P	V
		5858.6	49.28	-60.51	109.79	40.3	32.46	9.16	32.64	100	195	P	V
		5879.6	49.22	-52.56	101.78	40.28	32.48	9.1	32.64	100	195	P	V
		5938.4	48.83	-19.37	68.2	39.95	32.53	9.01	32.66	100	195	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz	*	5825	99.44	-	-	90.4	32.43	9.23	32.62	100	115	P	H
	*	5825	92.24	-	-	83.2	32.43	9.23	32.62	100	115	A	H
		5852.8	47.89	-67.93	115.82	38.92	32.44	9.16	32.63	100	115	P	H
		5855.2	50.31	-60.43	110.74	41.32	32.46	9.16	32.63	100	115	P	H
		5905.2	49.8	-33.01	82.81	40.86	32.51	9.07	32.64	100	115	P	H
		5944.2	49.24	-18.96	68.2	40.34	32.55	9.01	32.66	100	115	P	H
													H
													H
	*	5825	97.34	-	-	88.3	32.43	9.23	32.62	100	193	P	V
	*	5825	89.84	-	-	80.8	32.43	9.23	32.62	100	193	A	V
		5851.8	47.73	-70.37	118.1	38.76	32.44	9.16	32.63	100	193	P	V
		5857.8	48.55	-61.46	110.01	39.57	32.46	9.16	32.64	100	193	P	V
		5878.2	50.15	-52.67	102.82	41.18	32.48	9.13	32.64	100	193	P	V
		5928.4	50.35	-17.85	68.2	41.43	32.53	9.04	32.65	100	193	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	44.96	-29.04	74	58.62	39.81	12.74	66.21	100	0	P	H
		17235	45.67	-22.53	68.2	53.91	41.02	16.76	66.02	100	0	P	H
													H
													H
		11490	45.04	-28.96	74	58.7	39.81	12.74	66.21	100	0	P	V
		17235	45.42	-22.78	68.2	53.66	41.02	16.76	66.02	100	0	P	V
													V
													V
802.11n HT20 CH 157 5785MHz		11570	44.58	-29.42	74	58.28	39.69	12.8	66.19	100	0	P	H
		17355	46.18	-22.02	68.2	53.62	41.58	16.86	65.88	100	0	P	H
													H
													H
		11570	44.64	-29.36	74	58.34	39.69	12.8	66.19	100	0	P	V
		17355	45.2	-23	68.2	52.64	41.58	16.86	65.88	100	0	P	V
													V
													V
802.11n HT20 CH 165 5825MHz		11650	44.72	-29.28	74	58.44	39.58	12.87	66.17	100	0	P	H
		17475	46.37	-21.83	68.2	53.01	42.14	16.96	65.74	100	0	P	H
													H
													H
		11650	45.2	-28.8	74	58.92	39.58	12.87	66.17	100	0	P	V
		17475	46.14	-22.06	68.2	52.78	42.14	16.96	65.74	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5618.8	48.53	-19.67	68.2	40.21	32.22	8.64	32.54	100	118	P	H
		5674	48.79	-37.21	86	40.25	32.27	8.83	32.56	100	118	P	H
		5715.6	50	-59.57	109.57	41.32	32.31	8.95	32.58	100	118	P	H
		5723.6	49.45	-69.56	119.01	40.7	32.32	9.01	32.58	100	118	P	H
	*	5755	95.81	-	-	86.9	32.36	9.14	32.59	100	118	P	H
	*	5755	88.01	-	-	79.1	32.36	9.14	32.59	100	118	A	H
		5853.2	48.36	-66.54	114.9	39.39	32.44	9.16	32.63	100	118	P	H
		5870.4	48.97	-57.52	106.49	40.02	32.46	9.13	32.64	100	118	P	H
		5897.6	49.43	-39.01	88.44	40.5	32.5	9.07	32.64	100	118	P	H
		5929.2	49.22	-18.98	68.2	40.3	32.53	9.04	32.65	100	118	P	H
													H
													H
		5632.4	49.56	-18.64	68.2	41.19	32.22	8.7	32.55	100	189	P	V
		5660.6	48.22	-27.85	76.07	39.75	32.26	8.77	32.56	100	189	P	V
		5701.8	47.84	-57.86	105.7	39.15	32.31	8.95	32.57	100	189	P	V
		5724	48.15	-71.77	119.92	39.4	32.32	9.01	32.58	100	189	P	V
	*	5755	94.43	-	-	85.52	32.36	9.14	32.59	100	189	P	V
	*	5755	86.15	-	-	77.24	32.36	9.14	32.59	100	189	A	V
		5853	47.77	-67.59	115.36	38.8	32.44	9.16	32.63	100	189	P	V
		5874.6	48.86	-56.45	105.31	39.89	32.48	9.13	32.64	100	189	P	V
		5910.6	48.04	-30.78	78.82	39.11	32.51	9.07	32.65	100	189	P	V
		5925.2	49.21	-18.99	68.2	40.29	32.53	9.04	32.65	100	189	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5645.2	49.06	-19.14	68.2	40.67	32.24	8.7	32.55	100	117	P	H
		5667.2	48.1	-32.86	80.96	39.56	32.27	8.83	32.56	100	117	P	H
		5700.2	48.24	-57.02	105.26	39.57	32.29	8.95	32.57	100	117	P	H
		5725	47.47	-74.73	122.2	38.72	32.32	9.01	32.58	100	117	P	H
	*	5795	94.73	-	-	85.69	32.39	9.26	32.61	100	117	P	H
	*	5795	87.88	-	-	78.84	32.39	9.26	32.61	100	117	A	H
		5854	48.36	-64.72	113.08	39.37	32.46	9.16	32.63	100	117	P	H
		5872	48.76	-57.28	106.04	39.79	32.48	9.13	32.64	100	117	P	H
		5911.6	48.87	-29.22	78.09	39.94	32.51	9.07	32.65	100	117	P	H
		5941.2	48.71	-19.49	68.2	39.81	32.55	9.01	32.66	100	117	P	H
													H
													H
		5634.2	48.27	-19.93	68.2	39.88	32.24	8.7	32.55	100	193	P	V
		5695.8	47.7	-54.4	102.1	39.09	32.29	8.89	32.57	100	193	P	V
		5717.2	48.29	-61.73	110.02	39.61	32.31	8.95	32.58	100	193	P	V
		5725	49.07	-73.13	122.2	40.32	32.32	9.01	32.58	100	193	P	V
	*	5795	93.78	-	-	84.74	32.39	9.26	32.61	100	193	P	V
	*	5795	85.63	-	-	76.59	32.39	9.26	32.61	100	193	A	V
		5851.8	46.6	-71.5	118.1	37.63	32.44	9.16	32.63	100	193	P	V
		5869.8	47.66	-58.99	106.65	38.71	32.46	9.13	32.64	100	193	P	V
		5892.2	48.92	-43.52	92.44	39.96	32.5	9.1	32.64	100	193	P	V
		5931	47.88	-20.32	68.2	38.96	32.53	9.04	32.65	100	193	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5639.2	47.86	-20.34	68.2	39.47	32.24	8.7	32.55	100	118	P	H
		5697.4	50.25	-53.03	103.28	41.64	32.29	8.89	32.57	100	118	P	H
		5718.6	53.27	-57.14	110.41	44.52	32.32	9.01	32.58	100	118	P	H
		5724.2	51.76	-68.62	120.38	43.01	32.32	9.01	32.58	100	118	P	H
	*	5775	93.03	-	-	84.05	32.38	9.2	32.6	100	118	P	H
	*	5775	84.96	-	-	75.98	32.38	9.2	32.6	100	118	A	H
		5855	47.87	-62.93	110.8	38.88	32.46	9.16	32.63	100	118	P	H
		5866.2	49.55	-58.11	107.66	40.6	32.46	9.13	32.64	100	118	P	H
		5900.8	48.96	-37.11	86.07	40.03	32.5	9.07	32.64	100	118	P	H
		5933.8	47.58	-20.62	68.2	38.69	32.53	9.01	32.65	100	118	P	H
													H
													H
		5602	47.76	-20.44	68.2	39.52	32.2	8.58	32.54	102	191	P	V
		5696.2	49.63	-52.77	102.4	41.02	32.29	8.89	32.57	102	191	P	V
		5719	50.93	-59.59	110.52	42.18	32.32	9.01	32.58	102	191	P	V
		5720.4	50.89	-60.82	111.71	42.14	32.32	9.01	32.58	102	191	P	V
	*	5775	89.8	-	-	80.82	32.38	9.2	32.6	102	191	P	V
	*	5775	83.06	-	-	74.08	32.38	9.2	32.6	102	191	A	V
		5854.6	48.26	-63.45	111.71	39.27	32.46	9.16	32.63	102	191	P	V
		5862.8	49.96	-58.65	108.61	41.01	32.46	9.13	32.64	102	191	P	V
		5910.4	49.32	-29.65	78.97	40.39	32.51	9.07	32.65	102	191	P	V
		5949	48	-20.2	68.2	39.1	32.55	9.01	32.66	102	191	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



EUT connect to Battery backpack

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5607.8	48.64	-19.56	68.2	40.4	32.2	8.58	32.54	100	114	P	H
		5680.8	48.82	-42.21	91.03	40.29	32.27	8.83	32.57	100	114	P	H
		5709	48.02	-59.7	107.72	39.34	32.31	8.95	32.58	100	114	P	H
		5723.8	46.82	-72.64	119.46	38.07	32.32	9.01	32.58	100	114	P	H
	*	5785	95.55	-	-	86.58	32.38	9.2	32.61	100	114	P	H
	*	5785	88.44	-	-	79.47	32.38	9.2	32.61	100	114	A	H
		5855	47.35	-63.45	110.8	38.36	32.46	9.16	32.63	100	114	P	H
		5863.2	48.73	-59.77	108.5	39.78	32.46	9.13	32.64	100	114	P	H
		5922.6	48.2	-21.77	69.97	39.28	32.53	9.04	32.65	100	114	P	H
		5936.4	49.22	-18.98	68.2	40.34	32.53	9.01	32.66	100	114	P	H
													H
													H
		5638.4	48.12	-20.08	68.2	39.73	32.24	8.7	32.55	241	199	P	V
		5680	48.11	-42.33	90.44	39.58	32.27	8.83	32.57	241	199	P	V
		5710	47.6	-60.4	108	38.92	32.31	8.95	32.58	241	199	P	V
		5721.6	48.12	-66.33	114.45	39.37	32.32	9.01	32.58	241	199	P	V
	*	5785	95.76	-	-	86.79	32.38	9.2	32.61	241	199	P	V
	*	5785	88.45	-	-	79.48	32.38	9.2	32.61	241	199	A	V
		5851.6	47.69	-70.86	118.55	38.72	32.44	9.16	32.63	241	199	P	V
		5874.4	48.98	-56.39	105.37	40.01	32.48	9.13	32.64	241	199	P	V
		5919.4	48.71	-23.62	72.33	39.81	32.51	9.04	32.65	241	199	P	V
		5936.6	47.6	-20.6	68.2	38.72	32.53	9.01	32.66	241	199	P	V
													V
													V

**EUT connect to Battery backpack****WIFI 802.11a (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		11570	44.34	-29.66	74	58.04	39.69	12.8	66.19	100	0	P	H
		17355	44.97	-23.23	68.2	52.41	41.58	16.86	65.88	100	0	P	H
													H
													H
		11570	44.57	-29.43	74	58.27	39.69	12.8	66.19	100	0	P	V
		17355	45.47	-22.73	68.2	52.91	41.58	16.86	65.88	100	0	P	V
													V
													V

Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		90.21	28.75	-14.75	43.5	44.47	14.81	1.25	31.78	-	-	P	H
		160.95	31.03	-12.47	43.5	44.51	16.55	1.75	31.78	100	0	P	H
		195.51	30.65	-12.85	43.5	45.64	14.91	1.88	31.78	-	-	P	H
		483.4	26.64	-19.36	46	32.11	23.6	2.8	31.87	-	-	P	H
		740.3	31.61	-14.39	46	31.92	28.18	3.5	31.99	-	-	P	H
		927.2	33.52	-12.48	46	31.1	29.62	4.02	31.22	-	-	P	H
													H
													H
													H
													H
													H
													H
		47.01	31.59	-8.41	40	46.88	15.61	0.91	31.81	100	0	P	V
		107.22	29.26	-14.24	43.5	43	16.75	1.29	31.78	-	-	P	V
		167.97	30.08	-13.42	43.5	44.15	15.88	1.83	31.78	-	-	P	V
		530.3	27.49	-18.51	46	32.35	24.09	2.98	31.93	-	-	P	V
		727.7	31.62	-14.38	46	32.62	27.55	3.46	32.01	-	-	P	V
		838.3	33.34	-12.66	46	32.62	28.7	3.75	31.73	-	-	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 = 55.45 (dBμV/m)
2. Over Limit(dB)
 = Level(dBμV/m) – Limit Line(dBμV/m)
 = 55.45(dBμV/m) – 74(dBμV/m)
 = -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
 = 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
 = 43.54(dBμV/m) – 54(dBμV/m)
 = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots



Test Engineer :	Daniel Lee, Master Huang, and J.C. Liang	Temperature :	18~22°C
		Relative Humidity :	48~53%

Note symbol



-L	Low channel location
-R	High channel location



Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)




WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 770829 Mode : 36	 Site : 03CH10-HY Condition : PEAK(UNII)_3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 770829 Mode : 36





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-I-VY Condition : PEAK_85(149)_16-24 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018.03.10	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018.03.10



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	Site : 03CH10-IHY Condition : PEAK_BE(B4)_15-24 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 : 37	Site : 03CH10-IHY Condition : PEAK(B4)_15-24 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 : 37
Peak	Site : 03CH10-IHY Condition : PEAK_BE(B4)_15-24 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 : 37	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 37	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 37
	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 37	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-I-VY Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 38	 Site : 03CH10-I-VY Condition : PEAK(FUND) 3m HORN 9120D-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 38





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Vertical	Fundamental
Peak	Site : 03CH10-I-VY Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 38	Site : 03CH10-I-VY Condition : PEAK(FUND) 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 38






Band 4 5725~5850MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 39	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 39






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-I-VY Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 39	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 39



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(04)_15-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 40	 Site : 03CH10-HY Condition : PEAK(FUND) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 40
Peak	 Site : 03CH10-HY Condition : PEAK_BE(04)_15-24 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 40	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 40	 Site : 03CH10-IHY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 40
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 40	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	Site : 03CH10-IHV Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018.03.10	Site : 03CH10-IHV Condition : PEAK(FUND) 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018.03.10






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-I-VY Condition : PEAK_BE(84)_16-24 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018.03.10	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018.03.10






Band 4 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 42	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 42
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 42	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 42	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 42
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 42	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018-03-10 PEAK_BE(84)_16-24	 Site : 03CH10-IHY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018-03-10 PEAK(UNII)_3m
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(84)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 Date: 2018-03-10 PEAK_BE(84)_16-24	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 43	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 43
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 43	Left blank



Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 44	 Site : 03CH10-HY Condition : PEAK(UNIT) 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 44
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 44	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(04)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 44	 Site : 03CH10-IHY Condition : PEAK_BE(04)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 44
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(04)_16-24 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 7D0829 Mode : 44	Left blank






EUT connect to Battery backpack

WIFI 802.11a (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 45 connect battery backpack	 Site : 03CH10-HY Condition : PEAK(B4)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 45 connect battery backpack
Peak	 Site : 03CH10-HY Condition : PEAK_BE(B4)_16-24 3m HORN 91200-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 7D0829 45 connect battery backpack	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 45 : connect battery backpack	 Site : 03CH10-IHY Condition : PEAK(UNIT) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 45 : connect battery backpack
Peak	 Site : 03CH10-IHY Condition : PEAK_BE(B4)_16-24 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 45 : connect battery backpack	Left blank





Band 4 - 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 36	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 36





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 37	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 37





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 38	 Site : 03CH10-IHV Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 38





Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 39	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 39





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 40	 Site : 03CH10-HY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 40





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : -41	 Site : 03CH10-I-VY Condition : PEAK(UNII) 3m HORN 91200-HF VERTICAL Detector : Peak Project : 7D0829 Mode : -41

EUT connect to Battery backpack
WIFI 802.11a (Harmonic @ 3m)


WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH10-IHY Condition : PEAK(UNIT) 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 45 : connect battery backpack	 Site : 03CH10-IHY Condition : PEAK(UNIT) 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 7D0829 Mode : 45 : connect battery backpack

Emission below 1GHz
5GHz WIFI 802.11a (LF)


WIFI	5GHz 5725~5850MHz	
ANT	802.11a LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 03CH10-HY Condition : QP 3m BT-LOG 6111D-LF HORIZONTAL Detector : Peak Project : 7D0829 Mode : 46	 Site : 03CH10-HY Condition : QP 3m BT-LOG 6111D-LF VERTICAL Detector : Peak Project : 7D0829 Mode : 46

Appendix E. Duty Cycle Plots


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1+2	802.11a for Ant. 1	92.79	2060	0.49	1kHz	0.32
1+2	802.11a for Ant. 2	93.64	2060	0.49	1kHz	0.29
1+2	5GHz 802.11n HT20 for Ant. 1	92.31	1920	0.52	1kHz	0.35
1+2	5GHz 802.11n HT20 for Ant. 2	93.24	1930	0.52	1kHz	0.30
1+2	5GHz 802.11n HT40 for Ant. 1	87.85	940	1.06	3kHz	0.56
1+2	5GHz 802.11n HT40 for Ant. 2	87.16	950	1.05	3kHz	0.60
1+2	5GHz 802.11ac VHT20 for Ant. 1	93.20	1920	0.52	1kHz	0.31
1+2	5GHz 802.11ac VHT20 for Ant. 2	93.20	1920	0.52	1kHz	0.31
1+2	5GHz 802.11ac VHT40 for Ant. 1	87.56	950	1.05	3kHz	0.58
1+2	5GHz 802.11ac VHT40 for Ant. 2	85.59	950	1.05	3kHz	0.68
1+2	5GHz 802.11ac VHT80 for Ant. 1	86.05	740	1.35	3kHz	0.65
1+2	5GHz 802.11ac VHT80 for Ant. 2	86.05	740	1.35	3kHz	0.65

MIMO<Ant. 1>
802.11a



Date: 28.DEC.2017 21:08:29

802.11n HT20


Date: 28.DEC.2017 21:11:10


802.11n HT40


Date: 28.DEC.2017 21:25:02

802.11ac VHT20



Date: 28.DEC.2017 21:15:04

802.11ac VHT40



Date: 28.DEC.2017 21:18:56


802.11ac VHT80



Date: 28.DEC.2017 21:32:21


MIMO<Ant. 2>

802.11a




Date: 28.DEC.2017 21:09:07


802.11n HT20




Date: 28.DEC.2017 21:10:22




802.11ac VHT20



802.11ac VHT40


Date: 28.DEC.2017 21:17:53

802.11ac VHT80


Date: 28.DEC.2017 21:29:30