TEST REPORT

Reference No.	:	WTF17S1093240-2E
FCC ID	:	2AN8J-150KB-S
Applicant.....	:	JIANGSU LIANGDI TECH CORPORATION
Address.....	:	NO.1 WEISHANHU ROAD, XIXIASHU, XINBEI DISTRICT, CHANGZHOU, JIANGSU, CHINA
Manufacturer	:	The same as above
Address.....	:	The same as above
Product.....	:	Infrared Patio Heater
Model(s).	:	LDHR062-150KB-S
Standards.....	:	FCC CFR47 Part 15.247:2016
Date of Receipt sample	:	2017-10-23
Date of Test	:	2017-10-24 to 2017-11-14
Date of Issue.....	:	2017-11-15
Test Result.....	:	**Pass**

Remarks:
The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Services (Shenzhen) Co., Ltd.
Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China
Tel :+86-755-83551033
Fax:+86-755-83552400

Compiled by:

Jack Wen / Project Engineer

Approved by:

Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services (Shenzhen) Co., Ltd is a professional third-party testing and certification laboratory with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by ILAC (International Laboratory Accreditation Cooperation) member. A2LA (American Association for Laboratory Accreditation) of USA, Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CEC(California energy efficiency), IC(Industry Canada). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as Intertek(ETL-SEMKO), TÜV Rheinland, TÜV SÜD, etc.

Waltek Services (Shenzhen) Co., Ltd is one of the largest and the most comprehensive third party testing laboratory in China. Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), and energy performance, wireless radio. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

2.1 Test Facility

A. Accreditations for Conformity Assessment (International)

Country/Region	Accreditation Body	Scope	Note
USA	**A2LA (Certificate No.: 4243.01)**	FCC ID \ DOC \ VOC	1
Canada		IC ID \ VOC	2
Japan		MIC-T \ MIC-R	-
Europe		EMCD \ RED	-
Taiwan		NCC	-
Hong Kong		OFCA	-
Australia		RCM	-
India	**International Services**	WPC	-
Thailand		NTC	-
Singapore		IDA	-

Note:

1. FCC Designation No.: CN1201. Test Firm Registration No.: 523476.
2. IC Canada Registration No.: 7760A

B.TCBs and Notify Bodies Recognized Testing Laboratory.

Recognized Testing Laboratory of …	Notify body number
TUV Rheinland	Optional.
Intertek	
TUV SUD	
SGS	
Phoenix Testlab GmbH	0700
Element Materials Technology Warwick Ltd	0891
Timco Engineering, Inc.	1177
Eurofins Product Service GmbH	0681

2 Contents

Page

1 COVER PAGE 1

2 LABORATORIES INTRODUCTION 2

2.1 TEST FACILITY 3

2 CONTENTS 4

3 REVISION HISTORY 6

4 GENERAL INFORMATION 7

4.1 GENERAL DESCRIPTION OF E.U.T. 7
4.2 DETAILS OF E.U.T. 7
4.3 CHANNEL LIST 8
4.4 TEST MODE 9

5 TEST SUMMARY 10

6 EQUIPMENT USED DURING TEST 11

6.1 EQUIPMENTS LIST 11
6.2 DESCRIPTION OF SUPPORT UNITS 12
6.3 MEASUREMENT UNCERTAINTY 12
6.4 TEST EQUIPMENT CALIBRATION 12

7 CONDUCTED EMISSION 13

7.1 E.U.T. OPERATION 13
7.2 EUT SETUP 13
7.3 MEASUREMENT DESCRIPTION 13
7.4 CONDUCTED EMISSION TEST RESULT 14

8 RADIATED EMISSIONS 16

8.1 EUT OPERATION 16
8.2 TEST SETUP 17
8.3 SPECTRUM ANALYZER SETUP 18
8.4 TEST PROCEDURE 19
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION 19
8.6 SUMMARY OF TEST RESULTS 20

9 CONDUCTED SPURIOUS EMISSIONS 23

9.1 TEST PROCEDURE 23
9.2 TEST RESULT 24

10 BAND EDGE MEASUREMENT 27

10.1 TEST PRODUCE 27
10.2 TEST RESULT 28

11 6 DB BANDWIDTH MEASUREMENT 29

11.1 TEST PROCEDURE: 29
11.2 TEST RESULT: 29

12 MAXIMUM PEAK OUTPUT POWER 32

12.1 TEST PROCEDURE: 32
12.2 TEST RESULT: 33

13 POWER SPECTRAL DENSITY 35

13.1 TEST PROCEDURE: 35
13.2 TEST RESULT: 35

14 ANTENNA REQUIREMENT 38

15 SAR EVALUATION 39
16 PHOTOGRAPHS – TEST SETUP PHOTOS 40
16.1 RADIATED EMISSION 40
16.2 CONDUCTED EMISSION 42
17 PHOTOGRAPHS – CONSTRUCTIONAL DETAILS 43
17.1 EUT– EXTERNAL PHOTOS 43
17.2 EUT– INTERNAL PHOTOS 47

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTF17S1093240-2E	2017-10-23	2017-10-24 to 2017-11-14	2017-11-15	original	-	Valid

4 General Information(Only applied to BLE)

4.1 General Description of E.U.T.

Product:	Infrared Patio Heater
Model(s):	LDHR062-150KB-S
Model Description:	N/A
The Lowest Oscillator:	32.768kHz

4.2 Details of E.U.T.

Operation Frequency:	2402~2480MHz, 40 channels in total
Max. RF output power:	-0.40dBm
Type of Modulation:	GFSK
Antenna installation:	BLE: External antenna with RP-SMA connector
Antenna Gain:	0dBi
Ratings:	Input: AC 120V, 60Hz, 1500W

4.3 Channel List

BLE

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	1	2404	2	2406	3	2408
4	2410	5	2412	6	2414	7	2416
8	2418	9	2420	10	2422	11	2424
12	2426	13	2428	14	2430	15	2432
16	2434	17	2436	18	2438	19	2440
20	2442	21	2444	22	2446	23	2448
24	2450	25	2452	26	2454	27	2456
28	2458	29	2460	30	2462	31	2464
32	2466	33	2468	34	2470	35	2472
36	2474	37	2476	38	2478	39	2480

4.4 Test Mode

Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	BT BLE	1 Mbps	0/19/39	TX
Power Spectral Density	BT BLE	1 Mbps	0/19/39	TX
6dB Bandwidth	BT BLE	1 Mbps	0/19/39	TX
Band Edge	BT BLE	1 Mbps	0/19/39	TX
Transmitter Spurious Emissions	BT BLE	1 Mbps	0/19/39	TX
Transmitter Conducted Emissions	BT BLE	1 Mbps	0/19/39	TX

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

5 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	PASS
Conducted Emissions	15.207(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

6 Equipment Used during Test

6.1 Equipments List

Conducted Emissions Test Site 1#						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	EMI Test Receiver	R&S	ESCI	100947	2017-09-12	2018-09-11
2.	LISN	R&S	ENV216	101215	2017-09-12	2018-09-11
3.	Cable	Top	TYPE16(3.5M)	-	2017-09-12	2018-09-11
Conducted Emissions Test Site 2#						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	EMI Test Receiver	R&S	ESCI	101155	2017-09-12	2018-09-11
2.	LISN	SCHWARZBECK	NSLK 8128	8128-289	2017-09-12	2018-09-11
3.	Limiter	York	MTS-IMP-136	261115-001-0024	2017-09-12	2018-09-11
4.	Cable	LARGE	RF300	-	2017-09-12	2018-09-11
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1	Spectrum Analyzer	R&S	FSP	100091	2017-04-29	2018-04-28
2	Active Loop Antenna	Beijing Dazhi	ZN30900A	-	2017-04-09	2018-04-08
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2017-04-09	2018-04-08
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2017-09-12	2018-09-11
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2017-04-09	2018-04-08
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2017-04-09	2018-04-08
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2017-04-13	2018-04-12
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2017-04-13	2018-04-12
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No**	**Last Calibration Date**	**Calibration Due Date**
1	Test Receiver	R&S	ESCI	101296	2017-04-13	2018-04-12
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2017-04-09	2018-04-08
3	Amplifier	Compliance pirection systems inc	PAP-0203	22024	2017-04-13	2018-04-12
4	Cable	HUBER+SUHNER	CBL2	525178	2017-04-13	2018-04-12

RF Conducted Testing						
Item	**Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Last Calibration Date**	**Calibration Due Date**
1.	EMC Analyzer (9k~26.5GHz)	Agilent	E7405A	MY45114943	2017-09-12	2018-09-11
2.	Spectrum Analyzer (9k-6GHz)	R&S	FSL6	100959	2017-09-12	2018-09-11
3.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2017-09-12	2018-09-11

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB(AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10^{-7}Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval：95%. Confidence factor:k=2	

6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

7 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Class/Severity: Class B

Limit:

Frequency (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

7.1 E.U.T. Operation

Operating Environment :

Temperature: 21.5 °C

Humidity: 51.9 % RH

Atmospheric Pressure: 101.2kPa

EUT Operation :

The test was performed in TX transmitting mode, the worst data were shown in the report.

7.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



7.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

7.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1620	42.61	9.64	52.25	65.36	-13.11	QP	
2	0.1620	21.16	9.64	30.80	55.36	-24.56	AVG	
3	0.3060	42.44	9.64	52.08	60.08	-8.00	QP	
4	0.3060	30.46	9.64	40.10	50.08	-9.98	AVG	
5	0.4460	28.18	9.64	37.82	56.95	-19.13	QP	
6	0.4460	14.00	9.64	23.64	46.95	-23.31	AVG	
7	0.8460	25.33	9.79	35.12	56.00	-20.88	QP	
8	0.8460	11.97	9.79	21.76	46.00	-24.24	AVG	
9	3.5820	40.00	9.94	49.94	56.00	-6.06	QP	
10	3.5820	26.53	9.94	36.47	46.00	-9.53	AVG	
11	12.1420	23.38	10.19	33.57	60.00	-26.43	QP	
12	12.1420	15.48	10.19	25.67	50.00	-24.33	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1580	42.78	9.64	52.42	65.56	-13.14	QP	
2	0.1580	16.45	9.64	26.09	55.56	-29.47	AVG	
3	0.2980	41.83	9.64	51.47	60.30	-8.83	QP	
4	0.2980	29.56	9.64	39.20	50.30	-11.10	AVG	
5	0.8300	24.85	9.79	34.64	56.00	-21.36	QP	
6	0.8300	11.65	9.79	21.44	46.00	-24.56	AVG	
7	3.4500	40.53	9.93	50.46	56.00	-5.54	QP	
8	3.4500	27.16	9.93	37.09	46.00	-8.91	AVG	
9	12.2340	15.77	10.19	25.96	60.00	-34.04	QP	
10	12.2340	7.12	10.19	17.31	50.00	-32.69	AVG	
11	20.9619	17.53	10.35	27.88	60.00	-32.12	QP	
12	20.9619	2.28	10.35	12.63	50.00	-37.37	AVG	

8 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa

EUT Operation :

The test was performed in TX transmitting mode, the test data were shown in the report.

8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.

The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed ..... Auto
IF Bandwidth..... 10kHz
Video Bandwidth..... 10kHz
Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed ..... Auto
Detector ..... PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed ..... Auto
Detector ..... PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector ..... Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used druing radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – Limit

8.6 Summary of Test Results

Test Frequency: 32.768KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Low Channel 2402MHz									
268.12	35.02	QP	41	1.1	H	-13.35	21.67	46.00	-24.33
268.12	40.08	QP	104	1.0	V	-13.35	26.73	46.00	-19.27
4804.00	45.29	PK	155	1.2	V	-1.06	44.23	74.00	-29.77
4804.00	42.35	Ave	155	1.2	V	-1.06	41.29	54.00	-12.71
7206.00	45.07	PK	7	1.7	H	1.33	46.40	74.00	-27.60
7206.00	36.39	Ave	7	1.7	H	1.33	37.72	54.00	-16.28
2319.52	45.33	PK	209	1.8	V	-13.19	32.14	74.00	-41.86
2319.52	39.92	Ave	209	1.8	V	-13.19	26.73	54.00	-27.27
2369.56	44.86	PK	113	1.4	H	-13.14	31.72	74.00	-42.28
2369.56	36.66	Ave	113	1.4	H	-13.14	23.52	54.00	-30.48
2489.34	43.02	PK	331	1.3	V	-13.08	29.94	74.00	-44.06
2489.34	37.13	Ave	331	1.3	V	-13.08	24.05	54.00	-29.95

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK Middle Channel 2440MHz									
268.12	35.89	QP	214	1.6	H	-13.35	22.54	46.00	-23.46
268.12	41.24	QP	160	1.1	V	-13.35	27.89	46.00	-18.11
4880.00	43.46	PK	300	1.5	V	-0.62	42.84	74.00	-31.16
4880.00	43.74	Ave	300	1.5	V	-0.62	43.12	54.00	-10.88
7320.00	44.47	PK	140	1.6	H	2.21	46.68	74.00	-27.32
7320.00	36.40	Ave	140	1.6	H	2.21	38.61	54.00	-15.39
2334.14	45.66	PK	262	1.6	V	-13.19	32.47	74.00	-41.53
2334.14	39.92	Ave	262	1.6	V	-13.19	26.73	54.00	-27.27
2384.09	43.02	PK	218	1.3	H	-13.14	29.88	74.00	-44.12
2384.09	36.70	Ave	218	1.3	H	-13.14	23.56	54.00	-30.44
2499.30	42.12	PK	260	1.7	V	-13.08	29.04	74.00	-44.96
2499.30	37.19	Ave	260	1.7	V	-13.08	24.11	54.00	-29.89

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
GFSK High Channel 2480MHz									
268.12	36.79	QP	313	1.2	H	-13.35	23.44	46.00	-22.56
268.12	42.14	QP	210	2.0	V	-13.35	28.79	46.00	-17.21
4960.00	44.15	PK	121	1.1	V	-0.24	43.91	74.00	-30.09
4960.00	43.63	Ave	121	1.1	V	-0.24	43.39	54.00	-10.61
7440.00	45.80	PK	252	1.6	H	2.84	48.64	74.00	-25.36
7440.00	35.46	Ave	252	1.6	H	2.84	38.30	54.00	-15.70
2314.90	46.54	PK	261	1.4	V	-13.19	33.35	74.00	-40.65
2314.90	37.19	Ave	261	1.4	V	-13.19	24.00	54.00	-30.00
2366.34	43.92	PK	57	1.7	H	-13.14	30.78	74.00	-43.22
2366.34	37.38	Ave	57	1.7	H	-13.14	24.24	54.00	-29.76
2484.65	43.58	PK	0	1.5	V	-13.08	30.50	74.00	-43.50
2484.65	37.04	Ave	0	1.5	V	-13.08	23.96	54.00	-30.04

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

9 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

Test Result: PASS

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

9.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:

Blow 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto

Detector function = peak, Trace = max hold

Above 30MHz:

RBW = 1MHz, VBW = 3MHz, Sweep = auto

Detector function = peak, Trace = max hold

9.2 Test Result

BLE

Low Channel



Middle Channel



High Channel



BLE

Low Channel



Middle Channel



High Channel



10 Band Edge Measurement

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016
Test Limit:	Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode:	Transmitting

10.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

10.2 Test Result

Test result plots shown as follows:

BLE

Band edge-left side



Band edge-right side



11 6 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

11.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

11.2 Test Result:

Operation mode	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low channel	0.725	1.066
Middle channel	0.701	1.066
High channel	0.713	1.066

Test result plot:

BLE:

Mode:Low channel



Mode:Middle channel



Mode:High channel



12 Maximum Peak Output Power

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

12.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

section 9.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

a)Set the RBW ≥ DTS bandwidth.

b)Set VBW ≥ 3 RBW.

c)Set span ≥ 3 x RBW

d)Sweep time = auto couple.

e)Detector = peak.

f)Trace mode = max hold.

g)Allow trace to fully stabilize.

h)Use peak marker function to determine the peak amplitude level.

section 9.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.

a)Set the RBW = 1 MHz.

b)Set the VBW ≥ 3 RBW

c)Set the span ≥ 1.5 x DTS bandwidth.

d)Detector = peak.

e)Sweep time = auto couple.

f)Trace mode = max hold.

g)Allow trace to fully stabilize.

h)Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

12.2 Test Result:

Maximum Peak Output Power (dBm)		
Low channel	Middle channel	High channel
-0.56	-0.82	**-0.40**
Limit: 1W/30dBm		

BLE

Low Channel



Middle Channel



High Channel



13 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

13.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016 section 10.2

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.

2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.

3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

13.2 Test Result:

Power Spectral Density(dBm)		
Low channel	Middle channel	High channel
-15.72	-16.55	-16.06
Limit: 8dBm per 3kHz		

BLE:

Test mode: Low channel



Test mode: Middle channel



Test mode: High channel



14 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Result:

The EUT has a External antenna with RP-SMA connector, meets the requirements of FCC 15.203.

15 SAR Evaluation

Please refer to SAR report.

16 Photographs – Test Setup Photos

16.1 Radiated Emission

Test frequency Below 30MHz



Test frequency from 30MHz to 1GHz





Test frequency above 1GHz



16.2 Conducted Emission

17 Photographs – Constructional Details

17.1 EUT– External Photos





Infrared Patio Heater
3179365
CONFORMS TO
UL STD.1278
CERTIFIED TO CSA
STD C22.2
NO.46
CAUTION:RISK OF FIRE-KEEP COMBUSTIBLE MATERIAL
AWAY FROM FRONT OF HEATER
AVERTISSEMENT:RISQUE D' INCENDIE-NE
LAISSEZ PAS DE MATERIAU COMBUSTIBLE
DEVANT LE RADIATEUR

17.2 EUT– Internal Photos



BLE ANT








66
65
64
63
62
1cm 2 3 4 5 6


67
66
65
64
63
62
61
1cm 2 3 4 5



====== End of Report ======