

TEST REPORT

Product Name : Bluetooth voice remote control
Brand Mark : N/A
Model No. : AN4806-0KG-001
Extension model : AN4806-0KG-002, AN4806-0KG-003,
AN4806-0KG-004, AN4806-0KG-005,
AN4806-0KG-006, AN4806-0KG-007
FCC ID : 2AN9IU6-AN4806
Report Number : BLA-EMC-202205-A3803
Date of Sample Receipt : 2022/5/13
Date of Test : 2022/5/13 to 2022/5/26
Date of Issue : 2022/5/26
Test Standard : 47 CFR Part 1.1307, Part 2.1093, KDB
447498
Test Result : Pass

Prepared for:

Dongguan Anycon Intelligent Technology Co., Ltd
No12, Limin Road, Jinxiaotang Industrial Park, Fenggang, Dongguan,
Guangdong, China


Prepared by:

BlueAsia of Technical Services (Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:



Approved by:



Review by:



Date:

2022/5/26



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/5/26	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	4
2	GENERAL INFORMATION	5
3	GENERAL DESCRIPTION OF E.U.T.	5
4	LABORATORY LOCATION	6
5	RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1	STANDARD REQUIREMENT	7
5.2	LIMITS	7
5.3	EUT RF EXPOSURE	7

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	PASS

2 GENERAL INFORMATION

Applicant	Dongguan Anycon Intelligent Technology Co.,Ltd
Address	No12,LiminRoad,jinxiaotangIndustrialPark,Fenggang,Dongguan,Guangdong, China
Manufacturer	Dongguan Anycon Intelligent Technology Co.,Ltd
Address	No12,LiminRoad,jinxiaotangIndustrialPark,Fenggang,Dongguan,Guangdong, China
Factory	Dongguan Anycon Intelligent Technology Co.,Ltd
Address	No12,LiminRoad,jinxiaotangIndustrialPark,Fenggang,Dongguan,Guangdong, China
Product Name	Bluetooth voice remote control
Test Model No.	AN4806-0KG-001
Extension model	AN4806-0KG-002, AN4806-0KG-003, AN4806-0KG-004, AN4806-0KG-005, AN4806-0KG-006, AN4806-0KG-007
Note	Their electrical circuit design, layout, components used and internal wiring are identical, only the Item number and color are different.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V0.4
Software Version	V0.04
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	2dBi(Provided by the applicant)

4 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.3 EUT RF EXPOSURE

Operational Mode: BLE						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2402 MHz	2.243	±1	3.243	2.11	0.65	3.0
2442 MHz	1.168	±1	2.168	1.65	0.51	
2480 MHz	1.157	±1	2.157	1.64	0.52	
Conclusion: the calculated value ≤3.0. SAR is exempted.						

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.