







802.11ax (HE40) Modulation



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.



Middle Channel Spurious Emission(2437MHz)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAK Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.


4.6 Radiated Spurious Emission Measurement

4.6.1 Test Specification


Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10: 2020				
Frequency Range:	9 kHz to 26 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation Mode:	Transmitting mode with modulation				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)
	0.009-0.490		2400/F(KHz)		300
	0.490-1.705		24000/F(KHz)		30
	1.705-30		30		30
	30-88		100		3
	88-216		150		3
	216-960		200		3
	Above 960		500		3
	Frequency		Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	Above 1GHz		500	3	Average
			5000	3	Peak

Test Setup:


For radiated emissions below 30MHz



30MHz to 1GHz



Above 1GHz



**Test Procedure:**

1. For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
2. For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal.
The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
4. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
6. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Test results:

PASS



4.6.2 Test Instruments


Radiated Emission Test Site (966)					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum analyzer	Agilent	N9020A	HKE-025	Feb. 06, 2026	Feb. 05, 2027
Spectrum analyzer	KEYSIGHT	N9020A	HKE-117	Feb. 06, 2026	Feb. 05, 2027
Spectrum analyzer	R&S	FSV3044	HKE-126	Feb. 06, 2026	Feb. 05, 2027
Preamplifier	Schwarzbeck	EMC051845SE	HKE-006	Feb. 04, 2026	Feb. 03, 2027
Preamplifier	Agilent	83051A	HKE-016	Feb. 04, 2026	Feb. 03, 2027
Preamplifier	QJD	QJD18-40-50	HKE-030	Feb. 05, 2026	Feb. 04, 2027
6dB Attenuator	Pasternack	6dB	HKE-007	Feb. 06, 2026	Feb. 05, 2027
EMI Test Receiver	R&S	ESR-7	HKE-010	Feb. 06, 2026	Feb. 05, 2027
Broadband Antenna	Schwarzbeck	VULB9168	HKE-167	Feb. 06, 2026	Feb. 05, 2028
Loop Antenna	COM-POWER	AL-130R	HKE-014	Feb. 06, 2026	Feb. 05, 2028
Horn Antenna	Schwarzbeck	9120D	HKE-013	Feb. 06, 2026	Feb. 05, 2028
Broadband Horn Antenna	A-INFO	LB-180400-KF	HKE-031	Feb. 06, 2026	Feb. 05, 2028
EMI Test Software	Tonscend	JS32-RE 5.0.0	HKE-082	/	/
RSE Test Software	Tonscend	JS36-RSE 5.0.0	HKE-184	/	/

4.6.3 Test Data

Below 1GHz Test Results

All the test modes completed for test. Only the worst result of reported as below:


Antenna polarity: Horizontal



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	140.691	-18.30	47.73	29.43	43.50	14.07	100	254	Horizontal
2	199.920	-14.52	42.52	28.00	43.50	15.50	100	111	Horizontal
3	265.946	-12.73	46.51	33.78	46.00	12.22	100	16	Horizontal
4	364.014	-10.54	44.42	33.88	46.00	12.12	100	162	Horizontal
5	575.686	-6.25	45.77	39.52	46.00	6.48	100	12	Horizontal
6	931.061	-1.04	27.18	26.14	46.00	19.86	100	194	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	65.926	-15.37	42.37	27.00	40.00	13.00	100	242	Vertical
2	138.749	-18.31	47.72	29.41	43.50	14.09	100	188	Vertical
3	267.888	-12.76	38.55	25.79	46.00	20.21	100	114	Vertical
4	367.898	-10.60	37.50	26.90	46.00	19.10	100	146	Vertical
5	575.686	-6.25	44.53	38.28	46.00	7.72	100	312	Vertical
6	931.061	-1.04	31.06	30.02	46.00	15.98	100	0	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Harmonics and Spurious Emissions

Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: 1. Emission Level=Reading+ Cable loss-Antenna factor-Amp factor


2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Above 1GHz Test Results

All the test modes completed for test. Only the worst result was reported as below:

For 1GHz to 18GHz


Antenna polarity: Horizontal



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1341.834	53.52	34.89	-18.63	74.00	39.11	150	277	Horizontal
2	1697.270	53.72	35.47	-18.25	74.00	38.53	150	309	Horizontal
3	3585.059	53.31	40.63	-12.68	74.00	33.37	150	125	Horizontal
4	5505.251	51.51	42.48	-9.03	74.00	31.52	150	106	Horizontal
5	7987.999	50.24	48.41	-1.83	74.00	25.59	150	249	Horizontal
6	9291.629	51.17	50.44	-0.73	74.00	23.56	150	72	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical




Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1381.038	53.74	35.16	-18.58	74.00	38.84	150	338	Vertical
2	1624.262	53.59	35.08	-18.51	74.00	38.92	150	192	Vertical
3	2991.999	53.07	40.40	-12.67	74.00	33.60	150	292	Vertical
4	4527.153	52.86	42.50	-10.36	74.00	31.50	150	122	Vertical
5	7968.497	51.06	48.97	-2.09	74.00	25.03	150	309	Vertical
6	9494.149	50.17	50.25	0.08	74.00	23.75	150	297	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

For 18GHz to 26GHz


Antenna polarity: Horizontal



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	18929.693	39.67	45.30	5.63	74.00	28.70	150	110	Horizontal
2	19944.994	39.68	45.86	6.18	74.00	28.14	150	320	Horizontal
3	20753.075	40.21	45.92	5.71	74.00	28.08	150	280	Horizontal
4	21665.967	41.52	46.96	5.44	74.00	27.04	150	20	Horizontal
5	22112.411	42.24	47.98	5.74	74.00	26.02	150	300	Horizontal
6	23091.709	41.20	46.79	5.59	74.00	27.21	150	100	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	18744.074	39.21	44.71	5.50	74.00	29.29	150	280	Vertical
2	19323.332	38.88	44.90	6.02	74.00	29.10	150	250	Vertical
3	20049.805	39.17	45.35	6.18	74.00	28.65	150	120	Vertical
4	20787.479	40.19	45.85	5.66	74.00	28.15	150	300	Vertical
5	21756.376	42.22	47.75	5.53	74.00	26.25	150	290	Vertical
6	22504.450	42.37	48.01	5.64	74.00	25.99	150	260	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

4.7 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction



The antenna used in this product is a FPC antenna, need professional installation, not easy to remove. It conforms to the standard requirements. The best case gain of the antenna is Antenna port 1: 1.13dBi and Antenna port 2: 1.57dBi.

WIFI Antenna




5. Test Setup Photos of the EUT


Radiated Emission




AC Conducted Emission



RF Conducted Emission ANT 1



ANT 2





HUAKE TESTING

Page 97 of 97

Report No.: HK2604100402-3E

6. Photos of the EUT

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos

-----End of test report-----



The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China