

RF Exposure Report

Report No.: SA171031D16C

FCC ID: 2AN9V-DVTRF001

Test Model: DVTRF001

Received Date: June 21, 2019

Test Date: July 23 to 29, 2019

Issued Date: Aug. 13, 2019

Applicant: Devialet

Address: 10 Place Vendome 75001 Paris France

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA171031D16C	Original release.	Aug. 13, 2019

1 Certificate of Conformity

Product: WCBN3507A-D6

Brand: Devialet

Test Model: DVTRF001

Sample Status: R&D SAMPLE

Applicant: Devialet

Test Date: July 23 to 29, 2019


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Phoenix Huang / Specialist

Date:

Aug. 13, 2019

Approved by :


May Chen / Manager

Date:

Aug. 13, 2019

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Original									
Antenna set 1									
Transmitter Circuit	Brand	Model	Antenna Type	2.4GHz Gain <with cable loss> (dBi)	5GHz Gain <with cable loss> (dBi)	2.4GHz Cable Loss (dB)	5G Cable Loss (dB)	Connector Type	Cable Length (mm)
Chain (0)	WNC	81-EBJ15.0 05	PIFA	3.62	Band 1&2: 3.08 Band 3: 4.76 Band 4: 4.76	1.15	Band 1&2:1.70 Band 3: 1.74 Band 4: 1.79	IPEX	300
Chain (1)	WNC	81-EBJ15.0 05	PIFA	3.62	Band 1&2: 3.08 Band 3: 4.76 Band 4: 4.76	1.15	Band 1&2:1.70 Band 3: 1.74 Band 4: 1.79	IPEX	300
Antenna set 2									
Transmitter Circuit	Brand	Model	Antenna Type	2.4GHz Gain <with cable loss> (dBi)	5GHz Gain <with cable loss> (dBi)	Cable Loss (dB)	Connector Type	Cable Length (mm)	
Chain (0)	Tongda	T-543-82010 44-A (Ant 1)	PIFA	3.572	Band 1&2: 3.002 Band 3: 4.546 Band 4: 4.416	NA	IPEX	77	
Chain (1)	Tongda	T-543-82010 44-A (Ant 2)	PIFA	3.325	Band 1&2: 2.942 Band 3: 4.622 Band 4: 4.586	NA	IPEX	61	
Antenna set 3									
Transmitter Circuit	Brand	Model	Antenna Type	2.4GHz Gain <with cable loss> (dBi)	5GHz Gain <with cable loss> (dBi)	Cable Loss (dB)		Connector Type	
Chain (0)	ethertronics	M830520	chip	1.1	3.2	NA		IPEX	
Chain (1)	ethertronics	M830520	chip	1.1	3.2	NA		IPEX	
Antenna set 4									
Transmitter Circuit	Brand	Model	Antenna Type	2.4GHz Gain <with cable loss> (dBi)	5GHz Gain <with cable loss> (dBi)	Cable Loss (dB)		Connector Type	
Chain (0)	ethertronics	1002298	PIFA	3.6	5.1	NA		IPEX	
Chain (1)	ethertronics	1002298	PIFA	3.6	5.1	NA		IPEX	
Newly									
Antenna set 5									
Transmitter Circuit	Brand	Model	Antenna Type	2.4GHz Gain <with cable loss> (dBi)	5GHz Gain <with cable loss> (dBi)	2.4GHz Cable Loss (dB)	5G Cable Loss (dB)	Connector Type	Cable Length (mm)
Chain (0)	Devialet	DVT-BA-M-1 311-P	Monopole G	3.4	5.8	0.8	1.5	IPEX	150
Chain (1)	Devialet	DVT-BA-PF-1408-P	IFA	5.2	3.3	0.8	1.5	IPEX	150
Note:									
1. All of antenna can be application for WLAN and Bluetooth.									
2. The Bluetooth technology will fix transmission on Chain (0)									

2.5 Calculation Result of Maximum Conducted Power

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN (2.4GHz)	2437	469.401	7.36	20	0.50848	1
WLAN (U-NII-1)	5240	77.033	7.65	20	0.08921	1
WLAN (U-NII-2A)	5300	72.825	7.65	20	0.08434	1
WLAN (U-NII-2C)	5580	74.001	7.65	20	0.08570	1
WLAN (U-NII-3)	5785	61.885	7.65	20	0.07167	1
BT-EDR	2480	14.488	3.4	20	0.00631	1
BT-LE	2480	1.95	3.4	20	0.00085	1

Note:

2.4GHz: For newly antenna set, the directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 7.36 \text{ dBi}$

5GHz: For newly antenna set, the directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 7.65 \text{ dBi}$

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 5GHz + Bluetooth = $0.08921 / 1 + 0.00631 / 1 = 0.09552$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---