



中国认可
国际互认
检测
TESTING
CNAS-L4963

TEST REPORT

Applicant: Raven Connected Inc.
Address: 441 MacLaren St Suite 408 Ottawa, Ontario K2P 2H3
Equipment Type: Raven Pro
Model Name: RVC0A0
Brand Name: Raven
FCC ID: 2AN9Y-RVC0A0
Test Standard: 47 CFR Part 2.1091-2023
KDB 447498 D04 v01
Sample Arrival Date: N/A
Test Date: N/A
Date of Issue: Jun. 09, 2025

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center



Prepared by: Huang Xiaoqin

Reviewed by: Cai Xueguo

Approved by: Zhang Yanqing
(Laboratory Manager)

Huang Xiaoqin

Cai Xueguo

Zhang Yanqing

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Jun. 09, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information.....	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Technical Information	4
3	SUMMARY OF TEST RESULT	5
3.1	Test Standards.....	5
3.2	Limit Standards	5
4	DEVICE CATEGORY AND LEVELS LIMITS	6
5	ASSESSMENT RESULT	8
5.1	Output Power	8
5.2	Tune-up power	10
5.3	RF Exposure Evaluation Result.....	11
5.4	Collocated Power Calculation.....	11
5.5	Conclusion	12

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1st to 2nd floors, Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai, China

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1st to 2nd floors, Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 29671.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Raven Connected Inc.
Address	441 MacLaren St Suite 408 Ottawa, Ontario K2P 2H3

2.2 Manufacturer Information

Manufacturer	Raven Connected Inc.
Address	441 MacLaren St Suite 408 Ottawa, Ontario K2P 2H3

2.3 General Description for Equipment under Test (EUT)

EUT Name	Raven Pro
Model Name Under Test	RVC0A0
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	RVC0A0
Software Version	3.0.1
Dimensions (Approx.)	200mm*28mm*50mm
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	2G Network GSM 850/1900 MHz 3G Network WCDM Band 2/4/5 4G Network LTE FDD Band 2/4/5/7/12/13/25/26/66 TDD Band 38/41 Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n HT40, 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) ,5.8G SRD, GPS, GLONASS, BDS, Galileo
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	GSM, WCDMA, LTE, WIFI, Bluetooth	
Frequency Range	Bluetooth	2402 ~ 2480 MHz
	2.4G WIFI	2412 ~ 2462 MHz
	5G WIFI	U-NII-1: 5150 ~ 5250MHz U-NII-2A: 5250 ~ 5350MHz U-NII-2C: 5470 ~ 5725MHz U-NII-3: 5725 ~ 5850MHz

	GSM 850	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA B2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA B4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	WCDMA B5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE B2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE B4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE B5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE B7	TX: 2500 ~ 2570 MHz	RX: 2620 ~ 2690 MHz
	LTE B12	TX: 699 ~ 716 MHz	RX: 729 ~ 746 MHz
	LTE B13	TX: 777 ~ 787 MHz	RX: 746 ~ 756 MHz
	LTE B25	TX: 1850 ~ 1915 MHz	RX: 1930 ~ 1995 MHz
	LTE B26	TX: 814 ~ 849 MHz	RX: 859 ~ 894 MHz
	LTE B66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2180 MHz
	LTE B38	TX: 2570 ~ 2620 MHz	RX: 2570 ~ 2620 MHz
	LTE B41	TX: 2535 ~ 2655 MHz	RX: 2535 ~ 2655 MHz
Antenna Type	WIFI	PIFA	
	Bluetooth	PIFA	
	WWAN	PIFA	
Exposure Category	General Population/Uncontrolled Exposure		
Product Type	Mobile Device		

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	KDB 447498 D04 v01 ☆	447498 D04 Interim General RF Exposure Guidance v01

3.2 Limit Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091-2023	Radiofrequency radiation exposure evaluation: mobile devices

4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Devices:

CFR Title 47 §2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Table B-2 Example Power Thresholds (mW)											
Frequency (MHz)	Distance (mm)										
	5	10	15	20	25	30	35	40	45	50	
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

5 ASSESSMENT RESULT

5.1 Output Power

GSM					
Mode	Burst Average Power(dBm)		Division	Frame-Averaged power (dBm)	
	GSM 850	GSM 1900	Factors	GSM 850	GSM 1900
GSM	31.35	28.98	9.19	22.16	19.79
GPRS (GMSK, 1-Slot)	31.35	28.98	9.19	22.16	19.79
GPRS (GMSK, 2-Slots)	30.78	27.96	6.13	24.65	21.83
GPRS (GMSK, 3-Slots)	28.61	26.32	4.42	24.19	21.90
GPRS (GMSK, 4-Slots)	27.51	25.15	3.18	24.33	21.97
EGPRS (8PSK, 1-Slot)	26.31	25.38	9.19	17.12	16.19
EGPRS (8PSK, 2-Slots)	25.38	24.70	6.13	19.25	18.57
EGPRS (8PSK, 3-Slots)	22.36	23.27	4.42	17.94	18.85
EGPRS (8PSK, 4-Slots)	20.98	21.99	3.18	17.80	18.81
Antenna Gain (dB)	-1.10	0.40	N/A	-1.05	0.70
MAX ERP/EIRP (dBm)	28.10	29.38	N/A	21.45	22.67
Note: This report listed the worst case conducted power value, please refer to RF test report No.BL-SH2530203-501 for more details.					

WCDMA			
Mode	Band 2	Band 4	Band 5
Conducted Power (dBm)	22.55	22.27	22.64
Antenna Gain (dBi)	0.40	2.70	-1.10
ERP/EIRP (dBm)	22.95	24.97	19.39
Note: This report listed the worst case conducted power value, please refer to RF test report No.BL-SH2530203-501 for more details.			

LTE						
Mode	Band 2	Band 4	Band 5	Band 7	Band 12	Band 13
Conducted Power (dBm)	23.19	22.85	22.54	21.94	23.03	22.32
Antenna Gain (dBi)	0.40	2.70	-1.10	2.40	-1.60	2.20
ERP/EIRP (dBm)	23.59	25.55	19.29	24.34	19.28	22.37
Note: This report listed the worst case conducted power value, please refer to RF test report No.BL-SH2530203-501 for more details.						
LTE						
Mode	Band 25	Band 26	Band 66	Band 38	Band 41	/
Conducted Power (dBm)	22.42	22.40	22.43	21.84	21.88	/
Antenna Gain (dBi)	0.40	-1.10	2.70	1.90	1.90	/
ERP/EIRP (dBm)	22.82	19.15	25.13	23.74	23.78	/
Note: This report listed the worst case conducted power value, please refer to RF test report No.BL-SH2530203-501 for more details.						

Bluetooth					
Mode	GFSK	$\pi/4$ 4-DQPSK	8-DPSK	BLE 1Mbps	BLE 2Mbps
Conducted Power (dBm)	6.45	5.57	6.19	7.32	7.87
Antenna Gain (dBi)	1.12	1.12	1.12	1.12	1.12
EIRP (dBm)	7.57	6.69	7.31	8.44	8.99
Note: This report listed the worst case conducted power value, please refer to RF test report No. BL-SH2530203-601 and BL-SH2530203-602 for more details.					

WLAN					
Mode	2.4GWIFI Max	5GWIFI (U-NII-1) Max	5GWIFI (U-NII-2A) Max	5GWIFI (U-NII-2C) Max	5GWIFI (U-NII-3) Max
Conducted Power (dBm)	16.54	14.25	14.32	13.71	13.92
Antenna Gain (dBi)	1.12	1.40	1.27	-0.46	-0.65
EIRP (dBm)	17.66	15.65	15.59	13.25	13.27
Note: This report listed the worst case conducted power value, please refer to RF test report No. BL-SH2530203-603 and BL-SH2530203-604 for more details.					

5.2 Tune-up power

Mode		Conducted Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)
GSM	GSM 850	【23.50,25.50】	/	【20.30,22.30】
	GSM 1900	【21.00,23.00】	【20.30,22.30】	【18.15,20.15】
WCDMA	Band 2	【21.50,23.50】	【22.20,24.20】	【20.05,22.05】
	Band 4	【21.00,23.00】	【23.78,25.78】	【21.63,23.63】
	Band 5	【21.50,23.50】	/	【18.30,20.30】
LTE	Band 2	【22.00,24.00】	【22.70,24.70】	【20.55,22.55】
	Band 4	【22.00,24.00】	【23.78,25.78】	【21.63,23.63】
	Band 5	【21.5,23.50】	/	【18.30,20.30】
	Band 7	【21.00,23.00】	【23.84,25.84】	【21.69,23.69】
	Band 12	【22.00,24.00】	/	【18.21,20.21】
	Band 13	【22.50,23.50】	/	【17.89,19.89】
	Band 25	【21.00,23.00】	【21.76,23.76】	【19.61,21.61】
	Band 26	【21.00,23.00】	/	【17.80,19.80】
	Band 66	【21.00,23.00】	【23.78,25.78】	【21.63,23.63】
	Band 38	【21.00,23.00】	【22.57,24.57】	【20.42,22.42】
	Band 41	【20.50,22.50】	【22.76,24.76】	【20.61,22.61】
Bluetooth		【7.00,9.00】	【7.00,9.00】	【5.97,7.97】
2.4GWIFI		【15.50,17.50】	【15.50,17.50】	【14.47,16.47】
5GWIFI(U-NII-1: 5150-5250MHz)		【13.50,15.50】	【13.50,15.50】	【12.75,14.75】
5GWIFI(U-NII-2A: 5250-5350MHz)		【13.50,15.50】	【13.50,15.50】	【12.62,14.62】
5GWIFI(U-NII-2C: 5470-5725MHz)		【13.00,15.00】	【13.00,15.00】	【10.39,12.39】
5GWIFI(U-NII-3: 5725-5850MHz)		【13.00,15.00】	【13.00,15.00】	【10.20,12.20】
Note1: ERP= EIRP -2.15dB.				
Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.				

5.3 RF Exposure Evaluation Result

Evolution mode		Frequency (MHz)	Distance (cm)	Maximum power Tune up(dBm)	Maximum power (mw)	Threshold Power (mW)	P/Plimit	Verdict
GSM	GSM850	824	20	25.50	354.81	1680.96	0.2111	Pass
	GSM1900	1850	20	23.00	199.53	3060.00	0.0652	Pass
WCDMA	Band 2	1850	20	23.50	223.87	3060.00	0.0732	Pass
	Band 4	1710	20	23.55	226.46	3060.00	0.0740	Pass
	Band 5	824	20	23.50	223.87	1680.96	0.1332	Pass
LTE	Band 2	1850	20	24.00	251.19	3060.00	0.0821	Pass
	Band 4	1710	20	24.55	285.10	3060.00	0.0932	Pass
	Band 5	824	20	23.50	223.87	1680.96	0.1332	Pass
	Band 7	2500	20	23.25	211.35	3060.00	0.0691	Pass
	Band 12	699	20	24.00	251.19	1425.96	0.1762	Pass
	Band 13	777	20	23.55	226.46	1585.08	0.1429	Pass
	Band 25	1850	20	23.00	199.53	3060.00	0.0652	Pass
	Band 26	814	20	23.00	199.53	1660.56	0.1202	Pass
	Band 66	1710	20	23.55	226.46	3060.00	0.0740	Pass
	Band 38	2570	20	23.00	199.53	3060.00	0.0652	Pass
	Band 41	2535	20	22.50	177.83	3060.00	0.0581	Pass
Bluetooth		2402	20	9.00	7.94	3060.00	0.0026	Pass
2.4G WIFI		2412	20	17.50	56.23	3060.00	0.0184	Pass
5GWIFI(U-NII-1: 5150-5250MHz)		5150	20	15.50	35.48	3060.00	0.0116	Pass
5GWIFI(U-NII-2A: 5250-5350MHz)		5250	20	15.50	35.48	3060.00	0.0116	Pass
5GWIFI(U-NII-2C: 5470-5725MHz)		5470	20	15.00	31.62	3060.00	0.0103	Pass
5GWIFI(U-NII-3: 5725-5850MHz)		5725	20	15.00	31.62	3060.00	0.0103	Pass

5.4 Collocated Power Calculation

Evolution mode	Frequency(MHz)	Power /Limit	Σ (Power / Limit) of WWAN + WLAN	Verdict
GSM850	824MHz ~ 849 MHz	0.2111	0.2295	Pass

2.4G WLAN	2412MHz ~ 2462MHz	0.0184		
-----------	-------------------	--------	--	--

Note:

1. $\Sigma(\text{Power} / \text{Limit})$: This is a summation of [(power for each transmitter/ antenna included in the simultaneous transmission)/ (corresponding Power limit)], for WWAN+ WLAN or WWAN+ Bluetooth.
2. Both of the WWAN+ WLAN can transmit simultaneously, the formula of calculated the Power is $CP1 / LP1 + CP2 / LP2 + \dots \text{etc.} < 1$
 CP = Calculation power
 LP = Limit of power
3. Both of the 2.4GHz/5GHz WIFI and Bluetooth can't transmit simultaneously at same time.
4. The worst-case situation is 0.2295, which is less than "1". This confirmed that the device comply with FCC KDB 447498 D04 Power limit.
5. The DUT work frequency range used is 824MHz ~ 849MHz, 1850MHz ~ 1910MHz, 1710MHz ~ 1755MHz, 824MHz ~ 849MHz, 1850MHz ~ 1910MHz, 1710MHz ~ 1755MHz, 699MHz ~ 716 MHz, 777MHz ~ 787MHz, 814MHz ~ 849MHz, 2412MHz~2462MHz, 2570MHz ~ 2620MHz, 2535 MHz ~ 2655MHz, 5150MHz ~ 5250MHz, 5250MHz ~ 5350MHz, 5470MHz ~ 5725MHz, 5725MHz ~ 5850MHz the result close to the limit by the above formula, so we select worst case power to calculate the exclusion power threshold.
6. More power list please refer to RF test report.

5.5 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--