

FCC Test Report

Report No. : 1815C50549412501

Applicant : Momax Technology (Shenzhen) Limited

Address : 4th Floor, Weiyu Long Buji Factory Building
A, No. 2016, Xuegang Road, Gangtou
Community, Bantian Street, Longgang
District, Shenzhen City, China

Product Name : 1-Charge Q.Port2 Qi2.2 3-in-1 Magnetic
Wireless Charging Station

Report Date : 2025-11-26

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Modes	6
1.5. Description Of Test Setup	8
1.6. Test Equipment List	9
1.7. Measurement Uncertainty	10
1.8. Description of Test Facility	10
1.9. Disclaimer	10
2. Summary of Test Results	11
3. Conducted Emission Test	12
3.1. Test Standard and Limit	12
3.2. Test Setup	12
3.3. Test Procedure	12
3.4. Test Data	12
4. Radiation Spurious Emission Test	15
4.1. Test Standard and Limit	15
4.2. Test Setup	15
4.3. Test Procedure	16
4.4. Test Data	16
5. 20dB Occupy Bandwidth Test	23
5.1. Test Standard and Limit	23
5.2. Test Setup	23
5.3. Test Procedure	23
5.4. Test Data	23
6. Antenna Requirement	27
6.1. Test Standard and Requirement	27
6.2. Antenna Connected Construction	27
APPENDIX I -- TEST SETUP PHOTOGRAPH	28
APPENDIX II -- EXTERNAL PHOTOGRAPH	28
APPENDIX III -- INTERNAL PHOTOGRAPH	28

TEST REPORT

Applicant : Momax Technology (Shenzhen) Limited

Manufacturer : iMX Electronic (Shenzhen) Co.,LTD

Product Name : 1-Charge Q.Port2 Qi2.2 3-in-1 Magnetic Wireless Charging Station

Model No. : UD31Q22

Trade Mark : momax

Input: 12V=3A, 15V=3A

Output for mobile phone: 5W, 7.5W, 10W, 15W, 25W

Rating(s) : Output for mobile airpods: 5W Max

Output for mobile watch: 5W Max

Total Output: 35W Max

Test Standard(s) : FCC Part15 Subpart C

Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt 2025-10-16

Date of Test 2025-10-16 to 2025-11-07

Prepared By

Lene Chen

(Lene Chen)

Approved & Authorized Signer

Hugo Chen

(Hugo Chen)

Revision History

Report Version	Description	Issued Date
R00	Original Issue.	2025-11-26

1. General Information

1.1. Client Information

Applicant	:	Momax Technology (Shenzhen) Limited
Address	:	4th Floor, Weiyu Long Buji Factory Building A, No. 2016, Xuegang Road, Gangtuo Community, Bantian Street, Longgang District, Shenzhen City, China
Manufacturer	:	iMX Electronic (Shenzhen) Co.,LTD
Address	:	F/4,East Side Mech.Factory,EVOC Tech.Industrial Park,No.11,Gaoxin Rd,Gaoxin Area,Dongzhou Community,Guangming Street, Guangming District,Shenzhen City,Guangdong Province,P.R.China
Factory	:	iMX Electronic (Shenzhen) Co.,LTD
Address	:	F/4,East Side Mech.Factory,EVOC Tech.Industrial Park,No.11,Gaoxin Rd,Gaoxin Area,Dongzhou Community,Guangming Street, Guangming District,Shenzhen City,Guangdong Province,P.R.China

1.2. Description of Device (EUT)

Product Name	:	1-Charge Q.Port2 Qi2.2 3-in-1 Magnetic Wireless Charging Station
Model No.	:	UD31Q22
Trade Mark	:	momax
Test Power Supply	:	AC 120V/60Hz for Adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Operation Frequency	:	For mobile phone: 360KHz+127.7KHz MPP: 25W for 360KHz BPP: 5W, 7.5W, 10W, 15W for 127.7KHz For airpods: 111-148KHz For watch: 326.5KHz(2.5W&3W)+1.778MHz(5W)
Modulation Type	:	ASK
Antenna Type	:	Inductive loop coil Antenna
Remark: 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
Ifory 65W adapter	ifory	191106C	/
Xiaomi 67W adapter(RE)	Xiaomi	MDY-13-ES	WA622091100529G
Full-function watch wireless charging test stand	Shenzhen Hancal Microelectronics Co., Ltd.	HC-RX-20231001	/
Wireless load	BAECOAR	15W Smart wireless charger fixture wireless charging	/
Apple AirPods	Apple	AirPods Pro	/
Apple Watch	Apple	iwatch s6	/

1.4. Description of Test Modes



To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Modes	Descriptions
TM1	Adapter+WPT Mode (Phone(25W) + Watch(5W) + Earphone(5W))
TM2	Adapter+WPT Mode (Phone(15W) + Watch(5W) + Earphone(5W))
TM3	Adapter+WPT Mode (Phone(10W) + Watch(5W) + Earphone(5W))
TM4	Adapter+WPT Mode (Phone(7.5W) + Watch(5W) + Earphone(5W))
TM5	Adapter+WPT Mode (Phone(5W) + Watch(5W) + Earphone(5W))
TM6	Adapter+WPT Mode (Phone(25W) + Watch(5W))
TM7	Adapter+WPT Mode (Phone(15W) + Watch(5W))
TM8	Adapter+WPT Mode (Phone(10W) + Watch(5W))
TM9	Adapter+WPT Mode (Phone(7.5W) + Watch(5W))
TM10	Adapter+WPT Mode (Phone(5W) + Watch(5W))
TM11	Adapter+WPT Mode (Phone(25W) + Earphone(5W))
TM12	Adapter+WPT Mode (Phone(15W) + Earphone(5W))
TM13	Adapter+WPT Mode (Phone(10W) + Earphone(5W))
TM14	Adapter+WPT Mode (Phone(7.5W) + Earphone(5W))
TM15	Adapter+WPT Mode (Phone(5W) + Earphone(5W))

TM16	Adapter+WPT Mode (Watch(5W) + Earphone(5W))
TM17	Adapter+WPT Mode (Phone(25W))
TM18	Adapter+WPT Mode (Phone(15W))
TM19	Adapter+WPT Mode (Phone(10W))
TM20	Adapter+WPT Mode (Phone(7.5W))
TM21	Adapter+WPT Mode (Phone(5W))
TM22	Adapter+WPT Mode (Watch(5W))
TM23	Adapter+WPT Mode (Earphone(5W))
TM24	Standby Mode
TM25	Adapter+WPT Mode (Phone(25W) + Watch(3W) + Earphone(5W))
TM26	Adapter+WPT Mode (Phone(15W) + Watch(3W) + Earphone(5W))
TM27	Adapter+WPT Mode (Phone(10W) + Watch(3W) + Earphone(5W))
TM28	Adapter+WPT Mode (Phone(7.5W) + Watch(3W) + Earphone(5W))
TM29	Adapter+WPT Mode (Phone(5W) + Watch(3W) + Earphone(5W))
TM30	Adapter+WPT Mode (Phone(25W) + Watch(3W))
TM31	Adapter+WPT Mode (Phone(15W) + Watch(3W))
TM32	Adapter+WPT Mode (Phone(10W) + Watch(3W))
TM33	Adapter+WPT Mode (Phone(7.5W) + Watch(3W))
TM34	Adapter+WPT Mode (Phone(5W) + Watch(3W))
TM35	Adapter+WPT Mode (Watch(3W) + Earphone(5W))
TM36	Adapter+WPT Mode (Watch(3W))

Note: Battery Status: <1%, Battery Status: 50%, and Battery Status: >98% load cases(Phone, Watch and Earphone) were pre-tested for all modes, but we only recorded the worst case(TM1: WPT Mode (Phone(25W)(Battery Status: <1%) + Watch(5W/3W)(Battery Status: <1%) + Earphone(5W)(Battery Status: <1%)) in this report.

1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	2025-09-05	1 Year
2.	Three Phase V- type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT00 1	2025-01-13	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	2025-01-13	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	2025-01-14	1 Year
5.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	2025-09-05	1 Year
6.	EMI Preamplifier	SKET Electronic	LNPA-0118G- 45	SKET-PA-002	2025-01-13	1 Year
7.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	2025-09-05	3 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	2025-09-05	3 Year
9.	Loop Antenna(9K- 30M)	Schwarzbeck	FMZB1519B	00053	2025-09-05	1 Year
10.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	2024-01-22	3 Year
11.	Pre-amplifier	SONOMA	310N	186860	2025-01-14	1 Year
12.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
13.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	2025-09-05	1 Year
14.	MXG RF Vector Signal Generator	Agilent	N5182A	MY47420647	2025-01-14	1 Year
15.	Signal Generator	Agilent	E4421B	MY41000743	2025-02-21	1 Year
16.	DC Power Supply	IVYTECH	IV3605	1804D360510	2025-09-05	1 Year
17.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	2025-10-10	1 Year
18.	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102150	2025-04-25	1 Year

1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.2dB
Occupied Bandwidth	925Hz
Radiated spurious emissions (Below 30MHz)	3.26dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.70dB; Vertical: 4.42dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission Test	PASS
15.205/15.209	Spurious Emission	PASS
15.215(c)	20dB Occupy Bandwidth	PASS


Note: N/A" denotes test is not applicable in this Test Report

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.
Please to see the following pages.

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: TM1
Test Specification: AC 120V/60Hz for Adapter
Comment: Live Line
Temp.(°C)/Hum.(%RH): 23.1°C/52%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1539	27.54	27.84	55.38	65.78	-10.40	QP	
2	0.3620	21.10	27.83	48.93	58.68	-9.75	QP	
3	0.3620	16.65	27.83	44.48	48.68	-4.20	AVG	
4	0.5100	11.21	27.87	39.08	56.00	-16.92	QP	
5	1.0820	13.17	27.87	41.04	56.00	-14.96	QP	
6	1.0820	7.98	27.87	35.85	46.00	-10.15	AVG	
7	2.5220	8.86	27.86	36.72	46.00	-9.28	AVG	
8	3.2380	15.11	27.86	42.97	56.00	-13.03	QP	
9	3.2380	11.08	27.86	38.94	46.00	-7.06	AVG	
10	4.3220	11.51	27.86	39.37	56.00	-16.63	QP	
11	4.9940	7.51	27.87	35.38	46.00	-10.62	AVG	
12	6.0739	11.86	27.89	39.75	50.00	-10.25	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: TM1
Test Specification: AC 120V/60Hz for Adapter
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 23.1°C/52%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	29.80	27.83	57.63	65.99	-8.36	QP	
2	0.1860	22.01	27.83	49.84	64.21	-14.37	QP	
3	0.3620	21.45	27.83	49.28	58.68	-9.40	QP	
4	0.3620	16.52	27.83	44.35	48.68	-4.33	AVG	
5	0.4380	10.42	27.84	38.26	47.10	-8.84	AVG	
6	0.5220	13.44	27.87	41.31	56.00	-14.69	QP	
7	1.0820	8.04	27.87	35.91	46.00	-10.09	AVG	
8	3.2420	17.35	27.86	45.21	56.00	-10.79	QP	
9	3.2420	11.07	27.86	38.93	46.00	-7.07	AVG	
10	4.7220	15.31	27.87	43.18	56.00	-12.82	QP	
11	4.9940	7.61	27.87	35.48	46.00	-10.52	AVG	
12	5.7140	9.14	27.88	37.02	50.00	-12.98	AVG	

4. Radiation Spurious Emission Test

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data


PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

Test Results (Between 9KHz – 150KHz)


Test Mode: TM26
Distance: 3m
Power Source: AC 120V/60Hz for Adapter
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH
Fundamental



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	0.0200	10.95	20.29	31.24	121.41	-90.17	peak	
2	0.0320	11.58	20.56	32.14	117.36	-85.22	peak	
3	0.0509	7.91	20.41	28.32	113.35	-85.03	peak	
4	0.0709	3.31	20.37	23.68	110.49	-86.81	peak	
5	0.0767	6.22	20.37	26.59	109.81	-83.22	peak	
6	0.1277	24.31	20.34	44.65	105.46	-60.81	peak	

Test Results (Between 0.15MHz – 30MHz)


Test Mode: TM26
Distance: 3m
Power Source: AC 120V/60Hz for Adapter
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH
Fundamental



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	0.1955	14.63	20.31	34.94	101.73	-66.79	peak	
2	0.2548	15.70	20.30	36.00	99.44	-63.44	peak	
3	0.3265	16.92	20.28	37.20	95.97	-58.77	peak	
4	0.5020	9.84	20.27	30.11	73.59	-43.48	QP	
5	0.7752	11.21	20.25	31.46	69.83	-38.37	QP	
6	1.4032	1.28	20.27	21.55	64.69	-43.14	QP	


Test Results (Between 9KHz – 150KHz)

Test Mode: TM1
Distance: 3m
Power Source: AC 120V/60Hz for Adapter
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH



Test Results (Between 0.15MHz – 30MHz)

Test Mode: TM1
Distance: 3m
Power Source: AC 120V/60Hz for Adapter
Polarization: Coplane
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH
Fundamental




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	0.1955	21.13	20.31	41.44	101.73	-60.29	peak	
2	0.2519	16.58	20.30	36.88	99.54	-62.66	peak	
3	0.3600	28.62	20.28	48.90	96.46	-47.56	peak	
4	0.4374	11.09	20.27	31.36	94.78	-63.42	peak	
5	0.6338	14.13	20.27	34.40	71.57	-37.17	QP	
6	1.7716	22.18	20.27	42.45	69.50	-27.05	QP	

Remark: According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.


Test Results (Between 30MHz –1000 MHz)

Test Mode: TM1
Distance: 3m
Power Source: AC 120V/60Hz for Adapter
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 22.5°C/55%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	35.2512	44.61	-18.25	26.36	40.00	-13.64	QP	
2	55.0274	38.27	-17.73	20.54	40.00	-19.46	QP	
3	109.4116	44.29	-19.10	25.19	43.50	-18.31	QP	
4	148.4410	50.92	-22.67	28.25	43.50	-15.25	QP	
5	287.9904	48.19	-17.12	31.07	46.00	-14.93	QP	
6	431.0316	37.73	-12.99	24.74	46.00	-21.26	QP	

Test Mode: TM1
Distance: 3m
Power Source: AC 120V/60Hz for Adapter
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 22.5°C/55%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	32.2925	55.86	-19.32	36.54	40.00	-3.46	QP	
2	35.2512	54.06	-18.25	35.81	40.00	-4.19	QP	
3	38.7518	51.88	-16.55	35.33	40.00	-4.67	QP	
4	105.6415	48.43	-18.89	29.54	43.50	-13.96	QP	
5	148.4410	54.46	-22.54	31.92	43.50	-11.58	QP	
6	601.4265	37.14	-9.67	27.47	46.00	-18.53	QP	

5. 20dB Occupy Bandwidth Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.215(c)
Test Limit	Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.2. Test Setup




5.3. Test Procedure

The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=1%-5%OBW, VBW≥3*RBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.


5.4. Test Data

Temperature:	25.7 °C	Humidity:	56 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------


Freq. (MHz)	Bandwidth (kHz)	Results
0.1277(For mobile phone)	0.847	PASS




Freq. (MHz)	Bandwidth (kHz)	Results
0.3265(For watch)	0.871	PASS




Freq. (MHz)	Bandwidth (kHz)	Results
0.360(For mobile phone)	0.831	PASS



Freq. (MHz)	Bandwidth (kHz)	Results
1.778(For watch)	0.892	PASS



Freq. (MHz)	Bandwidth (kHz)	Results
0.1277(For airpods)	0.811	PASS



Note: The measured signal is Cw-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300Hz to perform the occupied bandwidth test.

6. Antenna Requirement

6.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

6.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached. It complies with the standard requirement.

APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----