



RF Test Report

For


Applicant Name: Cj Global Inc.
Address: 20-21 Wagaraw Road Bldg 30 Fair Lawn, New Jersey, NJ 0740,
United States
EUT Name: 2-in-1 True Wireless Earbuds with Wireless Speaker
Brand Name: N/A
Model Number: 71581-DI
Series Model Number: N/A


Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park,
Tantou Community, Songgang Street, Bao'an District, Shenzhen,
China

Report Number: BTF230628R01101
Test Standards: 47 CFR Part 15.247

Test Conclusion: Pass
FCC ID: 2AND8-BT23SP3
Test Date: 2023-06-30 to 2023-07-04
Date of Issue: 2023-07-11

Prepared By: 
Date: Elma. Yang / Project Engineer
2023-07-11

Approved By: 
Date: Ryan CJ / EMC Manager
2023-07-11

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.



Test Report Number: BTF230628R01101

Revision History		
Version	Issue Date	Revisions Content
R_V0	2023-07-11	Original
<i>Note: Once the revision has been made, then previous versions reports are invalid.</i>		

Table of Contents

1	INTRODUCTION	5
1.1	Identification of Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Announcement	5
2	PRODUCT INFORMATION.....	6
2.1	Application Information	6
2.2	Manufacturer Information.....	6
2.3	Factory Information	6
2.4	General Description of Equipment under Test (EUT)	6
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards.....	7
3.2	Uncertainty of Test	7
3.3	Summary of Test Result	7
4	TEST CONFIGURATION	8
4.1	Test Equipment List	8
4.2	Test Auxiliary Equipment	13
4.3	Test Modes	13
5	EVALUATION RESULTS (EVALUATION).....	14
5.1	Antenna requirement	14
5.1.1	Conclusion:.....	14
6	RADIO SPECTRUM MATTER TEST RESULTS (RF).....	15
6.1	Conducted Emission at AC power line	15
6.1.1	E.U.T. Operation:	15
6.1.2	Test Setup Diagram:	15
6.1.3		16
6.2	Occupied Bandwidth	18
6.2.1	E.U.T. Operation:	18
6.2.2	Test Setup Diagram:	19
6.2.3	Test Data:	19
6.3	Maximum Conducted Output Power	20
6.3.1	E.U.T. Operation:	20
6.3.2	Test Setup Diagram:	21
6.3.3	Test Data:	21
6.4	Channel Separation	22
6.4.1	E.U.T. Operation:	22
6.4.2	Test Setup Diagram:	23
6.4.3	Test Data:	23
6.5	Number of Hopping Frequencies	24
6.5.1	E.U.T. Operation:	24
6.5.2	Test Setup Diagram:	25
6.5.3	Test Data:	25
6.6	Dwell Time.....	26
6.6.1	E.U.T. Operation:	26
6.6.2	Test Setup Diagram:	27
6.6.3	Test Data:	27
6.7	Emissions in non-restricted frequency bands	28

6.7.1	E.U.T. Operation:	28
6.7.2	Test Setup Diagram:	29
6.7.3	Test Data:	29
6.8	Band edge emissions (Radiated).....	30
6.8.1	E.U.T. Operation:	30
6.8.2	Test Data:	31
6.9	Emissions in restricted frequency bands (below 1GHz).....	34
6.9.1	E.U.T. Operation:	34
6.9.2	Test Data:	35
6.10	Emissions in restricted frequency bands (above 1GHz)	37
6.10.1	E.U.T. Operation:	37
6.10.2	Test Data:	38
7	TEST SETUP PHOTOS	43
APPENDIX		46

1 Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130
FCC Registration Number:	518915
Designation Number:	CN1330

1.3 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 Product Information

2.1 Application Information

Company Name:	Cj Global Inc.
Address:	20-21 Wagaraw Road Bldg 30 Fair Lawn, New Jersey, NJ 0740, United States

2.2 Manufacturer Information

Company Name:	Cj Global Inc.
Address:	20-21 Wagaraw Road Bldg 30 Fair Lawn, New Jersey, NJ 0740, United States

2.3 Factory Information

Company Name:	/
Address:	/

2.4 General Description of Equipment under Test (EUT)

EUT Name:	2-in-1 True Wireless Earbuds with Wireless Speaker
Test Model Number:	71581-DI
Series Model Number:	N/A
Hardware Version:	V01
Software and Firmware Version:	AC6966B
Sample No.:	BTFSN230628E011-1/1

2.5 Technical Information

Power Supply:	From 3.7V 500mAh Battery and recharged by DC 5V.
Power Adaptor:	/
Operation Frequency:	2402MHz to 2480MHz
Number of Channels:	79
Channel Spacing:	1MHz
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	PCB ANT
Antenna Gain#:	-0.68 dBi

Note:

#: The antenna gain provided by the applicant, and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.

3 Summary of Test Results

3.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

3.2 Uncertainty of Test

Item	Measurement Uncertainty
Conducted Emission (150 kHz-30 MHz)	±2.64dB
The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3.3 Summary of Test Result

Item	Standard	Requirement	Result
Antenna requirement	47 CFR Part 15.247	Part 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
Occupied Bandwidth	47 CFR Part 15.247	47 CFR 15.215(c)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(1)	Pass
Channel Separation	47 CFR Part 15.247	47 CFR 15.247(a)(1)	Pass
Number of Hopping Frequencies	47 CFR Part 15.247	47 CFR 15.247(a)(1)(iii)	Pass
Dwell Time	47 CFR Part 15.247	47 CFR 15.247(a)(1)(iii)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
Emissions in restricted frequency bands (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
Emissions in restricted frequency bands (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d)	Pass

4 Test Configuration

4.1 Test Equipment List

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	00953	2022-11-24	2023-11-23
Coaxial Switcher	SCHWARZBECK	CX210	CX210	2022-11-24	2023-11-23
V-LISN	SCHWARZBECK	NSLK 8127	01073	2022-11-24	2023-11-23
LISN	AFJ	LS16/110VAC	16010020076	2023-02-23	2024-02-22
EMI Receiver	ROHDE&SCHWARZ	ESCI3	101422	2022-11-24	2023-11-23

Occupied Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Maximum Conducted Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Channel Separation					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/

RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Number of Hopping Frequencies

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Dwell Time

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Emissions in non-restricted frequency bands

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Band edge emissions (Radiated)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMAMAM-10m	21101566	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMAMAM-1m	21101568	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2021-11-28	2023-11-27
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCi7	101032	2022-11-24	2023-11-23
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2021-11-28	2023-11-27

Emissions in restricted frequency bands (below 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2022-11-24	2023-11-23

RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2021-11-28	2023-11-27
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2022-11-24	2023-11-23
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2021-11-28	2023-11-27

Emissions in restricted frequency bands (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2021-11-28	2023-11-27
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2022-11-24	2023-11-23
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/



Test Report Number: BTF230628R01101

Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2021-11-28	2023-11-27
----------------------	-------------	-----------	-------	------------	------------

4.2 Test Auxiliary Equipment

The EUT was tested as an independent device.

4.3 Test Modes


No.	Test Modes	Description
TM1	TX-GFSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation.
TM2	TX-Pi/4DQPSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with Pi/4DQPSK modulation.
TM3	TX-8DPSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation.
TM4	TX-GFSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation,.
TM5	TX-Pi/4DQPSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with Pi/4DQPSK modulation.
TM6	TX-8DPSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with 8DPSK modulation.

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	--

5.1.1 Conclusion:



6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Method:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
*Decreases with the logarithm of the frequency.			

6.1.1 E.U.T. Operation:

Operating Environment:	
Temperature:	22.3 °C
Humidity:	52.8 %
Atmospheric Pressure:	1010 mbar


6.1.2 Test Setup Diagram:



6.1.3 Test Data:


Note: Level = Reading level + Factor

TM1 / Line: Line / Band: 2.4G / BW: 1 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1518	16.48	20.08	36.56	65.90	-29.34	QP	P	
2	0.1518	10.70	20.08	30.78	55.90	-25.12	AVG	P	
3	0.1625	16.55	20.08	36.63	65.34	-28.71	QP	P	
4	0.1625	10.41	20.08	30.49	55.34	-24.85	AVG	P	
5	0.3130	17.25	20.12	37.37	59.89	-22.52	QP	P	
6	0.3130	14.46	20.12	34.58	49.89	-15.31	AVG	P	
7	0.4450	12.17	20.15	32.32	56.97	-24.65	QP	P	
8	0.4450	8.87	20.15	29.02	46.97	-17.95	AVG	P	
9	0.7036	14.65	20.22	34.87	56.00	-21.13	QP	P	
10 *	0.7036	10.73	20.22	30.95	46.00	-15.05	AVG	P	
11	13.2368	9.95	20.50	30.45	60.00	-29.55	QP	P	
12	13.2368	5.49	20.50	25.99	50.00	-24.01	AVG	P	

TM1 / Line: Neutral / Band: 2.4G / BW: 1 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1573	16.76	20.08	36.84	65.61	-28.77	QP	P	
2	0.1573	10.78	20.08	30.86	55.61	-24.75	AVG	P	
3	0.3138	17.53	20.12	37.65	59.87	-22.22	QP	P	
4	0.3138	14.67	20.12	34.79	49.87	-15.08	AVG	P	
5	0.7770	15.08	20.24	35.32	56.00	-20.68	QP	P	
6 *	0.7770	11.92	20.24	32.16	46.00	-13.84	AVG	P	
7	0.8405	11.57	20.26	31.83	56.00	-24.17	QP	P	
8	0.8405	8.38	20.26	28.64	46.00	-17.36	AVG	P	
9	2.4887	10.93	20.40	31.33	56.00	-24.67	QP	P	
10	2.4887	6.24	20.40	26.64	46.00	-19.36	AVG	P	
11	5.8932	10.75	20.43	31.18	60.00	-28.82	QP	P	
12	5.8932	6.12	20.43	26.55	50.00	-23.45	AVG	P	

6.2 Occupied Bandwidth


Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013
Test Limit:	Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Procedure:	a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2. d) Steps a) through c) might require iteration to adjust within the specified tolerances. e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value. f) Set detection mode to peak and trace mode to max hold. g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value). h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument. i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j). j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth. k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

6.2.1 E.U.T. Operation:

Operating Environment:

Temperature:	25.2 ℃
Humidity:	50.2 %
Atmospheric Pressure:	1010 mbar

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.


6.3 Maximum Conducted Output Power

Test Requirement:	For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Test Method:	Output power test procedure for frequency-hopping spread-spectrum (FHSS) devices
Test Limit:	For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Procedure:	This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test: - Use the following spectrum analyzer settings: - Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel. - RBW > 20 dB bandwidth of the emission being measured. - VBW >= RBW. - Sweep: Auto. - Detector function: Peak. - Trace: Max hold. - Allow trace to stabilize. - Use the marker-to-peak function to set the marker to the peak of the emission. - The indicated level is the peak output power, after any corrections for external attenuators and cables. - A plot of the test results and setup description shall be included in the test report. NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

6.3.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.2 °C
Humidity:	50.2 %
Atmospheric Pressure:	1010 mbar

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.


6.4 Channel Separation

Test Requirement:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
Test Method:	Carrier frequency separation
Test Limit:	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: Wide enough to capture the peaks of two adjacent channels. b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel. c) Video (or average) bandwidth (VBW) $\geq$ RBW. d) Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

6.4.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.2 °C
Humidity:	50.2 %
Atmospheric Pressure:	1010 mbar

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.


6.5 Number of Hopping Frequencies

Test Requirement:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	Number of hopping frequencies
Test Limit:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen. b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. c) VBW $\geq$ RBW. d) Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize. It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

6.5.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.2 °C
Humidity:	50.2 %
Atmospheric Pressure:	1010 mbar

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.


6.6 Dwell Time

Test Requirement:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	Time of occupancy (dwell time)
Test Limit:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: Zero span, centered on a hopping channel. b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel. c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel. d) Detector function: Peak. e) Trace: Max hold. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation: $(\text{Number of hops in the period specified in the requirements}) = (\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time})$ The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation. The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

6.6.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.2 °C
Humidity:	50.2 %
Atmospheric Pressure:	1010 mbar

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

Please Refer to Appendix for Details.


6.7 Emissions in non-restricted frequency bands

Test Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	Conducted spurious emissions test methodology
Test Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Procedure:	Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers. Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

6.7.1 E.U.T. Operation:

Operating Environment:	
Temperature:	25.2 °C
Humidity:	50.2 %
Atmospheric Pressure:	1010 mbar

6.7.2 Test Setup Diagram:



6.7.3 Test Data:

Please Refer to Appendix for Details.

6.8 Band edge emissions (Radiated)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	Radiated emissions tests		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.			
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.8.1 E.U.T. Operation:

Operating Environment:	
Temperature:	24.9 °C
Humidity:	49.4 %
Atmospheric Pressure:	1010 mbar

6.8.2 Test Data:

Note: Level = Reading level + Factor

TM1 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	67.60	-30.59	37.01	74.00	-36.99	peak	P
2	2390.000	69.81	-30.49	39.32	74.00	-34.68	peak	P
3	2400.000	79.19	-30.48	48.71	74.00	-25.29	peak	P

TM1 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	68.61	-30.59	38.02	74.00	-35.98	peak	P
2	2390.000	70.12	-30.49	39.63	74.00	-34.37	peak	P
3	2400.000	78.35	-30.48	47.87	74.00	-26.13	peak	P

TM1 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	79.40	-30.39	49.01	74.00	-24.99	peak	P
2	2500.000	71.51	-30.37	41.14	74.00	-32.86	peak	P

TM1 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	80.47	-30.39	50.08	74.00	-23.92	peak	P
2	2500.000	71.06	-30.37	40.69	74.00	-33.31	peak	P

TM2 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	67.19	-30.59	36.60	74.00	-37.40	peak	P
2	2390.000	70.81	-30.49	40.32	74.00	-33.68	peak	P
3	2400.000	78.05	-30.48	47.57	74.00	-26.43	peak	P

TM2 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	67.96	-30.59	37.37	74.00	-36.63	peak	P
2	2390.000	69.26	-30.49	38.77	74.00	-35.23	peak	P
3	2400.000	78.10	-30.48	47.62	74.00	-26.38	peak	P

TM2 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	81.00	-30.39	50.61	74.00	-23.39	peak	P
2	2500.000	70.69	-30.37	40.32	74.00	-33.68	peak	P

TM2 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	79.40	-30.39	49.01	74.00	-24.99	peak	P
2	2500.000	71.10	-30.37	40.73	74.00	-33.27	peak	P

TM3 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	67.18	-30.59	36.59	74.00	-37.41	peak	P
2	2390.000	69.55	-30.49	39.06	74.00	-34.94	peak	P
3	2400.000	78.78	-30.48	48.30	74.00	-25.70	peak	P

TM3 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2310.000	67.87	-30.59	37.28	74.00	-36.72	peak	P
2	2390.000	70.13	-30.49	39.64	74.00	-34.36	peak	P
3	2400.000	77.92	-30.48	47.44	74.00	-26.56	peak	P

TM3 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	79.65	-30.39	49.26	74.00	-24.74	peak	P
2	2500.000	70.41	-30.37	40.04	74.00	-33.96	peak	P

TM3 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2483.500	80.95	-30.39	50.56	74.00	-23.44	peak	P
2	2500.000	70.12	-30.37	39.75	74.00	-34.25	peak	P

6.9 Emissions in restricted frequency bands (below 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	Radiated emissions tests		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.			
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.9.1 E.U.T. Operation:

Operating Environment:	
Temperature:	24.9 °C
Humidity:	49.4 %
Atmospheric Pressure:	1010 mbar

6.9.2 Test Data:

Note: All the mode have been tested, and only the worst case of GFSK mode are in the report
Level = Reading level + Factor

TM1 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	46.6664	42.39	-17.82	24.57	40.00	-15.43	QP	100	309	P	
2	56.1974	42.94	-17.96	24.98	40.00	-15.02	QP	299	127	P	
3	128.1130	46.45	-18.26	28.19	43.50	-15.31	QP	299	11	P	
4	159.7844	45.24	-17.23	28.01	43.50	-15.49	QP	100	35	P	
5	595.1329	46.00	-11.76	34.24	46.00	-11.76	QP	100	63	P	
6 *	878.3214	45.35	-8.15	37.20	46.00	-8.80	QP	299	11	P	

TM1 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	43.3534	43.52	-17.68	25.84	40.00	-14.16	QP	300	349	P	
2	52.5753	42.14	-17.74	24.40	40.00	-15.60	QP	300	349	P	
3	128.1130	47.85	-18.26	29.59	43.50	-13.91	QP	100	36	P	
4	159.7844	44.28	-17.23	27.05	43.50	-16.45	QP	100	12	P	
5	345.5952	43.34	-16.55	26.79	46.00	-19.21	QP	300	349	P	
6 *	595.1329	45.92	-11.76	34.16	46.00	-11.84	QP	100	12	P	

6.10 Emissions in restricted frequency bands (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Method:	Radiated emissions tests		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.			
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.10.1 E.U.T. Operation:

Operating Environment:	
Temperature:	24.6 ℃
Humidity:	49.4 %
Atmospheric Pressure:	1010 mbar

6.10.2 Test Data:

Note: Level = Reading level + Factor

1G~25G:

TM1 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2649.978	68.94	-30.12	38.82	74.00	-35.18	peak	P
2	4278.063	68.09	-28.93	39.17	74.00	-34.83	peak	P
3	6084.803	64.20	-25.36	38.84	74.00	-35.16	peak	P
4	8645.005	70.51	-25.47	45.04	74.00	-28.96	peak	P
5	11999.553	68.84	-22.56	46.28	74.00	-27.72	peak	P
6	15649.538	71.74	-21.00	50.74	74.00	-23.26	peak	P

TM1 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2649.765	70.35	-30.59	39.76	74.00	-34.24	peak	P
2	4277.642	68.98	-29.43	39.55	74.00	-34.45	peak	P
3	6086.227	65.05	-24.65	40.40	74.00	-33.60	peak	P
4	8646.356	69.09	-25.17	43.92	74.00	-30.08	peak	P
5	11999.102	68.26	-24.16	44.10	74.00	-29.90	peak	P
6	15650.396	70.34	-21.94	48.40	74.00	-25.60	peak	P

TM1 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3250.868	67.33	-28.82	38.50	74.00	-35.50	peak	P
2	4500.760	69.47	-29.40	40.06	74.00	-33.94	peak	P
3	6654.494	67.74	-25.48	42.26	74.00	-31.74	peak	P
4	8577.100	69.44	-26.13	43.32	74.00	-30.68	peak	P
5	11286.745	67.55	-24.19	43.36	74.00	-30.64	peak	P
6	13500.212	70.97	-20.35	50.62	74.00	-23.38	peak	P

TM1 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3249.771	66.56	-28.74	37.82	74.00	-36.18	peak	P
2	4500.660	69.49	-29.79	39.70	74.00	-34.30	peak	P
3	6654.784	67.76	-25.70	42.06	74.00	-31.94	peak	P
4	8576.560	70.05	-24.62	45.43	74.00	-28.57	peak	P
5	11285.209	68.69	-22.40	46.29	74.00	-27.71	peak	P
6	13499.149	70.46	-20.60	49.86	74.00	-24.14	peak	P

TM1 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3250.382	66.99	-30.28	36.71	74.00	-37.29	peak	P
2	4499.172	67.95	-28.13	39.81	74.00	-34.19	peak	P
3	6653.221	67.09	-25.60	41.49	74.00	-32.51	peak	P
4	8576.263	69.87	-26.05	43.82	74.00	-30.18	peak	P
5	11285.310	68.30	-22.76	45.53	74.00	-28.47	peak	P
6	13500.820	71.51	-19.82	51.69	74.00	-22.31	peak	P

TM1 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3249.419	67.64	-29.37	38.27	74.00	-35.73	peak	P
2	4499.853	68.59	-28.31	40.28	74.00	-33.72	peak	P
3	6654.281	66.54	-25.75	40.80	74.00	-33.20	peak	P
4	8576.375	70.16	-24.80	45.35	74.00	-28.65	peak	P
5	11285.954	68.16	-22.44	45.71	74.00	-28.29	peak	P
6	13499.221	71.24	-19.57	51.67	74.00	-22.33	peak	P

TM2 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2450.708	69.69	-29.43	40.25	74.00	-33.75	peak	P
2	4276.159	67.52	-28.76	38.77	74.00	-35.23	peak	P
3	6084.683	64.32	-25.92	38.40	74.00	-35.60	peak	P
4	8644.953	68.83	-25.80	43.03	74.00	-30.97	peak	P
5	12000.383	67.32	-22.92	44.40	74.00	-29.60	peak	P
6	15649.614	71.72	-21.68	50.04	74.00	-23.96	peak	P

TM2 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2450.304	69.16	-29.39	39.77	74.00	-34.23	peak	P
2	4276.122	68.05	-29.40	38.66	74.00	-35.34	peak	P
3	6084.518	64.25	-25.43	38.81	74.00	-35.19	peak	P
4	8645.398	68.94	-24.55	44.39	74.00	-29.61	peak	P
5	11999.961	67.50	-23.57	43.93	74.00	-30.07	peak	P
6	15649.053	71.75	-21.24	50.51	74.00	-23.49	peak	P

TM2 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2864.093	68.87	-29.38	39.48	74.00	-34.52	peak	P
2	4277.601	68.65	-29.75	38.90	74.00	-35.10	peak	P
3	6084.715	65.27	-25.28	39.99	74.00	-34.01	peak	P
4	8645.741	69.32	-25.48	43.85	74.00	-30.15	peak	P
5	12000.556	67.04	-23.47	43.58	74.00	-30.42	peak	P
6	16664.690	71.27	-21.00	50.27	74.00	-23.73	peak	P

TM2 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2864.723	70.63	-30.33	40.30	74.00	-33.70	peak	P
2	4277.213	68.09	-29.48	38.61	74.00	-35.39	peak	P
3	6085.082	64.55	-26.31	38.23	74.00	-35.77	peak	P
4	8645.051	69.69	-24.08	45.62	74.00	-28.38	peak	P
5	11999.153	67.51	-24.23	43.28	74.00	-30.72	peak	P
6	16665.635	70.58	-21.84	48.73	74.00	-25.27	peak	P

TM2 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3249.373	66.22	-29.26	36.96	74.00	-37.04	peak	P
2	4499.825	68.80	-29.35	39.45	74.00	-34.55	peak	P
3	6654.984	66.64	-25.47	41.18	74.00	-32.82	peak	P
4	8575.816	70.01	-26.01	44.00	74.00	-30.00	peak	P
5	11286.796	68.64	-24.04	44.60	74.00	-29.40	peak	P
6	13500.038	71.90	-19.36	52.55	74.00	-21.45	peak	P

TM2 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: H

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3249.963	66.41	-29.20	37.21	74.00	-36.79	peak	P
2	4499.625	68.46	-29.60	38.86	74.00	-35.14	peak	P
3	6654.484	68.23	-24.57	43.66	74.00	-30.34	peak	P
4	8577.000	70.10	-25.26	44.84	74.00	-29.16	peak	P
5	11286.497	67.11	-22.52	44.59	74.00	-29.41	peak	P
6	13499.704	70.56	-20.85	49.70	74.00	-24.30	peak	P

TM3 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2865.985	70.09	-29.45	40.65	74.00	-33.35	peak	P
2	4276.721	68.27	-28.61	39.66	74.00	-34.34	peak	P
3	6084.859	64.16	-26.06	38.10	74.00	-35.90	peak	P
4	8645.160	69.61	-24.83	44.78	74.00	-29.22	peak	P
5	11999.681	67.49	-22.65	44.84	74.00	-29.16	peak	P
6	16664.722	71.42	-20.72	50.70	74.00	-23.30	peak	P

TM3 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: L

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	2864.152	69.90	-29.81	40.09	74.00	-33.91	peak	P
2	4277.696	67.32	-29.81	37.51	74.00	-36.49	peak	P
3	6084.966	64.92	-24.67	40.26	74.00	-33.74	peak	P
4	8646.571	70.18	-24.74	45.44	74.00	-28.56	peak	P
5	12000.224	67.32	-22.79	44.53	74.00	-29.47	peak	P
6	16665.831	71.35	-20.95	50.40	74.00	-23.60	peak	P

TM3 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3250.363	66.85	-30.26	36.59	74.00	-37.41	peak	P
2	4500.232	68.81	-29.03	39.78	74.00	-34.22	peak	P
3	6653.246	66.93	-24.46	42.47	74.00	-31.53	peak	P
4	8575.328	69.09	-25.85	43.24	74.00	-30.76	peak	P
5	11286.934	67.26	-22.88	44.38	74.00	-29.62	peak	P
6	13500.933	70.69	-20.12	50.57	74.00	-23.43	peak	P

TM3 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: M

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3249.203	66.75	-29.11	37.64	74.00	-36.36	peak	P
2	4500.557	69.54	-29.85	39.69	74.00	-34.31	peak	P
3	6654.106	67.93	-24.93	43.01	74.00	-30.99	peak	P
4	8575.318	70.46	-25.37	45.09	74.00	-28.91	peak	P
5	11286.040	68.44	-23.89	44.54	74.00	-29.46	peak	P
6	13500.831	71.72	-19.92	51.80	74.00	-22.20	peak	P

TM3 / Polarization: Horizontal / Band: 2.4G / BW: 1 / CH: H


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3358.563	67.90	-29.99	37.91	74.00	-36.09	peak	P
2	4499.638	69.73	-28.85	40.88	74.00	-33.12	peak	P
3	6750.285	67.04	-26.16	40.87	74.00	-33.13	peak	P
4	8576.529	69.67	-25.98	43.69	74.00	-30.31	peak	P
5	11285.978	68.11	-23.14	44.97	74.00	-29.03	peak	P
6	16554.401	71.43	-19.98	51.45	74.00	-22.55	peak	P

TM3 / Polarization: Vertical / Band: 2.4G / BW: 1 / CH: H


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	3359.270	67.11	-29.79	37.31	74.00	-36.69	peak	P
2	4500.177	68.16	-29.04	39.12	74.00	-34.88	peak	P
3	6750.802	68.19	-24.80	43.39	74.00	-30.61	peak	P
4	8576.430	69.63	-25.49	44.13	74.00	-29.87	peak	P
5	11286.869	67.18	-23.08	44.10	74.00	-29.90	peak	P
6	16554.814	70.85	-20.36	50.49	74.00	-23.51	peak	P

7 Test Setup Photos

Conducted Emission at AC power line



Band edge emissions (Radiated)
Emissions in restricted frequency bands (above 1GHz)



Emissions in restricted frequency bands (below 1GHz)



Test Report Number: BTF230628R01101

EUT Constructional Details (EUT Photos)

Please refer to the Appendix EUT Photos.


Appendix



1. Bandwidth



1.1 OBW



1.1.1 Test Result



Condition	Antenna	Modulation	Frequency (MHz)	99%OBW(MHz)
NVNT	ANT1	1-DH1	2402.00	0.900
NVNT	ANT1	1-DH1	2441.00	0.950
NVNT	ANT1	1-DH1	2480.00	0.966
NVNT	ANT1	2-DH1	2402.00	1.090
NVNT	ANT1	2-DH1	2441.00	1.100
NVNT	ANT1	2-DH1	2480.00	1.219
NVNT	ANT1	3-DH1	2402.00	1.133
NVNT	ANT1	3-DH1	2441.00	1.138
NVNT	ANT1	3-DH1	2480.00	1.196
















1.2 20dB BW



1.2.1 Test Result



Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	if larger than CFS
NVNT	ANT1	1-DH1	2402.00	0.941	No
NVNT	ANT1	1-DH1	2441.00	1.025	Yes
NVNT	ANT1	1-DH1	2480.00	1.041	Yes
NVNT	ANT1	2-DH1	2402.00	1.133	Yes
NVNT	ANT1	2-DH1	2441.00	1.141	Yes
NVNT	ANT1	2-DH1	2480.00	1.291	Yes
NVNT	ANT1	3-DH1	2402.00	1.211	Yes
NVNT	ANT1	3-DH1	2441.00	1.215	Yes
NVNT	ANT1	3-DH1	2480.00	1.270	Yes














2. Maximum Conducted Output Power



2.1 Power



2.1.1 Test Result



Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1-DH1	2402.00	1.38	1.38	1000	Pass
NVNT	ANT1	1-DH1	2441.00	1.34	1.36	125	Pass
NVNT	ANT1	1-DH1	2480.00	0.99	1.26	125	Pass
NVNT	ANT1	2-DH1	2402.00	2.17	1.65	125	Pass
NVNT	ANT1	2-DH1	2441.00	1.99	1.58	125	Pass
NVNT	ANT1	2-DH1	2480.00	1.78	1.51	125	Pass
NVNT	ANT1	3-DH1	2402.00	2.01	1.59	125	Pass
NVNT	ANT1	3-DH1	2441.00	1.99	1.58	125	Pass
NVNT	ANT1	3-DH1	2480.00	2.29	1.69	125	Pass











3. Carrier Frequency Separation

3.1 Ant1

3.1.1 Test Result

Condition	Antenna	Modulation	Frequency(MHz)	Hopping NO.0 (MHz)	Hopping NO.1 (MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	1-DH1	2402.00	2401.858	2402.869	1.01	0.941	Pass
NVNT	ANT1	1-DH1	2441.00	2440.858	2441.854	1.00	0.683	Pass
NVNT	ANT1	1-DH1	2480.00	2478.863	2479.845	0.98	0.694	Pass
NVNT	ANT1	2-DH1	2402.00	2401.858	2402.866	1.01	0.755	Pass
NVNT	ANT1	2-DH1	2441.00	2440.855	2441.857	1.00	0.761	Pass
NVNT	ANT1	2-DH1	2480.00	2478.870	2480.019	1.15	0.861	Pass
NVNT	ANT1	3-DH1	2402.00	2401.849	2402.857	1.01	0.807	Pass
NVNT	ANT1	3-DH1	2441.00	2440.867	2441.851	0.98	0.810	Pass
NVNT	ANT1	3-DH1	2480.00	2478.855	2480.031	1.18	0.847	Pass



Carrier Frequencies Separation (Hopping) NVNT ANT1 1-DH1 Hopping




Carrier Frequencies Separation (Hopping) NVNT ANT1 1-DH1 Hopping





Carrier Frequencies Separation (Hopping) NVNT_ANT1 2-DH1 Hopping



Carrier Frequencies Separation (Hopping) NVNT_ANT1 2-DH1 Hopping






Carrier Frequencies Separation (Hopping) NVNT_ANT1 3-DH1 Hopping



Carrier Frequencies Separation (Hopping) NVNT_ANT1 3-DH1 Hopping









5. Time of Occupancy (Dwell Time)


5.1 Ant1


5.1.1 Test Result


Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	1-DH1	0.378	319.00	120.582	0.40	Pass
NVNT	ANT1	1-DH3	1.634	166.00	271.244	0.40	Pass
NVNT	ANT1	1-DH5	2.881	100.00	288.100	0.40	Pass
NVNT	ANT1	2-DH1	0.388	315.00	122.220	0.40	Pass
NVNT	ANT1	2-DH3	1.639	151.00	247.489	0.40	Pass
NVNT	ANT1	2-DH5	2.887	96.00	277.152	0.40	Pass
NVNT	ANT1	3-DH1	0.388	318.00	123.384	0.40	Pass
NVNT	ANT1	3-DH3	1.638	170.00	278.460	0.40	Pass
NVNT	ANT1	3-DH5	2.889	96.00	277.344	0.40	Pass























6. Unwanted Emissions In Non-restricted Frequency Bands

6.1 Spurious Emissions


6.1.1 Test Result

Condition	Antenna	Modulation	TX Mode	Spurious MAX.Value(dBm)	Limit	Result
NVNT	ANT1	1-DH1	2402.00	-44.066	-18.873	Pass
NVNT	ANT1	1-DH1	2441.00	-44.859	-18.942	Pass
NVNT	ANT1	1-DH1	2480.00	-44.250	-19.350	Pass
NVNT	ANT1	2-DH1	2402.00	-45.913	-18.817	Pass
NVNT	ANT1	2-DH1	2441.00	-43.757	-18.909	Pass
NVNT	ANT1	2-DH1	2480.00	-45.954	-19.363	Pass
NVNT	ANT1	3-DH1	2402.00	-43.949	-18.818	Pass
NVNT	ANT1	3-DH1	2441.00	-44.795	-18.916	Pass
NVNT	ANT1	3-DH1	2480.00	-46.211	-19.355	Pass


1 Reference Level NVNT_ANT1_1-DH1_2402




2 Spurious Emissions NVNT_ANT1_1-DH1_2402




1 Reference Level NVNT_ANT1_1-DH1_2441




2 Spurious Emissions NVNT_ANT1_1-DH1_2441



1 Reference Level NVNT_ANT1_1-DH1_2480




2 Spurious Emissions NVNT_ANT1_1-DH1_2480



1 Reference Level NVNT ANT1 2-DH1 2402




2 Spurious Emissions NVNT ANT1 2-DH1 2402




1 Reference Level NVNT ANT1 2-DH1 2441




2 Spurious Emissions NVNT ANT1 2-DH1 2441



1 Reference Level NVNT ANT1 2-DH1 2480




2 Spurious Emissions NVNT ANT1 2-DH1 2480



1 Reference Level NVNT_ANT1_3-DH1_2402




2 Spurious Emissions NVNT_ANT1_3-DH1_2402



1 Reference Level NVNT_ANT1_3-DH1_2441




2 Spurious Emissions NVNT_ANT1_3-DH1_2441



1 Reference Level NVNT_ANT1_3-DH1_2480



2 Spurious Emissions NVNT_ANT1_3-DH1_2480



6.2 Bandedge


6.2.1 Test Result

Condition	Antenna	Modulation	TX Mode	Bandedge MAX.Value	Limit	Result
NVNT	ANT1	1-DH1	2402.00	-51.086	-18.873	Pass
NVNT	ANT1	1-DH1	Hopping_LCH	-55.024	-18.506	Pass
NVNT	ANT1	1-DH1	2480.00	-52.665	-19.350	Pass
NVNT	ANT1	1-DH1	Hopping_HCH	-48.858	-18.953	Pass
NVNT	ANT1	2-DH1	2402.00	-50.247	-18.817	Pass
NVNT	ANT1	2-DH1	Hopping_LCH	-52.600	-18.463	Pass
NVNT	ANT1	2-DH1	2480.00	-54.837	-19.363	Pass
NVNT	ANT1	2-DH1	Hopping_HCH	-48.750	-18.999	Pass
NVNT	ANT1	3-DH1	2402.00	-52.289	-18.818	Pass
NVNT	ANT1	3-DH1	Hopping_LCH	-55.013	-18.524	Pass
NVNT	ANT1	3-DH1	2480.00	-53.860	-19.355	Pass
NVNT	ANT1	3-DH1	Hopping_HCH	-48.796	-18.843	Pass


1 Reference Level NVNT ANT1 1-DH1 2402




2 Bandedge NVNT ANT1 1-DH1 2402




1 Reference_Level_Hopping_NVNT_ANT1_1-DH1_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_1-DH1_Hopping




1 Reference Level NVNT ANT1 1-DH1 2480




2 Bandedge NVNT ANT1 1-DH1 2480



1 Reference_Level_Hopping_NVNT_ANT1_1-DH1_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_1-DH1_Hopping




1 Reference Level NVNT ANT1 2-DH1 2402




2 Bandedge NVNT ANT1 2-DH1 2402




1 Reference_Level_Hopping_NVNT_ANT1_2-DH1_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_2-DH1_Hopping




1 Reference Level NVNT ANT1 2-DH1 2480



2 Bandedge NVNT ANT1 2-DH1 2480



1 Reference_Level_Hopping_NVNT_ANT1_2-DH1_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_2-DH1_Hopping




1 Reference Level NVNT ANT1 3-DH1 2402




2 Bandedge NVNT ANT1 3-DH1 2402



1 Reference_Level_Hopping_NVNT_ANT1_3-DH1_Hopping




2 Band_Edge_(Hopping)_NVNT_ANT1_3-DH1_Hopping




1 Reference Level NVNT ANT1 3-DH1 2480




2 Bandedge NVNT ANT1 3-DH1 2480



1 Reference_Level_Hopping_NVNT_ANT1_3-DH1_Hopping



2 Band_Edge_(Hopping)_NVNT_ANT1_3-DH1_Hopping





Test Report Number: BTF230628R01101



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

-- END OF REPORT --