



Antenna Specification

Manufacture: TUYA

Product Name: T3AI-V Antenna

Antenna Type: PCB

Test Date: 2025.12.2

Tested by: Zhang Yinhua

Approved by: Licco



Content

1.General Description	1
2.Test Configurations	2
2.1 Test Environment	2
2.2 Test Equipment	2
2.3 Test Principle.....	2
3.Test Results	3
3.1 Gain and Efficiency.....	3
3.2 Radiation Pattern	4
4.Antenna Dimensions	6
5.EUT Photo.....	6
6.Test Setup Photo	7



1.General Description

Manufacturer	Hangzhou Tuya Information Technology Co.,Ltd
Address	Room 301, Building 1, Huace Center, Xihu District, Hangzhou City, Zhejiang Province, China
Test Location	Room 106, Building 3, Letong Science Park, No. 500, Qiuyi Road, Binjiang District, Hangzhou
Product Name	T3AI-V Antenna
Product model	T3AI-V
Antenna Type	PCB Antenna
Test Items	Gain; Efficiency; Radiation Pattern
Test Frequency	2400-2500MHz
Test Standard	ANSI/IEEE Std 149-1979

2.Test Configurations


2.1 Test Environment

Temperature (°C)	25
Humidity (%RH)	60
Atmospheric Pressure (kPa)	100.5

2.2 Test Equipment

Test System	TEM 24 Multi-probe Microwave Chamber
Test Instrument	Agilent E5071B

2.3 Test Principle






3.Test Results

3.1 Gain and Efficiency


Frequency (MHz)	Peak Gain (dBi)	Efficiency (%)
2400	1.78	35.32
2410	1.54	39.36
2420	2.34	44.46
2430	1.89	42.17
2440	1.82	39.26
2450	1.2	38.64
2460	2	42.07
2470	2.27	40.18
2480	2.56	40.27
2490	1.76	35.97
2500	2.44	38.11

3.2 Radiation Pattern


Phi 0 2D




Phi 90 2D




Theta 90 2D




2400MHz 3D




2450MHz 3D



2500MHz 3D



4. Antenna Dimensions



单位: mm

5. EUT Photo

6.Test Setup Photo

