

RF Exposure Evaluation Report

APPLICANT : Hangzhou Tuya Information Technology Co., Ltd
EQUIPMENT : Wi-Fi and Bluetooth Module
MODEL NAME : WR11-2S
FCC ID : 2ANDL-WR112S
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Jun. 13, 2025 and completed on Jun. 13, 2025. We, Sporton International Inc. (Kunshan), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	7
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	8
5.1. Standalone Power Density Calculation	8

**Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA542204	Rev. 01	Initial issue of report.	Jun. 20, 2025



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Hangzhou Tuya Information Technology Co., Ltd
Address	Room 301,Building 1,Huace Center,Xihu District,Hangzhou City,Zhejiang Province, China

Manufacturer	
Company Name	Hangzhou Tuya Information Technology Co., Ltd
Address	Room 301,Building 1,Huace Center,Xihu District,Hangzhou City,Zhejiang Province, China

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Wi-Fi and Bluetooth Module
Model Name	WR11-2S
FCC ID	2ANDL-WR112S
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth LE
Antenna Gain	WLAN2.4GHz/Bluetooth: 0.95 dBi WLAN5.2GHz: 0.70 dBi WLAN5.3GHz: -0.25 dBi WLAN5.5GHz: -0.82 dBi WLAN5.8GHz: -0.44 dBi
Antenna Type	Bluetooth: Onboard PCB Antenna WLAN: Onboard PCB Antenna
HW Version	V1.0.1
SW Version	V3.5.0
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

**3. Maximum RF average output tune up power among production units****<2.4GHz WLAN >**

	Mode	Maximum Average Power (dBm)
2.4GHz	802.11b	18.00
	802.11g	20.00
	802.11n-HT20	20.00
	802.11n-HT40	20.00

<Bluetooth>

	Mode	Maximum Average power(dBm)
Bluetooth	LE	9.00

<5GHz WLAN >

	Mode	Maximum Average Power (dBm)
5.2GHz	802.11a	18.00
	802.11n-HT20	20.00
	802.11n-HT40	20.00
5.3GHz	802.11a	18.00
	802.11n-HT20	18.00
	802.11n-HT40	20.00
5.5GHz	802.11a	20.00
	802.11n-HT20	20.00
	802.11n-HT40	20.00
5.8GHz	802.11a	20.00
	802.11n-HT20	20.00
	802.11n-HT40	20.00

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
Bluetooth	2402.0	0.95	9.00	9.950	9.886	0.002	1.000
2.4GHz WLAN	2412.0	0.95	20.00	20.950	124.451	0.025	1.000
5.2GHz WLAN	5180.0	0.70	20.00	20.700	117.490	0.023	1.000
5.3GHz WLAN	5260.0	-0.25	20.00	19.750	94.406	0.019	1.000
5.5GHz WLAN	5500.0	-0.82	20.00	19.180	82.794	0.016	1.000
5.8GHz WLAN	5745.0	-0.44	20.00	19.560	90.365	0.018	1.000

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, WLAN 2.4GHz and Bluetooth cannot transmit simultaneously.
4. According to the EUT characteristic, WLAN 5GHz and Bluetooth cannot transmit simultaneously.
5. According to the EUT characteristic, WLAN 2.4GHz and WLAN 5GHz cannot transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----