

FCC TEST REPORT

Report No.: ARFR-19SE2161VTSHPB-2

Test Model: SC101-WA2,SC101-WB2

Received: Sept.23, 2019

ISSUED: Nov.04, 2019

Applicant: Hangzhou Tuya Information Technology Co., Ltd

Address: Room701, Building3, More Center,No.87 GuDun Road, Hangzhou,
Zhejiang, China

Issued By: BUREAU VERITAS ADT (Shanghai) Corporation

Lab Location: No. 829, Xinzhuan Road, Shanghai, P.R.China (201612)

This test report consists of 22 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA, CNAS, or any government agency. The test results in the report only apply to the tested item. The test results in this report are traceable to the national or international standards.

Contents

1. TEST PROGRAM.....	3
2. Summary of Test Procedure and Test Results	4
3. Test Configuration of Equipment under Test	5
3.1 Manufacturer information.....	5
3.2 Feature of Equipment under Test.....	5
3.3 Description of support units	5
3.4 Measurement Uncertainty	6
4 Test of Conducted Emission	7
4.1 Test Limit	7
4.2 Test Procedures	8
4.3 Typical Test Setup	8
4.4 Measurement Equipment	9
4.5 Test Result and Data	10
4.6 Test Photographs	12
5 Test of Radiated Emission	13
5.1 Test Limit	13
5.2 Test Procedures	14
5.3 Typical Test Setup	14
5.4 Measurement Equipment	15
5.5 Test Result and Data (30MHz ~ 1GHz)	16
5.6 Test Result and Data (1GHz ~ 18GHz)	18
5.7 Test Photographs (30MHz ~ 1000MHz)	20
5.8 Test Photographs (1000MHz ~ 18000MHz)	21
6 Photographs of EUT	22

1. TEST PROGRAM

PRODUCT: Smart Camera
TEST MODEL: SC101-WA2, SC101-WB2
SERIES MODEL: --
APPLICANT: Hangzhou Tuya Information Technology Co., Ltd
TESTED: Sept.24 to Oct.16, 2019
STANDARDS: 47 CFR FCC Part15, Subpart B, Class B
ANSI C63.4:2014

We, BUREAU VERITAS ADT (Shanghai) Corporation, declare that the equipment above has been tested and found compliance with the requirement limits of applicable standards. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate under the standards herein specified.

PREPARED BY : Will Yan, **DATE:** Nov.04, 2019
Will YAN

Project Engineer

APPROVED BY : Daniel Sun, **DATE:** Nov.04, 2019
Daniel Sun
RF Supervisor



2. Summary of Test Procedure and Test Results

EMISSION(47 CFR FCC Part15, Subpart B)		
Test Item	Normative References	Test Result
Conducted Emission	47 CFR FCC Part15, Subpart B 15.107	Meets the Class B requirements
Radiated Emission	47 CFR FCC Part15, Subpart B 15.109	Meets the Class B requirements

Special Comment: All tests were performed on 120Vac 60Hz.



BUREAU
VERITAS

3. Test Configuration of Equipment under Test

3.1 Manufacturer information

Manufacturer : Hangzhou Tuya Information Technology Co., Ltd

Address : Room701, Building3, More Center, No.87 GuDun Road, Hangzhou, Zhejiang,
China

3.2 Feature of Equipment under Test

Product Name:	Smart Camera
Test Model:	SC101-WA2, SC101-WB2
Series Model:	--
Model Discrepancy:	--
EUT Power Rating:	5VDC/1A with adaptor 100-240Vac~, 50/60Hz

Note: Please refer to user manual.

3.3 Description of support units

NO.	PRODUCT	BRAND	MODEL NO.
1	AC adapter	--	KA1517-0502000USU
2	Mobile Phone	Vivo	--
3	Cable	--	--

3.4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

This listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement		Value
Conducted emissions		2.55 dB
Radiated emissions	30 MHz ~ 1GHz	3.22 dB
	Above 1GHz	2.89 dB

4 Test of Conducted Emission

4.1 Test Limit

TEST STANDARD:

CFR 47 FCC Part 15, Subpart B (Section: 15.107)

FREQUENCY (MHz)	Class A (dB μ V)		Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- NOTES:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.4 Measurement Equipment

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	E1R1001	Mar.04, 2020
LISN ROHDE & SCHWARZ	ENV216	E1L1011	Jul.17, 2020
Software ADT	ADT_Cond_V7.3.0	N/A	N/A



**BUREAU
VERITAS**

4.5 Test Result and Data

a. Conducted Emission Test Data

Phase : LINE

Location: Conduction 1

Date: 9/26/2019


Time: 7:50:42 PM

Phase L1

Temperatuer (C): 22

Humidity (%): 48

Approved by:



No.	Frequency	Corr. Factor	Reading dBuV		Emission dBuV		Limit dBuV		Margins dB		Notes
	MHz	dB	QP	AV	QP	AV	QP	AV	QP	AV	
+1	0.46671	9.72	32.37	28.81	42.09	38.53	56.57	46.57	-14.48	-8.04	
2	0.77951	9.59	29.22	21.68	38.81	31.27	56.00	46.00	-17.19	-14.73	
3	0.89681	9.59	27.84	20.26	37.43	29.85	56.00	46.00	-18.57	-16.15	
4	1.21896	9.63	28.44	20.90	38.07	30.53	56.00	46.00	-17.93	-15.47	
5	2.56791	9.82	24.41	16.09	34.23	25.91	56.00	46.00	-21.77	-20.09	
6	8.51502	10.28	15.58	7.60	25.86	17.88	60.00	50.00	-34.14	-32.12	

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



**BUREAU
VERITAS**

Phase : NEUTRAL

Location: Conduction 1

Date: 9/26/2019


Time: 7:54:24 PM

Phase N

Temperatuer (C): 22

Humidity (%): 48

Approved by:



	Frequency	Corr. Factor	Reading dBuV		Emission dBuV		Limit dBuV		Margins dB		Notes
No.	MHz	dB	QP	AV	QP	AV	QP	AV	QP	AV	
1	0.16955	9.83	26.98	11.65	36.81	21.48	64.98	54.98	-28.17	-33.50	
+2	0.45107	9.85	31.62	22.64	41.47	32.49	56.86	46.86	-15.38	-14.36	
3	0.88508	9.89	22.72	12.62	32.61	22.51	56.00	46.00	-23.39	-23.49	
4	1.25806	9.90	20.34	10.16	30.24	20.06	56.00	46.00	-25.76	-25.94	
5	2.26684	9.96	19.53	10.94	29.49	20.90	56.00	46.00	-26.51	-25.10	
6	3.22870	10.00	18.25	9.03	28.25	19.03	56.00	46.00	-27.75	-26.97	

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



**BUREAU
VERITAS**

4.6 Test Photographs



5 Test of Radiated Emission

5.1 Test Limit

TEST STANDARD:

CFR 47 FCC Part 15, Subpart B (Section: 15.109)

FOR FREQUENCY BELOW 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)		Class B (at 3m)	
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$
30 – 88	90	39.1	100	40.0
88 – 216	150	43.5	150	43.5
216 – 960	210	46.4	200	46.0
960 – 1000	300	49.5	500	54.0

LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A ($\text{dB}\mu\text{V/m}$) (at 3m)		Class B ($\text{dB}\mu\text{V/m}$) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80.0	60.0	74.0	54.0

- Note:** (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level ($\text{dB}\mu\text{V/m}$) = $20 \log$ Emission level ($\mu\text{V/m}$).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.


5.4 Measurement Equipment

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
EMI Test Spectrum ROHDE & SCHWARZ	ESR7	E1R1005	Dec.03, 2019
Spectrum Analyzer Keysight	N9030B	E1S1003	Jul.22, 2020
Broad-Band Antenna Schwarzbeck	VULB9168	E1A1012	Aug.25, 2020
Double Riaged Vroadband Horn Antenna Schwarzbeck	BBHA9120D	E1A1017	Jan.26, 2020
Preamplifier Agilent	8447D	E1A2001	Oct.13, 2020
Preamplifier Agilent	EMC051845SE	E1A2009	Jul.18, 2020

5.5 Test Result and Data (30MHz ~ 1GHz)

Position: Horizontal

Test Graph



NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	32.71	30.26	-10.37	19.89	40.00	20.11	100	195	Horizontal
2	83.73	39.23	-14.04	25.19	40.00	14.81	100	36	Horizontal
3	101.5	31.16	-13.24	17.92	43.50	25.58	100	330	Horizontal
4	149.8	29.27	-9.31	19.96	43.50	23.54	200	173	Horizontal
5	227.2	30.3	-11.22	19.08	46.50	27.42	100	98	Horizontal
6	405.0	31.32	-7.74	23.58	46.50	22.92	100	223	Horizontal


REMARKS:

1. Q.P. is abbreviation of quasi-peak individually.
2. The emission levels of other frequencies were very low against the limit.
3. QP Margin value = QP Limit value – QP value.
4. Factor = Antenna Factor + Amplifier Factor + Cable loss.
5. QP value = Factor + Reading Value.



Position: Vertical

Test Graph



NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	30.97	39.1	-10.59	28.51	40.00	11.49	100	190	Vertical
2	46.87	33.09	-9.63	23.46	40.00	16.54	100	121	Vertical
3	61.23	36.49	-10.75	25.74	40.00	14.26	100	340	Vertical
4	82.76	41.62	-13.96	27.66	40.00	12.34	200	277	Vertical
5	119.0	37.39	-11.75	25.64	43.50	17.86	100	187	Vertical
6	153.9	38.75	-9.15	29.60	43.50	13.90	100	105	Vertical

REMARKS:


1. Q.P. is abbreviation of quasi-peak individually.
2. The emission levels of other frequencies were very low against the limit.
3. QP Margin value = QP Limit value – QP value
4. Factor = Antenna Factor + Amplifier Factor + Cable loss
5. QP value = Factor + Reading Value.



5.6 Test Result and Data (1GHz ~ 18GHz)

Position: Horizontal

Test Graph



★ AV Detector

NO.	Freq. [MHz]	Reading [dB μV/m]	Factor [dB]	Level [dB μV/m]	Limit [dB μV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1561.	45.41	-17.76	27.65	54.00	26.35	100	59	Horizontal
2	1573.	51.23	-17.73	33.50	74.00	40.50	100	184	Horizontal
3	2410.	52.58	-15.92	36.66	74.00	37.34	100	262	Horizontal
4	2414.	45.91	-15.91	30.00	54.00	24.00	100	97	Horizontal
5	3878.	50.03	-11.83	38.20	74.00	35.80	100	339	Horizontal
6	3929.	43.76	-11.71	32.05	54.00	21.95	100	184	Horizontal
7	5713.	48.95	-8.45	40.50	74.00	33.50	100	301	Horizontal
8	5906.	42.46	-8.34	34.12	54.00	19.88	100	301	Horizontal
9	7866.	47.88	-3.16	44.72	74.00	29.28	100	301	Horizontal
10	7915.	41.15	-3.08	38.07	54.00	15.93	100	262	Horizontal
11	10924	45.54	1.20	46.74	74.00	27.26	100	184	Horizontal
12	11037	38.58	1.44	40.02	54.00	13.98	100	262	Horizontal


REMARKS:

1. The emission levels of other frequencies were very low against the limit.
2. Margin = Limit –Level



Position: Vertical

Test Graph




★ AV Detector

NO.	Freq. [MHz]	Reading [dB μV/m]	Factor [dB]	Level [dB μV/m]	Limit [dB μV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1232.	44.82	-18.73	26.09	54.00	27.91	100	108	Vertical
2	1235.	51.09	-18.72	32.37	74.00	41.63	100	185	Vertical
3	1932.	50.18	-16.93	33.25	74.00	40.75	100	185	Vertical
4	1950.	44.84	-16.89	27.95	54.00	26.05	100	340	Vertical
5	3209.	43.76	-13.73	30.03	54.00	23.97	100	108	Vertical
6	3225.	48.91	-13.68	35.23	74.00	38.77	100	224	Vertical
7	5123.	47.86	-9.05	38.81	74.00	35.19	100	108	Vertical
8	5147.	42.41	-9.03	33.38	54.00	20.62	100	108	Vertical
9	7682.	47.69	-3.49	44.20	74.00	29.80	100	340	Vertical
10	7730.	41.07	-3.40	37.67	54.00	16.33	100	262	Vertical
11	10813	44.56	0.93	45.49	74.00	28.51	100	69	Vertical
12	10919	39.39	1.19	40.58	54.00	13.42	100	108	Vertical

REMARKS:

1. The emission levels of other frequencies were very low against the limit.
2. Margin = Limit –Level


5.7 Test Photographs (30MHz ~ 1000MHz)





**BUREAU
VERITAS**

5.8 Test Photographs (1000MHz ~ 18000MHz)



6 Photographs of EUT



--- END ---