

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 1 of 159

TEST REPORT

Application No.: SZCR2511004907AT
Applicant: SZ DJI Osmo Technology Co.,Ltd.
Address of Applicant: Room S11, Floor 23, Tower 1, DJI Sky City, No.55 Xianyuan Road, Xili Community, Xili Street,Nanshan District, Shenzhen, China
Manufacturer: SZ DJI Osmo Technology Co., Ltd.
Address of Manufacturer: Room S11, Floor 23, Tower 1, DJI Sky City, No. 55 Xianyuan Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China.
Equipment Under Test (EUT):
EUT Name: DJI SDR Transmission 2 Transceiver
Model No.: DST-2
Trade Mark: DJI
FCC ID: 2ANDR-DST2501
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-11-10
Date of Test: 2025-12-03 to 2025-12-10
Date of Issue: 2025-12-10

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (EMC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 2 of 159

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-12-10		Original

Authorized for issue by:				
		Donjon Huang		
		Donjon Huang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Inspection Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	7
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility	8
4.6 Deviation from Standards	8
4.7 Abnormalities from Standard Conditions	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement	11
6.1 Antenna Requirement	11
6.1.1 Test Requirement:	11
6.1.2 Conclusion	11
7 Radio Spectrum Matter Test Results	12
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	12
7.1.1 E.U.T. Operation	12
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	13
7.1.4 Measurement Procedure and Data	13
7.2 Radiated Emissions which fall in the restricted bands	16
7.2.1 E.U.T. Operation	16
7.2.2 Test Mode Description	16
7.2.3 Test Setup Diagram	17
7.2.4 Measurement Procedure and Data	18
7.3 Radiated Spurious Emissions Below 1GHz	27
7.3.1 E.U.T. Operation	27
7.3.2 Test Mode Description	27
7.3.3 Test Setup Diagram	28
7.3.4 Measurement Procedure and Data	29
7.4 Radiated Spurious Emissions Above 1GHz	32
7.4.1 E.U.T. Operation	32
7.4.2 Test Mode Description	32
7.4.3 Test Setup Diagram	32
7.4.4 Measurement Procedure and Data	33
7.5 Conducted Peak Output Power	37
7.5.1 E.U.T. Operation	37



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 5 of 159

7.5.2	Test Mode Description	37
7.5.3	Test Setup Diagram	38
7.5.4	Measurement Procedure and Data.....	38
7.6	Minimum 6dB Bandwidth	39
7.6.1	E.U.T. Operation	39
7.6.2	Test Mode Description	39
7.6.3	Test Setup Diagram	39
7.6.4	Measurement Procedure and Data.....	39
7.7	Power Spectrum Density	40
7.7.1	E.U.T. Operation	40
7.7.2	Test Mode Description	40
7.7.3	Test Setup Diagram	40
7.7.4	Measurement Procedure and Data.....	40
7.8	Conducted Band Edges Measurement	41
7.8.1	E.U.T. Operation	41
7.8.2	Test Mode Description	41
7.8.3	Test Setup Diagram	41
7.8.4	Measurement Procedure and Data.....	42
7.9	Conducted Spurious Emissions	43
7.9.1	E.U.T. Operation	43
7.9.2	Test Mode Description	43
7.9.3	Test Setup Diagram	43
7.9.4	Measurement Procedure and Data.....	44
8	Test Setup Photo	45
9	EUT Constructional Details (EUT Photos)	45
10	Appendix.....	46



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	DC 5V from AC/DC adapter
Cable Loss (for RF conducted test):	1.5dB
Operation Frequency:	5MHz 5M-1-0: 2404.5MHz-2469.5MHz (14 Channel) 10M-2-0: 2405.26MHz-2462.26MHz (58 Channel) 10M-2-1: 2411.74MHz-2468.74MHz (58 Channel) 10MHz 40M-3-0: 2409.06MHz-2439.06MHz (31 Channel) 40M-3-1: 2422.5MHz-2452.5MHz (31 Channel) 40M-3-2: 2435.94MHz-2465.94MHz (31 Channel) 40M-4-0: 2407.86MHz-2437.86MHz (31 Channel) 40M-4-1: 2417.61MHz-2447.61MHz (31 Channel) 40M-4-2: 2427.39MHz-2457.39MHz (31 Channel) 40M-4-3: 2437.14MHz-2467.14MHz (31 Channel) 20MHz 20M-1-0: 2412.5MHz-2462.5MHz (51 Channel) 40MHz 40M-1-0: 2422.5MHz-2452.5MHz (31 Channel)
Modulation Type:	OFDM
Channel Spacing:	5MHz 5M-1-0: 5MHz 10M-2-0: 1MHz 10M-2-1: 1MHz 10MHz 40M-3-0: 1M 40M-3-1: 1M 40M-3-2: 1M 40M-4-0: 1M 40M-4-1: 1M 40M-4-2: 1M 40M-4-3: 1M 20MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

	20M-1-0: 1M 40MHz 40M-1-0: 1M
Antenna Type:	PIFA
Antenna Gain:	Ant0/2:1.5dBi; Ant1/3:2.5dBi
Cable Loss (for RF conducted test):	0.9dB

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	DJI	QC24-CN	N/A

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.2\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectrum Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-01-08	2026-01-07
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 10 of 159

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2025-03-04	2026-03-03
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna are following:

Band	Antenna Gain(dBi)			
	ANT0	ANT1	ANT2	ANT3
2.4G SDR	1.5	2.5	1.5	2.5

Antenna combination (MIMO mode)	Directional Gain (dBi)
	2.4G SDR
ANT0 & ANT1	5.51
ANT0 & ANT3	5.51
ANT2 & ANT1	5.51
ANT2 & ANT3	5.51

Antenna location: Refer to internal photos

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Test Engineer: Wade Li

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.4 °C

Humidity: 42.5 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Pre-scan	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Pre-scan	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode



7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark : Level=Read Level+ Cable Loss+ LISN Factor



Test Mode: 01; Line: Live line



Site : Shielding Room
Condition: Line
Job No. : 04907AT/04908AT
Test mode: 01

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1516	0.06	10.19	15.11	25.36	65.91	-40.55	QP
2	0.1516	0.06	10.19	3.97	14.22	55.91	-41.69	Average
3 *	0.8483	0.11	9.61	15.41	25.13	56.00	-30.87	QP
4 *	0.8483	0.11	9.61	13.84	23.56	46.00	-22.44	Average
5	0.9531	0.11	9.59	14.69	24.39	56.00	-31.61	QP
6	0.9531	0.11	9.59	9.08	18.78	46.00	-27.22	Average
7	1.6981	0.12	9.58	9.12	18.82	56.00	-37.18	QP
8	1.6981	0.12	9.58	5.95	15.65	46.00	-30.35	Average
9	4.6469	0.14	9.66	9.19	18.99	56.00	-37.01	QP
10	4.6469	0.14	9.66	0.75	10.55	46.00	-35.45	Average
11	8.3671	0.15	9.69	8.98	18.82	60.00	-41.18	QP
12	8.3671	0.15	9.69	3.98	13.82	50.00	-36.18	Average




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 15 of 159

Test Mode: 01; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 04907AT/04908AT
Test mode: 01

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1633	0.06	10.13	12.83	23.02	65.30	-42.28	QP
2	0.1633	0.06	10.13	5.16	15.35	55.30	-39.95	Average
3 *	0.4637	0.09	9.72	17.05	26.86	56.63	-29.77	QP
4 *	0.4637	0.09	9.72	12.88	22.69	46.63	-23.94	Average
5	0.9531	0.11	9.55	10.60	20.26	56.00	-35.74	QP
6	0.9531	0.11	9.55	6.52	16.18	46.00	-29.82	Average
7	1.6981	0.12	9.55	9.44	19.11	56.00	-36.89	QP
8	1.6981	0.12	9.55	5.89	15.56	46.00	-30.44	Average
9	4.6469	0.14	9.56	9.51	19.21	56.00	-36.79	QP
10	4.6469	0.14	9.56	1.84	11.54	46.00	-34.46	Average
11	22.6551	0.22	10.31	8.20	18.73	60.00	-41.27	QP
12	22.6551	0.22	10.31	2.66	13.19	50.00	-36.81	Average



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5
 Measurement Distance: 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_ Keep the EUT in transmitting mode
Final test	02	TX mode (2.4G SDR_10MHz)_ Keep the EUT in transmitting mode
Final test	03	TX mode (2.4G SDR_20MHz)_ Keep the EUT in transmitting mode
Final test	04	TX mode (2.4G SDR_40MHz)_ Keep the EUT in transmitting mode



7.2.3 Test Setup Diagram



30MHz-1GHz

Above 1GHz



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

k. All modes of all antenna combinations have been pre-tested, and the report only reflects data from the co-transmitting antenna with the worst performance.




2.4G SDR_5M_TX_CH_L_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2404.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	3.57	29.10	0.00	33.37	66.04	74.00	-7.96	Peak
2	2390.000	3.57	29.10	0.00	32.56	65.23	74.00	-8.77	Peak
3 p	2404.500	3.58	29.08	0.00	88.49	121.15	74.00	47.15	Peak


2.4G SDR_5M_TX_CH_L_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2404.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	3.57	29.10	0.00	17.98	50.65	54.00	-3.35	Average
2	2390.000	3.57	29.10	0.00	17.98	50.65	54.00	-3.35	Average
3 q	2404.500	3.58	29.08	0.00	79.02	111.62	54.00	57.62	Average


2.4G SDR_5M_TX_CH_L_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2404.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	3.57	29.10	0.00	33.19	65.86	74.00	-8.14	Peak
2	2390.000	3.57	29.10	0.00	33.19	65.86	74.00	-8.14	Peak
3 p	2404.500	3.58	29.08	0.00	86.28	118.94	74.00	44.94	Peak


2.4G SDR_5M_TX_CH_L_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2404.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	3.57	29.10	0.00	18.14	50.81	54.00	-3.19	Average
2	2390.000	3.57	29.10	0.00	18.14	50.81	54.00	-3.19	Average
3 q	2404.500	3.58	29.08	0.00	77.96	110.62	54.00	56.62	Average


2.4G SDR_5M_TX_CH_H_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2469.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2469.500	3.60	28.90	0.00	88.90	121.40	74.00	47.40	Peak
2	2483.500	3.60	28.90	0.00	28.65	61.15	74.00	-12.85	Peak
3	2496.568	3.61	28.90	0.00	29.87	62.38	74.00	-11.62	Peak


2.4G SDR_5M_TX_CH_H_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2469.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2469.500	3.60	28.90	0.00	79.84	112.34	54.00	58.34	Average
2	2483.500	3.60	28.90	0.00	16.80	49.30	54.00	-4.70	Average
3	2497.728	3.61	28.90	0.00	17.29	49.80	54.00	-4.20	Average


2.4G SDR_5M_TX_CH_H_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2469.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2469.500	3.60	28.90	0.00	85.13	117.63	74.00	43.63	Peak
2	2483.500	3.60	28.90	0.00	28.56	61.06	74.00	-12.94	Peak
3	2488.109	3.61	28.90	0.00	30.14	62.65	74.00	-11.35	Peak

2.4G SDR_5M_TX_CH_H_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2469.5 Band edge
: 2.4G SDR 5M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2469.500	3.60	28.90	0.00	76.14	108.64	54.00	54.64	Average
2	2483.500	3.60	28.90	0.00	16.96	49.46	54.00	-4.54	Average
3	2485.597	3.61	28.90	0.00	17.18	49.69	54.00	-4.31	Average




2.4G SDR_10M_TX_CH_L_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2407.86 Band edge
: 2.4G SDR 10M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV/m	Line	Limit	dB
1	2376.571	3.57	29.10	0.00	31.38	64.05	74.00	-9.95 Peak
2	2390.000	3.57	29.10	0.00	30.75	63.42	74.00	-10.58 Peak
3 p	2407.860	3.58	29.07	0.00	83.61	116.26	74.00	42.26 Peak


2.4G SDR_10M_TX_CH_L_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2407.86 Band edge
: 2.4G SDR 10M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV/m	Line	Limit	dB
1	2379.582	3.57	29.10	0.00	18.95	51.62	54.00	-2.38 Average
2	2390.000	3.57	29.10	0.00	17.55	50.22	54.00	-3.78 Average
3 q	2407.860	3.58	29.07	0.00	72.74	105.39	54.00	51.39 Average


2.4G SDR_10M_TX_CH_L_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2407.86 Band edge
: 2.4G SDR 10M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV/m	Line	Limit	dB
1	2380.064	3.57	29.10	0.00	32.23	64.90	74.00	-9.10 Peak
2	2390.000	3.57	29.10	0.00	29.62	62.29	74.00	-11.71 Peak
3 p	2407.860	3.58	29.07	0.00	84.06	116.71	74.00	42.71 Peak

2.4G SDR_10M_TX_CH_L_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2407.86 Band edge
: 2.4G SDR 10M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV/m	Line	Limit	dB
1	2380.426	3.57	29.10	0.00	19.54	52.21	54.00	-1.79 Average
2	2390.000	3.57	29.10	0.00	17.74	50.41	54.00	-3.59 Average
3 q	2407.860	3.58	29.07	0.00	71.77	104.42	54.00	50.42 Average




2.4G SDR_10M_TX_CH_H_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2467.14 Band edge
: 2.4G SDR 10M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 2467.140	3.60	28.90	0.00	85.98	118.48	74.00	44.48	Peak
2 2483.500	3.60	28.90	0.00	31.59	64.09	74.00	-9.91	Peak
3 2484.141	3.60	28.90	0.00	34.29	66.79	74.00	-7.21	Peak


2.4G SDR_10M_TX_CH_H_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2467.14 Band edge
: 2.4G SDR 10M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2467.140	3.60	28.90	0.00	74.21	106.71	54.00	52.71	Average
2 2483.500	3.60	28.90	0.00	18.91	51.41	54.00	-2.59	Average
3 2483.790	3.60	28.90	0.00	18.95	51.45	54.00	-2.55	Average


2.4G SDR_10M_TX_CH_H_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2467.14 Band edge
: 2.4G SDR 10M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 2467.140	3.60	28.90	0.00	87.16	119.66	74.00	45.66	Peak
2 2483.500	3.60	28.90	0.00	35.74	68.24	74.00	-5.76	Peak
3 2484.091	3.60	28.90	0.00	33.74	66.24	74.00	-7.76	Peak

2.4G SDR_10M_TX_CH_H_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2467.14 Band edge
: 2.4G SDR 10M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 2467.140	3.60	28.90	0.00	75.04	107.54	54.00	53.54	Average
2 2483.500	3.60	28.90	0.00	19.05	51.55	54.00	-2.45	Average
3 2484.141	3.60	28.90	0.00	19.23	51.73	54.00	-2.27	Average




2.4G SDR_20M_TX_CH_L_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.914	3.57	29.10	0.00	33.55	66.22	74.00	-7.78	Peak
2	2390.000	3.57	29.10	0.00	34.22	66.89	74.00	-7.11	Peak
3 p	2412.500	3.58	29.05	0.00	79.07	111.70	74.00	37.70	Peak


2.4G SDR_20M_TX_CH_L_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.914	3.57	29.10	0.00	20.06	52.73	54.00	-1.27	Average
2	2390.000	3.57	29.10	0.00	20.29	52.96	54.00	-1.04	Average
3 q	2412.500	3.58	29.05	0.00	67.85	100.48	54.00	46.48	Average


2.4G SDR_20M_TX_CH_L_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.773	3.57	29.10	0.00	33.16	65.83	74.00	-8.17	Peak
2	2390.000	3.57	29.10	0.00	32.83	65.50	74.00	-8.50	Peak
3 p	2412.500	3.58	29.05	0.00	77.17	109.80	74.00	35.80	Peak

2.4G SDR_20M_TX_CH_L_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2412.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.930	3.57	29.10	0.00	20.70	53.37	54.00	-0.63	Average
2	2390.000	3.57	29.10	0.00	20.59	53.26	54.00	-0.74	Average
3 q	2412.500	3.58	29.05	0.00	65.82	98.45	54.00	44.45	Average




2.4G SDR_20M_TX_CH_H_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.500	3.60	28.90	0.00	76.59	109.09	74.00	35.09	Peak
2	2483.500	3.60	28.90	0.00	36.22	68.72	74.00	-5.28	Peak
3	2483.837	3.60	28.90	0.00	36.68	69.18	74.00	-4.82	Peak


2.4G SDR_20M_TX_CH_H_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2462.500	3.60	28.90	0.00	65.93	98.43	54.00	44.43	Average
2	2483.500	3.60	28.90	0.00	19.56	52.06	54.00	-1.94	Average
3	2483.837	3.60	28.90	0.00	19.43	51.93	54.00	-2.07	Average


2.4G SDR_20M_TX_CH_H_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2462.500	3.60	28.90	0.00	77.17	109.67	74.00	35.67	Peak
2	2483.500	3.60	28.90	0.00	35.21	67.71	74.00	-6.29	Peak
3	2483.897	3.60	28.90	0.00	36.54	69.04	74.00	-4.96	Peak

2.4G SDR_20M_TX_CH_H_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2462.5 Band edge
: 2.4G SDR 20M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2462.500	3.60	28.90	0.00	65.49	97.99	54.00	43.99	Average
2	2483.500	3.60	28.90	0.00	19.65	52.15	54.00	-1.85	Average
3	2483.777	3.60	28.90	0.00	19.80	52.30	54.00	-1.70	Average




2.4G SDR_40M_TX_CH_L_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.912	3.57	29.10	0.00	34.67	67.34	74.00	-6.66	Peak
2	2390.000	3.57	29.10	0.00	34.37	67.04	74.00	-6.96	Peak
3 p	2422.500	3.58	29.01	0.00	72.74	105.33	74.00	31.33	Peak


2.4G SDR_40M_TX_CH_L_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.820	3.57	29.10	0.00	20.20	52.87	54.00	-1.13	Average
2	2390.000	3.57	29.10	0.00	20.02	52.69	54.00	-1.31	Average
3 q	2422.500	3.58	29.01	0.00	61.18	93.77	54.00	39.77	Average


2.4G SDR_40M_TX_CH_L_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.802	3.57	29.10	0.00	35.96	68.63	74.00	-5.37	Peak
2	2390.000	3.57	29.10	0.00	36.01	68.68	74.00	-5.32	Peak
3 p	2422.500	3.58	29.01	0.00	69.68	102.27	74.00	28.27	Peak


2.4G SDR_40M_TX_CH_L_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2422.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.820	3.57	29.10	0.00	20.54	53.21	54.00	-0.79	Average
2	2390.000	3.57	29.10	0.00	20.23	52.90	54.00	-1.10	Average
3 q	2422.500	3.58	29.01	0.00	58.70	91.29	54.00	37.29	Average


2.4G SDR_40M_TX_CH_H_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.500	3.59	28.90	0.00	72.48	104.97	74.00	30.97	Peak
2	2483.500	3.60	28.90	0.00	33.12	65.62	74.00	-8.38	Peak
3	2485.911	3.61	28.90	0.00	33.23	65.74	74.00	-8.26	Peak


2.4G SDR_40M_TX_CH_H_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2452.500	3.59	28.90	0.00	61.73	94.22	54.00	40.22	Average
2	2483.500	3.60	28.90	0.00	20.22	52.72	54.00	-1.28	Average
3	2483.865	3.60	28.90	0.00	20.24	52.74	54.00	-1.26	Average


2.4G SDR_40M_TX_CH_H_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	2452.500	3.59	28.90	0.00	72.49	104.98	74.00	30.98	Peak
2	2483.500	3.60	28.90	0.00	34.31	66.81	74.00	-7.19	Peak
3	2484.006	3.60	28.90	0.00	35.31	67.81	74.00	-6.19	Peak

2.4G SDR_40M_TX_CH_H_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2452.5 Band edge
: 2.4G SDR 40M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	2452.500	3.59	28.90	0.00	61.43	93.92	54.00	39.92	Average
2	2483.500	3.60	28.90	0.00	20.21	52.71	54.00	-1.29	Average
3	2484.993	3.61	28.90	0.00	20.68	53.19	54.00	-0.81	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, Shenzhen, China, CCC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Mason Wu

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 23.3 °C Humidity: 47.5 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Pre-scan	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Pre-scan	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.



Test Mode: 01; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL


Job No. : 04907AT/04908AT

Test Mode: 01

	Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.424	21.00	0.74	27.65	28.91	23.00	40.00	-17.00 QP
2	72.084	10.48	1.01	27.61	30.69	14.57	40.00	-25.43 QP
3	148.441	12.86	1.49	27.71	42.69	29.33	43.50	-14.17 QP
4	300.367	18.05	2.11	27.50	40.70	33.36	46.00	-12.64 QP
5 q	444.851	21.12	2.64	27.84	42.41	38.33	46.00	-7.67 QP
6	774.158	26.84	3.62	27.66	34.72	37.52	46.00	-8.48 QP



Test Mode: 01; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : 04907AT/04908AT

Test Mode: 01

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	32.067	20.24	0.76	27.65	38.47	31.82	40.00	-8.18	QP
2	63.092	11.16	0.94	27.62	40.54	25.02	40.00	-14.98	QP
3	148.441	12.86	1.49	27.71	44.33	30.97	43.50	-12.53	QP
4	366.823	20.35	2.38	27.67	38.09	33.15	46.00	-12.85	QP
5	444.851	21.12	2.64	27.84	39.45	35.37	46.00	-10.63	QP
6 q	742.259	26.27	3.53	27.73	35.93	38.00	46.00	-8.00	QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6
 Measurement Distance: 3m
 Test Engineer: Logic Wang

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 23.5 °C Humidity: 56.3 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Pre-scan	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Pre-scan	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Pre-scan	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
5. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
6. All modes of all antenna combinations have been pre-tested, and the report only reflects data from the co-transmitting antenna with the worst performance.




2.4G SDR_5M_TX_CH_L_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2404.5 RSE TX
: 2.4G SDR 5M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	dB
1	4367.058	7.10	34.54	54.26	57.29	44.67	74.00	-29.33 Peak
2	5439.885	8.09	34.68	53.69	56.65	45.73	74.00	-28.27 Peak
3	7476.006	8.42	36.05	53.15	55.28	46.60	74.00	-27.40 Peak
4	p 9613.430	10.74	37.43	53.35	68.57	63.39	74.00	-10.61 Peak
5	13059.820	10.64	38.28	53.18	55.49	51.23	74.00	-22.77 Peak
6	16793.680	10.99	42.89	52.68	56.81	58.01	74.00	-15.99 Peak


2.4G SDR_5M_TX_CH_L_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2404.5 RSE TX
: 2.4G SDR 5M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	dB
1	4859.975	7.45	34.54	54.21	46.33	34.11	54.00	-19.89 Average
2	7454.429	8.42	36.01	53.15	46.72	38.00	54.00	-16.00 Average
3	q 9613.770	10.74	37.43	53.35	55.73	50.55	54.00	-3.45 Average
4	12651.130	11.30	38.00	53.20	44.54	40.64	54.00	-13.36 Average
5	15622.990	10.88	41.12	52.10	43.99	43.89	54.00	-10.11 Average
6	17793.090	11.38	43.89	52.50	42.56	45.33	54.00	-8.67 Average


2.4G SDR_5M_TX_CH_L_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2404.5 RSE TX
: 2.4G SDR 5M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	dB
1	4485.090	7.12	34.74	54.26	56.61	44.21	74.00	-29.79 Peak
2	7898.049	8.95	36.50	53.11	55.05	47.39	74.00	-26.61 Peak
3	p 9613.430	10.74	37.43	53.35	76.88	71.70	74.00	-2.30 Peak
4	12089.760	11.63	37.79	53.20	55.84	52.06	74.00	-21.94 Peak
5	16315.230	10.95	42.00	52.15	56.69	57.49	74.00	-16.51 Peak
6	17741.740	11.35	43.84	52.53	55.67	58.33	74.00	-15.67 Peak

2.4G SDR_5M_TX_CH_L_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2404.5 RSE TX
: 2.4G SDR 5M

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Remark
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	Limit	dB
1	4790.245	7.40	34.22	54.22	46.63	34.03	54.00	-19.97 Average
2	7096.999	8.53	35.79	53.19	45.49	36.62	54.00	-17.38 Average
3	q 9613.770	10.74	37.43	53.35	57.15	51.97	54.00	-2.83 Average
4	12687.750	11.23	38.00	53.20	43.95	40.06	54.00	-13.94 Average
5	16174.370	10.93	41.77	52.00	43.53	44.23	54.00	-9.77 Average
6	17844.590	11.41	43.90	52.48	41.22	44.05	54.00	-9.95 Average




2.4G SDR_5M_TX_CH_M_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2437.26 RSE TX
Cable : 2.4G SDR 5M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5813.812	8.65	34.33	53.29	55.56	45.25	74.00	-28.75	Peak
2 8106.200	9.19	36.50	53.16	55.56	48.09	74.00	-25.91	Peak
3 p 9753.371	10.69	37.39	53.29	66.08	60.87	74.00	-13.13	Peak
4 13677.970	10.92	39.06	52.99	55.23	52.22	74.00	-21.78	Peak
5 16315.230	10.95	42.00	52.15	56.37	57.17	74.00	-16.83	Peak
6 17793.090	11.38	43.89	52.50	55.65	58.42	74.00	-15.58	Peak


2.4G SDR_5M_TX_CH_M_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2437.26 RSE TX
Cable : 2.4G SDR 5M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5949.811	8.86	34.70	53.15	45.71	36.12	54.00	-17.88	Average
2 8036.214	9.12	36.40	53.12	46.78	39.18	54.00	-14.82	Average
3 q 9753.841	10.69	37.39	53.29	55.22	50.01	54.00	-3.99	Average
4 12724.470	11.15	38.10	53.20	44.57	40.62	54.00	-13.38	Average
5 15668.210	10.89	41.17	52.06	42.95	42.95	54.00	-11.05	Average
6 17793.090	11.38	43.89	52.50	41.84	44.61	54.00	-9.39	Average


2.4G SDR_5M_TX_CH_M_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2437.26 RSE TX
Cable : 2.4G SDR 5M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5583.251	8.29	34.70	53.53	56.96	46.42	74.00	-27.58	Peak
2 7966.832	9.04	36.40	53.10	55.60	47.94	74.00	-26.06	Peak
3 p 9753.371	10.69	37.39	53.29	74.24	69.03	74.00	-4.97	Peak
4 13442.810	10.86	38.80	53.06	55.21	51.81	74.00	-22.19	Peak
5 16315.230	10.95	42.00	52.15	56.37	57.17	74.00	-16.83	Peak
6 17639.470	11.28	43.68	52.58	55.78	58.16	74.00	-15.84	Peak

2.4G SDR_5M_TX_CH_M_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2437.26 RSE TX
Cable : 2.4G SDR 5M


Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4874.043	7.47	34.60	54.21	47.69	35.55	54.00	-18.45	Average
2 7497.646	8.41	36.10	53.15	46.47	37.83	54.00	-16.17	Average
3 q 9753.841	10.69	37.39	53.29	56.45	51.24	54.00	-2.76	Average
4 13957.530	10.97	39.62	52.91	44.23	41.91	54.00	-12.09	Average
5 16315.230	10.95	42.00	52.15	43.49	44.29	54.00	-9.71	Average
6 17741.740	11.35	43.84	52.53	42.05	44.71	54.00	-9.29	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


2.4G SDR_5M_TX_CH_H_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2469.5 RSE TX
Cable : 2.4G SDR 5M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4944.993	7.52	34.61	54.20	56.79	44.72	74.00	-29.28	Peak
2 7117.542	8.52	35.80	53.19	55.01	46.14	74.00	-27.86	Peak
3 p 9866.789	10.66	37.23	53.25	67.50	62.14	74.00	-11.86	Peak
4 12361.950	11.62	37.90	53.20	58.56	54.88	74.00	-19.12	Peak
5 16842.290	10.99	43.03	52.73	56.81	58.10	74.00	-15.90	Peak
6 17793.090	11.38	43.89	52.50	55.55	58.32	74.00	-15.68	Peak


2.4G SDR_5M_TX_CH_H_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 04907AT\04908AT
Mode : 2469.5 RSE TX
Cable : 2.4G SDR 5M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4930.721	7.51	34.64	54.21	47.86	35.80	54.00	-18.20	Average
2 7920.911	8.98	36.46	53.11	45.91	38.24	54.00	-15.76	Average
3 q 9866.666	10.66	37.23	53.25	57.15	51.79	54.00	-2.21	Average
4 12361.840	11.62	37.90	53.20	54.17	50.49	54.00	-3.51	Average
5 15668.210	10.89	41.17	52.06	43.21	43.21	54.00	-10.79	Average
6 17793.090	11.38	43.89	52.50	42.05	44.82	54.00	-9.18	Average


2.4G SDR_5M_TX_CH_H_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2469.5 RSE TX
Cable : 2.4G SDR 5M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4944.993	7.52	34.61	54.20	57.66	45.59	74.00	-28.41	Peak
2 7411.461	8.44	35.85	53.16	56.37	47.50	74.00	-26.50	Peak
3 p 9866.789	10.66	37.23	53.25	74.76	69.40	74.00	-4.60	Peak
4 12361.950	11.62	37.90	53.20	61.91	58.23	74.00	-15.77	Peak
5 16793.680	10.99	42.89	52.68	57.10	58.30	74.00	-15.70	Peak
6 17793.090	11.38	43.89	52.50	55.13	57.90	74.00	-16.10	Peak

2.4G SDR_5M_TX_CH_H_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 04907AT\04908AT
Mode : 2469.5 RSE TX
Cable : 2.4G SDR 5M

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4930.721	7.51	34.64	54.21	47.40	35.34	54.00	-18.66	Average
2 7497.646	8.41	36.10	53.15	46.72	38.08	54.00	-15.92	Average
3 q 9866.789	10.66	37.23	53.25	56.32	50.96	54.00	-3.04	Average
4 12361.840	11.62	37.90	53.20	53.32	49.64	54.00	-4.36	Average
5 15668.210	10.89	41.17	52.06	42.84	42.84	54.00	-11.16	Average
6 17690.530	11.32	43.78	52.55	42.64	45.19	54.00	-8.81	Average



7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.1
 Test Engineer: Mingli Hu

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 26.1 °C Humidity: 65.3 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

All modes of all antenna combinations have been pre-tested, and the report only reflects data from the co-transmitting antenna with the worst performance.

Please Refer to Appendix for Details



7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2020) Section 11.8.1
 Test Engineer: Mingli Hu

Limit:
 ≥500 kHz


7.6.1 E.U.T. Operation

Operating Environment:
 Temperature: 26.1 °C Humidity: 65.3 % RH Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Note: All modes of all antenna combinations have been pre-tested, and the report only reflects data from the co-transmitting antenna with the worst performance.

Please Refer to Appendix for Details

7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
 Test Method: ANSI C63.10 (2020) Section 11.10.2
 Test Engineer: Mingli Hu

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 26.1 °C Humidity: 65.3 % RH Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Note: All modes of all antenna combinations have been pre-tested, and the report only reflects data from the co-transmitting antenna with the worst performance.

Please Refer to Appendix for Details

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Mingli Hu

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 26.1 °C Humidity: 65.3 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode

7.8.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch (Shenzhen) EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 42 of 159

7.8.4 Measurement Procedure and Data

Note: All modes of all antenna combinations have been pre-tested, and the report only reflects data from the co-transmitting antenna with the worst performance.

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn

中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.9 Conducted Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 11.11
 Test Engineer: Mingli Hu

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation


Operating Environment:

Temperature: 26.1 °C Humidity: 65.3 % RH Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	01	TX mode (2.4G SDR_5MHz)_Keep the EUT in transmitting mode
Final test	02	TX mode (2.4G SDR_10MHz)_Keep the EUT in transmitting mode
Final test	03	TX mode (2.4G SDR_20MHz)_Keep the EUT in transmitting mode
Final test	04	TX mode (2.4G SDR_40MHz)_Keep the EUT in transmitting mode

7.9.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 44 of 159

7.9.4 Measurement Procedure and Data

Note: All modes of all antenna combinations have been pre-tested, and the report only reflects data from the co-transmitting antenna with the worst performance.

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2511004907AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix – External and Internal Photos for SZCR2511004907AT



10 Appendix

Ant2&3

1. Duty Cycle

1.1 Test Result


1.1.1 Ant2

Ant2							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
5M	MIMO	2404.5	100.000	100.000	100.00	0.00	0.00
		2437.26	100.000	100.000	100.00	0.00	0.00
		2469.5	100.000	100.000	100.00	0.00	0.00
10M	MIMO	2407.86	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2467.14	100.000	100.000	100.00	0.00	0.00
20M	MIMO	2412.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2462.5	100.000	100.000	100.00	0.00	0.00
40M	MIMO	2422.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2452.5	100.000	100.000	100.00	0.00	0.00




1.2 Test Graph


1.2.1 Ant2




5M_HCH_2469.5MHz_Ant2_NTNV




10M_LCH_2407.86MHz_Ant2_NTNV




10M_MCH_2437.5MHz_Ant2_NTNV




10M_HCH_2467.14MHz_Ant2_NTNV




20M_LCH_2412.5MHz_Ant2_NTNV




20M_MCH_2437.5MHz_Ant2_NTNV




20M_HCH_2462.5MHz_Ant2_NTNV




40M_LCH_2422.5MHz_Ant2_NTNV



40M_MCH_2437.5MHz_Ant2_NTNV



40M_HCH_2452.5MHz_Ant2_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
5M	MIMO	2404.5	2	5.756	/	Pass
		2437.26	2	4.737	/	Pass
		2469.5	2	5.492	/	Pass
10M	MIMO	2407.86	2	6.981	/	Pass
		2437.5	2	10.455	/	Pass
		2467.14	2	6.953	/	Pass
20M	MIMO	2412.5	2	18.063	/	Pass
		2437.5	2	19.962	/	Pass
		2462.5	2	18.463	/	Pass
40M	MIMO	2422.5	2	36.238	/	Pass
		2437.5	2	39.051	/	Pass
		2452.5	2	36.476	/	Pass

2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
5M	MIMO	2404.5	2	4.413	≥ 0.5	Pass
		2437.26	2	4.372	≥ 0.5	Pass
		2469.5	2	4.326	≥ 0.5	Pass
10M	MIMO	2407.86	2	6.783	≥ 0.5	Pass
		2437.5	2	9.208	≥ 0.5	Pass
		2467.14	2	6.803	≥ 0.5	Pass
20M	MIMO	2412.5	2	17.948	≥ 0.5	Pass
		2437.5	2	18.095	≥ 0.5	Pass
		2462.5	2	18.219	≥ 0.5	Pass
40M	MIMO	2422.5	2	36.120	≥ 0.5	Pass
		2437.5	2	36.280	≥ 0.5	Pass
		2452.5	2	35.706	≥ 0.5	Pass

2.2 Test Graph

2.2.1 OBW




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


5M_HCH_2469.5MHz_Ant2_NTNV




10M_LCH_2407.86MHz_Ant2_NTNV




10M_MCH_2437.5MHz_Ant2_NTNV




10M_HCH_2467.14MHz_Ant2_NTNV




20M_LCH_2412.5MHz_Ant2_NTNV




20M_MCH_2437.5MHz_Ant2_NTNV




20M_HCH_2462.5MHz_Ant2_NTNV




40M_LCH_2422.5MHz_Ant2_NTNV




40M_MCH_2437.5MHz_Ant2_NTNV




40M_HCH_2452.5MHz_Ant2_NTNV




2.2.2 6dB BW




5M_HCH_2469.5MHz_Ant2_NTNV




10M_LCH_2407.86MHz_Ant2_NTNV




10M_MCH_2437.5MHz_Ant2_NTNV




10M_HCH_2467.14MHz_Ant2_NTNV




20M_LCH_2412.5MHz_Ant2_NTNV




20M_MCH_2437.5MHz_Ant2_NTNV




20M_HCH_2462.5MHz_Ant2_NTNV




40M_LCH_2422.5MHz_Ant2_NTNV



40M_MCH_2437.5MHz_Ant2_NTNV



40M_HCH_2452.5MHz_Ant2_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)				Verdict
			ANT2	ANT3	MIMO	Limit	
5M	MIMO	2404.5	22.70	22.09	25.42	<=30	Pass
		2437.26	22.53	22.18	25.37	<=30	Pass
		2469.5	23.19	22.46	25.85	<=30	Pass
10M	MIMO	2407.86	19.56	18.57	22.10	<=30	Pass
		2437.5	24.97	23.86	27.46	<=30	Pass
		2467.14	21.96	21.07	24.55	<=30	Pass
20M	MIMO	2412.5	18.68	17.35	21.08	<=30	Pass
		2437.5	25.65	24.72	28.22	<=30	Pass
		2462.5	16.63	15.11	18.95	<=30	Pass
40M	MIMO	2422.5	14.65	13.35	17.06	<=30	Pass
		2437.5	24.64	23.11	26.95	<=30	Pass
		2452.5	14.55	13.01	16.86	<=30	Pass

Note1: Antenna Gain: Ant2: 1.50dBi; Ant3: 2.50dBi;
Note2: Directional Gain: 2.5dBi

4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD


Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)				Verdict
			ANT2	ANT3	MIMO	Limit	
5M	MIMO	2404.5	2.76	1.99	5.08	<=8	Pass
		2437.26	2.30	1.85	4.66	<=8	Pass
		2469.5	3.20	2.32	5.55	<=8	Pass
10M	MIMO	2407.86	2.64	1.75	5.19	<=8	Pass
		2437.5	1.20	0.24	3.63	<=8	Pass
		2467.14	4.88	3.75	7.23	<=8	Pass
20M	MIMO	2412.5	-2.44	-3.77	-0.25	<=8	Pass
		2437.5	0.03	-1.04	2.02	<=8	Pass
		2462.5	-4.14	-5.85	-2.20	<=8	Pass
40M	MIMO	2422.5	-8.98	-10.80	-6.97	<=8	Pass
		2437.5	0.92	-0.90	2.96	<=8	Pass
		2452.5	-8.59	-10.04	-6.46	<=8	Pass

Note1: Antenna Gain: Ant2: 1.50dBi; Ant3: 2.50dBi;
Note2: Directional Gain: 2.5dBi



4.2 Test Graph


4.2.1 PSD




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


5M_LCH_2404.5MHz_MIMO_NTNV




5M_MCH_2437.26MHz_Ant2_NTNV




5M_MCH_2437.26MHz_Ant3_NTNV




5M_MCH_2437.26MHz_MIMO_NTNV




5M_HCH_2469.5MHz_Ant2_NTNV




5M_HCH_2469.5MHz_Ant3_NTNV




5M_HCH_2469.5MHz_MIMO_NTNV




10M_LCH_2407.86MHz_Ant2_NTNV




10M_LCH_2407.86MHz_Ant3_NTNV




10M_LCH_2407.86MHz_MIMO_NTNV




10M_MCH_2437.5MHz_Ant2_NTNV




10M_MCH_2437.5MHz_Ant3_NTNV




10M_MCH_2437.5MHz_MIMO_NTNV




10M_HCH_2467.14MHz_Ant2_NTNV



10M_HCH_2467.14MHz_Ant3_NTNV



10M_HCH_2467.14MHz_MIMO_NTNV




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


20M_LCH_2412.5MHz_Ant2_NTNV




20M_LCH_2412.5MHz_Ant3_NTNV




20M_LCH_2412.5MHz_MIMO_NTNV




20M_MCH_2437.5MHz_Ant2_NTNV




20M_MCH_2437.5MHz_Ant3_NTNV




20M_MCH_2437.5MHz_MIMO_NTNV




20M_HCH_2462.5MHz_Ant2_NTNV




20M_HCH_2462.5MHz_Ant3_NTNV




20M_HCH_2462.5MHz_MIMO_NTNV




40M_LCH_2422.5MHz_Ant2_NTNV




40M_LCH_2422.5MHz_Ant3_NTNV




40M_LCH_2422.5MHz_MIMO_NTNV




40M_MCH_2437.5MHz_Ant2_NTNV




40M_MCH_2437.5MHz_Ant3_NTNV




40M_MCH_2437.5MHz_MIMO_NTNV




40M_HCH_2452.5MHz_Ant2_NTNV



40M_HCH_2452.5MHz_Ant3_NTNV



40M_HCH_2452.5MHz_MIMO_NTNV



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251100490702

Page: 86 of 159

Ant0& Ant1

1. Duty Cycle

1.1 Test Result

1.1.1 Ant0

Ant0							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
5M	MIMO	2404.5	100.000	100.000	100.00	0.00	0.00
		2437.26	100.000	100.000	100.00	0.00	0.00
		2469.5	100.000	100.000	100.00	0.00	0.00
10M	MIMO	2407.86	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2467.14	100.000	100.000	100.00	0.00	0.00
20M	MIMO	2412.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2462.5	100.000	100.000	100.00	0.00	0.00
40M	MIMO	2422.5	100.000	100.000	100.00	0.00	0.00
		2437.5	100.000	100.000	100.00	0.00	0.00
		2452.5	100.000	100.000	100.00	0.00	0.00



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory


Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.2 Test Graph


1.2.1 Ant0




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


5M_HCH_2469.5MHz_Ant0_NTNV




10M_LCH_2407.86MHz_Ant0_NTNV




10M_MCH_2437.5MHz_Ant0_NTNV




10M_HCH_2467.14MHz_Ant0_NTNV




20M_LCH_2412.5MHz_Ant0_NTNV



20M_MCH_2437.5MHz_Ant0_NTNV



20M_HCH_2462.5MHz_Ant0_NTNV



40M_LCH_2422.5MHz_Ant0_NTNV

