

FCC ID: **2ANFAWB168**
Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.
According to KDB447498 D01 General RF Exposure Guidance V06
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
 $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
f(GHz) is the RF channel transmit frequency in GHz;
Power and distance are rounded to the nearest mW and mm before calculation;
The result is rounded to one decimal place for comparison;
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.
We use 5mm as separation distance to calculate.

Maximum measured transmitter power:
Antenna gain: 0dBi

Transmit Frequency (GHz)	Mode	peak conducted output power (dBm)	EIRP (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	-3.647	-3.647	-3	0.16	3.0
2.441	GFSK	-3.466	-3.466	-3	0.16	3.0
2.480	GFSK	-4.030	-4.030	-3	0.16	3.0
2.402	8DPSK	-2.091	-2.091	-1	0.25	3.0
2.441	8DPSK	-1.995	-1.995	-1	0.25	3.0
2.480	8DPSK	-2.556	-2.556	-1	0.25	3.0

Conclusion:
For the max result : $0.25 \leq 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature: 

Date: 2018-01-05

NAME AND TITLE (Please print or type): David Lee/Manager
COMPANY (Please print or type): EMTEK (Shenzhen) Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China