



TEST REPORT

Application No.: GZCR2207000879AT
Applicant: NURA OPERATIONS PTY LTD
Address of Applicant: PO BOX 95, BRUNSWICK, VIC 3056, AUSTRALIA
Manufacturer: NURA OPERATIONS PTY LTD
Address of Manufacturer: PO BOX 95, BRUNSWICK, VIC 3056, AUSTRALIA
Factory: Shenzhen Grandsun Electronic Co., Ltd
Address of Factory: East Park, Gaoqiao Industry Zone, Pingdi Street, Longgang, Shenzhen
Equipment Under Test (EUT):
EUT Name: nuratrue pro
Model No.: TOPB
Trade Mark: nura
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2022-06-28
Date of Test: 2022-06-28 to 2022-07-21
Date of Issue: 2022-07-25

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kobe Jian
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2022-07-25		Original

Authorized for issue by				
				
		Curry Wu/Project Engineer		
				
		Ricky Liu/Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty	7
4.4 Test Location	8
4.5 Test Facility.....	8
4.6 Deviation from Standards.....	9
4.7 Abnormalities from Standard Conditions.....	9
5 Equipment List	10
6 Radio Spectrum Technical Requirement.....	14
6.1 Antenna Requirement	14
6.1.1 Test Requirement:	14
6.1.2 Conclusion	14
7 Radio Spectrum Matter Test Results	15
7.1 Conducted Peak Output Power	15
7.1.1 E.U.T. Operation.....	15
7.1.2 Test Mode Description	15
7.1.3 Test Setup Diagram	16
7.1.4 Measurement Procedure and Data.....	16
7.2 Minimum 6dB Bandwidth.....	17
7.2.1 E.U.T. Operation.....	17
7.2.2 Test Mode Description	17
7.2.3 Test Setup Diagram	17
7.2.4 Measurement Procedure and Data.....	17
7.3 Power Spectrum Density	18
7.3.1 E.U.T. Operation.....	18
7.3.2 Test Mode Description	18
7.3.3 Test Setup Diagram	18
7.3.4 Measurement Procedure and Data.....	18
7.4 Conducted Band Edges Measurement	19
7.4.1 E.U.T. Operation.....	19
7.4.2 Test Mode Description	19
7.4.3 Test Setup Diagram	20
7.4.4 Measurement Procedure and Data.....	20
7.5 Conducted Spurious Emissions	21
7.5.1 E.U.T. Operation.....	21
7.5.2 Test Mode Description	21
7.5.3 Test Setup Diagram	22
7.5.4 Measurement Procedure and Data.....	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6	Radiated Emissions which fall in the restricted bands	23
7.6.1	E.U.T. Operation	23
7.6.2	Test Mode Description	23
7.6.3	Test Setup Diagram	24
7.6.4	Measurement Procedure and Data.....	24
7.7	Radiated Spurious Emissions (Below 1GHz)	41
7.7.1	E.U.T. Operation	41
7.7.2	Test Mode Description	41
7.7.3	Test Setup Diagram	42
7.7.4	Measurement Procedure and Data.....	42
7.8	Radiated Spurious Emissions (Above 1GHz).....	51
7.8.1	E.U.T. Operation	51
7.8.2	Test Mode Description	51
7.8.3	Test Setup Diagram	52
7.8.4	Measurement Procedure and Data.....	53
8	Test Setup Photo	78
9	EUT Constructional Details (EUT Photos).....	78
10	Appendix.....	79



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Left earbuds: Li-Ion Polymer Battery 3.7V 85mAh (Charge by Charging box) Right earbuds: Li-Ion Polymer Battery 3.7V 85mAh (Charge by Charging box) Charging box with backup battery: Li-Ion Polymer Battery 3.7V 500mAh (Charged by type-C port)
Cable(s):	Type-c cable: 19cm unshielded
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.3 Dual mode
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Data Rate:	Support 1Mb/s and 2Mb/s
Antenna Type:	PIFA
Antenna Gain:	-1.5dBi

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 5.00\text{dB}$ (30MHz-1GHz; 3m); $\pm 5.12\text{dB}$ (1GHz-6GHz); $\pm 5.38\text{dB}$ (6GHz-18GHz); $\pm 5.61\text{dB}$ (18GHz-40GHz)
Radiated Spurious Emissions (Below 1GHz)	$\pm 5.00\text{dB}$ (30MHz-1GHz; 3m); $\pm 4.38\text{dB}$ (30MHz-1GHz; 10m);
Radiated Spurious Emissions (Above 1GHz)	$\pm 5.12\text{dB}$ (1GHz-6GHz); $\pm 5.38\text{dB}$ (6GHz-18GHz); $\pm 5.61\text{dB}$ (18GHz-40GHz)
Remark: The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.	

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2018 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No. 198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None

5 Equipment List

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power Meter (U2021XA_Ch2)	Agilent Technologies	U2021XA_Ch2	SEM009-02	2022-05-16	2023-05-15
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2022-03-29	2023-03-28
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2022-03-29	2023-03-28
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2022-03-29	2023-03-28
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2022-03-29	2023-03-28
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A



Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2022-03-29	2023-03-28
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-12-17	2022-12-16
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-12-17	2022-12-16
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-12-17	2022-12-16
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2021-11-01	2022-10-31
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Notch Filter (5150-5880)	Mico-Tronics	BRM50716	EMC2168	2021-07-29	2022-07-28
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2021-08-30	2022-08-29

Radiated Spurious Emissions (Below 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-12-17	2022-12-16
Chamber cable	HangTianXing	N/A	EMC0542	2020-09-09	2022-09-08
Trilog Broadband Antenna(25MHz-1GHz)-Lab	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	SEM003-18	2019-08-08	2022-08-07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@sgs.com

Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2022-06-21	2023-06-20
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2022-04-06	2024-04-05
High Pass Filter (915MHz)	FSY MICROWAVE	HM1465-9SS	EMC2079	2021-12-17	2022-12-16
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2220	2022-05-20	2023-05-19

Radiated Spurious Emissions (Above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-12-17	2022-12-16
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-12-17	2022-12-16
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-12-17	2022-12-16
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2021-11-01	2022-10-31
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Notch Filter (5150-5880)	Mico-Tronics	BRM50716	EMC2168	2021-07-29	2022-07-28
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2021-08-30	2022-08-29



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2021-07-05	2022-07-05
				2022-07-05	2023-07-05
DMM	Fluke	73	EMC0007	2021-07-05	2022-07-05
				2022-07-05	2023-07-05



6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of 15.211, 15.213, 15.217, 15.219, 15.221, or 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -1.5dBi

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.3

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C


Humidity: 52.6 % RH

Atmospheric Pressure: 1015 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 24.5 °C

Humidity: 52.6 % RH

Atmospheric Pressure: 1015 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram**7.2.4 Measurement Procedure and Data**

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.3.1 E.U.T. Operation


Operating Environment:

Temperature: 24.5 °C Humidity: 52.6 % RH Atmospheric Pressure: 1015 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 24.5 °C Humidity: 52.6 % RH Atmospheric Pressure: 1015 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C


Humidity: 52.6 % RH

Atmospheric Pressure: 1015 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 52.5 % RH Atmospheric Pressure: 1015 mbar

7.6.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2388.850	52.68	27.33	3.48	37.59	45.90	74.00	-28.10	HORIZONTAL	Peak
2	2390.000	51.18	27.33	3.48	37.59	44.40	74.00	-29.60	HORIZONTAL	Peak
3 *	2402.000	103.98	27.35	3.50	37.59	97.24	74.00	23.24	HORIZONTAL	Peak


Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2389.659	52.35	27.33	3.48	37.59	45.57	74.00	-28.43	VERTICAL	Peak
2	2390.000	50.72	27.33	3.48	37.59	43.94	74.00	-30.06	VERTICAL	Peak
3 *	2402.000	100.98	27.35	3.50	37.59	94.24	74.00	20.24	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



race: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1 *	2480.000	103.58	27.47	3.60	37.57	97.08	74.00	23.08
2	2483.500	44.84	27.48	3.53	37.57	38.28	54.00	-15.72
3	2483.500	62.51	27.48	3.53	37.57	55.95	74.00	-18.05
4	2483.896	44.95	27.48	3.53	37.57	38.39	54.00	-15.61
5	2483.896	62.93	27.48	3.53	37.57	56.37	74.00	-17.63


Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:High



race: (Discrete)

		ReadAntenna	Cable	Preamp		Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	102.35	27.47	3.60	37.57	95.85	74.00	21.85	VERTICAL	Peak
2	2483.500	43.93	27.48	3.53	37.57	37.37	54.00	-16.63	VERTICAL	Average
3	2483.500	61.60	27.48	3.53	37.57	55.04	74.00	-18.96	VERTICAL	Peak
4	2483.871	43.84	27.48	3.53	37.57	37.28	54.00	-16.72	VERTICAL	Average
5	2483.871	61.03	27.48	3.53	37.57	54.47	74.00	-19.53	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2389.862	51.73	27.33	3.48	37.59	44.95	74.00	-29.05 HORIZONTAL Peak
2	2390.000	51.02	27.33	3.48	37.59	44.24	74.00	-29.76 HORIZONTAL Peak
3 *	2402.000	103.93	27.35	3.50	37.59	97.19	74.00	23.19 HORIZONTAL Peak


Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2369.692	51.85	27.28	3.43	37.60	44.96	74.00	-29.04	VERTICAL	Peak
2	2390.000	50.32	27.33	3.48	37.59	43.54	74.00	-30.46	VERTICAL	Peak
3 *	2402.000	100.88	27.35	3.50	37.59	94.14	74.00	20.14	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



race: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	103.48	27.47	3.60	37.57	96.98	74.00	22.98	HORIZONTAL	Peak
2	2483.500	47.98	27.48	3.53	37.57	41.42	54.00	-12.58	HORIZONTAL	Average
3	2483.500	63.36	27.48	3.53	37.57	56.80	74.00	-17.20	HORIZONTAL	Peak
4	2483.896	46.28	27.48	3.53	37.57	39.72	54.00	-14.28	HORIZONTAL	Average
5	2483.896	61.90	27.48	3.53	37.57	55.34	74.00	-18.66	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	102.21	27.47	3.60	37.57	95.71	74.00	21.71	VERTICAL	Peak
2	2483.500	46.95	27.48	3.53	37.57	40.39	54.00	-13.61	VERTICAL	Average
3	2483.500	61.99	27.48	3.53	37.57	55.43	74.00	-18.57	VERTICAL	Peak
4	2483.996	45.78	27.48	3.53	37.57	39.22	54.00	-14.78	VERTICAL	Average
5	2483.996	60.95	27.48	3.53	37.57	54.39	74.00	-19.61	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



race: (Discrete)

	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2382.076	51.88	27.31	3.46	37.60	45.05	74.00	-28.95	HORIZONTAL Peak
2	2390.000	50.70	27.33	3.48	37.59	43.92	74.00	-30.08	HORIZONTAL Peak
3 *	2402.000	103.17	27.35	3.50	37.59	96.43	74.00	22.43	HORIZONTAL Peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed on the reverse, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>, and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions.aspx#e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document may render it null and void. The results of the analysis may be reported to the Client. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443.

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Center EEC Laboratory.

中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sqs.china@sqs.com


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2383.187	51.42	27.31	3.46	37.60	44.59	74.00	-29.41	VERTICAL	Peak
2	2390.000	50.12	27.33	3.48	37.59	43.34	74.00	-30.66	VERTICAL	Peak
3 *	2402.000	100.61	27.35	3.50	37.59	93.87	74.00	19.87	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



race: (Discrete)

	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2480.000	102.69	27.47	3.60	37.57	96.19	74.00	22.19	HORIZONTAL Peak
2	2483.500	42.75	27.48	3.53	37.57	36.19	54.00	-17.81	HORIZONTAL Average
3	2483.500	61.13	27.48	3.53	37.57	54.57	74.00	-19.43	HORIZONTAL Peak
4	2483.846	59.91	27.48	3.53	37.57	53.35	74.00	-20.65	HORIZONTAL Peak




Unless otherwise agreed in writing this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or expiration date of this document is illegal and may be subject to criminal sanctions. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1444.

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Center EEC Laboratory.

中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	99.83	27.47	3.60	37.57	93.33	74.00	19.33	VERTICAL	Peak
2	2483.500	59.53	27.48	3.53	37.57	52.97	74.00	-21.03	VERTICAL	Peak
3	2483.946	57.31	27.48	3.53	37.57	50.75	74.00	-23.25	VERTICAL	Peak


Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2389.153	51.58	27.33	3.48	37.59	44.80	74.00	-29.20	HORIZONTAL	Peak
2	2390.000	51.37	27.33	3.48	37.59	44.59	74.00	-29.41	HORIZONTAL	Peak
3 *	2402.000	103.25	27.35	3.50	37.59	96.51	74.00	22.51	HORIZONTAL	Peak


Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2337.178	51.33	27.22	3.37	37.62	44.30	74.00	-29.70	VERTICAL	Peak
2	2390.000	49.95	27.33	3.48	37.59	43.17	74.00	-30.83	VERTICAL	Peak
3 *	2402.000	100.68	27.35	3.50	37.59	93.94	74.00	19.94	VERTICAL	Peak


Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



race: (Discrete)

		ReadAntenna	Cable	Preamp		Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	102.72	27.47	3.60	37.57	96.22	74.00	22.22	HORIZONTAL	Peak
2	2483.500	44.98	27.48	3.53	37.57	38.42	54.00	-15.58	HORIZONTAL	Average
3	2483.500	61.32	27.48	3.53	37.57	54.76	74.00	-19.24	HORIZONTAL	Peak
4	2483.896	59.73	27.48	3.53	37.57	53.17	74.00	-20.83	HORIZONTAL	Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2480.000	99.84	27.47	3.60	37.57	93.34	74.00	19.34	VERTICAL	Peak
2	2483.500	58.03	27.48	3.53	37.57	51.47	74.00	-22.53	VERTICAL	Peak
3	2484.096	59.28	27.48	3.53	37.57	52.72	74.00	-21.28	VERTICAL	Peak

7.7 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.6 °C Humidity: 52.7 % RH Atmospheric Pressure: 1015 mbar

7.7.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.7.3 Test Setup Diagram




7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	37.945	24.51	13.31	1.09	27.62	11.29	40.00	-28.71	HORIZONTAL	QP
2	54.261	24.60	13.86	1.18	27.60	12.04	40.00	-27.96	HORIZONTAL	QP
3	147.404	24.65	13.40	2.20	27.40	12.85	43.50	-30.65	HORIZONTAL	QP
4	321.061	24.30	14.05	3.32	27.32	14.35	46.00	-31.65	HORIZONTAL	QP
5	612.064	25.96	20.12	5.23	28.79	22.52	46.00	-23.48	HORIZONTAL	QP
6	942.131	26.09	23.99	7.12	28.11	29.09	46.00	-16.91	HORIZONTAL	QP


Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	39.437	23.55	13.50	1.10	27.61	10.54	40.00	-29.46	VERTICAL	QP
2	54.261	24.05	13.86	1.18	27.60	11.49	40.00	-28.51	VERTICAL	QP
3	155.910	23.94	13.61	2.30	27.37	12.48	43.50	-31.02	VERTICAL	QP
4	341.979	24.82	14.34	3.55	27.53	15.18	46.00	-30.82	VERTICAL	QP
5	595.133	26.44	20.04	5.10	28.79	22.79	46.00	-23.21	VERTICAL	QP
6	903.309	26.91	23.12	6.92	28.19	28.76	46.00	-17.24	VERTICAL	QP


Test Mode: 05; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	36.001	24.23	13.08	1.07	27.62	10.76	40.00	-29.24	HORIZONTAL	QP
2	51.481	23.92	13.97	1.16	27.60	11.45	40.00	-28.55	HORIZONTAL	QP
3	151.067	24.67	13.58	2.24	27.39	13.10	43.50	-30.40	HORIZONTAL	QP
4	322.189	24.07	14.07	3.35	27.32	14.17	46.00	-31.83	HORIZONTAL	QP
5	564.639	27.61	18.75	4.93	28.75	22.54	46.00	-23.46	HORIZONTAL	QP
6	909.667	25.72	23.22	6.96	28.18	27.72	46.00	-18.28	HORIZONTAL	QP

Test Mode: 05; Polarity: Vertical; Modulation: GFSK; ; Channel: Low




Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	36.895	24.08	13.20	1.08	27.62	10.74	40.00	-29.26	VERTICAL	QP
2	54.835	23.98	13.81	1.19	27.60	11.38	40.00	-28.62	VERTICAL	QP
3	137.903	24.57	12.91	2.05	27.48	12.05	43.50	-31.45	VERTICAL	QP
4	340.782	24.42	14.33	3.50	27.51	14.74	46.00	-31.26	VERTICAL	QP
5	649.660	27.17	20.42	5.51	28.75	24.35	46.00	-21.65	VERTICAL	QP
6	909.667	25.99	23.22	6.96	28.18	27.99	46.00	-18.01	VERTICAL	QP




Test Mode: 06; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	36.895	23.91	13.20	1.08	27.62	10.57	40.00	-29.43	HORIZONTAL	QP
2	51.121	24.09	13.97	1.15	27.60	11.61	40.00	-28.39	HORIZONTAL	QP
3	160.346	23.84	13.69	2.33	27.36	12.50	43.50	-31.00	HORIZONTAL	QP
4	334.859	24.71	14.29	3.46	27.43	15.03	46.00	-30.97	HORIZONTAL	QP
5	605.659	26.51	20.17	5.18	28.80	23.06	46.00	-22.94	HORIZONTAL	QP
6	955.438	26.08	24.31	7.18	28.08	29.49	46.00	-16.51	HORIZONTAL	QP


Test Mode: 06; Polarity: Vertical; Modulation: GFSK; ; Channel: Low



Site : SGS
Job :
Model :
Power :
Test Mode :


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	35.749	23.16	13.08	1.07	27.62	9.69	40.00	-30.31	VERTICAL	QP
2	55.805	22.42	13.74	1.20	27.60	9.76	40.00	-30.24	VERTICAL	QP
3	159.784	23.89	13.69	2.33	27.36	12.55	43.50	-30.95	VERTICAL	QP
4	423.540	24.58	16.20	4.04	28.10	16.72	46.00	-29.28	VERTICAL	QP
5	677.580	25.06	20.99	5.65	28.71	22.99	46.00	-23.01	VERTICAL	QP
6	955.438	24.93	24.31	7.18	28.08	28.34	46.00	-17.66	VERTICAL	QP

Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	40.845	23.10	13.32	1.10	27.18	10.34	40.00	-29.66	HORIZONTAL QP
2	60.918	23.93	13.10	1.27	27.16	11.14	40.00	-28.86	HORIZONTAL QP
3	148.963	23.23	13.47	2.22	26.84	12.08	43.50	-31.42	HORIZONTAL QP
4	337.216	24.15	14.10	3.46	26.81	14.90	46.00	-31.10	HORIZONTAL QP
5	601.427	25.46	19.77	5.14	28.21	22.16	46.00	-23.84	HORIZONTAL QP
6	982.620	24.78	23.82	7.31	27.68	28.23	54.00	-25.77	HORIZONTAL QP

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

Site : SGS

Condition:

Job :

Model :

Power :

Test Mode:

	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	42.302	22.66	13.51	1.11	27.17	10.11	40.00	-29.89	VERTICAL QP
2	58.407	22.96	13.43	1.24	27.16	10.47	40.00	-29.53	VERTICAL QP
3	156.458	23.06	13.43	2.30	26.81	11.98	43.50	-31.52	VERTICAL QP
4	339.589	23.03	14.10	3.50	26.84	13.79	46.00	-32.21	VERTICAL QP
5	758.041	25.67	22.08	6.01	28.08	25.68	46.00	-20.32	VERTICAL QP
6	989.536	24.93	23.85	7.37	27.67	28.48	54.00	-25.52	VERTICAL QP

7.8 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 24.3 °C Humidity: 52.5 % RH Atmospheric Pressure: 1015 mbar

7.8.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(1Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(2Mbps)_Keep the EUT(Left earbud) in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)_Keep the EUT(right earbud) in continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1477.276	48.18	25.48	2.77	38.13	38.30	74.00	-35.70	HORIZONTAL	Peak
2	4329.354	51.74	30.54	4.67	36.81	50.14	74.00	-23.86	HORIZONTAL	Peak
3	4804.000	49.21	31.42	5.40	36.83	49.20	74.00	-24.80	HORIZONTAL	Peak
4	5797.032	52.04	32.19	6.10	36.89	53.44	74.00	-20.56	HORIZONTAL	Peak
5	7206.000	48.62	35.54	5.98	37.38	52.76	74.00	-21.24	HORIZONTAL	Peak
6	9608.000	45.65	38.37	7.07	37.42	53.67	74.00	-20.33	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1692.231	48.35	25.70	2.80	37.89	38.96	74.00	-35.04	VERTICAL	Peak
2	4267.237	50.93	30.38	4.63	36.81	49.13	74.00	-24.87	VERTICAL	Peak
3	4804.000	50.65	31.42	5.40	36.83	50.64	74.00	-23.36	VERTICAL	Peak
4	6698.373	50.52	34.38	5.83	37.08	53.65	74.00	-20.35	VERTICAL	Peak
5	7206.000	48.99	35.54	5.98	37.38	53.13	74.00	-20.87	VERTICAL	Peak
6	9608.000	45.38	38.37	7.07	37.42	53.40	74.00	-20.60	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1667.951	49.25	25.66	2.80	37.91	39.80	74.00	-34.20	HORIZONTAL	Peak
2	4469.214	49.99	30.77	4.93	36.81	48.88	74.00	-25.12	HORIZONTAL	Peak
3	4880.000	48.41	31.54	5.50	36.84	48.61	74.00	-25.39	HORIZONTAL	Peak
4	6974.982	50.19	34.97	5.81	37.23	53.74	74.00	-20.26	HORIZONTAL	Peak
5	7320.000	47.47	36.00	6.13	37.43	52.17	74.00	-21.83	HORIZONTAL	Peak
6	9760.000	45.45	38.50	7.02	37.41	53.56	74.00	-20.44	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1677.621	48.23	25.68	2.80	37.91	38.80	74.00	-35.20	VERTICAL	Peak
2	4405.090	50.93	30.68	4.70	36.81	49.50	74.00	-24.50	VERTICAL	Peak
3	4880.000	48.98	31.54	5.50	36.84	49.18	74.00	-24.82	VERTICAL	Peak
4	6088.991	51.17	32.61	6.15	36.92	53.01	74.00	-20.99	VERTICAL	Peak
5	7320.000	46.73	36.00	6.13	37.43	51.43	74.00	-22.57	VERTICAL	Peak
6	9760.000	45.53	38.50	7.02	37.41	53.64	74.00	-20.36	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1667.951	48.92	25.66	2.80	37.91	39.47	74.00	-34.53	HORIZONTAL	Peak
2	4341.886	52.14	30.57	4.67	36.81	50.57	74.00	-23.43	HORIZONTAL	Peak
3	4960.000	50.24	31.65	5.65	36.84	50.70	74.00	-23.30	HORIZONTAL	Peak
4	6914.763	49.97	34.89	5.81	37.19	53.48	74.00	-20.52	HORIZONTAL	Peak
5	7440.000	48.27	36.27	6.22	37.47	53.29	74.00	-20.71	HORIZONTAL	Peak
6	9920.000	45.68	38.65	6.96	37.40	53.89	74.00	-20.11	HORIZONTAL	Peak


Test Mode: 04; Polarity: Vertical; Modulation:GFSK; ; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1587.975	48.19	25.57	2.80	37.98	38.58	74.00	-35.42	VERTICAL	Peak
2	4417.841	50.39	30.70	4.74	36.81	49.02	74.00	-24.98	VERTICAL	Peak
3	4960.000	49.07	31.65	5.65	36.84	49.53	74.00	-24.47	VERTICAL	Peak
4	6195.508	51.48	32.96	6.07	36.94	53.57	74.00	-20.43	VERTICAL	Peak
5	7440.000	48.16	36.27	6.22	37.47	53.18	74.00	-20.82	VERTICAL	Peak
6	9920.000	45.00	38.65	6.96	37.40	53.21	74.00	-20.79	VERTICAL	Peak


Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1625.121	48.67	25.61	2.80	37.95	39.13	74.00	-34.87	HORIZONTAL	Peak
2	4392.376	51.60	30.66	4.70	36.81	50.15	74.00	-23.85	HORIZONTAL	Peak
3	4804.000	48.78	31.42	5.40	36.83	48.77	74.00	-25.23	HORIZONTAL	Peak
4	6974.982	49.45	34.97	5.81	37.23	53.00	74.00	-21.00	HORIZONTAL	Peak
5	7206.000	48.24	35.54	5.98	37.38	52.38	74.00	-21.62	HORIZONTAL	Peak
6	9608.000	45.25	38.37	7.07	37.42	53.27	74.00	-20.73	HORIZONTAL	Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1687.347	48.29	25.69	2.80	37.91	38.87	74.00	-35.13	VERTICAL	Peak
2	4367.058	51.00	30.62	4.68	36.81	49.49	74.00	-24.51	VERTICAL	Peak
3	4804.000	48.40	31.42	5.40	36.83	48.39	74.00	-25.61	VERTICAL	Peak
4	6640.542	50.02	34.24	5.83	37.06	53.03	74.00	-20.97	VERTICAL	Peak
5	7206.000	48.89	35.54	5.98	37.38	53.03	74.00	-20.97	VERTICAL	Peak
6	9608.000	45.34	38.37	7.07	37.42	53.36	74.00	-20.64	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1672.779	48.13	25.67	2.80	37.91	38.69	74.00	-35.31
2	4157.664	51.65	30.06	4.60	36.80	49.51	74.00	-24.49
3	4880.000	48.73	31.54	5.50	36.84	48.93	74.00	-25.07
4	6974.982	50.03	34.97	5.81	37.23	53.58	74.00	-20.42
5	7320.000	47.55	36.00	6.13	37.43	52.25	74.00	-21.75
6	9760.000	45.31	38.50	7.02	37.41	53.42	74.00	-20.58

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1672.779	48.66	25.67	2.80	37.91	39.22	74.00	-34.78	VERTICAL	Peak
2	4456.315	50.95	30.75	4.88	36.81	49.77	74.00	-24.23	VERTICAL	Peak
3	4880.000	50.24	31.54	5.50	36.84	50.44	74.00	-23.56	VERTICAL	Peak
4	6001.626	52.03	32.40	6.20	36.90	53.73	74.00	-20.27	VERTICAL	Peak
5	7320.000	47.51	36.00	6.13	37.43	52.21	74.00	-21.79	VERTICAL	Peak
6	9760.000	45.41	38.50	7.02	37.41	53.52	74.00	-20.48	VERTICAL	Peak

Test Mode: 05; Polarity: Horizontal; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1644.019	48.51	25.63	2.80	37.93	39.01	74.00	-34.99	HORIZONTAL Peak
2	4405.090	51.33	30.68	4.70	36.81	49.90	74.00	-24.10	HORIZONTAL Peak
3	4960.000	49.36	31.65	5.65	36.84	49.82	74.00	-24.18	HORIZONTAL Peak
4	6934.778	49.97	34.92	5.81	37.19	53.51	74.00	-20.49	HORIZONTAL Peak
5	7440.000	47.81	36.27	6.22	37.47	52.83	74.00	-21.17	HORIZONTAL Peak
6	9920.000	45.00	38.65	6.96	37.40	53.21	74.00	-20.79	HORIZONTAL Peak

Test Mode: 05; Polarity: Vertical; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1702.042	48.03	25.72	2.80	37.89	38.66	74.00	-35.34	VERTICAL	Peak
2	4379.699	51.25	30.64	4.69	36.81	49.77	74.00	-24.23	VERTICAL	Peak
3	4960.000	49.00	31.65	5.65	36.84	49.46	74.00	-24.54	VERTICAL	Peak
4	6776.265	50.08	34.61	5.82	37.11	53.40	74.00	-20.60	VERTICAL	Peak
5	7440.000	48.33	36.27	6.22	37.47	53.35	74.00	-20.65	VERTICAL	Peak
6	9920.000	45.33	38.65	6.96	37.40	53.54	74.00	-20.46	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1574.265	48.36	25.56	2.80	38.00	38.72	74.00	-35.28	HORIZONTAL Peak
2	4443.453	50.98	30.73	4.83	36.81	49.73	74.00	-24.27	HORIZONTAL Peak
3	4804.000	49.82	31.42	5.40	36.83	49.81	74.00	-24.19	HORIZONTAL Peak
4	6717.762	50.58	34.44	5.83	37.09	53.76	74.00	-20.24	HORIZONTAL Peak
5	7206.000	48.54	35.54	5.98	37.38	52.68	74.00	-21.32	HORIZONTAL Peak
6	9608.000	45.46	38.37	7.07	37.42	53.48	74.00	-20.52	HORIZONTAL Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1697.129	48.35	25.71	2.80	37.89	38.97	74.00	-35.03	VERTICAL	Peak
2	4405.090	51.13	30.68	4.70	36.81	49.70	74.00	-24.30	VERTICAL	Peak
3	4804.000	49.16	31.42	5.40	36.83	49.15	74.00	-24.85	VERTICAL	Peak
4	6874.906	50.30	34.82	5.82	37.16	53.78	74.00	-20.22	VERTICAL	Peak
5	7206.000	47.65	35.54	5.98	37.38	51.79	74.00	-22.21	VERTICAL	Peak
6	9608.000	45.46	38.37	7.07	37.42	53.48	74.00	-20.52	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1702.042	48.44	25.72	2.80	37.89	39.07	74.00	-34.93
2	3879.027	51.75	29.66	4.60	36.83	49.18	74.00	-24.82
3	4880.000	48.28	31.54	5.50	36.84	48.48	74.00	-25.52
4	6874.906	50.12	34.82	5.82	37.16	53.60	74.00	-20.40
5	7320.000	46.85	36.00	6.13	37.43	51.55	74.00	-22.45
6	9760.000	45.11	38.50	7.02	37.41	53.22	74.00	-20.78

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1653.550	48.71	25.64	2.80	37.93	39.22	74.00	-34.78	VERTICAL	Peak
2	4050.904	52.36	29.87	4.60	36.80	50.03	74.00	-23.97	VERTICAL	Peak
3	4880.000	48.55	31.54	5.50	36.84	48.75	74.00	-25.25	VERTICAL	Peak
4	6914.763	49.75	34.89	5.81	37.19	53.26	74.00	-20.74	VERTICAL	Peak
5	7320.000	48.31	36.00	6.13	37.43	53.01	74.00	-20.99	VERTICAL	Peak
6	9760.000	45.50	38.50	7.02	37.41	53.61	74.00	-20.39	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1672.779	47.83	25.67	2.80	37.91	38.39	74.00	-35.61
2	4469.214	51.06	30.77	4.93	36.81	49.95	74.00	-24.05
3	4960.000	49.49	31.65	5.65	36.84	49.95	74.00	-24.05
4	6954.852	49.81	34.95	5.81	37.21	53.36	74.00	-20.64
5	7440.000	48.60	36.27	6.22	37.47	53.62	74.00	-20.38
6	9920.000	45.44	38.65	6.96	37.40	53.65	74.00	-20.35

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; ; Channel:High




	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1702.042	48.66	25.72	2.80	37.89	39.29	74.00	-34.71	VERTICAL	Peak
2	4379.699	51.18	30.64	4.69	36.81	49.70	74.00	-24.30	VERTICAL	Peak
3	4960.000	49.29	31.65	5.65	36.84	49.75	74.00	-24.25	VERTICAL	Peak
4	6995.172	49.93	35.00	5.81	37.25	53.49	74.00	-20.51	VERTICAL	Peak
5	7440.000	47.12	36.27	6.22	37.47	52.14	74.00	-21.86	VERTICAL	Peak
6	9920.000	45.03	38.65	6.96	37.40	53.24	74.00	-20.76	VERTICAL	Peak

Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low




	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1697.129	48.05	25.71	2.80	37.89	38.67	74.00	-35.33	HORIZONTAL Peak
2	4469.214	50.73	30.77	4.93	36.81	49.62	74.00	-24.38	HORIZONTAL Peak
3	4804.000	50.34	31.42	5.40	36.83	50.33	74.00	-23.67	HORIZONTAL Peak
4	6602.265	50.54	34.16	5.84	37.04	53.50	74.00	-20.50	HORIZONTAL Peak
5	7206.000	48.27	35.54	5.98	37.38	52.41	74.00	-21.59	HORIZONTAL Peak
6	9608.000	45.27	38.37	7.07	37.42	53.29	74.00	-20.71	HORIZONTAL Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1648.778	48.29	25.63	2.80	37.93	38.79	74.00	-35.21	VERTICAL	Peak
2	4392.376	50.80	30.66	4.70	36.81	49.35	74.00	-24.65	VERTICAL	Peak
3	4804.000	49.13	31.42	5.40	36.83	49.12	74.00	-24.88	VERTICAL	Peak
4	6717.762	50.51	34.44	5.83	37.09	53.69	74.00	-20.31	VERTICAL	Peak
5	7206.000	48.64	35.54	5.98	37.38	52.78	74.00	-21.22	VERTICAL	Peak
6	9608.000	45.63	38.37	7.07	37.42	53.65	74.00	-20.35	VERTICAL	Peak


Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1687.347	48.77	25.69	2.80	37.91	39.35	74.00	-34.65	HORIZONTAL Peak
2	4367.058	51.34	30.62	4.68	36.81	49.83	74.00	-24.17	HORIZONTAL Peak
3	4880.000	51.69	31.54	5.50	36.84	51.89	74.00	-22.11	HORIZONTAL Peak
4	6815.551	50.15	34.70	5.82	37.13	53.54	74.00	-20.46	HORIZONTAL Peak
5	7320.000	47.79	36.00	6.13	37.43	52.49	74.00	-21.51	HORIZONTAL Peak
6	9760.000	45.48	38.50	7.02	37.41	53.59	74.00	-20.41	HORIZONTAL Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1525.000	47.83	25.52	2.80	38.07	38.08	74.00	-35.92	VERTICAL	Peak
2	4392.376	51.10	30.66	4.70	36.81	49.65	74.00	-24.35	VERTICAL	Peak
3	4880.000	49.17	31.54	5.50	36.84	49.37	74.00	-24.63	VERTICAL	Peak
4	6737.207	50.12	34.50	5.82	37.09	53.35	74.00	-20.65	VERTICAL	Peak
5	7320.000	47.90	36.00	6.13	37.43	52.60	74.00	-21.40	VERTICAL	Peak
6	9760.000	45.46	38.50	7.02	37.41	53.57	74.00	-20.43	VERTICAL	Peak

Test Mode: 07; Polarity: Horizontal; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1692.231	48.54	25.70	2.80	37.89	39.15	74.00	-34.85	HORIZONTAL Peak
2	4482.150	50.73	30.78	4.99	36.81	49.69	74.00	-24.31	HORIZONTAL Peak
3	4960.000	50.22	31.65	5.65	36.84	50.68	74.00	-23.32	HORIZONTAL Peak
4	5932.638	52.32	32.34	6.00	36.90	53.76	74.00	-20.24	HORIZONTAL Peak
5	7440.000	48.68	36.27	6.22	37.47	53.70	74.00	-20.30	HORIZONTAL Peak
6	9920.000	45.09	38.65	6.96	37.40	53.30	74.00	-20.70	HORIZONTAL Peak

Test Mode: 07; Polarity: Vertical; Modulation:GFSK; ; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1677.621	48.99	25.68	2.80	37.91	39.56	74.00	-34.44	VERTICAL	Peak
2	4133.699	51.32	30.01	4.60	36.80	49.13	74.00	-24.87	VERTICAL	Peak
3	4960.000	49.41	31.65	5.65	36.84	49.87	74.00	-24.13	VERTICAL	Peak
4	6914.763	50.20	34.89	5.81	37.19	53.71	74.00	-20.29	VERTICAL	Peak
5	7440.000	48.43	36.27	6.22	37.47	53.45	74.00	-20.55	VERTICAL	Peak
6	9920.000	45.66	38.65	6.96	37.40	53.87	74.00	-20.13	VERTICAL	Peak

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for GZCR2207000879AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix – External and Internal Photos for GZCR2207000879AT

10 Appendix

For right earbud:


1. Duty Cycle

1.1 Ant1


1.1.1 Test Result

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	0.410	0.625	65.60	1.83	0.00
		2440	0.409	0.625	65.44	1.84	0.02
		2480	0.409	0.625	65.44	1.84	0.03
2M	SISO	2402	0.225	0.625	36.00	4.44	0.00
		2440	0.226	0.625	36.16	4.42	0.00
		2480	0.225	0.625	36.00	4.44	0.00


1.1.2 Test Graph




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV




2. Bandwidth

2.1 OBW


2.1.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)	Verdict
				Result	
1M	SISO	2402	1	1.048	Pass
		2440	1	1.049	Pass
		2480	1	1.046	Pass
2M	SISO	2402	1	2.073	Pass
		2440	1	2.073	Pass
		2480	1	2.071	Pass


2.1.2 Test Graph




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

2.2 6dB BW

2.2.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.724	≥ 0.5	Pass
		2440	1	0.729	≥ 0.5	Pass
		2480	1	0.730	≥ 0.5	Pass
2M	SISO	2402	1	1.258	≥ 0.5	Pass
		2440	1	1.268	≥ 0.5	Pass
		2480	1	1.215	≥ 0.5	Pass