



MPE/RF EXPOSURE TEST REPORT

FCC CFR 47 Part 1.1310

Report No.: KUMO06-U6_FCC_MPE Rev A

Company: Kumu Networks Inc

Model: Relay 2.0

MPE/RF EXPOSURE TEST REPORT

Company: Kumu Networks Inc.

Model: Relay 2.0

Standard: FCC CFR 47 Part 1.1310

Test Report Serial No.: KUMO06-U6 FCC MPE Rev A

This report supersedes: NONE

Applicant: Kumu Networks Inc
390 Hamlin Court
Sunnyvale, California 94089
USA

Issue Date: 14th September 2020

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = P_d (mW/cm²) = $EIRP / (4 * \pi * d^2)$

$EIRP = P * G$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = $10^{(G \text{ (dBi)}/10)}$

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
1850.0 – 1910.0	0.00	1.00	24.12	258.23	0.05137	1.00	4.53
700.0 - 800.0	0.00	1.00	23.81	240.44	0.0480	1.00	4.37

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com