


Test mode:	802.11n(HT20)
------------	---------------

Lowest channel




30MHz~25GHz

Middle channel




30MHz~25GHz


Highest channel



30MHz~25GHz

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	30MHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	30MHz-88MHz		40.00		Quasi-peak
	88MHz-216MHz		43.50		Quasi-peak
	216MHz-960MHz		46.00		Quasi-peak
	960MHz-1GHz		54.00		Quasi-peak
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:	Below 1GHz				
					
	Above 1GHz				

	
Test Procedure:	1. The EUT was placed on the top of a rotating table(0.8 meters below 1G and 1.5 meters above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement Data

■ Below 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
34.40	34.88	11.25	0.6	30.07	16.66	40	-23.34	Vertical
96.10	30.63	11.35	1.16	29.72	13.42	43.5	-30.08	Vertical
104.54	30.84	11.8	1.23	29.67	14.20	43.5	-29.30	Vertical
189.74	39.54	9.7	1.79	29.24	21.79	43.5	-21.71	Vertical
296.18	32.47	13.4	2.34	29.98	18.23	46	-27.77	Vertical
556.77	25.28	18.51	3.55	29.3	18.04	46	-27.96	Vertical
34.28	26.90	11.25	0.6	30.07	8.68	40	-31.32	Horizontal
89.59	28.37	10.6	1.11	29.75	10.33	43.5	-33.17	Horizontal
104.54	33.16	11.8	1.23	29.67	16.52	43.5	-26.98	Horizontal
197.89	34.78	10.2	1.83	29.21	17.60	43.5	-25.90	Horizontal
338.40	31.25	14.26	2.57	29.79	18.29	46	-27.71	Horizontal
614.21	24.03	19.37	3.77	29.29	17.88	46	-28.12	Horizontal

■ Above 1GHz

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	39.30	31.79	8.62	32.1	47.61	74	-26.39	Vertical
7236.00	33.55	36.19	11.68	31.97	49.45	74	-24.55	Vertical
9648.00	32.49	38.07	14.16	31.56	53.16	74	-20.84	Vertical
12060.00	*					74		Vertical
14472.00	*					74		Vertical
16884.00	*					74		Vertical
4824.00	38.46	31.79	8.62	32.1	46.77	74	-27.23	Horizontal
7236.00	33.61	36.19	11.68	31.97	49.51	74	-24.49	Horizontal
9648.00	32.27	38.07	14.16	31.56	52.94	74	-21.06	Horizontal
12060.00	*					74		Horizontal
14472.00	*					74		Horizontal
16884.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	28.50	31.79	8.62	32.1	36.81	54	-17.19	Vertical
7236.00	23.08	36.19	11.68	31.97	38.98	54	-15.02	Vertical
9648.00	22.51	38.07	14.16	31.56	43.18	54	-10.82	Vertical
12060.00	*					54		Vertical
14472.00	*					54		Vertical
16884.00	*					54		Vertical
4824.00	27.93	31.79	8.62	32.1	36.24	54	-17.76	Horizontal
7236.00	22.00	36.19	11.68	31.97	37.90	54	-16.10	Horizontal
9648.00	22.18	38.07	14.16	31.56	42.85	54	-11.15	Horizontal
12060.00	*					54		Horizontal
14472.00	*					54		Horizontal
16884.00	*					54		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	38.97	31.85	8.66	32.12	47.36	74	-26.64	Vertical
7311.00	34.00	36.37	11.71	31.91	50.17	74	-23.83	Vertical
9748.00	33.12	38.27	14.25	31.56	54.08	74	-19.92	Vertical
12185.00	*					74		Vertical
14622.00	*					74		Vertical
17059.00	*					74		Vertical
4874.00	39.44	31.85	8.66	32.12	47.83	74	-26.17	Horizontal
7311.00	32.23	36.37	11.71	31.91	48.40	74	-25.60	Horizontal
9748.00	33.57	38.27	14.25	31.56	54.53	74	-19.47	Horizontal
12185.00	*					74		Horizontal
14622.00	*					74		Horizontal
17059.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.51	31.85	8.66	32.12	37.90	54	-16.10	Vertical
7311.00	22.48	36.37	11.71	31.91	38.65	54	-15.35	Vertical
9748.00	22.93	38.27	14.25	31.56	43.89	54	-10.11	Vertical
12185.00	*					54		Vertical
14622.00	*					54		Vertical
17059.00	*					54		Vertical
4874.00	30.15	31.85	8.66	32.12	38.54	54	-15.46	Horizontal
7311.00	22.44	36.37	11.71	31.91	38.61	54	-15.39	Horizontal
9748.00	23.30	38.27	14.25	31.56	44.26	54	-9.74	Horizontal
12185.00	*					54		Horizontal
14622.00	*					54		Horizontal
17059.00	*					54		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	43.32	31.9	8.7	32.15	51.77	74	-22.23	Vertical
7386.00	34.63	36.49	11.76	31.83	51.05	74	-22.95	Vertical
9848.00	37.15	38.62	14.31	31.77	58.31	74	-15.69	Vertical
12310.00	*					74		Vertical
14772.00	*					74		Vertical
17234.00	*					74		Vertical
4924.00	42.65	31.9	8.7	32.15	51.10	74	-22.90	Horizontal
7386.00	33.35	36.49	11.76	31.83	49.77	74	-24.23	Horizontal
9848.00	32.87	38.62	14.31	31.77	54.03	74	-19.97	Horizontal
12310.00	*					74		Horizontal
14772.00	*					74		Horizontal
17234.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	34.71	31.9	8.7	32.15	43.16	54	-10.84	Vertical
7386.00	23.93	36.49	11.76	31.83	40.35	54	-13.65	Vertical
9848.00	25.76	38.62	14.31	31.77	46.92	54	-7.08	Vertical
12310.00	*					54		Vertical
14772.00	*					54		Vertical
17234.00	*					54		Vertical
4924.00	33.21	31.9	8.7	32.15	41.66	54	-12.34	Horizontal
7386.00	22.36	36.49	11.76	31.83	38.78	54	-15.22	Horizontal
9848.00	22.48	38.62	14.31	31.77	43.64	54	-10.36	Horizontal
12310.00	*					54		Horizontal
14772.00	*					54		Horizontal
17234.00	*					54		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	39.90	31.79	8.62	32.1	48.21	74	-25.79	Vertical
7236.00	33.63	36.19	11.68	31.97	49.53	74	-24.47	Vertical
9648.00	32.07	38.07	14.16	31.56	52.74	74	-21.26	Vertical
12060.00	*					74		Vertical
14472.00	*					74		Vertical
16884.00	*					74		Vertical
4824.00	38.67	31.79	8.62	32.1	46.98	74	-27.02	Horizontal
7236.00	33.25	36.19	11.68	31.97	49.15	74	-24.85	Horizontal
9648.00	32.41	38.07	14.16	31.56	53.08	74	-20.92	Horizontal
12060.00	*					74		Horizontal
14472.00	*					74		Horizontal
16884.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	28.80	31.79	8.62	32.1	37.11	54	-16.89	Vertical
7236.00	22.70	36.19	11.68	31.97	38.60	54	-15.40	Vertical
9648.00	22.62	38.07	14.16	31.56	43.29	54	-10.71	Vertical
12060.00	*					54		Vertical
14472.00	*					54		Vertical
16884.00	*					54		Vertical
4824.00	28.29	31.79	8.62	32.1	36.60	54	-17.40	Horizontal
7236.00	22.83	36.19	11.68	31.97	38.73	54	-15.27	Horizontal
9648.00	22.36	38.07	14.16	31.56	43.03	54	-10.97	Horizontal
12060.00	*					54		Horizontal
14472.00	*					54		Horizontal
16884.00	*					54		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	38.69	31.85	8.66	32.12	47.08	74	-26.92	Vertical
7311.00	34.16	36.37	11.71	31.91	50.33	74	-23.67	Vertical
9748.00	34.09	38.27	14.25	31.56	55.05	74	-18.95	Vertical
12185.00	*					74		Vertical
14622.00	*					74		Vertical
17059.00	*					74		Vertical
4874.00	39.57	31.85	8.66	32.12	47.96	74	-26.04	Horizontal
7311.00	33.15	36.37	11.71	31.91	49.32	74	-24.68	Horizontal
9748.00	33.07	38.27	14.25	31.56	54.03	74	-19.97	Horizontal
12185.00	*					74		Horizontal
14622.00	*					74		Horizontal
17059.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.60	31.85	8.66	32.12	37.99	54	-16.01	Vertical
7311.00	23.00	36.37	11.71	31.91	39.17	54	-14.83	Vertical
9748.00	23.20	38.27	14.25	31.56	44.16	54	-9.84	Vertical
12185.00	*					54		Vertical
14622.00	*					54		Vertical
17059.00	*					54		Vertical
4874.00	28.89	31.85	8.66	32.12	37.28	54	-16.72	Horizontal
7311.00	22.20	36.37	11.71	31.91	38.37	54	-15.63	Horizontal
9748.00	23.87	38.27	14.25	31.56	44.83	54	-9.17	Horizontal
12185.00	*					54		Horizontal
14622.00	*					54		Horizontal
17059.00	*					54		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	43.90	31.9	8.7	32.15	52.35	74	-21.65	Vertical
7386.00	34.07	36.49	11.76	31.83	50.49	74	-23.51	Vertical
9848.00	36.95	38.62	14.31	31.77	58.11	74	-15.89	Vertical
12310.00	*					74		Vertical
14772.00	*					74		Vertical
17234.00	*					74		Vertical
4924.00	43.34	31.9	8.7	32.15	51.79	74	-22.21	Horizontal
7386.00	32.93	36.49	11.76	31.83	49.35	74	-24.65	Horizontal
9848.00	32.21	38.62	14.31	31.77	53.37	74	-20.63	Horizontal
12310.00	*					74		Horizontal
14772.00	*					74		Horizontal
17234.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	34.37	31.9	8.7	32.15	42.82	54	-11.18	Vertical
7386.00	24.59	36.49	11.76	31.83	41.01	54	-12.99	Vertical
9848.00	24.91	38.62	14.31	31.77	46.07	54	-7.93	Vertical
12310.00	*					54		Vertical
14772.00	*					54		Vertical
17234.00	*					54		Vertical
4924.00	34.11	31.9	8.7	32.15	42.56	54	-11.44	Horizontal
7386.00	22.61	36.49	11.76	31.83	39.03	54	-14.97	Horizontal
9848.00	22.78	38.62	14.31	31.77	43.94	54	-10.06	Horizontal
12310.00	*					54		Horizontal
14772.00	*					54		Horizontal
17234.00	*					54		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	43.20	31.79	8.62	32.1	51.51	74	-22.49	Vertical
7236.00	34.36	36.19	11.68	31.97	50.26	74	-23.74	Vertical
9648.00	37.32	38.07	14.16	31.56	57.99	74	-16.01	Vertical
12060.00	*					74		Vertical
14472.00	*					74		Vertical
16884.00	*					74		Vertical
4824.00	43.33	31.79	8.62	32.1	51.64	74	-22.36	Horizontal
7236.00	33.33	36.19	11.68	31.97	49.23	74	-24.77	Horizontal
9648.00	32.75	38.07	14.16	31.56	53.42	74	-20.58	Horizontal
12060.00	*					74		Horizontal
14472.00	*					74		Horizontal
16884.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	34.63	31.79	8.62	32.1	42.94	54	-11.06	Vertical
7236.00	24.25	36.19	11.68	31.97	40.15	54	-13.85	Vertical
9648.00	25.39	38.07	14.16	31.56	46.06	54	-7.94	Vertical
12060.00	*					54		Vertical
14472.00	*					54		Vertical
16884.00	*					54		Vertical
4824.00	32.94	31.79	8.62	32.1	41.25	54	-12.75	Horizontal
7236.00	22.69	36.19	11.68	31.97	38.59	54	-15.41	Horizontal
9648.00	22.85	38.07	14.16	31.56	43.52	54	-10.48	Horizontal
12060.00	*					54		Horizontal
14472.00	*					54		Horizontal
16884.00	*					54		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*” , means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	44.11	31.85	8.66	32.12	52.50	74	-21.50	Vertical
7311.00	34.31	36.37	11.71	31.91	50.48	74	-23.52	Vertical
9748.00	36.84	38.27	14.25	31.56	57.80	74	-16.20	Vertical
12185.00	*					74		Vertical
14622.00	*					74		Vertical
17059.00	*					74		Vertical
4874.00	43.28	31.85	8.66	32.12	51.67	74	-22.33	Horizontal
7311.00	32.94	36.37	11.71	31.91	49.11	74	-24.89	Horizontal
9748.00	32.78	38.27	14.25	31.56	53.74	74	-20.26	Horizontal
12185.00	*					74		Horizontal
14622.00	*					74		Horizontal
17059.00	*					74		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	34.88	31.85	8.66	32.12	43.27	54	-10.73	Vertical
7311.00	24.72	36.37	11.71	31.91	40.89	54	-13.11	Vertical
9748.00	25.39	38.27	14.25	31.56	46.35	54	-7.65	Vertical
12185.00	*					54		Vertical
14622.00	*					54		Vertical
17059.00	*					54		Vertical
4874.00	33.63	31.85	8.66	32.12	42.02	54	-11.98	Horizontal
7311.00	22.74	36.37	11.71	31.91	38.91	54	-15.09	Horizontal
9748.00	22.26	38.27	14.25	31.56	43.22	54	-10.78	Horizontal
12185.00	*					54		Horizontal
14622.00	*					54		Horizontal
17059.00	*					54		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*” means this data is too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	43.47	31.9	8.7	32.15	51.92	74	-22.08	Vertical
7386.00	34.64	36.49	11.76	31.83	51.06	74	-22.94	Vertical
9848.00	36.13	38.62	14.31	31.77	57.29	74	-16.71	Vertical
12310.00	*					74		Vertical
14772.00	*					74		Vertical
17234.00	*					74		Vertical
4924.00	42.55	31.9	8.7	32.15	51.00	74	-23.00	Horizontal
7386.00	32.69	36.49	11.76	31.83	49.11	74	-24.89	Horizontal
9848.00	33.65	38.62	14.31	31.77	54.81	74	-19.19	Horizontal
12310.00	*					74		Horizontal
14772.00	*					74		Horizontal
17234.00	*					74		Horizontal

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	35.08	31.9	8.7	32.15	43.53	54	-10.47	Vertical
7386.00	23.70	36.49	11.76	31.83	40.12	54	-13.88	Vertical
9848.00	24.79	38.62	14.31	31.77	45.95	54	-8.05	Vertical
12310.00	*					54		Vertical
14772.00	*					54		Vertical
17234.00	*					54		Vertical
4924.00	33.85	31.9	8.7	32.15	42.30	54	-11.70	Horizontal
7386.00	23.47	36.49	11.76	31.83	39.89	54	-14.11	Horizontal
9848.00	22.21	38.62	14.31	31.77	43.37	54	-10.63	Horizontal
12310.00	*					54		Horizontal
14772.00	*					54		Horizontal
17234.00	*					54		Horizontal

Remark:

- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.

8 Test Setup Photo

Radiated Emission




Conducted Emission







9 EUT Construcational Details



















-----End-----