

FCC ID: 2ANJP-ALS08L

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

[illegible]

Mode	CH	PK Output power(dBm)	Output power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11b	CH1	13.91	24.60	1	1.2589	0.00617
	CH6	13.47	22.23	1	1.2589	0.00557
	CH11	13.02	20.04	1	1.2589	0.00502
11g	CH1	12.85	19.28	1	1.2589	0.00483
	CH6	12.79	19.01	1	1.2589	0.00476
	CH11	12.35	17.18	1	1.2589	0.00430
11n/HT20	CH1	11.83	15.24	1	1.2589	0.00382
	CH6	12.28	16.90	1	1.2589	0.00424
	CH11	11.99	15.81	1	1.2589	0.00396
11n/HT40	CH1	10.67	11.67	1	1.2589	0.00292
	CH4	10.34	10.81	1	1.2589	0.00271
	CH7	10.01	10.02	1	1.2589	0.00251
$Pd = \frac{P_{out} * G}{4\pi r^2};$						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power= conducted power. Conducted power see the test report HK1904110790-E, antenna gain=1dBi.						

-----The End-----