

Test Report

Product name: LED TV

Trademark: PHILIPS

Model no.: 43E3FQ

Series Model(s).....: A7A01G, 43PQF7676/F6 A, 43PQF7676/F6,
43PQF7676/F7, 43PQF7656/F7, 43PQF7656/F8

FCC ID: 2ANM343E3FQ

Report No.....: C260605034-RF03

Test Standards.....: CFR47 FCC Part 15: Subpart C Section 15.247
CFR47 FCC Part 15: Subpart C Section 15.207
CFR47 FCC Part 15: Subpart C Section 15.209

Applicant.....: Shenzhen Chuangwei-RGB Electronics Co., Ltd.

Address of applicant.....: 13F-16F, Unit A, Skyworth Building, Shennan Road, Nanshan
District, Shenzhen, Guangdong, China.

Manufacturer.....: Shenzhen Chuangwei-RGB Electronics Co., Ltd.

Manufacturer Address.....: 13F-16F, Unit A, Skyworth Building, Shennan Road, Nanshan
District, Shenzhen, Guangdong, China.


Date of Test Date: Jun 05, 2026 to Jul 10, 2026

Date of issue.....: Sep 16, 2026

Test result: Compliance

Prepared By


:



Adil Yang/Engineer

Reviewed By

:



Greg Zhang/Engineer

Approved By

:



Tom Gan/Manager

The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of preparer, reviewer and approver. Any objections must be raised to CSIC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Revision History

Rev.	Issue Date	Description	Note	Revised By
R00	Sep 16, 2026	Original Report	Valid	Adil Yang

Table of Contents

	Page
1. TEST SUMMARY	4
1.1. TEST DESCRIPTION	4
1.2. TEST FACILITY	5
1.3. MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1. GENERAL DESCRIPTION OF EUT	6
2.2. DESCRIPTION OF TEST MODES AND TEST FREQUENCY	7
2.3. MEASUREMENT INSTRUMENTS LIST	8
2.4. DESCRIPTION OF THE TEST MODES	9
2.5. TEST SOFTWARE AND POWER LEVEL	10
2.6. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.7. DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.8. ENVIRONMENTAL CONDITIONS FOR TESTING	11
3. EMC TEST	12
3.1. CONDUCTED EMISSION ON AC MAINS MEASUREMENT	12
3.2. RADIATED SPURIOUS EMISSION MEASUREMENT	15
3.3. CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH MEASUREMENT	23
3.4. CONDUCTED POWER SPECTRAL DENSITY MEASUREMENT	24
3.5. 6dB BANDWIDTH MEASUREMENT	25
3.6. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT	26
3.7. ANTENNA REQUIREMENT	28
4. TEST PHOTOS	29
5. EUT PHOTOS	30

1. TEST SUMMARY

1.1. TEST DESCRIPTION

Test procedures according to the technical standards:

Item	Clause	Result	Note
Conducted Emission on AC Mains	Part 15.207(a)	PASS	
Maximum Conducted Output Power	Part 15.247(b)(3)	PASS	
Radiated Spurious Emission	Part 15.247(c) Part 15.205	PASS	
Conducted Spurious Emissions Measured in 100 kHz Bandwidth	Part 15.247(d)	PASS	
Conducted Power Spectral Density	Part 15.247(e)	PASS	
6dB Bandwidth	Part 15.247(a)(2)	PASS	
Antenna Requirement	Part 15.247(b)(4) Part 15.203	PASS	

Note:

- 1) "N/A" denotes test is not applicable in this Test Report.
- 2) All tests are according to ANSI C63.10-2020.
- 3) The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
- 4) The information of measurement uncertainty is available upon the customer's request.

1.2. TEST FACILITY

Shenzhen Central Standard International Center Co., Ltd. (CSIC)

Room 201, Building 1, Mogen Fashion Industrial Park, No. 10, Shilongzai Road, Xinshi Community, Dalang Street, Longhua District, Shenzhen.

The test facility is recognized, certified or accredited by the following organizations:

CNAS Registration No.: L11671

FCC Registration No.: 0031378433 Designation Number: CN1317

IC CAB identifier: CN0051

A2LA Lab Cert. No.: 6426.01

1.3. MEASUREMENT UNCERTAINTY

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Below is the best measurement capability for Shenzhen Central Standard International Center Co., Ltd.

Test Items	Measurement Uncertainty	Notes
RF output power, conducted	$\pm 1.06\text{dB}$	(1)
Unwanted Emissions, conducted	$\pm 1.32\text{dB}$	(1)
All emissions, radiated 9KHz-30MHz	$\pm 4.86\text{dB}$	(1)
All emissions, radiated 30-1GHz	$\pm 4.86\text{dB}$	(1)
All emissions, radiated 1G-6GHz	$\pm 5.08\text{dB}$	(1)
All emissions, radiated >6G	$\pm 5.30\text{dB}$	(1)
Conducted Emission (9KHz-150KHz)	$\pm 3.18\text{dB}$	(1)
Conducted Emission (150KHz-30MHz)	$\pm 3.20\text{dB}$	(1)

Note(1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2. GENERAL INFORMATION

2.1. GENERAL DESCRIPTION OF EUT

EUT(Product Specifications)	
Product Name:	LED TV
Model No.:	43E3FQ
Series Models:	A7A01G, 43PQF7676/F6 A, 43PQF7676/F6, 43PQF7676/F7, 43PQF7656/F7, 43PQF7656/F8
Power supply:	AC 120V ~ , 60Hz
Hardware version:	43PQF7676/F6 A
Software version:	Win7_MP_Kit_RTL11n_8723FU_USB_v0.39_20221019
WIFI-2.4G (RF Specifications)	
Supported type:	802.11 b / g / n(HT20) / n(HT40)
Modulation:	DSSS(DBPSK/DQPSK/CCK) for 802.11b OFDM(BPSK, QPSK, 16QAM, 64QAM) for 802.11g/n(HT20)/n(HT40)
Operation frequency:	2412MHz~2462MHz 2422MHz~2452MHz
Operation bandwidth:	20MHz, 40MHz
Channel number:	802.11b/g/n(HT20): 11 802.11n(HT40): 9
Antenna type:	PIFA
Antenna gain:	2.21dBi

Note:

1. For a more detailed features description, please refer to the manufacture's specifications or the user's manual.
2. Full tests were applied to the sample C260605034-Y01/01 only in this document.

2.2. DESCRIPTION OF TEST MODES AND TEST FREQUENCY

The EUT has been tested under typical operating conditions. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting mode for testing.

Operation Frequency List for WIFI:

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	08	2447
02	2417	09	2452
03	2422	10	2457
04	2427	11	2462
05	2432		
06	2437		
07	2442		

For 802.11b/g/n (20MHz)		
Test Channel	EUT Channel	Test Frequency (MHz)
lowest	CH01	2412
middle	CH06	2437
highest	CH11	2462

For 802.11n(40MHz)		
Test Channel	EUT Channel	Test Frequency (MHz)
lowest	CH03	2422
middle	CH06	2437
highest	CH09	2452

2.3. MEASUREMENT INSTRUMENTS LIST

RF Conducted measurement					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY50200391	May. 15, 2027
2	Vector Signal Generator	Agilent	N5182A	MY50140130	May. 15, 2027
3	Signal Generator	R&S	SMCV100B	103780	May. 15, 2027
4	MIMO power meter	KEYSIGHT	U2021XA	MY55080015	May. 15, 2027
5	Automatic control unit	MW	MW100-RFCB	MY54250020	May. 18, 2027
6	Programmable constant temperature and humidity chamber	Angui	AG1000L	2304061049	Jun. 15, 2027
7	MTS 8310E	MW	V 2.0.0.0		
RF Radiated measurement					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI TEST RECEIVER	R&S	ESRP3	101936	May. 15, 2027
2	Spectrum Analyzer	R&S	FSV40	101401	Feb.25, 2027
3	Bilog Antenna	Sunol	JB1	N/A	Jul.10, 2027
4	Horn Antenna	COMMW	ZAB-1-18G-50	20171109	May.16, 2028
5	Horn Antenna	COMMW	ZLB7-18-40G-777	N/A	Feb.28, 2027
6	Amplifier	COMMW	DLNA-30-1000-01	122417799	May 15, 2027
7	Amplifier	COMMW	DPA8-1000-18000-1012	8220837	Feb.25, 2027
8	Amplifier	SKET	LNPA_1840-50	SK201801801	Mar.03, 2027
9	Band Reject Filters	MICRO TRONICS	BRM 50702-02	006	May.20, 2027
10	Band Reject Filters	COMMW	ZBSF-C5500-800-168	N/A	May.20, 2027
11	Cable 6m-1	XINQY	XQY-CLA520-NJ-SMAJ-6M	25051772	May.20, 2027
12	Cable 1m	JunCoax	JA800-NMSM-1M	N/A	May.20, 2027
13	Cable-005	SUCOFLEX	104PEA4M	N/A	May.20, 2027
14	3M Chamber	Maor	9*6*6	--	Aug.15, 2028
15	EZ-EMC	Farad	V3.1		
Mains Terminal Disturbance Voltage Test equipment					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI3	101413	Feb.25, 2027
2	LISN	R&S	ENV216	100002	May.16, 2027
3	LISN	MEB	NNB 42	---	May.16, 2027
4	Cable 1.8m-1	XINQY	XQY-CMR200-NJ-BNCJ-1.8M	---	May.20, 2027
5	Shelding Room	Maor	8*4*3	--	Aug.14, 2028
6	EZ-EMC	Fara	V3.1		

Note: The cable loss has calculated in test result which connection between each test instruments.

2.4. DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n 20 CH1	6.5 Mbps
Mode 8	TX IEEE 802.11n 20 CH6	6.5 Mbps
Mode 9	TX IEEE 802.11n 20 CH11	6.5 Mbps
Mode 10	TX IEEE 802.11n 40 CH3	13.5 Mbps
Mode 11	TX IEEE 802.11n 40 CH6	13.5 Mbps
Mode 12	TX IEEE 802.11n 40 CH9	13.5 Mbps

Note:

- 1) The measurements are performed at the high, middle, low available channels.
- 2) All the bit rate of transmitter have been tested and found the lowest rate is found to be the worst case and recorded.
- 3) This test was performed with EUT in X, Y, Z position and worst case was found when EUT in X position.
- 4) For radiated emission above 1 GHz test, 1GHz-25GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.

2.5. TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	MP Version 0.0001,1020.2018		
Frequency	2412MHz	2437MHz	2462MHz
802.11b	16	16	16
802.11g	16	16	16
802.11n(HT20)	16	16	16
Frequency	2422MHz	2437MHz	2452MHz
802.11n(HT40)	13	13	13

2.6. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.7. DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories					
Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Support units					
Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Notebook	DELL	Vostro 3400	N/A	N/A
C-1	RJ45 Cable	N/A	100cm	N/A	N/A

Note:

- 1) The support equipment was authorized by Declaration of Confirmation.
- 2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.8. ENVIRONMENTAL CONDITIONS FOR TESTING

Test Item	Temperature (°C)	Relative Humidity (%)	Test Voltage	Tested by
Conducted Emission on AC Mains	24.0	69.0	AC 120V 60Hz	Max Ran
Radiated Spurious Emission	25.8	68.0	AC 120V 60Hz	Max Ran
Conducted Spurious Emissions Measured in 100 kHz Bandwidth	25.9	58.0	AC 120V 60Hz	Max Ran
Conducted Power Spectral Density	25.9	58.0	AC 120V 60Hz	Max Ran
6dB Bandwidth	25.9	58.0	AC 120V 60Hz	Max Ran
Maximum Conducted Output Power	25.9	58.0	AC 120V 60Hz	Max Ran

3. EMC TEST

3.1. Conducted Emission on AC Mains Measurement

Limit

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56 *	56 - 46 *
0.5 - 5	56	46
5 - 30	60	50

Note:

- 1) The tighter limit applies at the band edges.
- 2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
RBW	9 kHz

Test Procedure

- a) The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment's powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d) LISN at least 80 cm from nearest part of EUT chassis.
- e) For the actual test configuration, please refer to the related Item –EUT Test Photos.

Test Setup



Note:

- 1) Support units were connected to second LISN.
- 2) Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

Test Results

Note: All modes have been tested, and the report only reflects the worst mode.


Test Mode :	Mode 4	Test Voltage :	AC 120V/60Hz
-------------	--------	----------------	--------------

L



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1P	0.1539	35.40	13.75	10.55	45.95	24.30	65.78	55.79	-19.83	-31.49	Pass
2P	0.2020	31.02	18.72	10.49	41.51	29.21	63.52	53.53	-22.01	-24.32	Pass
3*	0.7220	33.70	20.54	10.23	43.93	30.77	56.00	46.00	-12.07	-15.23	Pass
4P	1.4060	33.31	17.80	9.94	43.25	27.74	56.00	46.00	-12.75	-18.26	Pass
5P	5.5300	31.93	18.45	9.73	41.66	28.18	60.00	50.00	-18.34	-21.82	Pass
6P	10.3020	31.80	17.89	9.78	41.58	27.67	60.00	50.00	-18.42	-22.33	Pass

N



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1P	0.1580	36.07	21.23	10.55	46.62	31.78	65.56	55.57	-18.94	-23.79	Pass
2P	0.2060	32.44	17.52	10.49	42.93	28.01	63.36	53.37	-20.43	-25.36	Pass
3P	0.4860	28.31	19.88	10.39	38.70	30.27	56.24	46.24	-17.54	-15.97	Pass
4*	0.6460	31.80	16.23	10.28	42.08	26.51	56.00	46.00	-13.92	-19.49	Pass
5P	10.5020	32.04	17.29	9.79	41.83	27.08	60.00	50.00	-18.17	-22.92	Pass
6P	12.1620	30.79	16.77	9.81	40.60	26.58	60.00	50.00	-19.40	-23.42	Pass

Correction Factor = insertion loss of LISN + cable loss;

Reading = Reading Amplitude in the instrument;

Result = Correction Factor + Reading;

Margin = Result – Limit

3.2. Radiated Spurious Emission Measurement

Limit

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205 (a)&209(a) limit in the table and according to ANSI C63.10 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- 1) The limit for radiated test was performed according to FCC PART 15C.
- 2) The tighter limit applies at the band edges.
- 3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

For FCC:

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission	
Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AVG
Start Frequency	9 KHz/150KHz(Peak/QP/AVG)
Stop Frequency	150KHz/30MHz(Peak/QP/AVG)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/
	9KHz (From 0.15MHz to 30MHz);
	200Hz (From 9kHz to 0.15MHz)/
	9KHz (From 0.15MHz to 30MHz)
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz
Attenuation	Auto
Detector	Peak/AVG
Start Frequency	1000 MHz(Peak/AVG)
Stop Frequency	10th carrier hamonic(Peak/AVG)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak)
	1 MHz/1/T MHz(AVG)
For Restricted band	
Spectrum Parameter	Setting
Detector	Peak/AVG
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz
	Upper Band Edge: 2476 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak)
	1 MHz/1/T MHz(AVG)
Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for Peak & AVG
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for Peak & AVG
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Test Procedure

- a) The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b) The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- e) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f) For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

DEVIATION FROM TEST STANDARD


No deviation.

Test Setup


1. Radiated Emission Test-Up Frequency Below 30MHz



2. Radiated Emission Test-Up Frequency 30MHz~1GHz



3. Radiated Emission Test-Up Frequency Above 1GHz



EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.


Test Result

Below 1GHz:


All modes have been tested, and the report only reflects the worst mode.

Test Mode: Mode 4

Horizontal



Vertical



Correction Factor = antenna factor + cable loss – amplifier gain;

Reading = Reading Amplitude in the instrument;

Result = Correction Factor + Reading;

Margin = Result – Limit.

Above 1GHz :

Note:


Note: Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

The margin values corresponding to all frequency points are less than 20dB=74dBuV/m - 54dBuV/m, meeting the 54dBuV/m requirement, no average test is performed.


All models were tested, and only the worst model (802.11g) were reported in the report.

Test Mode: 802.11g-Low

Horizontal



Vertical



Correction Factor = antenna factor + cable loss – amplifier gain;


Reading = Reading Amplitude in the instrument;

Result = Correction Factor + Reading;

Margin = Result – Limit.


Test Mode:	802.11g-Middle
------------	----------------

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Remark
1	4808.0000	60.29	-14.21	46.08	74.00	-27.92	peak
2	6508.0000	59.69	-10.66	49.03	74.00	-24.97	peak
3	9748.0000	54.56	-5.32	49.24	74.00	-24.76	peak
4	12185.0000	53.33	-2.23	51.10	74.00	-22.90	peak
5	14622.0000	50.64	1.98	52.62	74.00	-21.38	peak
6	14622.0000	36.93	1.98	38.91	54.00	-15.09	AVG
7	17796.0000	52.22	8.44	60.66	74.00	-13.34	peak
8*	17796.0000	35.11	8.44	43.55	54.00	-10.45	AVG

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Remark
1	4808.0000	65.36	-14.21	51.15	74.00	-22.85	peak
2	6508.0000	63.30	-10.66	52.64	74.00	-21.36	peak
3	6508.0000	49.40	-10.66	38.74	54.00	-15.26	AVG
4	9748.0000	54.92	-5.32	49.60	74.00	-24.40	peak
5	12185.0000	53.54	-2.23	51.31	74.00	-22.69	peak
6	14622.0000	51.33	1.98	53.31	74.00	-20.69	peak
7	14622.0000	37.71	1.98	39.69	54.00	-14.31	AVG
8	17830.0000	52.37	8.50	60.87	74.00	-13.13	peak
9*	17830.0000	35.07	8.50	43.57	54.00	-10.43	AVG

Correction Factor = antenna factor + cable loss – amplifier gain;


Reading = Reading Amplitude in the instrument;

Result = Correction Factor + Reading;

Margin = Result – Limit.


Test Mode:	802.11g-High
------------	--------------

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Remark
1	4808.0000	61.69	-14.21	47.48	74.00	-26.52	peak
2	6576.0000	59.34	-10.14	49.20	74.00	-24.80	peak
3	9848.0000	53.65	-5.00	48.65	74.00	-25.35	peak
4	12310.0000	54.05	-2.00	52.05	74.00	-21.95	peak
5	12310.0000	40.65	-2.00	38.65	54.00	-15.35	AVG
6	14772.0000	52.19	2.39	54.58	74.00	-19.42	peak
7	14772.0000	38.59	2.39	40.98	54.00	-13.02	AVG
8	17796.0000	52.41	8.44	60.85	74.00	-13.15	peak
9*	17796.0000	34.94	8.44	43.38	54.00	-10.62	AVG

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin(dB)	Remark
1	4808.0000	64.13	-14.21	49.92	74.00	-24.08	peak
2	6576.0000	60.72	-10.14	50.58	74.00	-23.42	peak
3	9848.0000	54.74	-5.00	49.74	74.00	-24.26	peak
4	12310.0000	53.82	-2.00	51.82	74.00	-22.18	peak
5	14772.0000	52.48	2.39	54.87	74.00	-19.13	peak
6	14772.0000	38.04	2.39	40.43	54.00	-13.57	AVG
7	17796.0000	52.68	8.44	61.12	74.00	-12.88	peak
8*	17796.0000	35.66	8.44	44.10	54.00	-9.90	AVG

Correction Factor = antenna factor + cable loss – amplifier gain;

Reading = Reading Amplitude in the instrument;

Result = Correction Factor + Reading;

Margin = Result – Limit.

3.3. Conducted Spurious Emissions Measured in 100 kHz Bandwidth Measurement


Limit

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Test Procedure

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold
For Band edge	
Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2327 – 2427 MHz
	Upper Band Edge: 2447 – 2547 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

Test Configuration



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.4. Conducted Power Spectral Density Measurement

Limits

Section	Test Item	Limit	Frequency Range (MHz)
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5

Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.5. 6dB Bandwidth Measurement

Limits

Section	Test Item	Limit	Frequency Range (MHz)
15.247 (a)(2)	6dB Bandwidth	≥500KHz	2400-2483.5

Test Procedure

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW- 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be- 6 dB.

TEST SETUP



EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.6. Maximum Conducted Output Power Measurement

Limits

Section	Test Item	Limit	Frequency Range (MHz)
15.247 (b)(3)	Output Power	1 watt or 30dBm	2400-2483.5

Test Procedure

Some regulatory agencies permit the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for determining compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than to the DTS bandwidth (see 11.2 for definitions and 6.9.2 for measurement guidance).

When using a spectrum analyzer or EMI receiver to perform these measurements, it shall be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span / RBW, to set a bin-to-bin spacing of $\leq \text{RBW} / 2$ so that narrowband signals are not lost between frequency bins. If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see 11.6).

The intent is to test at 100% duty cycle; however, a small reduction in duty cycle (to no lower than 98%) is permitted, if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test laboratory to permit such continuous operation.

If continuous transmission (or at least 98% duty cycle) cannot be achieved because of hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level, with the transmit duration as long as possible, and the duty cycle as high as possible during which sweep triggering/signal gating techniques may be used to perform the measurement over the transmission duration.

Measurement using a power meter (PM):

1. Method AVGPM:

Method AVGPM is a measurement using an RF average power meter, as follows:

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied:

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.


c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.

d) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

2. Method AVGPM-G:

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

TEST SETUP**EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.7. ANTENNA REQUIREMENT

STANDARD REQUIREMENT

According to the manufacturer declared, the EUT has PIFA, the directional gain of antenna is 2.21dBi, and the antenna connector is designed with a reverse polarity socket and does not consider replacement. Therefore, the EUT is considered sufficient to comply with the provision.

EUT ANTENNA

The EUT antenna is PIFA. It complies with the standard requirement.



4. TEST PHOTOS

Please refer to Appendix D Test Setup.

5. EUT PHOTOS

External Photos Please refer to Appendix B and Internal Photos Please refer to Appendix C.

*****THE END*****