

RF Exposure Evaluation

FCC ID: 2ANM4SL-9068

1. Client Information

Applicant : Shenzhen qiuyu Electronic Co.,Ltd
Address : 3F, E Building, Hongzhuyongqi Industrial Park, Lezhujiao village, xixiang town, Bao'an District, Shenzhen, China
Manufacturer : Shenzhen qiuyu Electronic Co.,Ltd
Address : 3F, E Building, Hongzhuyongqi Industrial Park, Lezhujiao village, xixiang town, Bao'an District, Shenzhen, China

2. General Description of EUT

EUT Name	:	Bluetooth speaker desk lamp	
Models No.	:	SL-9068	
Product Description	:	Operation Frequency:	Bluetooth V4.0: 2402~2480 MHz
		RF Output Power:	Bluetooth: 2.063dBm(GFSK)
		Antenna Gain:	1.2dBi PCB Antenna
Power Supply	:	DC Voltage supplied by AC/DC Adapter	
Power Rating	:	Adapter Mode(SL120300) Input:100-240V 50/60Hz 0.8A Output:12V/3A	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR}$$

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] * [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0 \text{ for 10-g SAR}$$

2. Calculation:

Test separation: 5mm

Bluetooth Mode (GFSK)

Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	2.063	1.5±1	2.5	1.778	0.551	3.0
2.441	1.500	1.5±1	2.5	1.778	0.556	3.0
2.480	0.846	1.5±1	2.5	1.778	0.560	3.0

Bluetooth Mode ($\pi/4$ -DQPSK)

Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	0.824	0±1	1	1.259	0.390	3.0
2.441	0.468	0±1	1	1.259	0.393	3.0
2.480	-0.203	0±1	1	1.259	0.397	3.0

Bluetooth Mode (8-DPSK)

Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dbm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	1.012	0.5±1	1.5	1.413	0.438	3.0
2.441	0.250	0.5±1	1.5	1.413	0.441	3.0
2.480	-0.170	0.5±1	1.5	1.413	0.445	3.0

So standalone SAR measurements are not required.

-----END OF REPORT-----