LTA
Laboratory for Test & Approval Co.,Ltd.
243 Jubug-Ri,Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159
Tel: +82-31-323-6008 Fax: +82-31-323-6010
http://www.ltalab.com

Dates of Tests: September 10 ~ September 28, 2017
Test Report S/N: LR500111710F
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID. **2ANM8IDRM1A**

APPLICANT **INDI TAG Co.,Ltd.**

Equipment Class	:	**Digital Transmission System (DTS)**
Manufacturing Description	:	**Remote Controller**
Manufacturer	:	**INDI TAG Co.,Ltd.**
Model name	:	**IDRM1A**
Test Device Serial No.:	:	**Identical prototype**
Rule Part(s)	:	**FCC Part 15.247 Subpart C ; ANSI C-63.4-2014**
Frequency Range	:	**2405 MHz ~ 2480 MHz**
Max. Output Power	:	**Max 7.84 dBm – Conducted**
Data of issue	:	**September 30, 2017**

This test report is issued under the authority of:

Yong-Cheol, Wang / Manager

The test was supervised by:

Eun-hwan, Jung / Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NVLAP LAB Code.: 200723-0

Copyright © 2017, LTA Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION ---------- 3

2. INFORMATION ABOUT TEST ITEM ---------- 4

3. TEST REPORT ---------- 6

3.1 SUMMARY OF TESTS ---------- 6

3.2 TECHNICAL CHARACTERISTICS TEST ---------- 7

3.2.1 6 dB BANDWIDTH ---------- 7

3.2.2 PEAK OUTPUT POWER ---------- 10

3.2.3 POWER SPECTRAL DENSITY ---------- 13

3.2.4 BAND EDGE ---------- 16

3.2.5 CONDUCTED SPURIOUS EMISSIONS ---------- 19

3.2.6 RADIATED SPURIOUS EMISSIONS ---------- 22

APPENDIX

APPENDIX TEST EQUIPMENT USED FOR TESTS ---------- 34

Copyright © 2017, LTA Co., Ltd.

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
Address : 243, Jubug-ri,Yangji-Myeon,Youngin-Si, Kyunggi-Do, Korea. 17159
Web site : http://www.ltalab.com
E-mail : chahn@ltalab.com
Telephone : +82-31-323-6008
Facsimile +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2017-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2019-04-13	FCC CAB
VCCI	JAPAN	R2133(10 m), C2307	Updating	VCCI registration
VCCI	JAPAN	T-2009	2017-12-23	VCCI registration
VCCI	JAPAN	G-563	2018-12-13	VCCI registration
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

Copyright © 2017, LTA Co., Ltd.

2. Information about test item

2-1 Client & Manufacturer

Company name	:	INDI TAG Co., Ltd.
Address	:	Nambusunhwan-ro 347-gil Seocho-gu, Seoul, Korea
Tel / Fax	:	TEL No : +82-2-3272-0068

2-3 Equipment Under Test (EUT)

Trade name	:	INDI TAG Co.,Ltd.
Model name	:	IDRM1A
Serial number	:	Identical prototype
Date of receipt	:	September 10, 2017
EUT condition	:	Pre-production, not damaged
Antenna type	:	IFA antenna - Max Gain 0 dBi
Frequency Range	:	2405 MHz ~ 2480 MHz
RF output power	:	Max 7.04 dBm – Conducted
Number of channels	:	16
Type of Modulation	:	Direct Sequence Spread Spectrum(DSSS)
Power Source	:	12 Vdc
Firmware Version	:	V1.0.0

Copyright © 2017, LTA Co., Ltd.

2-3 Tested frequency

Zigbee	LOW	MID	HIGH
Frequency (MHz)	2405	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	CR720	MS-1736	MSI

Copyright © 2017, LTA Co., Ltd.

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Transmitter Peak Output Power	< 1 Watt		C
15.247(d)	Transmitter Power Spectral Density	< 8 dBm @ 3 kHz		C
15.247(d)	Band Edge	> 20 dBc		C
15.209	Field Strength of Harmonics	Emission	Radiated	C
15.207	AC Conducted Emissions	Emissions	Conducted	N/A
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

→ Antenna Requirement
The INDI TAG Co.,Ltd. FCC ID: 2ANM8IDRM1A unit complies with the requirement of §15.203.
The antenna type is IFA Antenna

The sample was tested according to the following specification:
*FCC Parts 15.247; ANSI C-63.4-2014
*FCC KDB Publication No. 558074 v03r05
*FCC TCB Workshop 2012, April

Copyright © 2017, LTA Co., Ltd.

3.2 Technical Characteristics Test

3.2.1 6 dB Bandwidth

Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz

Span = 5 MHz

VBW = 100 kHz (VBW ≥ RBW)

Sweep = auto

Trace = max hold

Detector function = peak

Measurement Data : Complies

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	**1.5991**	Complies
2440	**1.6064**	Complies
2480	**1.6136**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

6 dB Bandwidth > 500 kHz

Measurement Setup



Figure 1: Measurement setup for the carrier frequency separation

Low Channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4047178 GHz	2.59 dBm	ndB down	1.5991 MHz
T1		1	2.4041823 GHz	-3.13 dBm	ndB	6.00 dB
T2		1	2.4057815 GHz	-3.23 dBm	Q factor	1503.8

Middle Channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4402388 GHz	2.43 dBm	ndB down	1.6064 MHz
T1		1	2.4391751 GHz	-3.69 dBm	ndB	6.00 dB
T2		1	2.4407815 GHz	-3.39 dBm	Q factor	1519.1

Copyright © 2017, LTA Co., Ltd.

High Channel



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.479725 GHz	1.85 dBm	ndB down	1.6136 MHz
T1		1	2.4791751 GHz	-4.11 dBm	ndB	6.00 dB
T2		1	2.4807887 GHz	-4.26 dBm	Q factor	1536.8

3.2.2 Peak Output Power Measurement

Procedure:

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1MHz

Span = auto

VBW = 1MHz (VBW ≥ RBW)

Sweep = auto

Detector function = peak

Measurement Data (Port 1) : Complies

Frequency (MHz)	Test Results		
	dBm	W	Result
2405	**6.61**	**0.0046**	Complies
2440	**7.82**	**0.0061**	Complies
2480	**7.84**	**0.0061**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

Peak output power	< 1 W

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2017, LTA Co., Ltd.

Low Channel



Middle Channel



Copyright © 2017, LTA Co., Ltd.

High Channel



3.2.3 Power Spectral Density

Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 3 kHz	Span = 300 kHz
VBW = 3 kHz	Sweep = auto
Detector function = peak	Trace = max hold

Measurement Data (Port 1) : Complies

Frequency (MHz)	Test Results	
	dBm @ 3kHz	Result
2405	**-9.14**	Complies
2440	**-9.54**	Complies
2480	**-9.83**	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

Power Spectral Density	< 8 dBm @ 3 kHz BW

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2017, LTA Co., Ltd.

Power Density Measurement

Low Channel



Middle Channel



Copyright © 2017, LTA Co., Ltd.

High Channel



3.2.4 Band - edge

Procedure:

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz	VBW = 100 kHz
Span = 40 MHz	Detector function = peak
Trace = max hold	Sweep = auto

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK:	RBW = VBW = 1 MHz, Sweep=Auto
Average:	RBW = 1 MHz, VBW=10 Hz, Sweep=Auto
Measurement Distance:	3 m
Polarization:	Horizontal / Vertical

Measurement Data: Complies

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the require ment.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc

Copyright © 2017, LTA Co., Ltd.

Band edge

Lower edge



Upper edge



Copyright © 2017, LTA Co., Ltd.

Radiated Band-edges in the restricted band 2310-2390 MHz measurement

Frequency [MHz]	Reading [dBuV/m] AV	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna	Correction Factor Amp. Gain + Cable Loss	Limits [dBuV/m] AV	Limits [dBuV/m] Peak	Result [dBuV/m] AV	Result [dBuV/m] Peak	Margin [dB] AV	Margin [dB] Peak
2375.2	31.2	47.5	V	25.4	30.1	54.0	74.0	26.5	42.8	27.5	31.2

Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV/m] AV	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna	Correction Factor Amp. Gain + Cable Loss	Limits [dBuV/m] AV	Limits [dBuV/m] Peak	Result [dBuV/m] AV	Result [dBuV/m] Peak	Margin [dB] AV	Margin [dB] Peak
2487.4	43.9	57.9	V	25.4	30.1	54.0	74.0	39.2	53.2	14.8	20.8

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented

Copyright © 2017, LTA Co., Ltd.

3.2.5 Conducted Spurious Emissions

Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels..

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz Detector function = peak

Trace = max hold

Measurement Data: **Complies**

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the require ment.
- See next pages for actual measured spectrum plots.

Minimum Standard:	> 20 dBc

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)

Copyright © 2017, LTA Co., Ltd.

Unwanted Emission – Low Channel

Frequency Range = 30 MHz ~ 26.5 GHz



Middle Channel



High Channel



3.2.6 Radiated Spurious Emissions

Procedure:

The EUT was placed on a 0.8m high wooden table inside a shielded enclosure. An antenna was placed near the EUT and measurements of frequencies and amplitudes of field strengths were recorded for reference during final measurements. For final radiated testing, measurements were performed in OATS. Measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 100 kHz (30 MHz ~ 1 GHz) VBW ≥ RBW

= 1 MHz (1 GHz ~ 10th harmonic)

Span = 100 MHz Detector function = peak

Trace = max hold Sweep = auto

below 30 MHz



below 1 GHz (30 MHz to 1 GHz)



above 1 GHz



Measurement Data: Complies

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30 MHz.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) **(@ 300 m)**
0.490 ~ 1.705	24000/F(kHz) **(@ 30 m)**
1.705 ~ 30	30**(@ 30 m)**
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-80 6 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Copyright © 2017, LTA Co., Ltd.

Measurement Data : (Above 1 GHz)

Frequency [MHz]	Reading [dBuV/m] AV	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna	Correction Factor Amp.Gain+Cable	Limits [dBuV/m] AV	Limits [dBuV/m] Peak	Result [dBuV/m] AV	Result [dBuV/m] Peak	Margin [dB] AV	Margin [dB] Peak
2055.3	32.4	47.7	H	8.33	6.42	60.0	80.0	34.31	49.61	25.69	30.39
2848.7	31.5	45.4	H	10.33	4.23	60.0	80.0	38.50	52.00	21.50	28.00
2055.2	33.4	47.5	H	8.33	6.42	60.0	80.0	35.31	49.41	24.69	30.59

- No other emissions were detected at a level greater than 20 dB below limit.

Measurement Data : (Below 1 GHz)

Frequency [MHz]	Reading [dBuV/m] AV	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna	Correction Factor Amp.Gain+Cable	Limits [dBuV/m] AV	Limits [dBuV/m] Peak	Result [dBuV/m] AV	Result [dBuV/m] Peak	Margin [dB] AV	Margin [dB] Peak
38.73	50.63	59.24	V	11.32	-25.67	54.0	74.0	45.9	54.5	8.1	19.5
38.73	50.74	57.95	V	11.32	-25.67	54.0	74.0	46.0	53.3	8.0	20.8
38.73	50.81	60.24	V	11.32	-25.67	54.0	74.0	46.1	55.5	7.9	18.5

- No other emissions were detected at a level greater than 20 dB below limit.

Measurement Data: (9 kHz – 30 MHz)

Frequency [MHz]	Reading [dBuV/m] Peak	Pol.	Correction Factor Antenna +Cable-Amp.Gain	Limits [dBuV/m] Peak	Result [dBuV/m] Peak	Margin [dB] Peak
*No emissions were detected at a level greater than 20 dB below limit.						

*No emissions were detected at a level greater than 20 dB below limit.

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4 GHz Zigbee(Low) mode, Vertical

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: IDRM1A Temp/Humi: 24 / 58

Test Mode : Wireless mode (LOW) Tested by: LEE H W

Data: 1615 File: C:\Program Files (x86)\e3\1709-1.EM6 (1680)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
38.73	50.63	-14.35	36.28	39.00	2.72	218	97	VERTICAL
63.95	49.90	-15.04	34.86	39.00	4.14	205	54	VERTICAL
125.06	47.14	-13.31	33.83	43.50	9.67	188	251	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4 GHz Zigbee(Low) mode, Horizontal

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: IDRM1A Temp/Humi: 24 / 58

Test Mode : Wireless mode (LOW) Tested by: LEE H W

Data: 1614 File: C:\Program Files (x86)\e3\1709-1.EM6 (1680)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
350.10	37.38	-9.59	27.79	46.40	18.61	299	54	HORIZONTAL
400.54	33.43	-8.49	24.94	46.40	21.46	320	266	HORIZONTAL
505.30	31.92	-6.54	25.38	46.40	21.02	322	41	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee(Middle) mode, Vertical

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: IDRM1A Temp/Humi: 24 / 58

Test Mode : Wireless mode (MID) Tested by: LEE H W

Data: 1617 File: C:\Program Files (x86)\e3\1709-1.EM6 (1680)



Freq	Reading	C.F	Result QP	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
38.73	50.74	-14.35	36.39	39.00	2.61	207	133	VERTICAL
65.89	49.15	-15.32	33.83	39.00	5.17	117	82	VERTICAL
125.06	47.50	-13.31	34.19	43.50	9.31	205	96	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee(Middle) mode, Horizontal

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: IDRM1A Temp/Humi: 24 / 58

Test Mode : Wireless mode (MID) Tested by: LEE H W

Data: 1616 File: C:\Program Files (x86)\e3\1709-1.EM6 (1680)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
350.10	38.16	-9.59	28.57	46.40	17.83	211	305	HORIZONTAL
375.32	35.99	-8.94	27.05	46.40	19.35	211	168	HORIZONTAL
500.45	33.72	-6.64	27.08	46.40	19.32	259	55	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4GHz Zigbee(High) mode, Vertical

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: IDRM1A Temp/Humi: 24 / 58

Test Mode : Wireless mode (HIGH) Tested by: LEE H W

Data: 1619 File: C:\Program Files (x86)\e3\1709-1.EM6 (1680)



Freq	Reading	C.F	Result QP	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
38.73	50.81	-14.35	36.46	39.00	2.54	288	128	VERTICAL
63.95	49.70	-15.04	34.66	39.00	4.34	209	255	VERTICAL
125.06	46.91	-13.31	33.60	43.50	9.90	266	175	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

- 1 -

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Below 1 GHz) – 2.4 GHz Zigbee(High) mode, Horizental

LTA
Laboratory for Test & Approval Co.,Ltd.
4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: IDRM1A Temp/Humi: 24 / 58

Test Mode : Wireless mode (HIGH) Tested by: LEE H W

Data: 1618 File: C:\Program Files (x86)\e3\1709-1.EM6 (1680)



Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
350.10	38.36	-9.59	28.77	46.40	17.63	215	25	HORIZONTAL
400.54	34.12	-8.49	25.63	46.40	20.77	229	63	HORIZONTAL
505.30	31.98	-6.54	25.44	46.40	20.96	277	310	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Copyright © 2017, LTA Co., Ltd.

Radiated Emissions (Above 1 GHz) – 2.4 GHz Zigbee(Low) mode

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: IDRM1A
Tested by : LEE H W
Test Mode: Wireless mode (LOW)
Temp/Humi: 24 / 58



	Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
1	2055.30	47.70	1.91	49.61	80.00	30.39	HORIZONTAL
2	2055.30	32.40	1.91	34.31	60.00	25.69	HORIZONTAL
3	2879.60	31.10	6.48	37.58	60.00	22.42	HORIZONTAL
4	2879.60	45.20	6.48	51.68	80.00	28.32	HORIZONTAL
5	2919.60	30.50	6.92	37.42	60.00	22.58	VERTICAL
6	2919.60	44.50	6.92	51.42	80.00	28.58	VERTICAL
7	2984.20	31.60	7.64	39.24	60.00	20.76	HORIZONTAL
8	2984.20	45.80	7.64	53.44	80.00	26.56	HORIZONTAL
9	5844.20	32.40	20.84	53.24	80.00	26.76	VERTICAL
10	5844.20	16.50	20.84	37.34	60.00	22.66	VERTICAL
11	5908.20	32.40	21.25	53.65	80.00	26.35	VERTICAL
12	5908.20	15.40	21.25	36.65	60.00	23.35	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

Radiated Emissions (Above 1 GHz) – 2.4 GHz Zigbee(Middle) mode

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: IDRM1A
Tested by : LEE H W
Test Mode: Wireless mode (MID)
Temp/Humi: 24 / 58



	Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
1	2108.60	48.30	2.14	50.44	80.00	29.56	VERTICAL
2	2108.60	33.80	2.14	35.94	60.00	24.06	VERTICAL
3	2848.70	45.90	6.10	52.00	80.00	28.00	HORIZONTAL
4	2848.70	32.40	6.10	38.50	60.00	21.50	HORIZONTAL
5	2948.20	31.50	7.18	38.68	60.00	21.32	HORIZONTAL
6	2948.20	45.40	7.18	52.58	80.00	27.42	HORIZONTAL
7	5153.60	32.90	18.47	51.37	80.00	28.63	HORIZONTAL
8	5153.60	16.80	18.47	35.27	60.00	24.73	HORIZONTAL
9	5845.60	15.40	20.85	36.25	60.00	23.75	VERTICAL
10	5845.60	30.50	20.85	51.35	80.00	28.65	VERTICAL
11	5984.60	31.50	21.81	53.31	80.00	26.69	VERTICAL
12	5984.60	15.40	21.81	37.21	60.00	22.79	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

Radiated Emissions (Above 1 GHz) – 2.4 GHz Zigbee(High) mode

LTA
Laboratory for Test & Approval Co.,Ltd.

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho.by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: IDRM1A Test Mode: Wireless mode (HIGH)

Tested by : LEE H W Temp/Humi: 24 / 58



	Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
1	2055.20	47.50	1.91	49.41	80.00	30.59	HORIZONTAL
2	2055.20	33.40	1.91	35.31	60.00	24.69	HORIZONTAL
3	2132.50	33.70	2.20	35.90	60.00	24.10	HORIZONTAL
4	2132.50	48.20	2.20	50.40	80.00	29.60	HORIZONTAL
5	5105.30	32.70	18.55	51.25	80.00	28.75	VERTICAL
6	5105.30	16.40	18.55	34.95	60.00	25.05	VERTICAL
7	5542.80	32.80	19.77	52.57	80.00	27.43	HORIZONTAL
8	5542.80	15.80	19.77	35.57	60.00	24.43	HORIZONTAL
9	5811.60	32.90	20.63	53.53	80.00	26.47	VERTICAL
10	5811.60	17.20	20.63	37.83	60.00	22.17	VERTICAL
11	5894.50	16.50	21.15	37.65	60.00	22.35	VERTICAL
12	5894.50	32.80	21.15	53.95	80.00	26.05	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

- 1 -

Copyright © 2017, LTA Co., Ltd.

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2017-09-07
2	■	Signal Generator (~3.2 GHz)	8648C	3623A02597	HP	1 year	2017-03-20
3		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2017-03-20
4		Attenuator (3 dB)	8491A	37822	HP	1 year	2017-09-07
5		Attenuator (10 dB)	8491A	63196	HP	1 year	2017-09-07
6	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2017-09-07
7	■	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2017-09-07
8	■	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2017-03-21
9	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2016-08-04
10		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2016-05-03
11	■	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2016-05-03
12	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2017-04-17
13		Temp.Humidity Data Logger	SK-L200TH II A	00801	SATO	1 year	2017-03-21
14		Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-	-
15	■	DC Power Supply	6674A	3637A01657	Agilent	-	-
16		Frequency Counter	5342A	2826A12411	HP	1 year	2017-03-21
17	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2017-03-20
18	■	Power Sensor	8481A	3318A94972	HP	1 year	2016-12-30
19		Audio Analyzer	8903B	3729A18901	HP	1 year	2017-09-07
20		Modulation Analyzer	8901B	3749A05878	HP	1 year	2017-09-07
21		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2017-09-07
22		Stop Watch	HS-3	812Q08R	CASIO	2 year	2017-03-21
23		LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2017-09-07
24		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2017-03-20
25		UNIVERSAL RADIO COMMUNICATION TESTER	CMU200	106243	R&S	1 year	2017-03-20
26		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2017-03-20
27		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2017-03-20
28		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2017-03-21
29		Signal Generator(100 kHz ~ 40 GHz)	SMB100A03	177621	R&S	1 year	2017-03-23
30		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2017-03-21

Copyright © 2017, LTA Co., Ltd.