

TEST REPORT

Report No.: BCTC2507643677-4E

Applicant: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY
CO.,LTD

Product Name: Smart Phone

Test Model: C3

Tested Date: 2025-06-10 to 2025-07-08
2025-07-17 to 2025-07-25

Issued Date: 2025-07-25

Shenzhen **BCTC** Testing Co., Ltd.



FCC ID: 2ANMU-C3

Product Name: Smart Phone

Trademark: OUKITEL

Model/Type reference: C3
C3 S, C3 Pro, C3 Ultra, C3 E, C3 Plus, C3 MAX

Prepared For: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD

Address: A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE,
GUANLAN, LONGHUA SHENZHEN, China

Manufacturer: SHENZHEN YUNJI INTELLIGENT TECHNOLOGY CO.,LTD

Address: A2 2F BUILDING ENET NEW INDUSTRIAL PARK, DAFU INDUSTRIAL ZONE,
GUANLAN, LONGHUA SHENZHEN, China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng,
Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2025-06-10

Sample tested Date: 2025-06-10 to 2025-07-08
2025-07-17 to 2025-07-25


Issue Date: 2025-07-25

Report No.: BCTC2507643677-4E

Test Standards: FCC Part15 15.407
ANSI C63.10-2013
KDB 789033 D02 v02r01

Test Results: PASS

Tested by:



Brave Zeng/ Project Handler

Approved by:



Zero Zhou/Reviewer


The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration	Page
1. Version	5
2. Test Summary	6
3. Measurement Uncertainty	7
4. Product Information And Test Setup	8
4.1 Product Information	8
4.2 Test Setup Configuration	8
4.3 Support Equipment	9
4.4 Channel List	9
4.5 Test Mode	10
5. Test Facility And Test Instrument Used	11
5.1 Test Facility	11
5.2 Test Instrument Used	11
6. Conducted Emissions	13
6.1 Block Diagram Of Test Setup	13
6.2 Limit	13
6.3 Test Procedure	13
6.4 EUT Operating Conditions	13
6.5 Test Result	14
7. Radiated Emissions	16
7.1 Block Diagram Of Test Setup	16
7.2 Limit	17
7.3 Test Procedure	18
7.4 EUT Operating Conditions	19
7.5 Test Result	19
8. Power Spectral Density Test	34
8.1 Block Diagram Of Test Setup	34
8.2 Limit	34
8.3 Test Procedure	35
8.4 EUT Operating Conditions	35
8.5 Test Result	36
9. 26dB & 6dB & 99% Emission Bandwidth	51
9.1 Block Diagram Of Test Setup	51
9.2 Limit	51
9.3 Test Procedure	51
9.4 EUT Operating Conditions	52
9.5 Test Result	52
10. Maximum Conducted Output Power	82
10.1 Block Diagram Of Test Setup	82
10.2 Limit	82
10.3 Test Procedure	82
10.4 EUT Operating Conditions	83
10.5 Test Result	84
11. Out Of Band Emissions	85


11.1	Block Diagram Of Test Setup.....	85
11.2	Limit	85
11.3	Test Procedure	85
11.4	EUT Operating Conditions	85
11.5	Test Result.....	86
12.	Spurious RF Conducted Emissions.....	98
12.1	Block Diagram Of Test Setup.....	98
12.2	Limit	98
12.3	Test Procedure	98
12.4	Test Result.....	98
13.	Frequency Stability Measurement.....	113
13.1	Block Diagram Of Test Setup.....	113
13.2	Limit	113
13.3	Test Procedure	113
13.4	Test Result.....	114
14.	Duty Cycle Of Test Signal	120
14.1	Standard Requirement	120
14.2	Formula.....	120
14.3	Test Procedure	120
14.4	Test Result.....	120
15.	Antenna Requirement	128
15.1	Limit	128
15.2	Test Result.....	128
16.	EUT Photographs.....	129
17.	EUT Test Setup Photographs.....	130

(Note: N/A Means Not Applicable)



1. Version

Report No.	Issue Date	Description	Approved
BCTC2507643677-4E	2025-07-25	Original	Valid



2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Spurious Radiated Emissions	15.209(a), 15.407 (b)(1) 15.407 (b)(4) 15.407 (b)(8)	PASS
2	Conducted Emission	15.207	PASS
3	26 dB and 99% Emission Bandwidth	15.407 (a)(12) 15.1049	PASS
4	Minimum 6 dB bandwidth	15.407(e)	PASS
5	Maximum Conducted Output Power	15.407 (a)(1) 15.407 (a)(3)	PASS
6	Band Edge	2.1051, 15.407(b)(1) 15.407(b)(4)	PASS
7	Power Spectral Density	15.407 (a)(1) 15.407 (a)(3)	PASS
8	Spurious Emissions at Antenna Terminals	2.1051, 15.407(b)	PASS
9	Antenna Requirement	15.203	PASS

Note: "N/A" means not applicable in this report.

Remark:

Based on the following changes in the original test report (BCTC2506663044-4E), No changes were made to the product.

Only changes the appearance of the product (the internal boards and circuits remain unchanged), Model/Type reference, Test Instrument Used, EUT Photographs, EUT Test Setup Photographs, and retests Conducted Emission & Radiated Emissions.

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C

4. Product Information And Test Setup

4.1 Product Information

Model/Type reference:	C3 C3 S, C3 Pro, C3 Ultra, C3 E, C3 Plus, C3 MAX
Model differences:	All the model are the same circuit and RF module, except model names.
Hardware Version:	J566A_610&310_D3EF_V1.0
Software Version:	OUKITELE_C2_EEA_V05_20250618
IEEE 802.11 WLAN Mode Supported	802.11a/n/ac(20MHz channel bandwidth) 802.11n/ac(40MHz channel bandwidth) 802.11ac(80MHz channel bandwidth)
Operation Frequency:	5180-5240MHz for 802.11a/n(HT20)/ac(HT20); 5190-5230MHz for 802.11n(HT40)/ac(HT40); 5210MHz for 802.11 ac(HT80); 5745-5825 MHz for 802.11a/n(HT20)/ac(HT20); 5755-5795 MHz for 802.11n(HT40)/ac(HT40); 5775MHz for 802.11 ac(HT80);
Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT20): NSS1, MCS0-MCS8 802.11ac(VHT40/VHT80):NSS1, MCS0-MCS
Type of Modulation:	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac; 4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band ; 2 channels for 802.11 n40/ac40 in the 5190-5230MHz band ;
Number Of Channel	1 channels for 802.11 ac80 in the 5210MHz band ; 5 channels for 802.11a/n20/ac20 in the 5745-5825MHz band ; 2 channels for 802.11 n40/ac40 in the 5755-5795MHz band ; 1 channels for 802.11 ac80 in the 5775MHz band
Antenna installation:	Internal antenna 0.84 dBi
Antenna Gain:	Remark: ☐ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. ☒ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information.
Ratings:	DC 5V from adapter/DC 3.87V from battery
Adapter Information:	Model: HJ-0502000N2-US Input: 100-240V~50/60Hz 0.3A Output: DC 5.0V 2.0A 10.0W

4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Smart Phone	OUKITEL	C3	N/A	EUT
E-2	Adapter	/	HJ-0502000N2-US	N/A	Auxiliary
E-3	TF card	SanDisk	32G	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0M	DC cable unshielded

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

5.1G

802.11a/n/ac (20MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

802.11n /ac(40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

802.11ac (80MHz) Carrier Frequency Channel	
Channel	Frequency (MHz)
42	5210

5.8G

802.11a/n/ac(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

802.11n/ac (40MHz) Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

802.11ac (80MHz) Carrier Frequency Channel	
Channel	Frequency (MHz)
155	5775

4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11a / n/ ac 20 CH36/ CH40/ CH 48 802.11a /n/ ac 20 CH149/ CH157/ CH 165
Mode 2	802.11n/ ac40 CH38/ CH 46 802.11n/ ac40 CH 151 / CH 159
Mode 3	802.11 ac80 CH 42/CH 155
Mode 4	WIFI Link

Note:

1. The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	CMD		
Parameters	DEF	DEF	DEF

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583


ISED CAB identifier: CN0017

5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 08, 2025	May 07, 2026
LISN	R&S	ENV216	101375	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 14, 2025	May 13, 2026


RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	\	May 14, 2025	May 13, 2026
Power Sensor (AV)	Keysight	E9300A	\	May 14, 2025	May 13, 2026
Signal Analyzer20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 14, 2025	May 13, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Communication test set	R&S	CMW500	126173	May 14, 2025	May 13, 2026
Radio frequency control box	MAIWEI	MW200-RFC B	\	\	\
Software	MAIWEI	MTS 8200	\	\	\

Radiated Emissions Test (966 Chamber02)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	SKET	966 Room	966	Oct. 31. 2024	Oct. 30. 2027
Receiver	R&S	ESR3	102075	May 14, 2025	May 13, 2026
Receiver	R&S	ESR317	100010	May 14, 2025	May 13, 2026
Amplifier	SKET	LNPA-30M01 G-30	SK2021082004	May 14, 2025	May 13, 2026
TRILOG Broadband Antenna	Schwarzbeck	VULB9168	1323	May 24, 2025	May 23, 2026
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 24, 2025	May 23, 2026
Amplifier	SKET	LAPA_01G18 G-45dB	SK202104090 1	May 14, 2025	May 13, 2026
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 24, 2025	May 23, 2026
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 14, 2025	May 13, 2026
Horn Antenna(18G Hz-40GHz)	Schwarzbeck	BBHA9170	00822	May 24, 2025	May 23, 2026
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	\	May 14, 2025	May 13, 2026
Communication test set	R&S	CMW500	126173	Nov. 11. 2024	Nov. 10, 2025
Software	Frad	EZ-EMC	FA-03A2 RE	\	\



6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:

- *Decreasing linearly with logarithm of frequency.
- The lower limit shall apply at the transition frequencies.

6.3 Test Procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	23.6 °C	Relative Humidity:	54 %
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 4	Test Voltage :	AC 120V/60Hz




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1500	42.59	20.04	62.63	66.00	-3.37	QP
2		0.1500	19.18	20.04	39.22	56.00	-16.78	AVG
3		0.2508	29.78	20.04	49.82	61.73	-11.91	QP
4		0.2508	9.88	20.04	29.92	51.73	-21.81	AVG
5		0.4941	28.02	20.06	48.08	56.10	-8.02	QP
6		0.4941	8.03	20.06	28.09	46.10	-18.01	AVG
7		0.7508	29.96	20.26	50.22	56.00	-5.78	QP
8		0.7508	13.76	20.26	34.02	46.00	-11.98	AVG
9		2.5400	21.37	20.30	41.67	56.00	-14.33	QP
10		2.5400	7.00	20.30	27.30	46.00	-18.70	AVG
11		22.8965	27.33	23.94	51.27	60.00	-8.73	QP
12		22.8965	12.24	23.94	36.18	50.00	-13.82	AVG

Temperature:	23.6 °C	Relative Humidity:	54 %
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 4	Test Voltage :	AC 120V/60Hz



Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz		dB	dBuV	dBuV	dB	
1		0.1500	38.56	20.04	58.60	66.00	-7.40	QP
2		0.1500	14.36	20.04	34.40	56.00	-21.60	AVG
3		0.3435	25.53	20.05	45.58	59.12	-13.54	QP
4		0.3435	4.50	20.05	24.55	49.12	-24.57	AVG
5		0.7304	26.93	20.26	47.19	56.00	-8.81	QP
6		0.7304	10.07	20.26	30.33	46.00	-15.67	AVG
7		2.5710	18.04	20.30	38.34	56.00	-17.66	QP
8		2.5710	4.65	20.30	24.95	46.00	-21.05	AVG
9		3.9705	18.53	20.60	39.13	56.00	-16.87	QP
10		3.9705	4.23	20.60	24.83	46.00	-21.17	AVG
11	*	24.8730	29.76	24.18	53.94	60.00	-6.06	QP
12		24.8730	12.33	24.18	36.51	50.00	-13.49	AVG


7. Radiated Emissions

7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log(2400/F(\text{kHz})) + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log(24000/F(\text{kHz})) + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

7.3 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	23.4 °C	Relative Humidity:	51 %
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	Mode 4	Polarization :	--


Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



Between 30MHz – 1GHz

Temperature:	23.4 °C	Relative Humidity:	51 %
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 4	Test Voltage:	AC 120V/60Hz




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.3173	33.37	-12.49	20.88	40.00	-19.12	QP
2	41.4215	31.89	-12.04	19.85	40.00	-20.15	QP
3	55.0274	29.40	-12.38	17.02	40.00	-22.98	QP
4	78.1389	31.04	-14.70	16.34	40.00	-23.66	QP
5	148.4410	29.43	-11.00	18.43	43.50	-25.07	QP
6 *	257.4222	46.08	-12.15	33.93	46.00	-12.07	QP

Temperature:	23.4 °C	Relative Humidity:	51 %
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 4	Test Voltage:	AC 120V/60Hz



Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Measurement = Reading Level + Correct Factor
- Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	30.0000	49.08	-12.50	36.58	40.00	-3.42	QP
2	41.1320	40.00	-12.05	27.95	40.00	-12.05	QP
3	55.2207	35.14	-12.40	22.74	40.00	-17.26	QP
4	135.9822	34.82	-11.83	22.99	43.50	-20.51	QP
5	204.2377	37.16	-14.41	22.75	43.50	-20.75	QP
6	268.4853	41.79	-11.77	30.02	46.00	-15.98	QP

Between 1GHz – 40GHz

Test Mode:	TX(5.1G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.140	72.49	-20.73	51.76	68.20	-16.44	PK
Vertical	4434.140	59.22	-20.73	38.49	54.00	-15.51	AV
Vertical	10360.089	63.00	-9.36	53.64	68.20	-14.56	PK
Vertical	10360.089	49.38	-9.36	40.02	54.00	-13.98	AV
Vertical	15540.020	62.82	-7.84	54.98	74.00	-19.02	PK
Vertical	15540.020	49.29	-7.84	41.45	54.00	-12.55	AV
Horizontal	4434.074	71.15	-20.73	50.42	68.20	-17.78	PK
Horizontal	4434.074	59.32	-20.73	38.59	54.00	-15.41	AV
Horizontal	10360.040	61.20	-9.36	51.84	68.20	-16.36	PK
Horizontal	10360.040	49.50	-9.36	40.14	54.00	-13.86	AV
Horizontal	15540.097	63.12	-7.84	55.28	74.00	-18.72	PK
Horizontal	15540.097	49.71	-7.84	41.87	54.00	-12.13	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.035	72.37	-20.42	51.96	74.00	-22.04	PK
Vertical	4592.035	59.72	-20.42	39.30	54.00	-14.70	AV
Vertical	10400.084	61.83	-9.30	52.53	68.20	-15.67	PK
Vertical	10400.084	49.78	-9.30	40.48	54.00	-13.52	AV
Vertical	15600.189	64.21	-7.82	56.39	74.00	-17.61	PK
Vertical	15600.189	49.23	-7.82	41.41	54.00	-12.59	AV
Horizontal	4592.113	74.59	-20.42	54.18	74.00	-19.82	PK
Horizontal	4592.113	59.40	-20.42	38.98	54.00	-15.02	AV
Horizontal	10400.000	60.41	-9.30	51.11	68.20	-17.09	PK
Horizontal	10400.000	49.53	-9.30	40.23	54.00	-13.77	AV
Horizontal	15600.097	63.88	-7.82	56.06	74.00	-17.94	PK
Horizontal	15600.097	49.79	-7.82	41.97	54.00	-12.03	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.167	71.64	-20.12	51.52	74.00	-22.48	PK
Vertical	4739.167	59.37	-20.12	39.25	54.00	-14.75	AV
Vertical	10480.114	63.40	-9.18	54.22	68.20	-13.98	PK
Vertical	10480.114	49.98	-9.18	40.80	54.00	-13.20	AV
Vertical	15720.045	64.37	-7.78	56.59	74.00	-17.41	PK
Vertical	15720.045	49.81	-7.78	42.03	54.00	-11.97	AV
Horizontal	4739.146	74.88	-20.12	54.76	74.00	-19.24	PK
Horizontal	4739.146	59.44	-20.12	39.32	54.00	-14.68	AV
Horizontal	10480.190	60.06	-9.18	50.88	68.20	-17.32	PK
Horizontal	10480.190	49.27	-9.18	40.09	54.00	-13.91	AV
Horizontal	15720.144	60.79	-7.78	53.01	74.00	-20.99	PK
Horizontal	15720.144	49.35	-7.78	41.57	54.00	-12.43	AV

Note: PK value is lower than the Average value limit, So average didn't record.
The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.
Emission level (dBuV/m) = 20 log Emission level (uV/m).
Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT20
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.074	73.09	-20.73	52.35	68.20	-15.85	PK
Vertical	4434.074	59.31	-20.73	38.58	54.00	-15.42	AV
Vertical	10360.148	60.03	-9.36	50.67	68.20	-17.53	PK
Vertical	10360.148	49.61	-9.36	40.25	54.00	-13.75	AV
Vertical	15540.054	64.19	-7.84	56.35	74.00	-17.65	PK
Vertical	15540.054	49.63	-7.84	41.79	54.00	-12.21	AV
Horizontal	4434.154	74.52	-20.73	53.79	68.20	-14.41	PK
Horizontal	4434.154	59.66	-20.73	38.93	54.00	-15.07	AV
Horizontal	10360.030	63.39	-9.36	54.03	68.20	-14.17	PK
Horizontal	10360.030	49.25	-9.36	39.89	54.00	-14.11	AV
Horizontal	15540.062	64.01	-7.84	56.17	74.00	-17.83	PK
Horizontal	15540.062	49.21	-7.84	41.37	54.00	-12.63	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.151	73.86	-20.42	53.45	74.00	-20.55	PK
Vertical	4592.151	59.27	-20.42	38.85	54.00	-15.15	AV
Vertical	10400.052	62.82	-9.30	53.52	68.20	-14.68	PK
Vertical	10400.052	49.59	-9.30	40.29	54.00	-13.71	AV
Vertical	15600.148	60.24	-7.82	52.42	74.00	-21.58	PK
Vertical	15600.148	49.09	-7.82	41.27	54.00	-12.73	AV
Horizontal	4592.108	74.12	-20.42	53.71	74.00	-20.29	PK
Horizontal	4592.108	59.38	-20.42	38.97	54.00	-15.03	AV
Horizontal	10400.163	64.52	-9.30	55.22	68.20	-12.98	PK
Horizontal	10400.163	49.00	-9.30	39.70	54.00	-14.30	AV
Horizontal	15600.136	63.59	-7.82	55.77	74.00	-18.23	PK
Horizontal	15600.136	50.00	-7.82	42.18	54.00	-11.82	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.167	74.71	-20.12	54.59	74.00	-19.41	PK
Vertical	4739.167	59.11	-20.12	38.99	54.00	-15.01	AV
Vertical	10480.161	60.86	-9.18	51.68	68.20	-16.52	PK
Vertical	10480.161	49.27	-9.18	40.09	54.00	-13.91	AV
Vertical	15720.199	60.90	-7.78	53.12	74.00	-20.88	PK
Vertical	15720.199	49.78	-7.78	42.00	54.00	-12.00	AV
Horizontal	4739.135	73.73	-20.12	53.61	74.00	-20.39	PK
Horizontal	4739.135	59.22	-20.12	39.10	54.00	-14.90	AV
Horizontal	10480.116	63.58	-9.18	54.40	68.20	-13.80	PK
Horizontal	10480.116	49.43	-9.18	40.25	54.00	-13.75	AV
Horizontal	15720.065	60.73	-7.78	52.95	74.00	-21.05	PK
Horizontal	15720.065	49.88	-7.78	42.10	54.00	-11.90	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11n-HT40
------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.144	71.11	-20.73	50.38	68.20	-17.82	PK
Vertical	4434.144	59.61	-20.73	38.88	54.00	-15.12	AV
Vertical	10380.027	64.53	-9.33	55.20	68.20	-13.00	PK
Vertical	10380.027	49.18	-9.33	39.85	54.00	-14.15	AV
Vertical	15570.033	60.11	-7.83	52.28	74.00	-21.72	PK
Vertical	15570.033	49.48	-7.83	41.65	54.00	-12.35	AV
Horizontal	4434.077	72.63	-20.73	51.90	74.00	-22.10	PK
Horizontal	4434.077	59.11	-20.73	38.38	54.00	-15.62	AV
Horizontal	10380.141	64.69	-9.33	55.36	68.20	-12.84	PK
Horizontal	10380.141	49.37	-9.33	40.04	54.00	-13.96	AV
Horizontal	15570.089	62.82	-7.83	54.99	74.00	-19.01	PK
Horizontal	15570.089	49.08	-7.83	41.25	54.00	-12.75	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.128	74.71	-20.12	54.59	68.20	-13.61	PK
Vertical	4739.128	59.78	-20.12	39.66	54.00	-14.34	AV
Vertical	10460.097	63.52	-9.21	54.31	68.20	-13.89	PK
Vertical	10460.097	49.07	-9.21	39.86	54.00	-14.14	AV
Vertical	15690.023	61.74	-7.79	53.95	74.00	-20.05	PK
Vertical	15690.023	49.75	-7.79	41.96	54.00	-12.04	AV
Horizontal	4739.128	73.12	-20.12	53.00	68.20	-15.20	PK
Horizontal	4739.128	59.59	-20.12	39.47	54.00	-14.53	AV
Horizontal	10460.119	62.11	-9.21	52.90	68.20	-15.30	PK
Horizontal	10460.119	49.89	-9.21	40.68	54.00	-13.32	AV
Horizontal	15690.030	63.22	-7.79	55.43	74.00	-18.57	PK
Horizontal	15690.030	49.41	-7.79	41.62	54.00	-12.38	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT20
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.039	71.77	-20.73	51.04	68.20	-17.16	PK
Vertical	4434.039	59.14	-20.73	38.41	54.00	-15.59	AV
Vertical	10360.171	60.71	-9.36	51.35	68.20	-16.85	PK
Vertical	10360.171	49.30	-9.36	39.94	54.00	-14.06	AV
Vertical	15540.148	62.23	-7.84	54.39	74.00	-19.61	PK
Vertical	15540.148	49.58	-7.84	41.74	54.00	-12.26	AV
Horizontal	4434.093	74.07	-20.73	53.34	68.20	-14.86	PK
Horizontal	4434.093	59.02	-20.73	38.29	54.00	-15.71	AV
Horizontal	10360.118	64.37	-9.36	55.01	68.20	-13.19	PK
Horizontal	10360.118	49.51	-9.36	40.15	54.00	-13.85	AV
Horizontal	15540.148	61.59	-7.84	53.75	74.00	-20.25	PK
Horizontal	15540.148	49.80	-7.84	41.96	54.00	-12.04	AV
Middle Channel (5200 MHz)-Above 1G							
Vertical	4592.089	74.14	-20.42	53.73	74.00	-20.27	PK
Vertical	4592.089	59.15	-20.42	38.73	54.00	-15.27	AV
Vertical	10400.157	62.75	-9.30	53.45	68.20	-14.75	PK
Vertical	10400.157	49.13	-9.30	39.83	54.00	-14.17	AV
Vertical	15600.071	60.52	-7.82	52.70	74.00	-21.30	PK
Vertical	15600.071	49.56	-7.82	41.74	54.00	-12.26	AV
Horizontal	4592.171	74.60	-20.42	54.19	74.00	-19.81	PK
Horizontal	4592.171	59.22	-20.42	38.81	54.00	-15.19	AV
Horizontal	10400.049	63.75	-9.30	54.45	68.20	-13.75	PK
Horizontal	10400.049	49.42	-9.30	40.12	54.00	-13.88	AV
Horizontal	15600.092	61.49	-7.82	53.67	74.00	-20.33	PK
Horizontal	15600.092	49.04	-7.82	41.22	54.00	-12.78	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.191	74.55	-20.12	54.43	74.00	-19.57	PK
Vertical	4739.191	59.61	-20.12	39.49	54.00	-14.51	AV
Vertical	10480.145	61.75	-9.18	52.57	68.20	-15.63	PK
Vertical	10480.145	49.44	-9.18	40.26	54.00	-13.74	AV
Vertical	15720.074	64.09	-7.78	56.31	74.00	-17.69	PK
Vertical	15720.074	49.73	-7.78	41.95	54.00	-12.05	AV
Horizontal	4739.042	74.22	-20.12	54.10	74.00	-19.90	PK
Horizontal	4739.042	59.41	-20.12	39.28	54.00	-14.72	AV
Horizontal	10480.169	61.84	-9.18	52.66	68.20	-15.54	PK
Horizontal	10480.169	49.80	-9.18	40.62	54.00	-13.38	AV
Horizontal	15720.163	60.02	-7.78	52.24	74.00	-21.76	PK
Horizontal	15720.163	49.68	-7.78	41.90	54.00	-12.10	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac-HT40
------------	--------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.047	70.37	-20.73	49.64	68.20	-18.56	PK
Vertical	4434.047	59.02	-20.73	38.29	54.00	-15.71	AV
Vertical	10380.098	60.64	-9.33	51.31	68.20	-16.89	PK
Vertical	10380.098	49.56	-9.33	40.23	54.00	-13.77	AV
Vertical	15570.003	64.49	-7.83	56.66	74.00	-17.34	PK
Vertical	15570.003	49.50	-7.83	41.67	54.00	-12.33	AV
Horizontal	4434.067	70.02	-20.73	49.29	74.00	-24.71	PK
Horizontal	4434.067	59.50	-20.73	38.77	54.00	-15.23	AV
Horizontal	10380.026	61.64	-9.33	52.31	68.20	-15.89	PK
Horizontal	10380.026	49.65	-9.33	40.32	54.00	-13.68	AV
Horizontal	15570.163	64.51	-7.83	56.68	74.00	-17.32	PK
Horizontal	15570.163	49.77	-7.83	41.94	54.00	-12.06	AV
Middle Channel (5230 MHz)-Above 1G							
Vertical	4739.041	73.97	-20.12	53.84	68.20	-14.36	PK
Vertical	4739.041	59.67	-20.12	39.55	54.00	-14.45	AV
Vertical	10460.069	60.04	-9.21	50.83	68.20	-17.37	PK
Vertical	10460.069	49.15	-9.21	39.94	54.00	-14.06	AV
Vertical	15690.175	63.46	-7.79	55.67	74.00	-18.33	PK
Vertical	15690.175	49.74	-7.79	41.95	54.00	-12.05	AV
Horizontal	4739.108	74.73	-20.12	54.60	68.20	-13.60	PK
Horizontal	4739.108	59.34	-20.12	39.21	54.00	-14.79	AV
Horizontal	10460.081	64.10	-9.21	54.89	68.20	-13.31	PK
Horizontal	10460.081	49.48	-9.21	40.27	54.00	-13.73	AV
Horizontal	15690.199	62.78	-7.79	54.99	74.00	-19.01	PK
Horizontal	15690.199	49.77	-7.79	41.98	54.00	-12.02	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX(5.1G) - 802.11ac 80
------------	------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5210 MHz)-Above 1G							
Vertical	4434.057	74.13	-20.73	53.40	68.20	-14.80	PK
Vertical	4434.057	59.22	-20.73	38.49	54.00	-15.51	AV
Vertical	10420.062	62.86	-9.27	53.59	68.20	-14.61	PK
Vertical	10420.062	49.68	-9.27	40.41	54.00	-13.59	AV
Vertical	15630.157	64.83	-7.81	57.02	74.00	-16.98	PK
Vertical	15630.157	49.01	-7.81	41.20	54.00	-12.80	AV
Horizontal	4434.126	71.86	-20.73	51.13	68.20	-17.07	PK
Horizontal	4434.126	59.34	-20.73	38.60	54.00	-15.40	AV
Horizontal	10420.100	43.50	9.27	52.77	68.20	-15.43	PK
Horizontal	10420.100	29.21	9.27	38.48	54.00	-15.52	AV
Horizontal	15630.045	60.16	-7.81	52.35	74.00	-21.65	PK
Horizontal	15630.045	49.97	-7.81	42.16	54.00	-11.84	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11a
------------	----------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.173	73.12	-20.24	52.88	74.00	-21.12	PK
Vertical	4679.173	59.29	-20.24	39.05	54.00	-14.95	AV
Vertical	11490.194	61.13	-8.79	52.34	68.20	-15.86	PK
Vertical	11490.194	49.96	-8.79	41.17	54.00	-12.83	AV
Vertical	17235.054	55.40	-3.18	52.22	68.20	-15.98	PK
Vertical	17235.054	44.27	-3.18	41.09	54.00	-12.91	AV
Horizontal	4679.176	74.27	-20.73	53.54	74.00	-20.46	PK
Horizontal	4679.176	59.03	-20.73	38.30	54.00	-15.70	AV
Horizontal	11490.084	64.39	-8.79	55.60	68.20	-12.60	PK
Horizontal	11490.084	49.14	-8.79	40.35	54.00	-13.65	AV
Horizontal	17235.136	56.95	-3.18	53.77	68.20	-14.43	PK
Horizontal	17235.136	44.63	-3.18	41.45	54.00	-12.55	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.115	74.03	-20.42	53.62	74.00	-20.38	PK
Vertical	4592.115	59.86	-20.42	39.44	54.00	-14.56	AV
Vertical	11570.025	62.17	-8.86	53.31	68.20	-14.89	PK
Vertical	11570.025	49.22	-8.86	40.36	54.00	-13.64	AV
Vertical	17355.167	55.06	-2.52	52.54	68.20	-15.66	PK
Vertical	17355.167	44.48	-2.52	41.96	54.00	-12.04	AV
Horizontal	4592.064	73.05	-20.42	52.64	74.00	-21.36	PK
Horizontal	4592.064	59.92	-20.42	39.50	54.00	-14.50	AV
Horizontal	11570.057	63.62	-8.86	54.76	68.20	-13.44	PK
Horizontal	11570.057	49.43	-8.86	40.57	54.00	-13.43	AV
Horizontal	17355.064	59.58	-2.52	57.06	68.20	-11.14	PK
Horizontal	17355.064	44.32	-2.52	41.80	54.00	-12.20	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.173	72.05	-18.93	53.12	68.20	-15.08	PK
Vertical	6039.173	59.09	-18.93	40.15	54.00	-13.85	AV
Vertical	11650.124	64.54	-8.92	55.62	74.00	-18.38	PK
Vertical	11650.124	49.77	-8.92	40.85	54.00	-13.15	AV
Vertical	17475.162	59.82	-1.86	57.96	68.20	-10.24	PK
Vertical	17475.162	44.56	-1.86	42.70	54.00	-11.30	AV
Horizontal	6039.012	74.31	-18.93	55.38	68.20	-12.82	PK
Horizontal	6039.012	59.72	-18.93	40.79	54.00	-13.21	AV
Horizontal	11650.066	64.86	-8.92	55.94	74.00	-18.06	PK
Horizontal	11650.066	49.05	-8.92	40.13	54.00	-13.87	AV
Horizontal	17475.005	57.12	-1.86	55.26	68.20	-12.94	PK
Horizontal	17475.005	44.48	-1.86	42.62	54.00	-11.38	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11n-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.047	72.60	-20.24	52.35	74.00	-21.65	PK
Vertical	4679.047	59.64	-20.24	39.40	54.00	-14.60	AV
Vertical	11490.120	61.10	-8.79	52.31	68.20	-15.89	PK
Vertical	11490.120	49.77	-8.79	40.98	54.00	-13.02	AV
Vertical	17235.086	57.69	-3.18	54.51	68.20	-13.69	PK
Vertical	17235.086	44.34	-3.18	41.16	54.00	-12.84	AV
Horizontal	4679.162	73.97	-20.24	53.73	74.00	-20.27	PK
Horizontal	4679.162	59.21	-20.24	38.96	54.00	-15.04	AV
Horizontal	11490.014	61.10	-8.79	52.31	68.20	-15.89	PK
Horizontal	11490.014	49.09	-8.79	40.30	54.00	-13.70	AV
Horizontal	17235.131	59.21	-3.18	56.03	68.20	-12.17	PK
Horizontal	17235.131	44.23	-3.18	41.05	54.00	-12.95	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.091	70.54	-20.42	50.12	74.00	-23.88	PK
Vertical	4592.091	59.72	-20.42	39.31	54.00	-14.69	AV
Vertical	11570.066	64.89	-8.86	56.03	68.20	-12.17	PK
Vertical	11570.066	49.20	-8.86	40.34	54.00	-13.66	AV
Vertical	17355.162	56.28	-2.52	53.76	68.20	-14.44	PK
Vertical	17355.162	44.17	-2.52	41.65	54.00	-12.35	AV
Horizontal	4592.170	72.02	-20.42	51.60	74.00	-22.40	PK
Horizontal	4592.170	59.34	-20.42	38.92	54.00	-15.08	AV
Horizontal	11570.024	60.07	-8.86	51.21	68.20	-16.99	PK
Horizontal	11570.024	49.69	-8.86	40.83	54.00	-13.17	AV
Horizontal	17355.117	57.22	-2.52	54.70	68.20	-13.50	PK
Horizontal	17355.117	44.06	-2.52	41.54	54.00	-12.46	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.056	73.40	-18.93	54.47	68.20	-13.73	PK
Vertical	6039.056	59.06	-18.93	40.12	54.00	-13.88	AV
Vertical	11650.134	60.71	-8.92	51.79	74.00	-22.21	PK
Vertical	11650.134	49.73	-8.92	40.81	54.00	-13.19	AV
Vertical	17475.098	58.27	-1.86	56.41	68.20	-11.79	PK
Vertical	17475.098	44.13	-1.86	42.27	54.00	-11.73	AV
Horizontal	6039.042	74.94	-18.93	56.01	68.20	-12.19	PK
Horizontal	6039.042	59.97	-18.93	41.04	54.00	-12.96	AV
Horizontal	11650.119	64.92	-8.92	56.00	74.00	-18.00	PK
Horizontal	11650.119	49.70	-8.92	40.78	54.00	-13.22	AV
Horizontal	17475.193	58.51	-1.86	56.65	68.20	-11.55	PK
Horizontal	17475.193	44.38	-1.86	42.52	54.00	-11.48	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode:	TX (5.8G) -- 802.11n-HT40
------------	---------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.015	71.13	-20.24	50.89	74.00	-23.11	PK
Vertical	4679.015	59.61	-20.24	39.36	54.00	-14.64	AV
Vertical	11510.150	63.75	-8.81	54.94	74.00	-19.06	PK
Vertical	11510.150	49.82	-8.81	41.01	54.00	-12.99	AV
Vertical	17265.023	55.68	-3.01	52.67	68.20	-15.53	PK
Vertical	17265.023	44.41	-3.01	41.40	54.00	-12.60	AV
Horizontal	4679.099	71.50	-20.24	51.26	74.00	-22.74	PK
Horizontal	4679.099	59.32	-20.24	39.08	54.00	-14.92	AV
Horizontal	11510.185	64.55	-8.81	55.74	74.00	-18.26	PK
Horizontal	11510.185	49.69	-8.81	40.88	54.00	-13.12	AV
Horizontal	17265.091	56.63	-3.01	53.62	68.20	-14.58	PK
Horizontal	17265.091	44.99	-3.01	41.98	54.00	-12.02	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.018	72.37	-18.93	53.44	68.20	-14.76	PK
Vertical	6039.018	59.78	-18.93	40.85	54.00	-13.15	AV
Vertical	11590.082	62.40	-8.87	53.53	74.00	-20.47	PK
Vertical	11590.082	49.48	-8.87	40.61	54.00	-13.39	AV
Vertical	17385.060	58.51	-2.35	56.16	68.20	-12.04	PK
Vertical	17385.060	44.45	-2.35	42.10	54.00	-11.90	AV
Horizontal	6039.041	70.60	-18.93	51.66	68.20	-16.54	PK
Horizontal	6039.041	59.25	-18.93	40.32	54.00	-13.68	AV
Horizontal	11590.096	63.19	-8.87	54.32	74.00	-19.68	PK
Horizontal	11590.096	49.30	-8.87	40.43	54.00	-13.57	AV
Horizontal	17385.008	55.70	-2.35	53.35	68.20	-14.85	PK
Horizontal	17385.008	44.28	-2.35	41.93	54.00	-12.07	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX (5.8G) --802.11ac-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.189	70.32	-20.24	50.08	74.00	-23.92	PK
Vertical	4679.189	59.23	-20.24	38.99	54.00	-15.01	AV
Vertical	11490.077	62.16	-8.79	53.37	68.20	-14.83	PK
Vertical	11490.077	49.19	-8.79	40.40	54.00	-13.60	AV
Vertical	17235.001	57.55	-3.18	54.37	68.20	-13.83	PK
Vertical	17235.001	44.62	-3.18	41.44	54.00	-12.56	AV
Horizontal	4679.013	73.52	-20.24	53.27	74.00	-20.73	PK
Horizontal	4679.013	59.02	-20.24	38.78	54.00	-15.22	AV
Horizontal	11490.156	61.71	-8.79	52.92	68.20	-15.28	PK
Horizontal	11490.156	49.39	-8.79	40.60	54.00	-13.40	AV
Horizontal	17235.187	57.71	-3.18	54.53	68.20	-13.67	PK
Horizontal	17235.187	44.67	-3.18	41.49	54.00	-12.51	AV
Middle Channel (5785 MHz)-Above 1G							
Vertical	4592.131	74.48	-20.42	54.06	74.00	-19.94	PK
Vertical	4592.131	59.24	-20.42	38.82	54.00	-15.18	AV
Vertical	11570.030	64.68	-8.86	55.82	68.20	-12.38	PK
Vertical	11570.030	49.31	-8.86	40.45	54.00	-13.55	AV
Vertical	17355.071	55.40	-2.52	52.88	68.20	-15.32	PK
Vertical	17355.071	44.18	-2.52	41.66	54.00	-12.34	AV
Horizontal	4592.193	73.84	-20.42	53.42	74.00	-20.58	PK
Horizontal	4592.193	59.58	-20.42	39.17	54.00	-14.83	AV
Horizontal	11570.141	60.68	-8.86	51.82	68.20	-16.38	PK
Horizontal	11570.141	49.89	-8.86	41.03	54.00	-12.97	AV
Horizontal	17355.074	59.61	-2.52	57.09	68.20	-11.11	PK
Horizontal	17355.074	44.88	-2.52	42.36	54.00	-11.64	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.064	71.41	-18.93	52.48	68.20	-15.72	PK
Vertical	6039.064	59.87	-18.93	40.94	54.00	-13.06	AV
Vertical	11650.191	64.13	-8.92	55.21	74.00	-18.79	PK
Vertical	11650.191	49.47	-8.92	40.55	54.00	-13.45	AV
Vertical	17475.101	57.75	-1.86	55.89	68.20	-12.31	PK
Vertical	17475.101	44.40	-1.86	42.54	54.00	-11.46	AV
Horizontal	6039.102	74.87	-18.93	55.93	68.20	-12.27	PK
Horizontal	6039.102	59.99	-18.93	41.06	54.00	-12.94	AV
Horizontal	11650.056	62.88	-8.92	53.96	74.00	-20.04	PK
Horizontal	11650.056	49.18	-8.92	40.26	54.00	-13.74	AV
Horizontal	17475.008	57.62	-1.86	55.76	68.20	-12.44	PK
Horizontal	17475.008	44.11	-1.86	42.25	54.00	-11.75	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ac-HT40
-------------	----------------------------

Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.014	70.69	-20.24	50.45	74.00	-23.55	PK
Vertical	4679.014	59.15	-20.24	38.91	54.00	-15.09	AV
Vertical	11510.173	64.07	-8.81	55.26	74.00	-18.74	PK
Vertical	11510.173	49.17	-8.81	40.36	54.00	-13.64	AV
Vertical	17265.188	59.46	-3.01	56.45	68.20	-11.75	PK
Vertical	17265.188	44.66	-3.01	41.65	54.00	-12.35	AV
Horizontal	4679.029	73.59	-20.24	53.35	74.00	-20.65	PK
Horizontal	4679.029	59.93	-20.24	39.69	54.00	-14.31	AV
Horizontal	11510.044	63.79	-8.81	54.98	74.00	-19.02	PK
Horizontal	11510.044	49.84	-8.81	41.03	54.00	-12.97	AV
Horizontal	17265.179	57.89	-3.01	54.88	68.20	-13.32	PK
Horizontal	17265.179	44.98	-3.01	41.97	54.00	-12.03	AV
Middle Channel (5795 MHz)-Above 1G							
Vertical	6039.067	74.63	-18.93	55.70	68.20	-12.50	PK
Vertical	6039.067	59.23	-18.93	40.30	54.00	-13.70	AV
Vertical	11590.027	61.72	-8.87	52.85	74.00	-21.15	PK
Vertical	11590.027	49.90	-8.87	41.03	54.00	-12.97	AV
Vertical	17385.105	58.50	-2.35	56.15	68.20	-12.05	PK
Vertical	17385.105	44.74	-2.35	42.39	54.00	-11.61	AV
Horizontal	6039.021	72.23	-18.93	53.30	68.20	-14.90	PK
Horizontal	6039.021	59.48	-18.93	40.55	54.00	-13.45	AV
Horizontal	11590.094	60.82	-8.87	51.95	74.00	-22.05	PK
Horizontal	11590.094	49.20	-8.87	40.33	54.00	-13.67	AV
Horizontal	17385.101	58.23	-2.35	55.88	68.20	-12.32	PK
Horizontal	17385.101	44.99	-2.35	42.64	54.00	-11.36	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX (5.8G) -- 802.11ac 80
-------------	--------------------------


Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)	Over (dB)	Detector Type
Low Channel (5775 MHz)-Above 1G							
Vertical	4679.011	72.21	-20.24	51.97	74.00	-22.03	PK
Vertical	4679.011	59.43	-20.24	39.19	54.00	-14.81	AV
Vertical	11550.075	60.01	-8.84	51.17	74.00	-22.83	PK
Vertical	11550.075	49.13	-8.84	40.29	54.00	-13.71	AV
Vertical	17325.077	59.93	-2.68	57.25	68.20	-10.95	PK
Vertical	17325.077	44.42	-2.68	41.74	54.00	-12.26	AV
Horizontal	4679.043	72.66	-20.24	52.41	74.00	-21.59	PK
Horizontal	4679.043	59.84	-20.24	39.60	54.00	-14.40	AV
Horizontal	11550.165	62.63	-8.84	53.79	74.00	-20.21	PK
Horizontal	11550.165	49.95	-8.84	41.11	54.00	-12.89	AV
Horizontal	17325.045	57.86	-2.68	55.18	68.20	-13.02	PK
Horizontal	17325.045	44.08	-2.68	41.40	54.00	-12.60	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



8. Power Spectral Density Test

8.1 Block Diagram Of Test Setup



8.2 Limit

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.3 Test Procedure


For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.

8.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




8.5 Test Result



Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	DC 3.87V
Test Mode:	(U-NII-1) 5180MHz-5240MHz (U-NII-3) 5745MHz-5825MHz		



Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/1MHz)	Limit (dBm/1MHz)	Verdict
NVNT	a	5180	-0.81	11	Pass
NVNT	a	5200	-0.9	11	Pass
NVNT	a	5240	0.65	11	Pass
NVNT	n20	5180	-2.23	11	Pass
NVNT	n20	5200	-2.49	11	Pass
NVNT	n20	5240	-2.05	11	Pass
NVNT	n40	5190	-6.73	11	Pass
NVNT	n40	5230	-6.58	11	Pass
NVNT	ac20	5180	-2.16	11	Pass
NVNT	ac20	5200	-2.27	11	Pass
NVNT	ac20	5240	-2.23	11	Pass
NVNT	ac40	5190	-6.58	11	Pass
NVNT	ac40	5230	-6.73	11	Pass
NVNT	ac80	5210	-11.59	11	Pass



Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/510KHz)	Conducted PSD (dBm/500KHz)	Limit (dBm/500KHz)	Verdict
NVNT	a	5745	-3.52	-3.606	30	Pass
NVNT	a	5785	-3.22	-3.306	30	Pass
NVNT	a	5825	-4.12	-4.206	30	Pass
NVNT	n20	5745	-5.54	-5.626	30	Pass
NVNT	n20	5785	-5.05	-5.136	30	Pass
NVNT	n20	5825	-5.46	-5.546	30	Pass
NVNT	n40	5755	-9.35	-9.436	30	Pass
NVNT	n40	5795	-9.24	-9.326	30	Pass
NVNT	ac20	5745	-5.18	-5.266	30	Pass
NVNT	ac20	5785	-5.29	-5.376	30	Pass
NVNT	ac20	5825	-5.53	-5.616	30	Pass
NVNT	ac40	5755	-9.19	-9.276	30	Pass
NVNT	ac40	5795	-9.21	-9.296	30	Pass
NVNT	ac80	5775	-12.94	-13.026	30	Pass



Note: Correction Factor = $10\log(500\text{KHz}/\text{RBW in measurement}) = -0.086$















































9. 26dB & 6dB & 99% Emission Bandwidth

9.1 Block Diagram Of Test Setup



9.2 Limit

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.
(6dB bandwidth)>500kHz

9.3 Test Procedure

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = Peak.
- Trace mode = max hold.
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

The following procedure shall be used for measuring (99 %) power bandwidth:

- Set center frequency to the nominal EUT channel center frequency.
- Set span = 1.5 times to 5.0 times the OBW.
- Set RBW = 1 % to 5 % of the OBW
- Set VBW $\geq 3 \cdot$ RBW
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99 % power bandwidth function of the instrument (if available).
- If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6dB

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.

6. Allow the trace to stabilize.

7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

9.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

9.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	DC 3.87V
Test Mode:	TX Frequency U-NII-1 (5180-5240MHz)		

Condition	Mode	Frequency (MHz)	99% bandwidth (MHz)	-26dB bandwidth (MHz)	Result
NVNT	a	5180	16.631	29.67	Pass
NVNT	a	5200	16.61	29.137	Pass
NVNT	a	5240	16.617	26.112	Pass
NVNT	n20	5180	17.608	25.815	Pass
NVNT	n20	5200	17.641	28.39	Pass
NVNT	n20	5240	17.665	27.169	Pass
NVNT	n40	5190	36.175	43.253	Pass
NVNT	n40	5230	36.272	44.487	Pass
NVNT	ac20	5180	17.636	26.633	Pass
NVNT	ac20	5200	17.616	28.104	Pass
NVNT	ac20	5240	17.627	27.776	Pass
NVNT	ac40	5190	36.22	44.505	Pass
NVNT	ac40	5230	36.201	44.819	Pass
NVNT	ac80	5210	75.569	84.134	Pass

