


FCC Radio Test Report

FCC ID: 2ANNW-AN-H311A

Report No. : TB-FCC158228
Applicant : Shenzhen Annidigital Technology Co., Ltd
Equipment Under Test (EUT)
EUT Name : Video Doorbell
Model No. : AN-H311A
Serial Model No. : Please see the page 5
Brand Name :  anni
Receipt Date : 2018-02-01
Test Date : 2018-02-02 to 2018-03-06
Issue Date : 2018-03-07
Standards : FCC Part 15, Subpart C (15.231(a):2017)
Test Method : ANSI C63.10:2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC requirements

Test/Witness Engineer :  Terry Su
Engineer Supervisor :  Ivan Su
Engineer Manager :  Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS	2
1. GENERAL INFORMATION ABOUT EUT	5
1.1 Client Information	5
1.2 General Description of EUT (Equipment Under Test)	5
1.3 Block Diagram Showing the Configuration of System Tested	6
1.4 Description of Support Units	6
1.5 Description of Test Mode	7
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	8
1.8 Test Facility	8
2. TEST SUMMARY	9
3. TEST EQUIPMENT	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit	11
4.2 Test Setup	11
4.3 Test Procedure	12
4.4 Test Data	12
5. RADIATED EMISSION TEST	13
5.1 Test Standard and Limit	13
5.2 Test Setup	14
5.3 Test Procedure	15
5.4 EUT Operating Condition	16
5.5 Test Data	16
6. BANDWIDTH	17
6.1 Test Standard and Limit	17
6.2 Test Setup	17
6.3 Test Procedure	17
6.4 EUT Operating Condition	17
6.5 Test Data	17
7. RELEASE TIME MEASUREMENT	18
7.1 Test Standard and Limit	18
7.2 Test Setup	18
7.3 Test Procedure	18
7.4 EUT Operating Condition	18
7.6 Test Data	18
8. DUTY CYCLE	19
8.1 Test Standard and Limit	19
8.2 Test Setup	19
8.3 Test Procedure	19

8.4 EUT Operating Condition	19
8.6 Test Data.....	19
9. ANTENNA REQUIREMENT.....	20
9.1 Standard Requirement.....	20
9.2 Antenna Connected Construction	20
ATTACHMENT A--CONDUCTED EMISSION TEST DATA	20
ATTACHMENT B-- RADIATED EMISSION TEST DATA	23
ATTACHMENT C--BANDWIDTH DATA	30
ATTACHMENT D-- RELEASE TIME MEASUREMENT DATA.....	31
ATTACHMENT E--DUTY CYCLE DATA.....	32

Revision History

Report No.	Version	Description	Issued Date
TB-RF158227	Rev.01	Initial issue of report	2018-03-06

1. General Information about EUT

1.1 Client Information

Applicant : Shenzhen Annidigital Technology Co., Ltd
Address : 3rd Floor, Hasee Bldg, NO.1, Banlan Road, Bantian, Buji Town, Longgang, Shenzhen, China
Manufacturer : Shenzhen Annidigital Technology Co., Ltd
Address : 3rd Floor, Hasee Bldg, NO.1, Banlan Road, Bantian, Buji Town, Longgang, Shenzhen, China

1.2 General Description of EUT (Equipment Under Test)


EUT Name	:	Video Doorbell	
Models No.	:	AN-H311A, AN-H311C, AN-HXXXX, AN-HXXXXX, AN-XXXXX, AN-XXXXXX("X" dedicated to A to Z and/or 0 to 999 up to 8 digits)	
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is appearance shape and color.	
Product Description	:	Operation Frequency:	433.92 MHz
		Out Power:	73.05dBuV/m (PK Max.) 71.37dBuV/m (AV Max.)
		Antenna Gain:	Internal Antenna(0dBi)
		Modulation Type:	GFSK
Power Supply	:	DC Voltage supplied by AC/DC Adapter DC Voltage supplied by Li-ion battery	
Power Rating	:	AC/DC Adapter Model(MXM6-0502000U): Input: AC 120~240V 50-60Hz 0.3A Output: DC 5V/2A DC 3.7V by 6000mAh Li-ion battery	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:


- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

1.3 Block Diagram Showing the Configuration of System Tested

USB Charging Mode



TX Mode



1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	NO	NO	1.25M	

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

Test Items	Note
Conducted Emission	Charging Mode
Radiated Emission	Continuously transmitting
Bandwidth	Continuously transmitting
Duty Cycle	Continuously transmitting
Release Time	Normal Mode

Note:

- (1) During the testing procedure, the continuously transmitting mode was programmed by the customer.
- (2) The EUT is considered a portable unit, and it was pre-tested on the positioned of each 3 axis: X axis, Y axis and Z axis. The worst case was found positioned on Z-plane. There for only the test data of this Z-plane were used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of transmitting mode.

RF Power Setting in Test SW:	DEF
------------------------------	-----

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz	± 3.42 dB
	150kHz to 30MHz	± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at: 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation (A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart (15.231(a))			
Standard Section	Test Item	Judgment	Remark
FCC			
15.203	Antenna Requirement	PASS	N/A
15.207	Conducted Emission	PASS	N/A
15.231	Release Time	PASS	N/A
	Radiation Emission	PASS	N/A
	20 dB Bandwidth	PASS	N/A
	Duty Cycle	PASS	N/A
Note: N/A is an abbreviation for Not Applicable.			

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 20, 2017	Jul. 19, 2018
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 20, 2017	Jul. 19, 2018
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 20, 2017	Jul. 19, 2018
LISN	Rohde & Schwarz	ENV216	101131	Jul. 20, 2017	Jul. 19, 2018
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 20, 2017	Jul. 19, 2018
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 20, 2017	Jul. 19, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.25, 2017	Mar. 24, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.24, 2017	Mar. 23, 2018
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.24, 2017	Mar. 23, 2018
Loop Antenna	Laplace instrument	RF300	0701	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	Sonoma	310N	185903	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar.25, 2017	Mar. 24, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.24, 2017	Mar. 23, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 20, 2017	Jul. 19, 2018
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 20, 2017	Jul. 19, 2018
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Oct. 26, 2017	Oct. 25, 2018
Vector Signal Generator	Agilent	N5182A	MY50141294	Oct. 26, 2017	Oct. 25, 2018
Analog Signal Generator	Agilent	N5181A	MY50141953	Oct. 26, 2017	Oct. 25, 2018
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Oct. 26, 2017	Oct. 25, 2018
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Oct. 26, 2017	Oct. 25, 2018

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC 15.207

4.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

4.4 Test Data

Please refer to the Attachment A.

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC 15.231

5.1.2 Test Limit

According to FCC 15.231(a) requirement:

In addition to the provisions of Section 15.205, the field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolt/meter) at 3m	Field Strength of Spurious Emissions (microvolt/meter) at 3m
40.66~40.70	2250	225
70~130	1250	125
130~174	1250 to 3750(**)	125 to 375(**)
174~260	3750	375
260~470	3750 to 12500(**)	375 to 1250(**)
Above 470	12500	1250

** Linear interpolations, the formulas for calculating the maximum permitted fundamental field strengths are as follows:

- (1) for the band 130~174 MHz, $\mu\text{V/m}$ at 3 meters= $56.81818(F)-6136.3636$;
- (2) for the band 260~470 MHz, $\mu\text{V/m}$ at 3 meter= $41.6667(F)-7083.3333$.
- (3) The maximum permitted unwanted emissions level is 20 dB below the maximum permitted fundamental level. In addition field strength of any emissions which appear inside of the restriction band shall not exceed the general radiated emissions limits in RSS Gen 8.9.

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	2400/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3

216~960	200	3
Above 960	500	3


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)


So the field strength of emission limits have been calculated in below table.

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolt/meter) at 3m
433.92 MHz	80.82 (Average)
433.92 MHz	100.82 (Peak)


5.2 Test Setup



Bellow 30MHz Test Setup



Bellow 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz. The EUT was placed on a rotating 0.8m high above the ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by

3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Please refer to the Attachment B.

6. Bandwidth

6.1 Test Standard and Limit

6.1.1 Test Standard


FCC 15.231

6.1.2 Test Limit

The 99% bandwidth of the emissions shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. So the emission bandwidth limits have been calculated in below table.

Fundamental Frequency	20 dB Bandwidth Limits (MHz)
433.92 MHz	1.0847

6.2 Test Setup



6.3 Test Procedure

- (1) Set Spectrum Analyzer Center Frequency= Fundamental Frequency, RBW=10 kHz, VBW= 30 kHz, Span= 1 MHz.
- (2) Measured the spectrum width with power higher than 20 dB below carrier.

6.4 EUT Operating Condition

The Equipment Under Test was Programmed to be in continuously transmitting mode.

6.5 Test Data

Please refer to the Attachment C.

7. Release Time Measurement

7.1 Test Standard and Limit


7.1.1 Test Standard

FCC 15.231

7.1.2 Test Limit

According to FCC 15.231a, A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

7.2 Test Setup



7.3 Test Procedure

- (1) Setup the EUT as show in the block diagram above.
- (2) Set Spectrum Analyzer Centre Frequency= Fundamental Frequency, RBW=100 kHz, VBW= 300 kHz, Span= 0 Hz. Sweep Time= 5 Seconds.
- (3) Setup the EUT as normal operation and press Transmitter button.
- (4) Set Spectrum Analyzer View, Delta Mark time.

7.4 EUT Operating Condition

The EUT was set to work in transmitting mode.

7.6 Test Data


Please refer to the Attachment D.

8. Duty Cycle

8.1 Test Standard and Limit

5.1.1 Test Standard
FCC 15.231

8.2 Test Setup



8.3 Test Procedure

- (1) The EUT was placed on a turntable which is 0.8m above ground plane.
- (2) Set EUT operating in continuous transmitting mode.
- (3) Set the Spectrum Analyzer to the transmitter carrier frequency, and set the spectrum analyzer resolution bandwidth (RBW) to 100 kHz and video bandwidth (VBW) to 300 kHz, Span was set to 0 Hz.
- (4) The Duty Cycle was measured and recorded.

8.4 EUT Operating Condition

The EUT was programmed to be in transmitting mode.

8.6 Test Data

Please refer to the Attachment E.

9. Antenna Requirement

9.1 Standard Requirement

9.1.1 Standard

FCC Part 15.203

9.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 0dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.


Result

The EUT antenna is an Internal Antenna. It complies with the standard requirement.

Antenna Type
☐ Permanent attached antenna
☒ Unique connector antenna
☐ Professional installation antenna

Attachment A--Conducted Emission Test Data


Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	Charging Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.4580	21.26	9.60	30.86	56.73	-25.87	QP
2		0.4580	12.54	9.60	22.14	46.73	-24.59	AVG
3		0.5380	27.82	9.60	37.42	56.00	-18.58	QP
4		0.5380	18.98	9.60	28.58	46.00	-17.42	AVG
5	*	0.6419	35.34	9.61	44.95	56.00	-11.05	QP
6		0.6419	22.19	9.61	31.80	46.00	-14.20	AVG
7		1.3060	22.17	9.60	31.77	56.00	-24.23	QP
8		1.3060	9.60	9.60	19.20	46.00	-26.80	AVG
9		2.4700	19.75	9.63	29.38	56.00	-26.62	QP
10		2.4700	11.69	9.63	21.32	46.00	-24.68	AVG
11		14.3820	22.23	10.42	32.65	60.00	-27.35	QP
12		14.3820	9.46	10.42	19.88	50.00	-30.12	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor




Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 230V/50Hz		
Terminal:	Line		
Test Mode:	Charging Mode		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.5899	27.55	9.60	37.15	56.00	-18.85	QP
2		0.5899	18.25	9.60	27.85	46.00	-18.15	AVG
3		0.6419	39.60	9.61	49.21	56.00	-6.79	QP
4	*	0.6419	32.06	9.61	41.67	46.00	-4.33	AVG
5		1.1420	29.11	9.60	38.71	56.00	-17.29	QP
6		1.1420	19.29	9.60	28.89	46.00	-17.11	AVG
7		1.5700	25.78	9.61	35.39	56.00	-20.61	QP
8		1.5700	15.21	9.61	24.82	46.00	-21.18	AVG
9		2.0100	29.94	9.61	39.55	56.00	-16.45	QP
10		2.0100	19.72	9.61	29.33	46.00	-16.67	AVG
11		2.8660	25.76	9.64	35.40	56.00	-20.60	QP
12		2.8660	10.26	9.64	19.90	46.00	-26.10	AVG

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor



Attachment B-- Radiated Emission Test Data


9 KHz to 30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Fundamental and Harmonics emissions (30MHz-1GHz)

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX Mode		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		148.4410	54.38	-20.64	33.74	43.50	-9.76	peak
2	!	346.8091	55.91	-13.73	42.18	46.00	-3.82	peak
3	*	434.0649	84.85	-11.80	73.05	100.82	-27.77	peak
4	X	434.0649	81.63	-11.80	66.48	80.82	-14.34	AVG
5	!	545.1825	51.18	-9.21	41.97	46.00	-4.03	peak
6	X	869.1300	67.30	-4.84	62.46	100.82	-38.36	peak
7	X	869.1301	64.08	-4.84	55.89	80.82	-24.93	AVG

Average Value=Peak Value-6.57

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX Mode		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	!	148.4410	59.85	-20.64	39.21	43.50	-4.29	peak
2	!	346.8092	54.74	-13.73	41.01	46.00	-4.99	peak
3	*	434.0649	83.92	-11.80	72.12	100.82	-28.70	peak
4	X	434.0650	80.70	-11.80	65.55	80.82	-15.27	AVG
5	!	651.9417	50.71	-7.61	43.10	46.00	-2.90	peak
6	X	869.1299	66.00	-4.84	61.16	100.82	-39.66	peak
7	X	869.1302	62.78	-4.84	54.59	80.82	-26.23	AVG


Average Value=Peak Value-6.57

Emission Level= Read Level+ Correct Factor

- Note:**
- (1) All Readings are Peak Value.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss
 - (3) The QP measurement was not performed when the peak measured data under the limit of QP detection.

Above 1G

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Horizontal		
Test Mode:	TX Mode		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		1301.542	16.13	29.49	45.62	74.00	-28.38	peak
2	*	1301.542	12.91	29.49	39.05	54.00	-14.95	AVG
3		1735.950	11.78	31.34	43.12	74.00	-30.88	peak
4		1735.950	8.56	31.34	36.55	54.00	-17.45	AVG
5		2169.750	6.53	34.03	40.56	74.00	-33.44	peak
6		2169.750	3.31	34.03	33.99	54.00	-20.01	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-6.57

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.7V		
Ant. Pol.	Vertical		
Test Mode:	TX Mode		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		1301.671	23.72	29.49	53.21	74.00	-20.79	peak
2	*	1301.671	20.50	29.49	46.64	54.00	-7.36	AVG
3		1735.540	18.18	31.34	49.52	74.00	-24.48	peak
4		1735.540	14.96	31.34	42.95	54.00	-11.05	AVG
5		2169.750	13.20	34.03	47.23	74.00	-26.77	peak
6		2169.750	9.98	34.03	40.66	54.00	-13.34	AVG

Emission Level= Read Level+ Correct Factor

Average Value=Peak Value-6.57

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV. And AV is calculated by the following:
Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values.
Average Values=Peak Values+20log (Duty Cycle)
 - (2) Emission Level= Reading Level + Probe Factor +Cable Loss
 - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Pulse Desensitization Correction Factor

Note:

- (1) The Smallest Pulse Width (PW)=0.5ms
- (2) $2/PW=2/0.5 \text{ (ms)}=4 \text{ kHz}<100 \text{ kHz}$

Because $2/PW < RBW$, so the PDCF is not needed.

Attachment C--Bandwidth Data

Temperature	:	25 °C		
Relative Humidity	:	65 %		
Pressure	:	1010 hPa		
Test Power	:	DC 3.7V		
Frequency (MHz)	20dBc Bandwidth (kHz)	99% OBW (kHz)	Result	
433.92	37.211	48.3962	PASS	

Agilent

Ch Freq 433.92 MHz

Trig Line

Occupied Bandwidth

Center 433.920000 MHz

Ref 107 dBμV


Atten 10 dB

#Peak

Log

10

dB/



Center 433.9 MHz

#Res BW 10 kHz

#VBW 30 kHz

Sweep 10.36 ms (401 pts)

Span 1 MHz

Occupied Bandwidth

48.3962 kHz

Occ BW % Pwr

99.00 %

x dB

-20.00 dB

Transmit Freq Error

5.053 kHz

x dB Bandwidth

37.211 kHz

Freq/Channel

Center Freq 433.920000 MHz

Start Freq 433.420000 MHz

Stop Freq 434.420000 MHz

CF Step 100.000000 kHz

Auto

Man

Freq Offset 0.00000000 Hz

Signal Track

On


Off

Scale Type

Log

Lin

Attachment D-- Release Time Measurement Data



Attachment E--Duty Cycle Data

Plot 1: transmit once in 80ms, and each cycle is 55ms there are three kinds of pulse in each cycle, the large pulses total 14, the small pulses total 11.

Plot 2: one large pulse in a time period of 1.45ms


Plot 2: one middle pulse in a time period of 0.5ms

Duty Cycle=ON/Total=(14*1.45+11*0.5)/55=25.8/55=46.9%


20log (Duty Cycle)=-6.57

Average=Peak Value+20log (Duty Cycle), AV=PK-6.57

Plot 1



Plot 2



-----END OF REPORT-----