



SPECIFICATION FOR APPROVAL

1.MECHANICAL DIMENSION (UNIT:mm)



2. SCHEMATICS:



A	B	C	D	E	F	G	H
54±0.5	42±0.5	46.5±0.8	39.5±0.8	21±0.5	8.5±0.5	0.8±0.5	2.8Max

3.WINDING: 1.1

STEP	START-FINISH	WIRE TYPE	TURNS	TAPE	REMARK
N1	S-F	Silk-covered wireø0.08*105mm 2UEW	9TS (Ref)		

4. ELECTRICAL SPECIFICATION:

ITEM	L	DCR		Temperature	HI-POT
TEST	Coil and diskette	S-F		Normal state	
CON	100KHz, 0.25V	AT 25℃			
SPEC	6.5uH±10%	58mΩ Max		80℃	

5.BILF OF MATERIAL:

NO.	ITEM	MATERIAL SPECIFICATION	MANUFACTURER	SGS NO.
1	Silk-covered wire	Silk covered thread 0.08*105 strands	NANJINGJINNINGCO,LTD	
2	Lead-free tin strip	Lead-free tin strip	QIAODO	
3	Magnetic sheet	ø54*42*0.8Manganese zinc hard disk with L slot	TAIYI CO.,LTD	
4	glue	Yellow gum9999	LIANCHENG CO.,LTD	
5	High-temperature adhesive paper	8mmWide high temperature adhesive paper	CUDAK CO.,LTD	

HRSW ELECTRONICS CO.,LTD		PART NO	
		TITLE	5442Square coil 9 turns 35 long
DRAWN BY	CHECKED BY		APPROVED BY
He Weihua	Wei Lihong		Wei Lihong

Shenzhen Tengsai Technology Co., LTD
Room 203, Building A, No. 12, Xiawei Industrial Zone, Zhangxi Community,
Guanhu Street, Longhua District, Shenzhen