

FCC SAR Test Report

Report No. : SA171229W006

Applicant : Meizu Technology Co., Ltd.

Address : Meizu Tech Bldg., Technology & Innovation Coast, Zhuhai, Guangdong
Province, China

Product : LTE Mobile Phone

FCC ID : 2ANQ6-M881H

Brand : MEIZU

Model No. : M881H


Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2013
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02
KDB 248227 D01 v02r02 / KDB 447498 D01 v06 / KDB 648474 D04 v01r03
KDB 941225 D01 v03r01 / KDB 941225 D05 v02r05 / KDB 941225 D05A v01r02
KDB 941225 D06 v02r01

Sample Received Date : Jan. 13, 2018

Date of Testing : Jan. 14, 2018 ~ Feb. 26, 2018

CERTIFICATION: The above equipment have been tested by **BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By : 
Kei Zhang / Engineer

Approved By : 
Luke Lu / Manager



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	7
3.1 Definition of Specific Absorption Rate (SAR)	7
3.2 SPEAG DASY System	7
3.2.1 Robot	8
3.2.2 Probes	9
3.2.3 Data Acquisition Electronics (DAE)	9
3.2.4 Phantoms	10
3.2.5 Device Holder	11
3.2.6 System Validation Dipoles	11
3.2.7 Tissue Simulating Liquids	12
3.3 SAR System Verification	15
3.4 SAR Measurement Procedure	16
3.4.1 Area & Zoom Scan Procedure	16
3.4.2 Volume Scan Procedure	16
3.4.3 Power Drift Monitoring	17
3.4.4 Spatial Peak SAR Evaluation	17
3.4.5 SAR Averaged Methods	17
4. SAR Measurement Evaluation	18
4.1 EUT Configuration and Setting	18
4.2 EUT Testing Position	25
4.2.1 Head Exposure Conditions	25
4.2.2 Body-worn Accessory Exposure Conditions	27
4.2.3 Hotspot Mode Exposure Conditions	28
4.2.4 SAR Test Exclusion Evaluations	29
4.2.5 Simultaneous Transmission Possibilities	30
4.3 Tissue Verification	31
4.4 System Validation	31
4.5 System Verification	32
4.6 Maximum Output Power	33
4.6.1 Maximum Conducted Power	33
4.6.2 Measured Conducted Power Result	34
4.7 SAR Testing Results	43
4.7.1 SAR Test Reduction Considerations	43
4.7.2 SAR Results for Head Exposure Condition	45
4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap)	48
4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap)	49
4.7.5 SAR Measurement Variability	53
4.7.6 Simultaneous Multi-band Transmission Evaluation	54
5. Calibration of Test Equipment	73
6. Measurement Uncertainty	74
7. Information on the Testing Laboratories	76

Appendix A. SAR Plots of System Verification

Appendix B. SAR Plots of SAR Measurement

Appendix C. Calibration Certificate for Probe and Dipole

Appendix D. Photographs of EUT and Setup

Release Control Record

Report No.	Reason for Change	Date Issued
SA171229W006	Initial release	Apr. 02, 2018

FCC SAR Test Report

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Head SAR _{1g} (W/kg)	Highest Reported Body-worn SAR _{1g} (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR _{1g} (1.0 cm Gap) (W/kg)
PCE	GSM850	1.11	0.93	0.93
	GSM1900	0.45	0.64	1.32
	WCDMA II	0.29	0.47	0.75
	WCDMA V	0.21	0.29	0.29
	CDMA BC0	0.25	0.34	0.34
	LTE 4	0.58	0.09	0.15
	LTE 5	0.18	0.25	0.25
	LTE 7	0.57	0.65	0.65
	LTE 41	0.29	0.38	0.38
DTS	2.4G WLAN	0.17	0.04	0.04
NII	5.2G WLAN	-	-	0.03
	5.3G WLAN	0.23	0.01	-
	5.6G WLAN	0.20	0.00	-
	5.8G WLAN	0.37	0.02	0.03
DSS	Bluetooth	N/A	N/A	N/A
Highest Simultaneous Transmission SAR		Head (W/kg)	Body-worn (W/kg)	Hotspot (W/kg)
PCE + DTS		1.22	0.97	1.32
PCE + NII		1.42	0.93	1.32
PCE + DSS		N/A	1.30	N/A

Note:

- The SAR limit (Head & Body: SAR_{1g} 1.6 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

2. Description of Equipment Under Test

EUT Type	LTE Mobile Phone
FCC ID	2ANQ6-M881H
Brand Name	MEIZU
Model Name	M881H
IMEI Code	866776030000473/ 866776030000416
HW Version	V1.0
SW Version	Flyme7.0.2.0G
Tx Frequency Bands (Unit: MHz)	GSM850 : 824.2 ~ 848.8 GSM1900 : 1850.2 ~ 1909.8 WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band V : 826.4 ~ 846.6 CDMA BC0 : 824.7 ~ 848.31 LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 5 : 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~ 844 (10M) LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) LTE Band 41 : 2557.5 ~ 2652.5 (5M), 2560 ~ 2650 (10M), 2562.5 ~ 2647.5 (15M), 2565 ~ 2645 (20M) WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480
Uplink Modulations	GSM & GPRS : GMSK EDGE : 8PSK WCDMA : QPSK CDMA : QPSK LTE : QPSK, 16QAM, 64QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK, LE
Maximum Tune-up Conducted Power (Unit: dBm)	GSM850 : 33.0 GSM1900 : 30.0 WCDMA Band II : 23.5 WCDMA Band V : 23.5 CDMA BC0 : 24.5 LTE Band 4 : 23.5 LTE Band 5 : 23.0 LTE Band 7 : 23.5 LTE Band 41 : 23.5 WLAN 2.4G : 17.5 WLAN 5.2G : 17.5 WLAN 5.3G : 17.5 WLAN 5.6G : 17.5 WLAN 5.8G : 17.5 Bluetooth : 12.5
Antenna Type	WLAN: PIFA Antenna WWAN: Fixed Internal Antenna
EUT Stage	Production Unit

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

FCC SAR Test Report

List of Accessory:

Battery	Brand Name	MEIZU
	Model Name	BA881
	Power Rating	3.85Vdc, 3000mAh
	Type	Li-ion
Earphone	Brand Name	MEIZU
	Model Name	EP21HD
	Signal Line Type	1.2 meter non-shielded cable without ferrite core

FCC SAR Test Report

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

FCC SAR Test Report




Fig-3.1 DASY System Setup

3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig-3.2 DASY5

FCC SAR Test Report

3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	$< 5\mu$ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

FCC SAR Test Report

3.2.4 Phantoms


Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

FCC SAR Test Report

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	

Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	


3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W ($f < 1\text{GHz}$), > 40 W ($f > 1\text{GHz}$)	

FCC SAR Test Report

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53
For Body				
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30

FCC SAR Test Report


The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	28.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8	-	0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

FCC SAR Test Report

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	≤ 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	≤ 15 mm	≤ 12 mm	≤ 12 mm	≤ 10 mm	≤ 10 mm
Zoom Scan ($\Delta x, \Delta y$)	≤ 8 mm	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 4 mm
Zoom Scan (Δz)	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 3 mm	≤ 2 mm
Zoom Scan Volume	≥ 30 mm	≥ 30 mm	≥ 28 mm	≥ 25 mm	≥ 22 mm

Note:

When zoom scan is required and report SAR is ≤ 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: ≤ 8 mm, 3-4GHz: ≤ 7 mm, 4-6GHz: ≤ 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

FCC SAR Test Report

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for GSM/WCDMA/CDMA, and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to GSM / GPRS / EDGE for Setup and Testing>

The maximum multi-slot capability supported by this device is as below.

1. This EUT is class B device
2. This EUT supports GPRS multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)
3. This EUT supports EDGE multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)

For GSM850 frequency band, the power control level is set to 5 for GSM mode and GPRS (GMSK: CS1), and set to 8 for EDGE (GMSK: MCS1, 8PSK: MCS9). For GSM1900 frequency band, the power control level is set to 0 for GSM mode and GPRS (GMSK: CS1), and set to 2 for EDGE (GMSK: MCS1, 8PSK: MCS9).

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

<Considerations Related to WCDMA for Setup and Testing>

WCDMA Handsets Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the "Release 5 HSDPA Data Devices", for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

FCC SAR Test Report

Handsets with Release 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the "Release 6 HSPA Data Devices", for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.
Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.
Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSUPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

FCC SAR Test Report

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	11 / 15 ⁽³⁾	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75
2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 ⁽⁴⁾	15 / 15 ⁽⁴⁾	64	15 / 15 ⁽⁴⁾	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{OQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$
Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.
Note 3: For subtest 1 the β_c / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10 / 15$ and $\beta_d = 15 / 15$.
Note 4: For subtest 5 the β_c / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14 / 15$ and $\beta_d = 15 / 15$.
Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.
Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

<Considerations Related to CDMA for Setup and Testing>

CDMA 1xRTT Handsets Head SAR

SAR for next to the ear head exposure is measured in RC3 with the handset configured to transmit at full rate in SO55. The 3G SAR test reduction procedure is applied to RC1 with RC3 as the primary mode. Otherwise, SAR is required for the channel with maximum measured output in RC1 using the head exposure configuration that results in the highest reported SAR in RC3.

CDMA 1xRTT Handsets Body-worn SAR

Body-worn SAR is measured in RC3 with the handset configured in TDSO/SO32 to transmit at full rate on FCH only with all other code channels disabled. The 3G SAR test reduction procedure is applied to the multiple code channel configuration (FCH + SCH_n), with FCH only as the primary mode. Otherwise, SAR is required for multiple code channel configuration (FCH + SCH_n), with FCH at full rate and SCH₀ enabled at 9600 bps, using the highest reported SAR configuration for FCH only. The 3G SAR test reduction procedure is applied to body-worn SAR in RC1 with RC3 as the primary mode. Otherwise, SAR is required for RC1, with SO55 and full rate, using the highest reported SAR configuration for body-worn exposure in RC3.

Handsets with built-in EV-DO

The 3G SAR test reduction procedure is applied to EV-DO Rev. 0 with 1xRTT RC3 as the primary mode to determine body-worn test requirements. Otherwise, body-worn SAR is required for Rev. 0, at 153.6 kbps, using the highest reported SAR configuration for body-worn exposure in RC3. The 3G SAR test reduction procedure is applied separately to Rev. A and Rev. B, with Rev. 0 as the primary mode to determine body-worn SAR test requirements. When SAR is not required for Rev. 0, the 3G SAR test reduction is applied with 1xRTT RC3 as the primary mode. Otherwise, SAR is required for Rev. A or Rev. B, with a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 and 3 Physical Layer configurations, using the highest reported SAR configuration for body-worn exposure in Rev. 0 or RC3, as appropriate. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with ACK Channel transmitting in all slots is configured in the downlink for Rev. 0, Rev. A and Rev. B.

FCC SAR Test Report

EV-DO Data Devices

SAR is measured using the F/R TAP configurations required for Rev. 0, Rev. A and Rev. B. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations. A Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots are used for Subtype 2 and 3. FTAP, FETAP and FMCTAP are all configured with a Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with ACK Channel transmitting in all slots. AT power control is in "All Bits Up" conditions for the TAP / ETAP / MCTAP. Body-worn and other body SAR are measured using Subtype 0/1 Physical Layer configurations for Rev. 0. The 3G SAR test reduction procedure is applied to Rev. A, Subtype 2 Physical layer configuration, with Rev. 0 as the primary mode. Otherwise, SAR is measured for Rev. A using the highest reported SAR configuration for body-worn exposure in Rev. 0. SAR is required for Rev. B, Subtype 3; it is measured by applying both the "test 2" and "test 3" configurations used for power measurement.

EV-DO Data Devices Support 1xRTT

The 3G SAR test reduction procedure is applied to 1xRTT RC3 and RC1 with EV-DO Rev. 0, Rev. A and Rev. B as the respective primary modes. Otherwise, the "CDMA 1xRTT Handsets Body-worn SAR" procedures are applied.

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 3, supports QPSK / 16QAM / 64QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for QPSK / 16QAM / 64QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
41			V	V	V	V

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
64QAM	> 5	> 4	> 8	> 12	> 16	> 18	2

Note: MPR is according to the standard and implemented in the circuit (mandatory).


In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

FCC SAR Test Report

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592 • Ts	2192 • Ts	2560 • Ts	7680 • Ts	2192 • Ts	2560 • Ts
1	19760 • Ts			20480 • Ts		
2	21952 • Ts			23040 • Ts		
3	24144 • Ts			25600 • Ts		
4	26336 • Ts	4384 • Ts	5120 • Ts	7680 • Ts	4384 • Ts	5120 • Ts
5	6592 • Ts			20480 • Ts		
6	19760 • Ts			23040 • Ts		
7	21952 • Ts			12800 • Ts		
8	24144 • Ts	-	-	-	-	-
9	13168 • Ts			-	-	-

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

FCC SAR Test Report

LTE Downlink Carrier Aggregation (CA) Setup Configurations

LTE Carrier Aggregation (CA) was defined in 3GPP release 10 and higher. The LTE device in CA mode has one Primary Component Carrier (PCC) and one or more Secondary Component Carriers (SCC). PCC acts as the anchor carrier and can optionally cross-schedule data transmission on SCC. The RRC connection is only handled by one cell, the PCC for downlink and uplink communications. After making a data connection to the PCC, the LTE device adds the SCC on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. The combinations of downlink carrier aggregation supported by this device are listed in below.

EUT Supported Combinations of Downlink Carrier Aggregation							
Intra-Band Contiguous CA Operating Bands							
CA_41							

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration

FCC SAR Test Report

according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

4.2 EUT Testing Position

According to KDB 648474 D04, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

4.2.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
 - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
 - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
 - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines

2. Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear,

FCC SAR Test Report

move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).




Fig-4.2 Illustration for Cheek Position

3. Tilted Position

- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).




Fig-4.3 Illustration for Tilted Position

FCC SAR Test Report

4.2.2 Body-worn Accessory Exposure Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 D01 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance $\leq 5 \text{ mm}$ to support compliance.





Fig-4.4 Illustration for Body Worn Position

FCC SAR Test Report

4.2.3 Hotspot Mode Exposure Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225 D06. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed as below.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
WWAN Ant-0	V	V		V	V	
WWAN Ant-1	V	V	V	V		V
WLAN / BT	V	V	V		V	

FCC SAR Test Report

4.2.4 SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0 \text{ for SAR-1g, } \leq 7.5 \text{ for SAR-10g}$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Body-Worn		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
BT (2.48 GHz)	12.5	17.78	10	2.8	No

Note:

1. When separation distance <= 50 mm and the calculated result shown in above table is <= 3.0 for SAR-1g exposure condition, or <= 7.5 for SAR-10g exposure condition, the SAR testing exclusion is applied.

FCC SAR Test Report

4.2.5 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Head (Voice / VoIP)	Body-worn (Voice / VoIP)	Hotspot (Data)
1	GSM850 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
2	GSM1900 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
3	WCDMA II (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
4	WCDMA V (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
5	CDMA BC0 (Voice / Data) + WLAN (Data)	Yes	Yes	Yes
6	LTE 4 (Data) + WLAN (Data)	Yes	Yes	Yes
7	LTE 5 (Data) + WLAN (Data)	Yes	Yes	Yes
8	LTE 7 (Data) + WLAN (Data)	Yes	Yes	Yes
9	LTE 41 (Data) + WLAN (Data)	Yes	Yes	Yes
10	GSM850 (Voice / Data) + BT (Data)	No	Yes	No
11	GSM1900 (Voice / Data) + BT (Data)	No	Yes	No
12	WCDMA II (Voice / Data) + BT (Data)	No	Yes	No
13	WCDMA V (Voice / Data) + BT (Data)	No	Yes	No
14	CDMA BC0 (Voice / Data) + BT (Data)	No	Yes	No
15	LTE 4 (Data) + BT (Data)	No	Yes	No
16	LTE 5 (Data) + BT (Data)	No	Yes	No
17	LTE 7 (Data) + BT (Data)	No	Yes	No
18	LTE 41 (Data) + BT (Data)	No	Yes	No

Note :

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.
2. The WLAN and Bluetooth cannot transmit simultaneously, so there is no co-location test requirement for WLAN and Bluetooth.
3. Only 2.4G WLAN (802.11b/g/n) and 5G WLAN (802.11a/n/ac) Band 1/4 support wireless hotspot capability. 5G WLAN (802.11a/n/ac) Band 2/3 does not support wireless hotspot mode.
4. Both GSM/WCDMA/CDMA and LTE can transmit through either antenna-0 or antenna-1. However, only one technology (GSM/WCDMA/CDMA or LTE) can transmit from an antenna at a time, and the other technology transmits through the other antenna.

FCC SAR Test Report

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Jan. 21, 2018	H850	835	22.2	0.925	42.855	0.90	41.50	2.78	3.27
Jan. 19, 2018	H1750	1750	22.1	1.346	39.504	1.37	40.10	-1.75	-1.49
Jan. 18, 2018	H1900	1900	22.1	1.425	41.401	1.40	40.00	1.79	3.50
Feb. 24, 2018	H2450	2450	21.9	1.845	39.401	1.80	39.20	2.50	0.51
Jan. 14, 2018	H2600	2600	21.7	2.039	38.932	1.96	39.00	4.03	-0.17
Feb. 25, 2018	H5G	5250	22.2	4.691	35.327	4.71	35.90	-0.40	-1.60
Feb. 25, 2018	H5G	5600	22.2	5.041	34.826	5.07	35.50	-0.57	-1.90
Feb. 25, 2018	H5G	5800	22.2	5.249	34.537	5.27	35.30	-0.40	-2.16
Jan. 20, 2018	B850	835	22.3	0.976	54.382	0.97	55.20	0.62	-1.48
Jan. 22, 2018	B1750	1750	22.2	1.471	53.784	1.49	53.40	-1.28	0.72
Jan. 23, 2018	B1900	1900	22.4	1.571	53.584	1.52	53.30	3.36	0.53
Feb. 24, 2018	B2450	2450	21.9	1.963	50.972	1.95	52.70	0.67	-3.28
Jan. 17, 2018	B2600	2600	21.9	2.096	50.743	2.16	52.50	-2.96	-3.35
Feb. 26, 2018	B5G	5250	22.3	5.379	48.856	5.36	48.90	0.35	-0.09
Feb. 26, 2018	B5G	5600	22.3	5.871	48.168	5.77	48.50	1.75	-0.68
Feb. 26, 2018	B5G	5800	22.3	6.123	47.668	6.00	48.20	2.05	-1.10

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Jan. 21, 2018	3873	Head	835	0.925	42.855	Pass	Pass	Pass	GMSK	Pass	N/A
Jan. 19, 2018	3873	Head	1750	1.346	39.504	Pass	Pass	Pass	N/A	N/A	N/A
Jan. 18, 2018	3873	Head	1900	1.425	41.401	Pass	Pass	Pass	GMSK	Pass	N/A
Feb. 24, 2018	3873	Head	2450	1.845	39.401	Pass	Pass	Pass	OFDM	N/A	Pass
Jan. 14, 2018	3873	Head	2600	2.039	38.932	Pass	Pass	Pass	N/A	N/A	N/A
Feb. 25, 2018	3873	Head	5250	4.691	35.327	Pass	Pass	Pass	OFDM	N/A	Pass
Feb. 25, 2018	3873	Head	5600	5.041	34.826	Pass	Pass	Pass	OFDM	N/A	Pass
Feb. 25, 2018	3873	Head	5800	5.249	34.537	Pass	Pass	Pass	OFDM	N/A	Pass
Jan. 20, 2018	3873	Body	835	0.976	54.382	Pass	Pass	Pass	GMSK	Pass	N/A
Jan. 22, 2018	3873	Body	1750	1.471	53.784	Pass	Pass	Pass	N/A	N/A	N/A
Jan. 23, 2018	3873	Body	1900	1.571	53.584	Pass	Pass	Pass	GMSK	Pass	N/A
Feb. 24, 2018	3873	Body	2450	1.963	50.972	Pass	Pass	Pass	OFDM	N/A	Pass
Jan. 17, 2018	3873	Body	2600	2.096	50.743	Pass	Pass	Pass	N/A	N/A	N/A
Feb. 26, 2018	3873	Body	5250	5.379	48.856	Pass	Pass	Pass	OFDM	N/A	Pass
Feb. 26, 2018	3873	Body	5600	5.871	48.168	Pass	Pass	Pass	OFDM	N/A	Pass
Feb. 26, 2018	3873	Body	5800	6.123	47.668	Pass	Pass	Pass	OFDM	N/A	Pass

FCC SAR Test Report

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Jan. 21, 2018	Head	835	9.49	2.52	10.08	6.22	4d139	3873	1341
Jan. 19, 2018	Head	1750	37.30	9.27	37.08	-0.59	1071	3873	1341
Jan. 18, 2018	Head	1900	39.80	10.20	40.80	2.51	5d159	3873	1341
Feb. 24, 2018	Head	2450	52.60	13.50	54.00	2.66	893	3873	1341
Jan. 14, 2018	Head	2600	57.40	14.80	59.20	3.14	1110	3873	1341
Feb. 25, 2018	Head	5250	78.50	7.98	79.80	1.66	1133	3873	1341
Feb. 25, 2018	Head	5600	82.10	7.86	78.60	-4.26	1133	3873	1341
Feb. 25, 2018	Head	5800	80.10	7.51	75.10	-6.24	1133	3873	1341
Jan. 20, 2018	Body	835	9.71	2.32	9.28	-4.43	4d139	3873	1341
Jan. 22, 2018	Body	1750	38.30	9.64	38.56	0.68	1071	3873	1341
Jan. 23, 2018	Body	1900	40.30	10.70	42.80	6.20	5d159	3873	1341
Feb. 24, 2018	Body	2450	51.60	13.10	52.40	1.55	893	3873	1341
Jan. 17, 2018	Body	2600	53.80	13.80	55.20	2.60	1110	3873	1341
Feb. 26, 2018	Body	5250	76.60	7.53	75.30	-1.70	1133	3873	1341
Feb. 26, 2018	Body	5600	78.80	7.90	79.00	0.25	1133	3873	1341
Feb. 26, 2018	Body	5800	77.20	7.59	75.90	-1.68	1133	3873	1341

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

FCC SAR Test Report

4.6 Maximum Output Power

4.6.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	GSM850	GSM1900
GSM (GMSK, 1Tx-slot)	33.0	30.0
GPRS (GMSK, 1Tx-slot)	33.0	30.0
GPRS (GMSK, 2Tx-slot)	33.0	30.0
GPRS (GMSK, 3Tx-slot)	32.5	29.5
GPRS (GMSK, 4Tx-slot)	32.5	29.0
EDGE (8PSK, 1Tx-slot)	27.0	25.5
EDGE (8PSK, 2Tx-slot)	27.0	25.5
EDGE (8PSK, 3Tx-slot)	26.5	25.0
EDGE (8PSK, 4Tx-slot)	26.5	25.0

Mode	WCDMA Band II	WCDMA Band V
RMC 12.2K	23.5	23.5
HSDPA	22.5	22.5
DC-HSDPA	22.5	22.5
HSUPA	22.5	22.5

Mode	CDMA BC0
1xRTT	24.5
1xEVDO Rev.0	24.5
1xEVDO Rev.A	24.5

Mode	LTE 4	LTE 5	LTE 7	LTE 41
QPSK / 16QAM / 64QAM	23.5 / 22.5 / 21.5	23.0 / 22.0 / 21.0	23.5 / 22.5 / 21.5	23.5 / 22.5 / 21.5

Mode	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11b	17.5	N/A	N/A	N/A	N/A
802.11g	17.0	N/A	N/A	N/A	N/A
802.11a	N/A	17.5	17.5	17.5	17.5
802.11n HT20	16.5	16.5	16.5	17.0	17.0
802.11n HT40	N/A	16.0	15.5	16.5	16.5
802.11ac VHT80	N/A	15.5	15.5	16.0	15.5

Mode	2.4G Bluetooth
GFSK	12.5
$\pi/4$ -DQPSK	9.0
8DPSK	9.0
LE	0.5

FCC SAR Test Report

4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	32.63	32.83	32.89	29.47	29.84	29.76
GPRS (GMSK, 1Tx-slot)	32.55	32.75	32.81	29.41	29.78	29.70
GPRS (GMSK, 2Tx-slot)	32.42	32.62	32.68	29.31	29.68	29.60
GPRS (GMSK, 3Tx-slot)	32.22	32.42	32.48	28.92	29.29	29.21
GPRS (GMSK, 4Tx-slot)	32.01	32.21	32.27	28.75	28.92	28.84
EDGE (8PSK, 1Tx-slot)	26.47	26.67	26.73	25.24	25.41	25.33
EDGE (8PSK, 2Tx-slot)	26.31	26.51	26.57	25.04	25.21	25.13
EDGE (8PSK, 3Tx-slot)	26.08	26.28	26.34	24.75	24.92	24.84
EDGE (8PSK, 4Tx-slot)	25.84	26.04	26.10	24.46	24.63	24.55
Maximum Frame-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	23.63	23.83	23.89	20.47	20.84	20.76
GPRS (GMSK, 1Tx-slot)	23.55	23.75	23.81	20.41	20.78	20.70
GPRS (GMSK, 2Tx-slot)	26.42	26.62	26.68	23.31	23.68	23.60
GPRS (GMSK, 3Tx-slot)	27.96	28.16	28.22	24.66	25.03	24.95
GPRS (GMSK, 4Tx-slot)	29.01	29.21	29.27	25.75	25.92	25.84
EDGE (8PSK, 1Tx-slot)	17.47	17.67	17.73	16.24	16.41	16.33
EDGE (8PSK, 2Tx-slot)	20.31	20.51	20.57	19.04	19.21	19.13
EDGE (8PSK, 3Tx-slot)	21.82	22.02	22.08	20.49	20.66	20.58
EDGE (8PSK, 4Tx-slot)	22.84	23.04	23.10	21.46	21.63	21.55

Note:

- SAR testing was performed on the maximum frame-averaged power mode.
- The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:
Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8)
- The configuration of time-slot for GSM has transmitting signal in one time-slot during one frame (8 time-slots).

Band	WCDMA Band II			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	826.4	836.4	846.6	
RMC 12.2K	23.45	23.26	23.35	23.09	23.16	23.28	-
HSDPA Subtest-1	22.47	22.28	22.37	22.08	22.15	22.27	0
HSDPA Subtest-2	22.48	22.29	22.38	22.12	22.19	22.31	0
HSDPA Subtest-3	21.98	21.79	21.88	21.64	21.71	21.83	0.5
HSDPA Subtest-4	22.00	21.81	21.90	21.62	21.69	21.81	0.5
DC-HSDPA Subtest-1	22.38	22.19	22.28	22.04	22.11	22.23	0
DC-HSDPA Subtest-2	22.34	22.15	22.24	22.02	22.09	22.21	0
DC-HSDPA Subtest-3	21.86	21.67	21.76	21.57	21.64	21.76	0.5
DC-HSDPA Subtest-4	21.83	21.64	21.73	21.53	21.60	21.72	0.5
HSUPA Subtest-1	22.17	22.17	22.17	22.13	22.13	22.13	0
HSUPA Subtest-2	20.23	20.23	20.23	20.21	20.21	20.21	2
HSUPA Subtest-3	21.25	21.25	21.25	21.16	21.16	21.16	1
HSUPA Subtest-4	20.19	20.19	20.19	20.17	20.17	20.17	2
HSUPA Subtest-5	22.29	22.29	22.29	22.18	22.18	22.18	0

FCC SAR Test Report

Band	CDMA BC0		
Channel	1013	384	777
Frequency (MHz)	824.70	836.52	848.31
1xRTT RC1+SO55	24.08	24.18	24.13
1xRTT RC3+SO55	24.15	24.20	24.19
1xRTT RC3+SO32 (FCH)	24.12	24.17	24.15
1xRTT RC3+SO32 (SCH)	24.07	24.12	24.10
1xEVDO Rev.0 RTAP 153.6	23.98	24.08	24.03
1xEVDO Rev.A RETAP 4096	24.06	24.16	24.11

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 19193		Low CH 19957	Mid CH 20175	High CH 19193		Low CH 19957	Mid CH 20175	High CH 19193	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	22.99	23.11	22.99	0	22.28	22.34	22.25	1	21.11	21.21	21.13	2
	1	2	22.93	22.98	22.91	0	22.27	22.29	22.24	1	21.07	21.21	21.07	2
	1	5	22.81	22.84	22.75	0	22.19	22.24	22.20	1	21.10	21.12	21.07	2
	3	0	23.04	23.10	23.05	0	22.06	22.13	22.02	1	21.20	20.30	20.17	2
	3	1	23.05	23.12	22.95	0	21.99	22.14	21.99	1	21.17	20.29	20.14	2
	3	3	22.96	23.01	22.92	0	21.99	22.06	21.99	1	21.16	20.21	20.17	2
	6	0	22.00	22.03	21.96	1	21.03	21.15	21.01	2	20.19	20.26	20.15	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	23.01	23.13	22.98	0	22.25	22.40	22.28	1	21.17	21.24	21.07	2
	1	7	22.89	22.99	22.91	0	22.24	22.32	22.22	1	21.10	21.15	21.06	2
	1	14	22.77	22.84	22.75	0	22.22	22.24	22.20	1	21.11	21.14	21.07	2
	8	0	22.03	22.13	22.05	1	21.02	21.14	21.02	2	20.23	20.34	20.18	3
	8	3	21.98	22.12	21.97	1	21.04	21.09	21.02	2	20.21	20.23	20.19	3
	8	7	21.93	22.08	21.96	1	21.01	21.04	20.95	2	20.13	20.25	20.13	3
	15	0	21.97	22.04	21.90	1	21.03	21.09	21.04	2	20.21	20.23	20.19	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	23.02	23.08	22.99	0	22.26	22.36	22.28	1	21.11	21.21	21.13	2
	1	12	22.94	22.96	22.91	0	22.21	22.35	22.21	1	21.07	21.21	21.06	2
	1	24	22.78	22.83	22.79	0	22.22	22.24	22.19	1	21.04	21.19	21.07	2
	12	0	22.06	22.13	22.02	1	21.02	21.12	20.99	2	20.24	20.31	20.17	3
	12	6	21.98	22.13	21.98	1	21.01	21.13	20.98	2	20.15	20.30	20.18	3
	12	13	21.97	22.04	21.97	1	20.96	21.06	20.98	2	20.17	20.24	20.10	3
	25	0	21.95	22.07	21.93	1	21.03	21.10	21.01	2	20.17	20.29	20.17	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	22.99	23.11	22.99	0	22.26	22.33	22.24	1	21.10	21.22	21.10	2
	1	24	22.94	22.96	22.92	0	22.26	22.31	22.24	1	21.12	21.17	21.10	2
	1	49	22.75	22.87	22.75	0	22.22	22.25	22.16	1	21.10	21.13	21.04	2
	25	0	22.07	22.12	22.05	1	21.04	21.10	21.05	2	20.22	20.28	20.23	3
	25	12	22.04	22.07	21.98	1	21.05	21.07	21.03	2	20.22	20.29	20.12	3
	25	25	21.95	22.01	21.96	1	20.95	21.07	20.95	2	20.16	20.21	20.12	3
	50	0	22.00	22.07	21.90	1	21.07	21.09	21.05	2	20.22	20.25	20.18	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	23.06	23.11	22.96	0	22.30	22.40	22.24	1	21.12	21.23	21.11	2
	1	37	22.92	23.01	22.87	0	22.25	22.32	22.24	1	21.13	21.16	21.07	2
	1	74	22.81	22.90	22.76	0	22.18	22.30	22.18	1	21.06	21.12	21.07	2
	36	0	22.04	22.13	22.06	1	21.08	21.10	21.06	2	20.27	20.34	20.17	3
	36	19	22.05	22.12	21.98	1	20.99	21.11	20.99	2	20.16	20.23	20.14	3
	36	39	21.93	22.02	21.96	1	21.00	21.05	20.98	2	20.19	20.28	20.14	3
	75	0	22.00	22.05	21.95	1	21.08	21.12	20.98	2	20.21	20.23	20.19	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	23.07	23.15	23.04	0	22.33	22.41	22.30	1	21.18	21.26	21.15	2
	1	50	22.96	23.04	22.93	0	22.29	22.37	22.26	1	21.15	21.23	21.12	2
	1	99	22.83	22.91	22.80	0	22.24	22.32	22.21	1	21.12	21.20	21.09	2
	50	0	22.10	22.18	22.07	1	21.10	21.18	21.07	2	20.28	20.36	20.25	3
	50	25	22.06	22.14	22.03	1	21.07	21.15	21.04	2	20.23	20.31	20.20	3
	50	50	22.01	22.09	21.98	1	21.03	21.11	21.00	2	20.21	20.29	20.18	3
	100	0	22.01	22.09	21.98	1	21.09	21.17	21.06	2	20.23	20.31	20.20	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20407 824.7 MHz	20525 836.5 MHz	20643 848.3 MHz		20407 824.7 MHz	20525 836.5 MHz	20643 848.3 MHz		20407 824.7 MHz	20525 836.5 MHz	20643 848.3 MHz	
5 / 1.4M	1	0	22.64	22.77	22.79	0	21.81	21.88	21.93	1	20.70	20.81	20.87	2
	1	2	22.66	22.72	22.79	0	21.80	21.83	21.92	1	20.65	20.80	20.80	2
	1	5	22.63	22.67	22.72	0	21.72	21.78	21.88	1	20.69	20.72	20.81	2
	3	0	22.79	22.86	22.95	1	21.75	21.83	21.86	2	20.74	20.85	20.86	3
	3	1	22.81	22.89	22.86	1	21.67	21.83	21.82	2	20.74	20.87	20.86	3
	3	3	22.72	22.78	22.83	1	21.66	21.74	21.81	2	20.72	20.78	20.88	3
	6	0	21.81	21.85	21.92	1	20.74	20.87	20.87	2	19.76	19.84	19.87	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20415 825.5 MHz	20525 836.5 MHz	20635 847.5 MHz		20415 825.5 MHz	20525 836.5 MHz	20635 847.5 MHz		20415 825.5 MHz	20525 836.5 MHz	20635 847.5 MHz	
5 / 3M	1	0	22.66	22.79	22.78	0	21.78	21.94	21.96	1	20.76	20.84	20.81	2
	1	7	22.62	22.73	22.79	0	21.77	21.86	21.90	1	20.68	20.74	20.79	2
	1	14	22.59	22.67	22.72	0	21.75	21.78	21.88	1	20.70	20.74	20.81	2
	8	0	21.78	21.89	21.95	1	20.71	20.84	20.86	2	19.77	19.89	19.87	3
	8	3	21.74	21.89	21.88	1	20.72	20.78	20.85	2	19.78	19.81	19.91	3
	8	7	21.69	21.85	21.87	1	20.68	20.72	20.77	2	19.69	19.82	19.84	3
	15	0	21.78	21.86	21.86	1	20.74	20.81	20.90	2	19.78	19.81	19.91	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20425 826.5 MHz	20525 836.5 MHz	20625 846.5 MHz		20425 826.5 MHz	20525 836.5 MHz	20625 846.5 MHz		20425 826.5 MHz	20525 836.5 MHz	20625 846.5 MHz	
5 / 5M	1	0	22.67	22.74	22.79	0	21.79	21.90	21.96	1	20.70	20.81	20.87	2
	1	12	22.67	22.70	22.79	0	21.74	21.89	21.89	1	20.65	20.80	20.79	2
	1	24	22.60	22.66	22.76	0	21.75	21.78	21.87	1	20.63	20.79	20.81	2
	12	0	21.81	21.89	21.92	1	20.71	20.82	20.83	2	19.78	19.86	19.86	3
	12	6	21.74	21.90	21.89	1	20.69	20.82	20.81	2	19.72	19.88	19.90	3
	12	13	21.73	21.81	21.88	1	20.63	20.74	20.80	2	19.73	19.81	19.81	3
	25	0	21.76	21.89	21.89	1	20.74	20.82	20.87	2	19.74	19.87	19.89	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH	Mid CH	High CH		Low CH	Mid CH	High CH		Low CH	Mid CH	High CH	
			20450 829.0 MHz	20525 836.5 MHz	20600 844.0 MHz		20450 829.0 MHz	20525 836.5 MHz	20600 844.0 MHz		20450 829.0 MHz	20525 836.5 MHz	20600 844.0 MHz	
5 / 10M	1	0	22.72	22.81	22.84	0	21.86	21.95	21.98	1	20.77	20.86	20.89	2
	1	24	22.69	22.78	22.81	0	21.82	21.91	21.94	1	20.73	20.82	20.85	2
	1	49	22.65	22.74	22.77	0	21.77	21.86	21.89	1	20.71	20.80	20.83	2
	25	0	21.85	21.94	21.97	1	20.79	20.88	20.91	2	19.82	19.91	19.94	3
	25	12	21.82	21.91	21.94	1	20.75	20.84	20.87	2	19.80	19.89	19.92	3
	25	25	21.77	21.86	21.89	1	20.70	20.79	20.82	2	19.77	19.86	19.89	3
	50	0	21.82	21.91	21.94	1	20.80	20.89	20.92	2	19.80	19.89	19.92	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20775 MHz	Mid CH 21100 MHz	High CH 21425 MHz		Low CH 20775 MHz	Mid CH 21100 MHz	High CH 21425 MHz		Low CH 20775 MHz	Mid CH 21100 MHz	High CH 21425 MHz	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
7 / 5M	1	0	23.16	23.21	23.28	0	22.22	22.31	22.39	1	21.10	21.19	21.27	2
	1	12	23.12	23.13	23.24	0	22.17	22.30	22.32	1	21.05	21.18	21.19	2
	1	24	23.05	23.09	23.21	0	22.18	22.19	22.30	1	21.01	21.15	21.19	2
	12	0	22.17	22.23	22.28	1	21.12	21.21	21.24	2	20.25	20.31	20.33	3
	12	6	22.07	22.21	22.22	1	21.09	21.20	21.21	2	20.16	20.30	20.34	3
	12	13	22.05	22.11	22.20	1	21.05	21.14	21.22	2	20.18	20.24	20.26	3
	25	0	22.17	22.28	22.30	1	21.15	21.21	21.28	2	20.10	20.21	20.25	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20800 MHz	Mid CH 21100 MHz	High CH 21400 MHz		Low CH 20800 MHz	Mid CH 21100 MHz	High CH 21400 MHz		Low CH 20800 MHz	Mid CH 21100 MHz	High CH 21400 MHz	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
7 / 10M	1	0	23.13	23.24	23.28	0	22.22	22.28	22.35	1	21.09	21.20	21.24	2
	1	24	23.12	23.13	23.25	0	22.22	22.26	22.35	1	21.10	21.14	21.23	2
	1	49	23.02	23.13	23.17	0	22.18	22.20	22.27	1	21.07	21.09	21.16	2
	25	0	22.18	22.22	22.31	1	21.14	21.19	21.30	2	20.23	20.28	20.39	3
	25	12	22.13	22.15	22.22	1	21.13	21.14	21.26	2	20.23	20.29	20.28	3
	25	25	22.03	22.08	22.19	1	21.04	21.15	21.19	2	20.17	20.21	20.28	3
	50	0	22.22	22.28	22.27	1	21.19	21.20	21.32	2	20.15	20.17	20.26	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20825 MHz	Mid CH 21100 MHz	High CH 21375 MHz		Low CH 20825 MHz	Mid CH 21100 MHz	High CH 21375 MHz		Low CH 20825 MHz	Mid CH 21100 MHz	High CH 21375 MHz	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
7 / 15M	1	0	23.20	23.24	23.25	0	22.26	22.35	22.35	1	21.11	21.21	21.25	2
	1	37	23.10	23.18	23.20	0	22.21	22.27	22.35	1	21.11	21.13	21.20	2
	1	74	23.08	23.16	23.18	0	22.14	22.25	22.29	1	21.03	21.08	21.19	2
	36	0	22.15	22.23	22.32	1	21.18	21.19	21.31	2	20.28	20.34	20.33	3
	36	19	22.14	22.20	22.22	1	21.07	21.18	21.22	2	20.17	20.23	20.30	3
	36	39	22.01	22.09	22.19	1	21.09	21.13	21.22	2	20.20	20.28	20.30	3
	75	0	22.22	22.26	22.32	1	21.20	21.23	21.25	2	20.14	20.15	20.27	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20850 MHz	Mid CH 21100 MHz	High CH 21350 MHz		Low CH 20850 MHz	Mid CH 21100 MHz	High CH 21350 MHz		Low CH 20850 MHz	Mid CH 21100 MHz	High CH 21350 MHz	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
7 / 20M	1	0	23.21	23.28	23.33	0	22.29	22.36	22.41	1	21.17	21.24	21.29	2
	1	50	23.14	23.21	23.26	0	22.25	22.32	22.37	1	21.13	21.20	21.25	2
	1	99	23.10	23.17	23.22	0	22.20	22.27	22.32	1	21.09	21.16	21.21	2
	50	0	22.21	22.28	22.33	1	21.20	21.27	21.32	2	20.29	20.36	20.41	3
	50	25	22.15	22.22	22.27	1	21.15	21.22	21.27	2	20.24	20.31	20.36	3
	50	50	22.09	22.16	22.21	1	21.12	21.19	21.24	2	20.22	20.29	20.34	3
	100	0	22.23	22.30	22.35	1	21.21	21.28	21.33	2	20.16	20.23	20.28	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 40265	Mid CH 40740	High CH 41215		Low CH 40265	Mid CH 40740	High CH 41215		Low CH 40265	Mid CH 40740	High CH 41215	
			2557.5 MHz	2605 MHz	2652.5 MHz		2557.5 MHz	2605 MHz	2652.5 MHz		2557.5 MHz	2605 MHz	2652.5 MHz	
41 / 5M	1	0	23.33	23.10	23.16	0	22.26	22.07	22.14	1	21.34	21.15	21.22	2
	1	12	23.29	23.02	23.12	0	22.19	22.04	22.05	1	21.30	21.15	21.15	2
	1	24	23.19	22.95	23.06	0	22.22	21.95	22.05	1	21.27	21.13	21.16	2
	12	0	22.39	22.17	22.21	1	21.37	21.18	21.20	2	20.30	20.08	20.09	3
	12	6	22.33	22.19	22.19	1	21.35	21.18	21.18	2	20.23	20.09	20.12	3
	12	13	22.33	22.11	22.19	1	21.30	21.11	21.18	2	20.25	20.03	20.04	3
	25	0	22.37	22.20	22.21	1	21.40	21.18	21.24	2	20.20	20.03	20.06	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 40290	Mid CH 40740	High CH 41190		Low CH 40290	Mid CH 40740	High CH 41190		Low CH 40290	Mid CH 40740	High CH 41190	
			2560 MHz	2605 MHz	2650 MHz		2560 MHz	2605 MHz	2650 MHz		2560 MHz	2605 MHz	2650 MHz	
41 / 10M	1	0	23.30	23.13	23.16	0	22.26	22.04	22.10	1	21.33	21.16	21.19	2
	1	24	23.29	23.02	23.13	0	22.24	22.00	22.08	1	21.35	21.11	21.19	2
	1	49	23.16	22.99	23.02	0	22.22	21.96	22.02	1	21.33	21.07	21.13	2
	25	0	22.40	22.16	22.24	1	21.39	21.16	21.26	2	20.28	20.05	20.15	3
	25	12	22.39	22.13	22.19	1	21.39	21.12	21.23	2	20.30	20.08	20.06	3
	25	25	22.31	22.08	22.18	1	21.29	21.12	21.15	2	20.24	20.00	20.06	3
	50	0	22.42	22.20	22.18	1	21.44	21.17	21.28	2	20.25	19.99	20.07	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 40315	Mid CH 40740	High CH 41165		Low CH 40315	Mid CH 40740	High CH 41165		Low CH 40315	Mid CH 40740	High CH 41165	
			2562.5 MHz	2605 MHz	2647.5 MHz		2562.5 MHz	2605 MHz	2647.5 MHz		2562.5 MHz	2605 MHz	2647.5 MHz	
41 / 15M	1	0	23.37	23.13	23.13	0	22.30	22.11	22.10	1	21.35	21.17	21.20	2
	1	37	23.27	23.07	23.08	0	22.23	22.01	22.08	1	21.36	21.10	21.16	2
	1	74	23.22	23.02	23.03	0	22.18	22.01	22.04	1	21.29	21.06	21.16	2
	36	0	22.37	22.17	22.25	1	21.43	21.16	21.27	2	20.33	20.11	20.09	3
	36	19	22.40	22.18	22.19	1	21.33	21.16	21.19	2	20.24	20.02	20.08	3
	36	39	22.29	22.09	22.18	1	21.34	21.10	21.18	2	20.27	20.07	20.08	3
	75	0	22.42	22.18	22.23	1	21.45	21.20	21.21	2	20.24	19.97	20.08	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 40340	Mid CH 40740	High CH 41140		Low CH 40340	Mid CH 40740	High CH 41140		Low CH 40340	Mid CH 40740	High CH 41140	
			2565 MHz	2605 MHz	2645 MHz		2565 MHz	2605 MHz	2645 MHz		2565 MHz	2605 MHz	2645 MHz	
41 / 20M	1	0	23.38	23.17	23.21	0	22.33	22.12	22.16	1	21.41	21.20	21.24	2
	1	50	23.31	23.10	23.14	0	22.27	22.06	22.10	1	21.38	21.17	21.21	2
	1	99	23.24	23.03	23.07	0	22.24	22.03	22.07	1	21.35	21.14	21.18	2
	50	0	22.43	22.22	22.26	1	21.45	21.24	21.28	2	20.34	20.13	20.17	3
	50	25	22.41	22.20	22.24	1	21.41	21.20	21.24	2	20.31	20.10	20.14	3
	50	50	22.37	22.16	22.20	1	21.37	21.16	21.20	2	20.29	20.08	20.12	3
	100	0	22.43	22.22	22.26	1	21.46	21.25	21.29	2	20.26	20.05	20.09	3

FCC SAR Test Report

LTE Carrier Aggregation

Conducted Power Measurement for LTE-DLCA (Downlink Carrier Aggregation)									
PCC (Primary Component Carrier)					SCC (Secondary Component Carrier)			PCC Max. Tune-up Power	Tx Power with DL-CA Active
LTE Band	BW (MHz)	Uplink Channel	RB Size	RB Offset	LTE Band	BW (MHz)	Downlink Channel		
41	20	40340	1	0	41	20	40538	23.5	23.22

Note:

- The PCC Tx power is measured with SCC downlink carrier aggregation active, using the channel with highest measured maximum output power when downlink carrier aggregation is inactive, to confirm that when downlink carrier aggregation is active, uplink maximum output power remains within the specified tune-up tolerance limits and not more than 1/4 dB higher than the maximum output power measured when downlink carrier aggregation inactive.

Conducted Power Measurement for LTE-ULCA (Uplink Carrier Aggregation)														
PCC (Primary Component Carrier)						SCC (Secondary Component Carrier)						Single Carrier TX Power (dBm)	MPR Level (dB)	Tx Power with UL-CA Active (dBm)
LTE Band	BW (MHz)	Modulation	Uplink Channel	RB Size	RB Offset	LTE Band	BW (MHz)	Modulation	Uplink Channel	RB Size	RB Offset			
41	20	QPSK	40340	1	0	41	20	QPSK	40538	1	99	23.38	0-8.5	13.98
				1	99					1	0	23.24	0	22.98

Note:

- This device supports uplink carrier aggregation for LTE CA_41C with a maximum of 20MHz component carrier. For intraband contiguous carrier aggregation scenarios, 3GPP 36.101 Table 6.2.2A-1 specifies that the aggregate maximum allowed output power is equivalent to the single carrier scenarios. 3GPP 36.101 6.2.3A allows for several dB of MPR to be applied when non-contiguous RB allocation is implemented. The conducted power and MPR settings in this device are permanently implemented per the above 3GPP requirements.
- Per Fall 2017 TCB Workshop Notes, the output power with uplink CA active was measured for the configuration with the highest reported SAR with single carrier for each exposure condition. The power was measured with wideband signal integration over both component carriers.

FCC SAR Test Report

<WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	17.47	17.15	17.23
Mode	802.11g		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	16.85	16.74	16.83
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Average Power	16.29	16.12	16.42

<WLAN 5.2G>

Mode	802.11a		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Average Power	16.91	16.89	16.85
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Average Power	16.27	16.19	16.34
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	38 (5190)		46 (5230)
Average Power	15.47		15.37
Mode	802.11ac (VHT80)		
Channel / Frequency (MHz)	42 (5210)		
Average Power	15.37		

<WLAN 5.3G>

Mode	802.11a			
Channel / Frequency (MHz)	52 (5260)	56 (5280)	60 (5300)	64 (5320)
Average Power	16.97	16.09	16.66	16.74
Mode	802.11n (HT20)			
Channel / Frequency (MHz)	52 (5260)	56 (5280)	60 (5300)	64 (5320)
Average Power	16.38	16.01	16.18	16.11
Mode	802.11n (HT40)			
Channel / Frequency (MHz)	54 (5270)		62 (5310)	
Average Power	15.45		15.24	
Mode	802.11ac (VHT80)			
Channel / Frequency (MHz)	58 (5290)			
Average Power	15.41			

FCC SAR Test Report

<WLAN 5.6G>

Mode	802.11a							
Channel / Frequency (MHz)	100 (5500)	104 (5520)	108 (5540)	112 (5560)	116 (5580)	132 (5660)	136 (5680)	140 (5700)
Average Power	17.24	16.95	17.02	16.89	17.15	17.01	16.86	17.03
Mode	802.11n (HT20)							
Channel / Frequency (MHz)	100 (5500)	104 (5520)	108 (5540)	112 (5560)	116 (5580)	132 (5660)	136 (5680)	140 (5700)
Average Power	16.75	16.42	16.49	16.27	16.64	16.39	16.47	16.52
Mode	802.11n (HT40)							
Channel / Frequency (MHz)	102 (5510)				134 (5670)			
Average Power	16.23				16.06			
Mode	802.11ac (VHT80)							
Channel / Frequency (MHz)	106 (5530)							
Average Power	15.52							

<WLAN 5.8G>

Mode	802.11a		
Channel / Frequency (MHz)	149 (5745)	157 (5785)	165 (5825)
Average Power	17.15	17.21	16.71
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	149 (5745)	157 (5785)	165 (5825)
Average Power	16.54	16.59	16.12
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	151 (5755)		159 (5795)
Average Power	16.09		16.04
Mode	802.11ac (VHT80)		
Channel / Frequency (MHz)	155 (5775)		
Average Power	15.16		

<Bluetooth>

Mode	Bluetooth GFSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	12.13	11.09	12.40
Mode	Bluetooth $\pi/4$ -DQPSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	8.25	6.71	8.67
Mode	Bluetooth 8DPSK		
Channel / Frequency (MHz)	0 (2402)	39 (2441)	78 (2480)
Average Power	7.76	6.73	8.69
Mode	Bluetooth LE		
Channel / Frequency (MHz)	0 (2402)	19 (2440)	39 (2480)
Average Power	-0.47	-1.87	0.15

FCC SAR Test Report

4.7 SAR Testing Results

4.7.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

(1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

(2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

(3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

(4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

FCC SAR Test Report

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.

FCC SAR Test Report

4.7.2 SAR Results for Head Exposure Condition

Plot No.	Band	Mode	Test Position	Ch.	Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	GSM850	GPRS12	Right Cheek	251	0	32.5	32.27	-0.09	0.993	1.05	1.05
	GSM850	GPRS12	Right Tilted	251	0	32.5	32.27	0.00	0.803	1.05	0.85
	GSM850	GPRS12	Left Cheek	251	0	32.5	32.27	-0.01	1.02	1.05	1.08
	GSM850	GPRS12	Left Tilted	251	0	32.5	32.27	0.03	0.829	1.05	0.87
	GSM850	GPRS12	Right Cheek	251	1	32.5	32.27	-0.13	0.463	1.05	0.49
	GSM850	GPRS12	Right Tilted	251	1	32.5	32.27	0.00	0.23	1.05	0.24
	GSM850	GPRS12	Left Cheek	251	1	32.5	32.27	0.03	0.343	1.05	0.36
	GSM850	GPRS12	Left Tilted	251	1	32.5	32.27	0.10	0.206	1.05	0.22
	GSM850	GPRS12	Right Cheek	128	0	32.5	32.01	-0.13	0.94	1.12	1.05
	GSM850	GPRS12	Right Cheek	189	0	32.5	32.21	-0.01	0.958	1.07	1.02
	GSM850	GPRS12	Right Tilted	128	0	32.5	32.01	-0.12	0.742	1.12	0.83
	GSM850	GPRS12	Right Tilted	189	0	32.5	32.21	-0.15	0.789	1.07	0.84
1	GSM850	GPRS12	Left Cheek	128	0	32.5	32.01	-0.04	0.989	1.12	1.11
	GSM850	GPRS12	Left Cheek	189	0	32.5	32.21	-0.05	1.01	1.07	1.08
	GSM850	GPRS12	Left Tilted	128	0	32.5	32.01	0.06	0.778	1.12	0.87
	GSM850	GPRS12	Left Tilted	189	0	32.5	32.21	-0.04	0.819	1.07	0.88
	GSM850	GPRS12	Left Cheek	128	0	32.5	32.01	-0.03	0.957	1.12	1.07
	GSM1900	GPRS12	Right Cheek	661	0	29.0	28.92	0.05	0.051	1.02	0.05
	GSM1900	GPRS12	Right Tilted	661	0	29.0	28.92	0.07	0.066	1.02	0.07
	GSM1900	GPRS12	Left Cheek	661	0	29.0	28.92	0.00	0.223	1.02	0.23
	GSM1900	GPRS12	Left Tilted	661	0	29.0	28.92	0.00	0.148	1.02	0.15
	GSM1900	GPRS12	Right Cheek	661	1	29.0	28.92	-0.03	0.167	1.02	0.17
	GSM1900	GPRS12	Right Tilted	661	1	29.0	28.92	0.01	0.215	1.02	0.22
2	GSM1900	GPRS12	Left Cheek	661	1	29.0	28.92	0.05	0.444	1.02	0.45
	GSM1900	GPRS12	Left Tilted	661	1	29.0	28.92	0.05	0.287	1.02	0.29
	WCDMA II	RMC12.2K	Right Cheek	9262	0	23.5	23.45	-0.01	0.057	1.01	0.06
	WCDMA II	RMC12.2K	Right Tilted	9262	0	23.5	23.45	0.02	0.051	1.01	0.05
	WCDMA II	RMC12.2K	Left Cheek	9262	0	23.5	23.45	-0.18	0.173	1.01	0.18
	WCDMA II	RMC12.2K	Left Tilted	9262	0	23.5	23.45	0.07	0.141	1.01	0.14
	WCDMA II	RMC12.2K	Right Cheek	9262	1	23.5	23.45	-0.03	0.108	1.01	0.11
	WCDMA II	RMC12.2K	Right Tilted	9262	1	23.5	23.45	0.01	0.139	1.01	0.14
3	WCDMA II	RMC12.2K	Left Cheek	9262	1	23.5	23.45	-0.11	0.287	1.01	0.29
	WCDMA II	RMC12.2K	Left Tilted	9262	1	23.5	23.45	0.03	0.186	1.01	0.19
	WCDMA V	RMC12.2K	Right Cheek	4233	0	23.5	23.28	0.01	0.193	1.05	0.20
	WCDMA V	RMC12.2K	Right Tilted	4233	0	23.5	23.28	-0.03	0.156	1.05	0.16
4	WCDMA V	RMC12.2K	Left Cheek	4233	0	23.5	23.28	-0.13	0.198	1.05	0.21
	WCDMA V	RMC12.2K	Left Tilted	4233	0	23.5	23.28	0.06	0.195	1.05	0.21
	WCDMA V	RMC12.2K	Right Cheek	4233	1	23.5	23.28	0.06	0.114	1.05	0.12
	WCDMA V	RMC12.2K	Right Tilted	4233	1	23.5	23.28	0.03	0.057	1.05	0.06
	WCDMA V	RMC12.2K	Left Cheek	4233	1	23.5	23.28	0.03	0.087	1.05	0.09
	WCDMA V	RMC12.2K	Left Tilted	4233	1	23.5	23.28	0.01	0.052	1.05	0.05
	CDMA BC0	RC3+SO55	Right Cheek	384	0	24.5	24.20	0.05	0.234	1.07	0.25
	CDMA BC0	RC3+SO55	Right Tilted	384	0	24.5	24.20	-0.04	0.198	1.07	0.21
5	CDMA BC0	RC3+SO55	Left Cheek	384	0	24.5	24.20	0.01	0.235	1.07	0.25
	CDMA BC0	RC3+SO55	Left Tilted	384	0	24.5	24.20	0.10	0.151	1.07	0.16
	CDMA BC0	RC3+SO55	Right Cheek	384	1	24.5	24.20	0.13	0.137	1.07	0.15
	CDMA BC0	RC3+SO55	Right Tilted	384	1	24.5	24.20	0.05	0.062	1.07	0.07
	CDMA BC0	RC3+SO55	Left Cheek	384	1	24.5	24.20	-0.04	0.087	1.07	0.09
	CDMA BC0	RC3+SO55	Left Tilted	384	1	24.5	24.20	0.08	0.053	1.07	0.06

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
6	LTE 4	QPSK20M	Right Cheek	20175	0	1	0	23.5	23.15	-0.13	0.175	1.08	0.19
	LTE 4	QPSK20M	Right Tilted	20175	0	1	0	23.5	23.15	0.08	0.16	1.08	0.17
	LTE 4	QPSK20M	Left Cheek	20175	0	1	0	23.5	23.15	-0.04	0.535	1.08	0.58
	LTE 4	QPSK20M	Left Tilted	20175	0	1	0	23.5	23.15	0.08	0.437	1.08	0.47
	LTE 4	QPSK20M	Right Cheek	20175	0	50	0	22.5	22.18	0.01	0.153	1.08	0.16
	LTE 4	QPSK20M	Right Tilted	20175	0	50	0	22.5	22.18	0.03	0.139	1.08	0.15
	LTE 4	QPSK20M	Left Cheek	20175	0	50	0	22.5	22.18	0.03	0.468	1.08	0.50
	LTE 4	QPSK20M	Left Tilted	20175	0	50	0	22.5	22.18	0.05	0.382	1.08	0.41
	LTE 4	QPSK20M	Right Cheek	20175	1	1	0	23.5	23.15	0.05	0.014	1.08	0.02
	LTE 4	QPSK20M	Right Tilted	20175	1	1	0	23.5	23.15	0.06	0.018	1.08	0.02
	LTE 4	QPSK20M	Left Cheek	20175	1	1	0	23.5	23.15	0.04	0.037	1.08	0.04
	LTE 4	QPSK20M	Left Tilted	20175	1	1	0	23.5	23.15	0.09	0.024	1.08	0.03
	LTE 4	QPSK20M	Right Cheek	20175	1	50	0	22.5	22.18	0.03	0.012	1.08	0.01
	LTE 4	QPSK20M	Right Tilted	20175	1	50	0	22.5	22.18	0.01	0.016	1.08	0.02
	LTE 4	QPSK20M	Left Cheek	20175	1	50	0	22.5	22.18	0.02	0.032	1.08	0.03
	LTE 4	QPSK20M	Left Tilted	20175	1	50	0	22.5	22.18	0.02	0.021	1.08	0.02
7	LTE 5	QPSK10M	Right Cheek	20600	0	1	0	23.0	22.84	-0.07	0.161	1.04	0.17
	LTE 5	QPSK10M	Right Tilted	20600	0	1	0	23.0	22.84	-0.03	0.144	1.04	0.15
	LTE 5	QPSK10M	Left Cheek	20600	0	1	0	23.0	22.84	-0.13	0.177	1.04	0.18
	LTE 5	QPSK10M	Left Tilted	20600	0	1	0	23.0	22.84	0.06	0.139	1.04	0.14
	LTE 5	QPSK10M	Right Cheek	20600	0	25	0	22.0	21.97	0.01	0.126	1.01	0.13
	LTE 5	QPSK10M	Right Tilted	20600	0	25	0	22.0	21.97	0.03	0.113	1.01	0.11
	LTE 5	QPSK10M	Left Cheek	20600	0	25	0	22.0	21.97	0.06	0.139	1.01	0.14
	LTE 5	QPSK10M	Left Tilted	20600	0	25	0	22.0	21.97	-0.03	0.109	1.01	0.11
	LTE 5	QPSK10M	Right Cheek	20600	1	1	0	23.0	22.84	0.05	0.084	1.04	0.09
	LTE 5	QPSK10M	Right Tilted	20600	1	1	0	23.0	22.84	0.15	0.044	1.04	0.05
	LTE 5	QPSK10M	Left Cheek	20600	1	1	0	23.0	22.84	0.00	0.061	1.04	0.06
	LTE 5	QPSK10M	Left Tilted	20600	1	1	0	23.0	22.84	0.08	0.043	1.04	0.04
	LTE 5	QPSK10M	Right Cheek	20600	1	25	0	22.0	21.97	-0.01	0.067	1.01	0.07
	LTE 5	QPSK10M	Right Tilted	20600	1	25	0	22.0	21.97	0.00	0.035	1.01	0.04
	LTE 5	QPSK10M	Left Cheek	20600	1	25	0	22.0	21.97	0.08	0.049	1.01	0.05
	LTE 5	QPSK10M	Left Tilted	20600	1	25	0	22.0	21.97	0.00	0.034	1.01	0.03
8	LTE 7	QPSK20M	Right Cheek	21350	0	1	0	23.5	23.33	0.06	0.053	1.04	0.06
	LTE 7	QPSK20M	Right Tilted	21350	0	1	0	23.5	23.33	0.05	0.037	1.04	0.04
	LTE 7	QPSK20M	Left Cheek	21350	0	1	0	23.5	23.33	0.01	0.239	1.04	0.25
	LTE 7	QPSK20M	Left Tilted	21350	0	1	0	23.5	23.33	0.01	0.167	1.04	0.17
	LTE 7	QPSK20M	Right Cheek	21350	0	50	0	22.5	22.33	0.01	0.043	1.04	0.04
	LTE 7	QPSK20M	Right Tilted	21350	0	50	0	22.5	22.33	0.03	0.03	1.04	0.03
	LTE 7	QPSK20M	Left Cheek	21350	0	50	0	22.5	22.33	0.08	0.192	1.04	0.20
	LTE 7	QPSK20M	Left Tilted	21350	0	50	0	22.5	22.33	-0.10	0.134	1.04	0.14
	LTE 7	QPSK20M	Right Cheek	21350	1	1	0	23.5	23.33	0.04	0.221	1.04	0.23
	LTE 7	QPSK20M	Right Tilted	21350	1	1	0	23.5	23.33	0.08	0.215	1.04	0.22
	LTE 7	QPSK20M	Left Cheek	21350	1	1	0	23.5	23.33	0.01	0.545	1.04	0.57
	LTE 7	QPSK20M	Left Tilted	21350	1	1	0	23.5	23.33	0.08	0.15	1.04	0.16
	LTE 7	QPSK20M	Right Cheek	21350	1	50	0	22.5	22.33	0.00	0.179	1.04	0.19
	LTE 7	QPSK20M	Right Tilted	21350	1	50	0	22.5	22.33	0.04	0.174	1.04	0.18
	LTE 7	QPSK20M	Left Cheek	21350	1	50	0	22.5	22.33	0.02	0.433	1.04	0.45
	LTE 7	QPSK20M	Left Tilted	21350	1	50	0	22.5	22.33	0.01	0.121	1.04	0.13

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE 41	QPSK20M	Right Cheek	40340	0	1	0	23.5	23.38	0.09	0.032	1.03	0.03
	LTE 41	QPSK20M	Right Tilted	40340	0	1	0	23.5	23.38	0.03	0.022	1.03	0.02
	LTE 41	QPSK20M	Left Cheek	40340	0	1	0	23.5	23.38	0.00	0.138	1.03	0.14
	LTE 41	QPSK20M	Left Tilted	40340	0	1	0	23.5	23.38	0.01	0.096	1.03	0.10
	LTE 41	QPSK20M	Right Cheek	40340	0	50	0	22.5	22.43	0.02	0.025	1.02	0.03
	LTE 41	QPSK20M	Right Tilted	40340	0	50	0	22.5	22.43	0.03	0.017	1.02	0.02
	LTE 41	QPSK20M	Left Cheek	40340	0	50	0	22.5	22.43	0.01	0.111	1.02	0.11
	LTE 41	QPSK20M	Left Tilted	40340	0	50	0	22.5	22.43	0.03	0.077	1.02	0.08
	LTE 41	QPSK20M	Right Cheek	40340	1	1	0	23.5	23.38	0.08	0.116	1.03	0.12
	LTE 41	QPSK20M	Right Tilted	40340	1	1	0	23.5	23.38	0.00	0.029	1.03	0.03
9	LTE 41	QPSK20M	Left Cheek	40340	1	1	0	23.5	23.38	0.08	0.278	1.03	0.29
	LTE 41	QPSK20M	Left Tilted	40340	1	1	0	23.5	23.38	-0.17	0.07	1.03	0.07
	LTE 41	QPSK20M	Right Cheek	40340	1	50	0	22.5	22.43	0.03	0.093	1.02	0.09
	LTE 41	QPSK20M	Right Tilted	40340	1	50	0	22.5	22.43	0.01	0.023	1.02	0.02
	LTE 41	QPSK20M	Left Cheek	40340	1	50	0	22.5	22.43	0.02	0.222	1.02	0.23
	LTE 41	QPSK20M	Left Tilted	40340	1	50	0	22.5	22.43	0.06	0.056	1.02	0.06
	LTE 41	QPSK20M	Left Cheek	PCC:40340 SCC:40538	1	1 1	99 0	23.5	22.98	0.13	0.230	1.13	0.26

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
10	802.11b	-	Right Cheek	1	17.5	17.47	0.10	0.173	1.01	0.17
	802.11b	-	Right Tilted	1	17.5	17.47	0.00	0.118	1.01	0.12
	802.11b	-	Left Cheek	1	17.5	17.47	0.08	0.072	1.01	0.07
	802.11b	-	Left Tilted	1	17.5	17.47	0.02	0.044	1.01	0.04
11	802.11a	-	Right Cheek	52	17.5	16.97	0.09	0.206	1.13	0.23
	802.11a	-	Right Tilted	52	17.5	16.97	0.00	0.128	1.13	0.14
	802.11a	-	Left Cheek	52	17.5	16.97	0.07	0.067	1.13	0.08
	802.11a	-	Left Tilted	52	17.5	16.97	0.00	0.053	1.13	0.06
12	802.11a	-	Right Cheek	100	17.5	17.24	0.08	0.193	1.06	0.20
	802.11a	-	Right Tilted	100	17.5	17.24	0.02	0.118	1.06	0.13
	802.11a	-	Left Cheek	100	17.5	17.24	0.07	0.08	1.06	0.08
	802.11a	-	Left Tilted	100	17.5	17.24	0.03	0.048	1.06	0.05
13	802.11a	-	Right Cheek	157	17.5	17.21	0.03	0.344	1.07	0.37
	802.11a	-	Right Tilted	157	17.5	17.21	0.03	0.269	1.07	0.29
	802.11a	-	Left Cheek	157	17.5	17.21	0.06	0.183	1.07	0.20
	802.11a	-	Left Tilted	157	17.5	17.21	0.00	0.154	1.07	0.16

FCC SAR Test Report

4.7.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	GSM850	GPRS12	Front Face	251	0	32.5	32.27	-0.05	0.405	1.05	0.43
	GSM850	GPRS12	Rear Face	251	0	32.5	32.27	0.01	0.466	1.05	0.49
	GSM850	GPRS12	Front Face	251	1	32.5	32.27	-0.08	0.777	1.05	0.82
20	GSM850	GPRS12	Rear Face	251	1	32.5	32.27	-0.05	0.881	1.05	0.93
	GSM850	GPRS12	Front Face	128	1	32.5	32.01	0.03	0.587	1.12	0.66
	GSM850	GPRS12	Front Face	189	1	32.5	32.21	0.00	0.676	1.07	0.72
	GSM850	GPRS12	Rear Face	128	1	32.5	32.01	-0.06	0.666	1.12	0.75
	GSM850	GPRS12	Rear Face	189	1	32.5	32.21	-0.03	0.766	1.07	0.82
	GSM850	GPRS12	Rear Face	251	1	32.5	32.27	-0.05	0.863	1.05	0.91
	GSM1900	GPRS12	Front Face	661	0	29.0	28.92	-0.07	0.037	1.02	0.04
	GSM1900	GPRS12	Rear Face	661	0	29.0	28.92	0.05	0.036	1.02	0.04
14	GSM1900	GPRS12	Front Face	661	1	29.0	28.92	0.15	0.624	1.02	0.64
	GSM1900	GPRS12	Rear Face	661	1	29.0	28.92	0.02	0.582	1.02	0.59
	WCDMA II	RMC12.2K	Front Face	9262	0	23.5	23.45	0.05	0.028	1.01	0.03
	WCDMA II	RMC12.2K	Rear Face	9262	0	23.5	23.45	0.09	0.029	1.01	0.03
15	WCDMA II	RMC12.2K	Front Face	9262	1	23.5	23.45	0.00	0.46	1.01	0.47
	WCDMA II	RMC12.2K	Rear Face	9262	1	23.5	23.45	-0.11	0.436	1.01	0.44
	WCDMA V	RMC12.2K	Front Face	4233	0	23.5	23.28	0.06	0.074	1.05	0.08
	WCDMA V	RMC12.2K	Rear Face	4233	0	23.5	23.28	-0.05	0.086	1.05	0.09
	WCDMA V	RMC12.2K	Front Face	4233	1	23.5	23.28	0.00	0.242	1.05	0.25
23	WCDMA V	RMC12.2K	Rear Face	4233	1	23.5	23.28	0.00	0.279	1.05	0.29
	CDMA BC0	RC3+SO32	Front Face	384	0	24.5	24.20	0.03	0.091	1.07	0.10
	CDMA BC0	RC3+SO32	Rear Face	384	0	24.5	24.20	0.01	0.105	1.07	0.11
	CDMA BC0	RC3+SO32	Front Face	384	1	24.5	24.20	0.04	0.295	1.07	0.32
24	CDMA BC0	RC3+SO32	Rear Face	384	1	24.5	24.20	0.01	0.315	1.07	0.34

Plot No.	Band	Mode	Test Position	Ch.	Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE 4	QPSK20M	Front Face	20175	0	1	0	23.5	23.15	0.06	0.031	1.08	0.03
	LTE 4	QPSK20M	Rear Face	20175	0	1	0	23.5	23.15	0.01	0.026	1.08	0.03
	LTE 4	QPSK20M	Front Face	20175	0	50	0	22.5	22.18	0.00	0.025	1.08	0.03
	LTE 4	QPSK20M	Rear Face	20175	0	50	0	22.5	22.18	0.04	0.021	1.08	0.02
16	LTE 4	QPSK20M	Front Face	20175	1	1	0	23.5	23.15	0.01	0.084	1.08	0.09
	LTE 4	QPSK20M	Rear Face	20175	1	1	0	23.5	23.15	0.09	0.08	1.08	0.09
	LTE 4	QPSK20M	Front Face	20175	1	50	0	22.5	22.18	0.03	0.071	1.08	0.08
	LTE 4	QPSK20M	Rear Face	20175	1	50	0	22.5	22.18	0.01	0.068	1.08	0.07
	LTE 5	QPSK10M	Front Face	20600	0	1	0	23.0	22.84	0.05	0.068	1.04	0.07
	LTE 5	QPSK10M	Rear Face	20600	0	1	0	23.0	22.84	0.08	0.077	1.04	0.08
	LTE 5	QPSK10M	Front Face	20600	0	25	0	22.0	21.97	0.00	0.054	1.01	0.05
	LTE 5	QPSK10M	Rear Face	20600	0	25	0	22.0	21.97	0.12	0.061	1.01	0.06
	LTE 5	QPSK10M	Front Face	20600	1	1	0	23.0	22.84	0.01	0.202	1.04	0.21
26	LTE 5	QPSK10M	Rear Face	20600	1	1	0	23.0	22.84	0.08	0.243	1.04	0.25
	LTE 5	QPSK10M	Front Face	20600	1	25	0	22.0	21.97	0.00	0.163	1.01	0.16
	LTE 5	QPSK10M	Rear Face	20600	1	25	0	22.0	21.97	0.10	0.196	1.01	0.20

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE 7	QPSK20M	Front Face	21350	0	1	0	23.5	23.33	0.03	0.014	1.04	0.01
	LTE 7	QPSK20M	Rear Face	21350	0	1	0	23.5	23.33	0.03	0.017	1.04	0.02
	LTE 7	QPSK20M	Front Face	21350	0	50	0	22.5	22.33	0.03	0.008	1.04	0.01
	LTE 7	QPSK20M	Rear Face	21350	0	50	0	22.5	22.33	0.01	0.00983	1.04	0.01
	LTE 7	QPSK20M	Front Face	21350	1	1	0	23.5	23.33	-0.01	0.601	1.04	0.62
27	LTE 7	QPSK20M	Rear Face	21350	1	1	0	23.5	23.33	-0.01	0.622	1.04	0.65
	LTE 7	QPSK20M	Front Face	21350	1	50	0	22.5	22.33	-0.03	0.536	1.04	0.56
	LTE 7	QPSK20M	Rear Face	21350	1	50	0	22.5	22.33	0.03	0.516	1.04	0.54
	LTE 41	QPSK20M	Front Face	40340	0	1	0	23.5	23.38	0.00	0.00641	1.03	0.01
	LTE 41	QPSK20M	Rear Face	40340	0	1	0	23.5	23.38	0.01	0.00778	1.03	0.01
	LTE 41	QPSK20M	Front Face	40340	0	50	0	22.5	22.43	0.00	0.00386	1.02	0.00
	LTE 41	QPSK20M	Rear Face	40340	0	50	0	22.5	22.43	0.04	0.00469	1.02	0.00
	LTE 41	QPSK20M	Front Face	40340	1	1	0	23.5	23.38	0.01	0.352	1.03	0.36
28	LTE 41	QPSK20M	Rear Face	40340	1	1	0	23.5	23.38	0.03	0.366	1.03	0.38
	LTE 41	QPSK20M	Front Face	40340	1	50	0	22.5	22.43	-0.04	0.303	1.02	0.31
	LTE 41	QPSK20M	Rear Face	40340	1	50	0	22.5	22.43	0.01	0.292	1.02	0.30
	LTE 41	QPSK20M	Rear Face	40340	1	1	99	23.5	22.98	0.09	0.244	1.13	0.28
	LTE 41	QPSK20M	Rear Face	40538	1	1	0						

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	802.11b	-	Front Face	1	17.5	17.47	0.08	0.018	1.01	0.02
28	802.11b	-	Rear Face	1	17.5	17.47	0.08	0.036	1.01	0.04
17	802.11a	-	Front Face	52	17.5	16.97	0.07	0.008	1.13	0.01
	802.11a	-	Rear Face	52	17.5	16.97	-0.01	0.00153	1.13	0.00
18	802.11a	-	Front Face	100	17.5	17.24	0.00	0.00137	1.06	0.00
	802.11a	-	Rear Face	100	17.5	17.24	0.02	0.00097	1.06	0.00
19	802.11a	-	Front Face	157	17.5	17.21	0.01	0.023	1.07	0.02
	802.11a	-	Rear Face	157	17.5	17.21	0.00	0.00145	1.07	0.00

4.7.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	GSM850	GPRS12	Front Face	251	0	32.5	32.27	-0.05	0.405	1.05	0.43
	GSM850	GPRS12	Rear Face	251	0	32.5	32.27	0.01	0.466	1.05	0.49
	GSM850	GPRS12	Right Side	251	0	32.5	32.27	-0.01	0.363	1.05	0.38
	GSM850	GPRS12	Top Side	251	0	32.5	32.27	0.00	0.368	1.05	0.39
	GSM850	GPRS12	Front Face	251	1	32.5	32.27	-0.08	0.777	1.05	0.82
20	GSM850	GPRS12	Rear Face	251	1	32.5	32.27	-0.05	0.881	1.05	0.93
	GSM850	GPRS12	Left Side	251	1	32.5	32.27	-0.07	0.249	1.05	0.26
	GSM850	GPRS12	Right Side	251	1	32.5	32.27	0.07	0.816	1.05	0.86
	GSM850	GPRS12	Bottom Side	251	1	32.5	32.27	0.02	0.787	1.05	0.83
	GSM850	GPRS12	Front Face	128	1	32.5	32.01	0.03	0.587	1.12	0.66
	GSM850	GPRS12	Front Face	189	1	32.5	32.21	0.00	0.676	1.07	0.72
	GSM850	GPRS12	Rear Face	128	1	32.5	32.01	-0.06	0.666	1.12	0.75
	GSM850	GPRS12	Rear Face	189	1	32.5	32.21	-0.03	0.766	1.07	0.82
	GSM850	GPRS12	Right Side	128	1	32.5	32.01	0.03	0.617	1.12	0.69
	GSM850	GPRS12	Right Side	189	1	32.5	32.21	0.05	0.709	1.07	0.76
	GSM850	GPRS12	Bottom Side	128	1	32.5	32.01	0.10	0.58	1.12	0.65
	GSM850	GPRS12	Bottom Side	189	1	32.5	32.21	0.02	0.673	1.07	0.72
	GSM850	GPRS12	Rear Face	251	1	32.5	32.27	-0.05	0.863	1.05	0.91

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Antenna	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	GSM1900	GPRS12	Front Face	661	0	29.0	28.92	-0.07	0.037	1.02	0.04
	GSM1900	GPRS12	Rear Face	661	0	29.0	28.92	0.05	0.036	1.02	0.04
	GSM1900	GPRS12	Right Side	661	0	29.0	28.92	0.01	0.016	1.02	0.02
	GSM1900	GPRS12	Top Side	661	0	29.0	28.92	0.08	0.054	1.02	0.06
	GSM1900	GPRS12	Front Face	661	1	29.0	28.92	0.15	0.624	1.02	0.64
	GSM1900	GPRS12	Rear Face	661	1	29.0	28.92	0.02	0.582	1.02	0.59
	GSM1900	GPRS12	Left Side	661	1	29.0	28.92	0.04	0.55	1.02	0.56
	GSM1900	GPRS12	Right Side	661	1	29.0	28.92	0.05	0.052	1.02	0.05
	GSM1900	GPRS12	Bottom Side	661	1	29.0	28.92	-0.02	0.957	1.02	0.97
21	GSM1900	GPRS12	Bottom Side	512	1	29.0	28.75	-0.10	1.25	1.06	1.32
	GSM1900	GPRS12	Bottom Side	810	1	29.0	28.84	-0.01	0.627	1.04	0.65
	GSM1900	GPRS12	Bottom Side	512	1	29.0	28.75	-0.10	1.2	1.06	1.27
	WCDMA II	RMC12.2K	Front Face	9262	0	23.5	23.45	0.05	0.028	1.01	0.03
	WCDMA II	RMC12.2K	Rear Face	9262	0	23.5	23.45	0.09	0.029	1.01	0.03
	WCDMA II	RMC12.2K	Right Side	9262	0	23.5	23.45	0.01	0.013	1.01	0.01
	WCDMA II	RMC12.2K	Top Side	9262	0	23.5	23.45	0.05	0.0435	1.01	0.04
	WCDMA II	RMC12.2K	Front Face	9262	1	23.5	23.45	0.00	0.46	1.01	0.47
	WCDMA II	RMC12.2K	Rear Face	9262	1	23.5	23.45	-0.11	0.436	1.01	0.44
	WCDMA II	RMC12.2K	Left Side	9262	1	23.5	23.45	-0.01	0.033	1.01	0.03
	WCDMA II	RMC12.2K	Right Side	9262	1	23.5	23.45	0.09	0.201	1.01	0.20
22	WCDMA II	RMC12.2K	Bottom Side	9262	1	23.5	23.45	0.06	0.739	1.01	0.75
	WCDMA V	RMC12.2K	Front Face	4233	0	23.5	23.28	0.06	0.074	1.05	0.08
	WCDMA V	RMC12.2K	Rear Face	4233	0	23.5	23.28	-0.05	0.086	1.05	0.09
	WCDMA V	RMC12.2K	Right Side	4233	0	23.5	23.28	0.09	0.067	1.05	0.07
	WCDMA V	RMC12.2K	Top Side	4233	0	23.5	23.28	-0.10	0.068	1.05	0.07
	WCDMA V	RMC12.2K	Front Face	4233	1	23.5	23.28	0.00	0.242	1.05	0.25
23	WCDMA V	RMC12.2K	Rear Face	4233	1	23.5	23.28	0.00	0.279	1.05	0.29
	WCDMA V	RMC12.2K	Left Side	4233	1	23.5	23.28	0.06	0.091	1.05	0.10
	WCDMA V	RMC12.2K	Right Side	4233	1	23.5	23.28	0.09	0.242	1.05	0.25
	WCDMA V	RMC12.2K	Bottom Side	4233	1	23.5	23.28	0.08	0.253	1.05	0.27
	CDMA BC0	RC3+SO32	Front Face	384	0	24.5	24.20	0.03	0.091	1.07	0.10
	CDMA BC0	RC3+SO32	Rear Face	384	0	24.5	24.20	0.01	0.105	1.07	0.11
	CDMA BC0	RC3+SO32	Right Side	384	0	24.5	24.20	-0.05	0.082	1.07	0.09
	CDMA BC0	RC3+SO32	Top Side	384	0	24.5	24.20	0.00	0.083	1.07	0.09
	CDMA BC0	RC3+SO32	Front Face	384	1	24.5	24.20	0.04	0.295	1.07	0.32
24	CDMA BC0	RC3+SO32	Rear Face	384	1	24.5	24.20	0.01	0.315	1.07	0.34
	CDMA BC0	RC3+SO32	Left Side	384	1	24.5	24.20	-0.01	0.111	1.07	0.12
	CDMA BC0	RC3+SO32	Right Side	384	1	24.5	24.20	0.05	0.297	1.07	0.32
	CDMA BC0	RC3+SO32	Bottom Side	384	1	24.5	24.20	0.05	0.309	1.07	0.33

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE 4	QPSK20M	Front Face	20175	0	1	0	23.5	23.15	0.06	0.031	1.08	0.03
	LTE 4	QPSK20M	Rear Face	20175	0	1	0	23.5	23.15	0.01	0.026	1.08	0.03
	LTE 4	QPSK20M	Right Side	20175	0	1	0	23.5	23.15	0.09	0.012	1.08	0.01
	LTE 4	QPSK20M	Top Side	20175	0	1	0	23.5	23.15	-0.07	0.039	1.08	0.04
	LTE 4	QPSK20M	Front Face	20175	0	50	0	22.5	22.18	0.00	0.025	1.08	0.03
	LTE 4	QPSK20M	Rear Face	20175	0	50	0	22.5	22.18	0.04	0.021	1.08	0.02
	LTE 4	QPSK20M	Right Side	20175	0	50	0	22.5	22.18	0.02	0.00969	1.08	0.01
	LTE 4	QPSK20M	Top Side	20175	0	50	0	22.5	22.18	0.01	0.0031	1.08	0.00
	LTE 4	QPSK20M	Front Face	20175	1	1	0	23.5	23.15	0.01	0.084	1.08	0.09
	LTE 4	QPSK20M	Rear Face	20175	1	1	0	23.5	23.15	0.09	0.08	1.08	0.09
	LTE 4	QPSK20M	Left Side	20175	1	1	0	23.5	23.15	0.04	0.035	1.08	0.04
	LTE 4	QPSK20M	Right Side	20175	1	1	0	23.5	23.15	0.00	0.011	1.08	0.01
25	LTE 4	QPSK20M	Bottom Side	20175	1	1	0	23.5	23.15	0.08	0.135	1.08	0.15
	LTE 4	QPSK20M	Front Face	20175	1	50	0	22.5	22.18	0.03	0.071	1.08	0.08
	LTE 4	QPSK20M	Rear Face	20175	1	50	0	22.5	22.18	0.01	0.068	1.08	0.07
	LTE 4	QPSK20M	Left Side	20175	1	50	0	22.5	22.18	0.02	0.029	1.08	0.03
	LTE 4	QPSK20M	Right Side	20175	1	50	0	22.5	22.18	0.00	0.00928	1.08	0.01
	LTE 4	QPSK20M	Bottom Side	20175	1	50	0	22.5	22.18	0.12	0.114	1.08	0.12
	LTE 5	QPSK10M	Front Face	20600	0	1	0	23.0	22.84	0.05	0.068	1.04	0.07
	LTE 5	QPSK10M	Rear Face	20600	0	1	0	23.0	22.84	0.08	0.077	1.04	0.08
	LTE 5	QPSK10M	Right Side	20600	0	1	0	23.0	22.84	0.07	0.06	1.04	0.06
	LTE 5	QPSK10M	Top Side	20600	0	1	0	23.0	22.84	0.07	0.061	1.04	0.06
	LTE 5	QPSK10M	Front Face	20600	0	25	0	22.0	21.97	0.00	0.054	1.01	0.05
	LTE 5	QPSK10M	Rear Face	20600	0	25	0	22.0	21.97	0.12	0.061	1.01	0.06
	LTE 5	QPSK10M	Right Side	20600	0	25	0	22.0	21.97	-0.03	0.047	1.01	0.05
	LTE 5	QPSK10M	Top Side	20600	0	25	0	22.0	21.97	0.01	0.048	1.01	0.05
	LTE 5	QPSK10M	Front Face	20600	1	1	0	23.0	22.84	0.01	0.202	1.04	0.21
26	LTE 5	QPSK10M	Rear Face	20600	1	1	0	23.0	22.84	0.08	0.243	1.04	0.25
	LTE 5	QPSK10M	Left Side	20600	1	1	0	23.0	22.84	0.12	0.081	1.04	0.08
	LTE 5	QPSK10M	Right Side	20600	1	1	0	23.0	22.84	0.02	0.201	1.04	0.21
	LTE 5	QPSK10M	Bottom Side	20600	1	1	0	23.0	22.84	0.03	0.208	1.04	0.22
	LTE 5	QPSK10M	Front Face	20600	1	25	0	22.0	21.97	0.00	0.163	1.01	0.16
	LTE 5	QPSK10M	Rear Face	20600	1	25	0	22.0	21.97	0.10	0.196	1.01	0.20
	LTE 5	QPSK10M	Left Side	20600	1	25	0	22.0	21.97	0.02	0.065	1.01	0.07
	LTE 5	QPSK10M	Right Side	20600	1	25	0	22.0	21.97	-0.01	0.162	1.01	0.16
	LTE 5	QPSK10M	Bottom Side	20600	1	25	0	22.0	21.97	0.03	0.168	1.01	0.17
	LTE 7	QPSK20M	Front Face	21350	0	1	0	23.5	23.33	0.03	0.014	1.04	0.01
	LTE 7	QPSK20M	Rear Face	21350	0	1	0	23.5	23.33	0.03	0.017	1.04	0.02
	LTE 7	QPSK20M	Right Side	21350	0	1	0	23.5	23.33	0.05	0.021	1.04	0.02
	LTE 7	QPSK20M	Top Side	21350	0	1	0	23.5	23.33	0.00	0.015	1.04	0.02
	LTE 7	QPSK20M	Front Face	21350	0	50	0	22.5	22.33	0.03	0.008	1.04	0.01
	LTE 7	QPSK20M	Rear Face	21350	0	50	0	22.5	22.33	0.01	0.00983	1.04	0.01
	LTE 7	QPSK20M	Right Side	21350	0	50	0	22.5	22.33	0.08	0.012	1.04	0.01
	LTE 7	QPSK20M	Top Side	21350	0	50	0	22.5	22.33	0.01	0.00867	1.04	0.01
	LTE 7	QPSK20M	Front Face	21350	1	1	0	23.5	23.33	-0.01	0.601	1.04	0.62
27	LTE 7	QPSK20M	Rear Face	21350	1	1	0	23.5	23.33	-0.01	0.622	1.04	0.65
	LTE 7	QPSK20M	Left Side	21350	1	1	0	23.5	23.33	-0.04	0.516	1.04	0.54
	LTE 7	QPSK20M	Right Side	21350	1	1	0	23.5	23.33	0.01	0.022	1.04	0.02
	LTE 7	QPSK20M	Bottom Side	21350	1	1	0	23.5	23.33	-0.15	0.286	1.04	0.30
	LTE 7	QPSK20M	Front Face	21350	1	50	0	22.5	22.33	-0.03	0.536	1.04	0.56
	LTE 7	QPSK20M	Rear Face	21350	1	50	0	22.5	22.33	0.03	0.516	1.04	0.54
	LTE 7	QPSK20M	Left Side	21350	1	50	0	22.5	22.33	0.01	0.428	1.04	0.45
	LTE 7	QPSK20M	Right Side	21350	1	50	0	22.5	22.33	0.02	0.018	1.04	0.02
	LTE 7	QPSK20M	Bottom Side	21350	1	50	0	22.5	22.33	-0.06	0.237	1.04	0.25

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Antenna	RB#	RB Offset	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	LTE 41	QPSK20M	Front Face	40340	0	1	0	23.5	23.38	0.00	0.00641	1.03	0.01
	LTE 41	QPSK20M	Rear Face	40340	0	1	0	23.5	23.38	0.01	0.00778	1.03	0.01
	LTE 41	QPSK20M	Right Side	40340	0	1	0	23.5	23.38	0.02	0.00961	1.03	0.01
	LTE 41	QPSK20M	Top Side	40340	0	1	0	23.5	23.38	0.04	0.00686	1.03	0.01
	LTE 41	QPSK20M	Front Face	40340	0	50	0	22.5	22.43	0.00	0.00386	1.02	0.00
	LTE 41	QPSK20M	Rear Face	40340	0	50	0	22.5	22.43	0.04	0.00469	1.02	0.00
	LTE 41	QPSK20M	Right Side	40340	0	50	0	22.5	22.43	-0.01	0.00579	1.02	0.01
	LTE 41	QPSK20M	Top Side	40340	0	50	0	22.5	22.43	0.03	0.00413	1.02	0.00
	LTE 41	QPSK20M	Front Face	40340	1	1	0	23.5	23.38	0.01	0.352	1.03	0.36
28	LTE 41	QPSK20M	Rear Face	40340	1	1	0	23.5	23.38	0.03	0.366	1.03	0.38
	LTE 41	QPSK20M	Left Side	40340	1	1	0	23.5	23.38	0.06	0.292	1.03	0.30
	LTE 41	QPSK20M	Right Side	40340	1	1	0	23.5	23.38	0.01	0.012	1.03	0.01
	LTE 41	QPSK20M	Bottom Side	40340	1	1	0	23.5	23.38	0.01	0.162	1.03	0.17
	LTE 41	QPSK20M	Front Face	40340	1	50	0	22.5	22.43	-0.04	0.303	1.02	0.31
	LTE 41	QPSK20M	Rear Face	40340	1	50	0	22.5	22.43	0.01	0.292	1.02	0.30
	LTE 41	QPSK20M	Left Side	40340	1	50	0	22.5	22.43	-0.03	0.242	1.02	0.25
	LTE 41	QPSK20M	Right Side	40340	1	50	0	22.5	22.43	0.01	0.011	1.02	0.01
	LTE 41	QPSK20M	Bottom Side	40340	1	50	0	22.5	22.43	-0.09	0.134	1.02	0.14
	LTE 41	QPSK20M	Rear Face	40340	1	1	99	23.5	22.98	0.11	0.244	1.13	0.28
				40538	1	1	0						

Plot No.	Band	Mode	Test Position	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)
	802.11b	-	Front Face	1	17.5	17.47	0.08	0.018	1.01	0.02
29	802.11b	-	Rear Face	1	17.5	17.47	0.08	0.036	1.01	0.04
	802.11b	-	Left Side	1	17.5	17.47	0.02	0.018	1.01	0.02
	802.11b	-	Top Side	1	17.5	17.47	0.09	0.022	1.01	0.02
	802.11a	-	Front Face	36	17.5	16.91	-0.01	0.018	1.15	0.02
	802.11a	-	Rear Face	36	17.5	16.91	0.00	0.00113	1.15	0.00
30	802.11a	-	Left Side	36	17.5	16.91	0.06	0.025	1.15	0.03
	802.11a	-	Top Side	36	17.5	16.91	0.01	0.015	1.15	0.02
	802.11a	-	Front Face	157	17.5	17.21	0.01	0.023	1.07	0.02
	802.11a	-	Rear Face	157	17.5	17.21	0.00	0.00145	1.07	0.00
31	802.11a	-	Left Side	157	17.5	17.21	0.06	0.032	1.07	0.03
	802.11a	-	Top Side	157	17.5	17.21	0.05	0.019	1.07	0.02

FCC SAR Test Report

4.7.5 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
GSM850	GPRS12	Left Cheek	128	0.989	0.997	1.03	N/A	N/A	N/A	N/A
GSM850	GPRS12	Rear Face	251	0.881	0.863	1.02	N/A	N/A	N/A	N/A
GSM1900	GPRS12	Bottom Side	512	1.25	1.2	1.04	N/A	N/A	N/A	N/A

FCC SAR Test Report

4.7.6 Simultaneous Multi-band Transmission Evaluation

<Estimated SAR Calculation>

According to KDB 447498 D01, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR was estimated according to following formula to result in substantially conservative SAR values of ≤ 0.4 W/kg to determine simultaneous transmission SAR test exclusion.

$$\text{Estimated SAR} = \frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \frac{\sqrt{f_{(\text{GHz})}}}{7.5}$$

If the minimum test separation distance is < 5 mm, a distance of 5 mm is used for estimated SAR calculation. When the test separation distance is > 50 mm, the 0.4 W/kg is used for SAR-1g.

Mode / Band	Frequency (GHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Estimated SAR (W/kg)
BT (DSS)	2.48	12.5	Body-worn	10	0.37

Note:

1. The separation distance is determined from the outer housing of the EUT to the user.
2. When standalone SAR testing is not required, an estimated SAR can be applied to determine simultaneous transmission SAR test exclusion.

FCC SAR Test Report

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

Antenna 0

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
1	GSM850 + WLAN (DTS)	Head	Right Cheek	1.05	0.17	1.22	Σ SAR < 1.6, Not required
			Right Tilted	0.85	0.12	0.97	Σ SAR < 1.6, Not required
			Left Cheek	1.11	0.07	1.18	Σ SAR < 1.6, Not required
			Left Tilted	0.88	0.04	0.92	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.43	0.02	0.45	Σ SAR < 1.6, Not required
			Rear Face	0.49	0.04	0.53	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.43	0.02	0.45	Σ SAR < 1.6, Not required
			Rear Face	0.49	0.04	0.53	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.38	0.00	0.38	Σ SAR < 1.6, Not required
			Top Side	0.39	0.02	0.41	Σ SAR < 1.6, Not required
2	GSM850 + WLAN (NII)	Head	Right Cheek	1.05	0.37	1.42	Σ SAR < 1.6, Not required
			Right Tilted	0.85	0.29	1.14	Σ SAR < 1.6, Not required
			Left Cheek	1.11	0.20	1.31	Σ SAR < 1.6, Not required
			Left Tilted	0.88	0.16	1.04	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.43	0.02	0.45	Σ SAR < 1.6, Not required
			Rear Face	0.49	0.00	0.49	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.43	0.02	0.45	Σ SAR < 1.6, Not required
			Rear Face	0.49	0.00	0.49	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.38	0.00	0.38	Σ SAR < 1.6, Not required
			Top Side	0.39	0.02	0.41	Σ SAR < 1.6, Not required
3	GSM850 + BT (DSS)	Body-Worn	Front Face	0.43	0.37	0.80	Σ SAR < 1.6, Not required
			Rear Face	0.49	0.37	0.86	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
4	GSM1900 + WLAN (DTS)	Head	Right Cheek	0.05	0.17	0.22	Σ SAR < 1.6, Not required
			Right Tilted	0.07	0.12	0.19	Σ SAR < 1.6, Not required
			Left Cheek	0.23	0.07	0.30	Σ SAR < 1.6, Not required
			Left Tilted	0.15	0.04	0.19	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.04	0.02	0.06	Σ SAR < 1.6, Not required
			Rear Face	0.04	0.04	0.08	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.04	0.02	0.06	Σ SAR < 1.6, Not required
			Rear Face	0.04	0.04	0.08	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.02	0.00	0.02	Σ SAR < 1.6, Not required
			Top Side	0.06	0.02	0.08	Σ SAR < 1.6, Not required
5	GSM1900 + WLAN (NII)	Head	Right Cheek	0.05	0.37	0.42	Σ SAR < 1.6, Not required
			Right Tilted	0.07	0.29	0.36	Σ SAR < 1.6, Not required
			Left Cheek	0.23	0.20	0.43	Σ SAR < 1.6, Not required
			Left Tilted	0.15	0.16	0.31	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.04	0.02	0.06	Σ SAR < 1.6, Not required
			Rear Face	0.04	0.00	0.04	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.04	0.02	0.06	Σ SAR < 1.6, Not required
			Rear Face	0.04	0.00	0.04	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.02	0.00	0.02	Σ SAR < 1.6, Not required
			Top Side	0.06	0.02	0.08	Σ SAR < 1.6, Not required
6	GSM1900 + BT (DSS)	Body-Worn	Front Face	0.04	0.37	0.41	Σ SAR < 1.6, Not required
			Rear Face	0.04	0.37	0.41	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
7	WCDMA II + WLAN (DTS)	Head	Right Cheek	0.06	0.17	0.23	Σ SAR < 1.6, Not required
			Right Tilted	0.05	0.12	0.17	Σ SAR < 1.6, Not required
			Left Cheek	0.18	0.07	0.25	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.04	0.18	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.04	0.07	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.04	0.07	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.04	0.02	0.06	Σ SAR < 1.6, Not required
8	WCDMA II + WLAN (NII)	Head	Right Cheek	0.06	0.37	0.43	Σ SAR < 1.6, Not required
			Right Tilted	0.05	0.29	0.34	Σ SAR < 1.6, Not required
			Left Cheek	0.18	0.20	0.38	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.16	0.30	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.00	0.03	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.00	0.03	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.04	0.02	0.06	Σ SAR < 1.6, Not required
9	WCDMA II + BT (DSS)	Body-Worn	Front Face	0.03	0.37	0.40	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.37	0.40	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
10	WCDMA V + WLAN (DTS)	Head	Right Cheek	0.20	0.17	0.37	Σ SAR < 1.6, Not required
			Right Tilted	0.16	0.12	0.28	Σ SAR < 1.6, Not required
			Left Cheek	0.21	0.07	0.28	Σ SAR < 1.6, Not required
			Left Tilted	0.21	0.04	0.25	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.08	0.02	0.10	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.04	0.13	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.08	0.02	0.10	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.04	0.13	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.07	0.00	0.07	Σ SAR < 1.6, Not required
			Top Side	0.07	0.02	0.09	Σ SAR < 1.6, Not required
11	WCDMA V + WLAN (NII)	Head	Right Cheek	0.20	0.37	0.57	Σ SAR < 1.6, Not required
			Right Tilted	0.16	0.29	0.45	Σ SAR < 1.6, Not required
			Left Cheek	0.21	0.20	0.41	Σ SAR < 1.6, Not required
			Left Tilted	0.21	0.16	0.37	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.08	0.02	0.10	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.00	0.09	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.08	0.02	0.10	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.00	0.09	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.07	0.00	0.07	Σ SAR < 1.6, Not required
			Top Side	0.07	0.02	0.09	Σ SAR < 1.6, Not required
12	WCDMA V + BT (DSS)	Body-Worn	Front Face	0.08	0.37	0.45	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.37	0.46	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
13	LTE 4 + WLAN (DTS)	Head	Right Cheek	0.19	0.17	0.36	Σ SAR < 1.6, Not required
			Right Tilted	0.17	0.12	0.29	Σ SAR < 1.6, Not required
			Left Cheek	0.58	0.07	0.65	Σ SAR < 1.6, Not required
			Left Tilted	0.47	0.04	0.51	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.04	0.07	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.04	0.07	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.04	0.02	0.06	Σ SAR < 1.6, Not required
14	LTE 4 + WLAN (NII)	Head	Right Cheek	0.19	0.37	0.56	Σ SAR < 1.6, Not required
			Right Tilted	0.17	0.29	0.46	Σ SAR < 1.6, Not required
			Left Cheek	0.58	0.20	0.78	Σ SAR < 1.6, Not required
			Left Tilted	0.47	0.16	0.63	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.00	0.03	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.00	0.03	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.04	0.02	0.06	Σ SAR < 1.6, Not required
15	LTE 4 + BT (DSS)	Body-Worn	Front Face	0.03	0.37	0.40	Σ SAR < 1.6, Not required
			Rear Face	0.03	0.37	0.40	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
16	LTE 5 + WLAN (DTS)	Head	Right Cheek	0.17	0.17	0.34	Σ SAR < 1.6, Not required
			Right Tilted	0.15	0.12	0.27	Σ SAR < 1.6, Not required
			Left Cheek	0.18	0.07	0.25	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.04	0.18	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.07	0.02	0.09	Σ SAR < 1.6, Not required
			Rear Face	0.08	0.04	0.12	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.07	0.02	0.09	Σ SAR < 1.6, Not required
			Rear Face	0.08	0.04	0.12	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.06	0.00	0.06	Σ SAR < 1.6, Not required
			Top Side	0.06	0.02	0.08	Σ SAR < 1.6, Not required
17	LTE 5 + WLAN (NII)	Head	Right Cheek	0.17	0.37	0.54	Σ SAR < 1.6, Not required
			Right Tilted	0.15	0.29	0.44	Σ SAR < 1.6, Not required
			Left Cheek	0.18	0.20	0.38	Σ SAR < 1.6, Not required
			Left Tilted	0.14	0.16	0.30	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.07	0.02	0.09	Σ SAR < 1.6, Not required
			Rear Face	0.08	0.00	0.08	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.07	0.02	0.09	Σ SAR < 1.6, Not required
			Rear Face	0.08	0.00	0.08	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.06	0.00	0.06	Σ SAR < 1.6, Not required
			Top Side	0.06	0.02	0.08	Σ SAR < 1.6, Not required
18	LTE 5 + BT (DSS)	Body-Worn	Front Face	0.07	0.37	0.44	Σ SAR < 1.6, Not required
			Rear Face	0.08	0.37	0.45	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
19	LTE 7 + WLAN (DTS)	Head	Right Cheek	0.06	0.17	0.23	Σ SAR < 1.6, Not required
			Right Tilted	0.04	0.12	0.16	Σ SAR < 1.6, Not required
			Left Cheek	0.25	0.07	0.32	Σ SAR < 1.6, Not required
			Left Tilted	0.17	0.04	0.21	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.02	0.04	0.06	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.02	0.04	0.06	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.02	0.00	0.02	Σ SAR < 1.6, Not required
			Top Side	0.02	0.02	0.04	Σ SAR < 1.6, Not required
20	LTE 7 + WLAN (NII)	Head	Right Cheek	0.06	0.37	0.43	Σ SAR < 1.6, Not required
			Right Tilted	0.04	0.29	0.33	Σ SAR < 1.6, Not required
			Left Cheek	0.25	0.20	0.45	Σ SAR < 1.6, Not required
			Left Tilted	0.17	0.16	0.33	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.02	0.00	0.02	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.02	0.00	0.02	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.02	0.00	0.02	Σ SAR < 1.6, Not required
			Top Side	0.02	0.02	0.04	Σ SAR < 1.6, Not required
21	LTE 7 + BT (DSS)	Body-Worn	Front Face	0.01	0.37	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.02	0.37	0.39	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
22	LTE 41 + WLAN (DTS)	Head	Right Cheek	0.03	0.17	0.20	Σ SAR < 1.6, Not required
			Right Tilted	0.02	0.12	0.14	Σ SAR < 1.6, Not required
			Left Cheek	0.14	0.07	0.21	Σ SAR < 1.6, Not required
			Left Tilted	0.10	0.04	0.14	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.01	0.04	0.05	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.01	0.04	0.05	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.01	0.02	0.03	Σ SAR < 1.6, Not required
23	LTE 41 + WLAN (NII)	Head	Right Cheek	0.03	0.37	0.40	Σ SAR < 1.6, Not required
			Right Tilted	0.02	0.29	0.31	Σ SAR < 1.6, Not required
			Left Cheek	0.14	0.20	0.34	Σ SAR < 1.6, Not required
			Left Tilted	0.10	0.16	0.26	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.01	0.00	0.01	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.01	0.02	0.03	Σ SAR < 1.6, Not required
			Rear Face	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.01	0.02	0.03	Σ SAR < 1.6, Not required
24	LTE 41 + BT (DSS)	Body-Worn	Front Face	0.01	0.37	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.01	0.37	0.38	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
25	CDMA BC0 + WLAN (DTS)	Head	Right Cheek	0.25	0.17	0.42	Σ SAR < 1.6, Not required
			Right Tilted	0.21	0.12	0.33	Σ SAR < 1.6, Not required
			Left Cheek	0.25	0.07	0.32	Σ SAR < 1.6, Not required
			Left Tilted	0.16	0.04	0.20	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.10	0.02	0.12	Σ SAR < 1.6, Not required
			Rear Face	0.11	0.04	0.15	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.10	0.02	0.12	Σ SAR < 1.6, Not required
			Rear Face	0.11	0.04	0.15	Σ SAR < 1.6, Not required
			Left Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Right Side	0.09	0.00	0.09	Σ SAR < 1.6, Not required
			Top Side	0.09	0.02	0.11	Σ SAR < 1.6, Not required
26	CDMA BC0 + WLAN (NII)	Head	Right Cheek	0.25	0.37	0.62	Σ SAR < 1.6, Not required
			Right Tilted	0.21	0.29	0.50	Σ SAR < 1.6, Not required
			Left Cheek	0.25	0.20	0.45	Σ SAR < 1.6, Not required
			Left Tilted	0.16	0.16	0.32	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.10	0.02	0.12	Σ SAR < 1.6, Not required
			Rear Face	0.11	0.00	0.11	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.10	0.02	0.12	Σ SAR < 1.6, Not required
			Rear Face	0.11	0.00	0.11	Σ SAR < 1.6, Not required
			Left Side	0.00	0.03	0.03	Σ SAR < 1.6, Not required
			Right Side	0.09	0.00	0.09	Σ SAR < 1.6, Not required
			Top Side	0.09	0.02	0.11	Σ SAR < 1.6, Not required
27	CDMA BC0 + BT (DSS)	Body-Worn	Front Face	0.10	0.37	0.47	Σ SAR < 1.6, Not required
			Rear Face	0.11	0.37	0.48	Σ SAR < 1.6, Not required

FCC SAR Test Report

Antenna 1

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
28	GSM850 + WLAN (DTS)	Head	Right Cheek	0.49	0.17	0.66	Σ SAR < 1.6, Not required
			Right Tilted	0.24	0.12	0.36	Σ SAR < 1.6, Not required
			Left Cheek	0.36	0.07	0.43	Σ SAR < 1.6, Not required
			Left Tilted	0.22	0.04	0.26	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.82	0.02	0.84	Σ SAR < 1.6, Not required
			Rear Face	0.93	0.04	0.97	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.82	0.02	0.84	Σ SAR < 1.6, Not required
			Rear Face	0.93	0.04	0.97	Σ SAR < 1.6, Not required
			Left Side	0.26	0.02	0.28	Σ SAR < 1.6, Not required
			Right Side	0.86	0.00	0.86	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.83	0.00	0.83	Σ SAR < 1.6, Not required
29	GSM850 + WLAN (NII)	Head	Right Cheek	0.49	0.37	0.86	Σ SAR < 1.6, Not required
			Right Tilted	0.24	0.29	0.53	Σ SAR < 1.6, Not required
			Left Cheek	0.36	0.20	0.56	Σ SAR < 1.6, Not required
			Left Tilted	0.22	0.16	0.38	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.82	0.02	0.84	Σ SAR < 1.6, Not required
			Rear Face	0.93	0.00	0.93	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.82	0.02	0.84	Σ SAR < 1.6, Not required
			Rear Face	0.93	0.00	0.93	Σ SAR < 1.6, Not required
			Left Side	0.26	0.03	0.29	Σ SAR < 1.6, Not required
			Right Side	0.86	0.00	0.86	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.83	0.00	0.83	Σ SAR < 1.6, Not required
30	GSM850 + BT (DSS)	Body-Worn	Front Face	0.82	0.37	1.19	Σ SAR < 1.6, Not required
			Rear Face	0.93	0.37	1.30	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
31	GSM1900 + WLAN (DTS)	Head	Right Cheek	0.17	0.17	0.34	Σ SAR < 1.6, Not required
			Right Tilted	0.22	0.12	0.34	Σ SAR < 1.6, Not required
			Left Cheek	0.45	0.07	0.52	Σ SAR < 1.6, Not required
			Left Tilted	0.29	0.04	0.33	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.64	0.02	0.66	Σ SAR < 1.6, Not required
			Rear Face	0.59	0.04	0.63	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.64	0.02	0.66	Σ SAR < 1.6, Not required
			Rear Face	0.59	0.04	0.63	Σ SAR < 1.6, Not required
			Left Side	0.56	0.02	0.58	Σ SAR < 1.6, Not required
			Right Side	0.05	0.00	0.05	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	1.32	0.00	1.32	Σ SAR < 1.6, Not required
32	GSM1900 + WLAN (NII)	Head	Right Cheek	0.17	0.37	0.54	Σ SAR < 1.6, Not required
			Right Tilted	0.22	0.29	0.51	Σ SAR < 1.6, Not required
			Left Cheek	0.45	0.20	0.65	Σ SAR < 1.6, Not required
			Left Tilted	0.29	0.16	0.45	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.64	0.02	0.66	Σ SAR < 1.6, Not required
			Rear Face	0.59	0.00	0.59	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.64	0.02	0.66	Σ SAR < 1.6, Not required
			Rear Face	0.59	0.00	0.59	Σ SAR < 1.6, Not required
			Left Side	0.56	0.03	0.59	Σ SAR < 1.6, Not required
			Right Side	0.05	0.00	0.05	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	1.32	0.00	1.32	Σ SAR < 1.6, Not required
33	GSM1900 + BT (DSS)	Body-Worn	Front Face	0.64	0.37	1.01	Σ SAR < 1.6, Not required
			Rear Face	0.59	0.37	0.96	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
34	WCDMA II + WLAN (DTS)	Head	Right Cheek	0.11	0.17	0.28	Σ SAR < 1.6, Not required
			Right Tilted	0.14	0.12	0.26	Σ SAR < 1.6, Not required
			Left Cheek	0.29	0.07	0.36	Σ SAR < 1.6, Not required
			Left Tilted	0.19	0.04	0.23	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.47	0.02	0.49	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.04	0.48	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.47	0.02	0.49	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.04	0.48	Σ SAR < 1.6, Not required
			Left Side	0.03	0.02	0.05	Σ SAR < 1.6, Not required
			Right Side	0.20	0.00	0.20	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.75	0.00	0.75	Σ SAR < 1.6, Not required
35	WCDMA II + WLAN (NII)	Head	Right Cheek	0.11	0.37	0.48	Σ SAR < 1.6, Not required
			Right Tilted	0.14	0.29	0.43	Σ SAR < 1.6, Not required
			Left Cheek	0.29	0.20	0.49	Σ SAR < 1.6, Not required
			Left Tilted	0.19	0.16	0.35	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.47	0.02	0.49	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.00	0.44	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.47	0.02	0.49	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.00	0.44	Σ SAR < 1.6, Not required
			Left Side	0.03	0.03	0.06	Σ SAR < 1.6, Not required
			Right Side	0.20	0.00	0.20	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.75	0.00	0.75	Σ SAR < 1.6, Not required
36	WCDMA II + BT (DSS)	Body-Worn	Front Face	0.47	0.37	0.84	Σ SAR < 1.6, Not required
			Rear Face	0.44	0.37	0.81	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
37	WCDMA V + WLAN (DTS)	Head	Right Cheek	0.12	0.17	0.29	Σ SAR < 1.6, Not required
			Right Tilted	0.06	0.12	0.18	Σ SAR < 1.6, Not required
			Left Cheek	0.09	0.07	0.16	Σ SAR < 1.6, Not required
			Left Tilted	0.05	0.04	0.09	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.25	0.02	0.27	Σ SAR < 1.6, Not required
			Rear Face	0.29	0.04	0.33	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.25	0.02	0.27	Σ SAR < 1.6, Not required
			Rear Face	0.29	0.04	0.33	Σ SAR < 1.6, Not required
			Left Side	0.10	0.02	0.12	Σ SAR < 1.6, Not required
			Right Side	0.25	0.00	0.25	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.27	0.00	0.27	Σ SAR < 1.6, Not required
38	WCDMA V + WLAN (NII)	Head	Right Cheek	0.12	0.37	0.49	Σ SAR < 1.6, Not required
			Right Tilted	0.06	0.29	0.35	Σ SAR < 1.6, Not required
			Left Cheek	0.09	0.20	0.29	Σ SAR < 1.6, Not required
			Left Tilted	0.05	0.16	0.21	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.25	0.02	0.27	Σ SAR < 1.6, Not required
			Rear Face	0.29	0.00	0.29	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.25	0.02	0.27	Σ SAR < 1.6, Not required
			Rear Face	0.29	0.00	0.29	Σ SAR < 1.6, Not required
			Left Side	0.10	0.03	0.13	Σ SAR < 1.6, Not required
			Right Side	0.25	0.00	0.25	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.27	0.00	0.27	Σ SAR < 1.6, Not required
39	WCDMA V + BT (DSS)	Body-Worn	Front Face	0.25	0.37	0.62	Σ SAR < 1.6, Not required
			Rear Face	0.29	0.37	0.66	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
40	LTE 4 + WLAN (DTS)	Head	Right Cheek	0.02	0.17	0.19	Σ SAR < 1.6, Not required
			Right Tilted	0.02	0.12	0.14	Σ SAR < 1.6, Not required
			Left Cheek	0.04	0.07	0.11	Σ SAR < 1.6, Not required
			Left Tilted	0.03	0.04	0.07	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.09	0.02	0.11	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.04	0.13	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.09	0.02	0.11	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.04	0.13	Σ SAR < 1.6, Not required
			Left Side	0.04	0.02	0.06	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.15	0.00	0.15	Σ SAR < 1.6, Not required
41	LTE 4 + WLAN (NII)	Head	Right Cheek	0.02	0.37	0.39	Σ SAR < 1.6, Not required
			Right Tilted	0.02	0.29	0.31	Σ SAR < 1.6, Not required
			Left Cheek	0.04	0.20	0.24	Σ SAR < 1.6, Not required
			Left Tilted	0.03	0.16	0.19	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.09	0.02	0.11	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.00	0.09	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.09	0.02	0.11	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.00	0.09	Σ SAR < 1.6, Not required
			Left Side	0.04	0.03	0.07	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.15	0.00	0.15	Σ SAR < 1.6, Not required
42	LTE 4 + BT (DSS)	Body-Worn	Front Face	0.09	0.37	0.46	Σ SAR < 1.6, Not required
			Rear Face	0.09	0.37	0.46	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
43	LTE 5 + WLAN (DTS)	Head	Right Cheek	0.09	0.17	0.26	Σ SAR < 1.6, Not required
			Right Tilted	0.05	0.12	0.17	Σ SAR < 1.6, Not required
			Left Cheek	0.06	0.07	0.13	Σ SAR < 1.6, Not required
			Left Tilted	0.04	0.04	0.08	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.21	0.02	0.23	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.04	0.29	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.21	0.02	0.23	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.04	0.29	Σ SAR < 1.6, Not required
			Left Side	0.08	0.02	0.10	Σ SAR < 1.6, Not required
			Right Side	0.21	0.00	0.21	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.22	0.00	0.22	Σ SAR < 1.6, Not required
44	LTE 5 + WLAN (NII)	Head	Right Cheek	0.09	0.37	0.46	Σ SAR < 1.6, Not required
			Right Tilted	0.05	0.29	0.34	Σ SAR < 1.6, Not required
			Left Cheek	0.06	0.20	0.26	Σ SAR < 1.6, Not required
			Left Tilted	0.04	0.16	0.20	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.21	0.02	0.23	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.00	0.25	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.21	0.02	0.23	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.00	0.25	Σ SAR < 1.6, Not required
			Left Side	0.08	0.03	0.11	Σ SAR < 1.6, Not required
			Right Side	0.21	0.00	0.21	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.22	0.00	0.22	Σ SAR < 1.6, Not required
45	LTE 5 + BT (DSS)	Body-Worn	Front Face	0.21	0.37	0.58	Σ SAR < 1.6, Not required
			Rear Face	0.25	0.37	0.62	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
46	LTE 7 + WLAN (DTS)	Head	Right Cheek	0.23	0.17	0.40	Σ SAR < 1.6, Not required
			Right Tilted	0.22	0.12	0.34	Σ SAR < 1.6, Not required
			Left Cheek	0.57	0.07	0.64	Σ SAR < 1.6, Not required
			Left Tilted	0.16	0.04	0.20	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.62	0.02	0.64	Σ SAR < 1.6, Not required
			Rear Face	0.65	0.04	0.69	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.62	0.02	0.64	Σ SAR < 1.6, Not required
			Rear Face	0.65	0.04	0.69	Σ SAR < 1.6, Not required
			Left Side	0.54	0.02	0.56	Σ SAR < 1.6, Not required
			Right Side	0.02	0.00	0.02	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.30	0.00	0.30	Σ SAR < 1.6, Not required
47	LTE 7 + WLAN (NII)	Head	Right Cheek	0.23	0.37	0.60	Σ SAR < 1.6, Not required
			Right Tilted	0.22	0.29	0.51	Σ SAR < 1.6, Not required
			Left Cheek	0.57	0.20	0.77	Σ SAR < 1.6, Not required
			Left Tilted	0.16	0.16	0.32	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.62	0.02	0.64	Σ SAR < 1.6, Not required
			Rear Face	0.65	0.00	0.65	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.62	0.02	0.64	Σ SAR < 1.6, Not required
			Rear Face	0.65	0.00	0.65	Σ SAR < 1.6, Not required
			Left Side	0.54	0.03	0.57	Σ SAR < 1.6, Not required
			Right Side	0.02	0.00	0.02	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.30	0.00	0.30	Σ SAR < 1.6, Not required
48	LTE 7 + BT (DSS)	Body-Worn	Front Face	0.62	0.37	0.99	Σ SAR < 1.6, Not required
			Rear Face	0.65	0.37	1.02	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
49	LTE 41 + WLAN (DTS)	Head	Right Cheek	0.12	0.17	0.29	Σ SAR < 1.6, Not required
			Right Tilted	0.03	0.12	0.15	Σ SAR < 1.6, Not required
			Left Cheek	0.29	0.07	0.36	Σ SAR < 1.6, Not required
			Left Tilted	0.07	0.04	0.11	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.36	0.02	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.38	0.04	0.42	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.36	0.02	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.38	0.04	0.42	Σ SAR < 1.6, Not required
			Left Side	0.30	0.02	0.32	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.17	0.00	0.17	Σ SAR < 1.6, Not required
50	LTE 41 + WLAN (NII)	Head	Right Cheek	0.12	0.37	0.49	Σ SAR < 1.6, Not required
			Right Tilted	0.03	0.29	0.32	Σ SAR < 1.6, Not required
			Left Cheek	0.29	0.20	0.49	Σ SAR < 1.6, Not required
			Left Tilted	0.07	0.16	0.23	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.36	0.02	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.38	0.00	0.38	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.36	0.02	0.38	Σ SAR < 1.6, Not required
			Rear Face	0.38	0.00	0.38	Σ SAR < 1.6, Not required
			Left Side	0.30	0.03	0.33	Σ SAR < 1.6, Not required
			Right Side	0.01	0.00	0.01	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.17	0.00	0.17	Σ SAR < 1.6, Not required
51	LTE 41 + BT (DSS)	Body-Worn	Front Face	0.36	0.37	0.73	Σ SAR < 1.6, Not required
			Rear Face	0.38	0.37	0.75	Σ SAR < 1.6, Not required

FCC SAR Test Report

No.	Conditions (SAR1 + SAR2)	Exposure Condition	Test Position	Max. SAR1	Max. SAR2	SAR Summation	SPLSR Analysis
52	CDMA BC0 + WLAN (DTS)	Head	Right Cheek	0.15	0.17	0.32	Σ SAR < 1.6, Not required
			Right Tilted	0.07	0.12	0.19	Σ SAR < 1.6, Not required
			Left Cheek	0.09	0.07	0.16	Σ SAR < 1.6, Not required
			Left Tilted	0.06	0.04	0.10	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.32	0.02	0.34	Σ SAR < 1.6, Not required
			Rear Face	0.37	0.04	0.41	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.32	0.02	0.34	Σ SAR < 1.6, Not required
			Rear Face	0.34	0.04	0.38	Σ SAR < 1.6, Not required
			Left Side	0.12	0.02	0.14	Σ SAR < 1.6, Not required
			Right Side	0.32	0.00	0.32	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.33	0.00	0.33	Σ SAR < 1.6, Not required
53	CDMA BC0 + WLAN (NII)	Head	Right Cheek	0.15	0.37	0.52	Σ SAR < 1.6, Not required
			Right Tilted	0.07	0.29	0.36	Σ SAR < 1.6, Not required
			Left Cheek	0.09	0.20	0.29	Σ SAR < 1.6, Not required
			Left Tilted	0.06	0.16	0.22	Σ SAR < 1.6, Not required
		Body-Worn	Front Face	0.32	0.02	0.34	Σ SAR < 1.6, Not required
			Rear Face	0.37	0.00	0.37	Σ SAR < 1.6, Not required
		Hotspot	Front Face	0.32	0.02	0.34	Σ SAR < 1.6, Not required
			Rear Face	0.34	0.00	0.34	Σ SAR < 1.6, Not required
			Left Side	0.12	0.03	0.15	Σ SAR < 1.6, Not required
			Right Side	0.32	0.00	0.32	Σ SAR < 1.6, Not required
			Top Side	0.00	0.02	0.02	Σ SAR < 1.6, Not required
			Bottom Side	0.33	0.00	0.33	Σ SAR < 1.6, Not required
54	CDMA BC0 + BT (DSS)	Body-Worn	Front Face	0.32	0.37	0.69	Σ SAR < 1.6, Not required
			Rear Face	0.37	0.37	0.74	Σ SAR < 1.6, Not required

Test Engineer : Kei Zhang, and Xianxiong Qin

FCC SAR Test Report

5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D835V2	4d139	Aug. 28, 2017	1 Year
System Validation Dipole	SPEAG	D1750V2	1071	Aug. 26, 2017	1 Year
System Validation Dipole	SPEAG	D1900V2	5d159	Aug. 26, 2017	1 Year
System Validation Dipole	SPEAG	D2450V2	893	Aug. 29, 2017	1 Year
System Validation Dipole	SPEAG	D2600V2	1110	Aug. 29, 2017	1 Year
System Validation Dipole	SPEAG	D5GHZV2	1133	Sep. 18, 2017	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3873	Aug. 25, 2017	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1341	Aug. 23, 2017	1 Year
Radio Communication Analyzer	ANRITSU	MT8820C	6201300717	Jul. 24, 2017	1 Year
Wireless Communication Test Set	Agilent	E5515C	MY50260600	Jun. 28, 2017	1 Year
ENA Series Network Analyzer	Agilent	E5071C	MY46214638	Jul. 24, 2017	1 Year
Spectrum Analyzer	KEYSIGHT	N9010A	MY54510355	Jun. 27, 2017	1 Year
MXG Analog Signal Generator	KEYSIGHT	N5183A	MY50143024	Mar. 01, 2017	1 Year
Power Meter	Agilent	N1914A	MY52180044	Aug. 12, 2016	2 Years
Power Sensor	Agilent	E9304A H18	MY52050011	Jan. 04, 2018	1 Year
Power Meter	ANRITSU	ML2495A	1506002	Mar. 01, 2017	1 Year
Power Sensor	ANRITSU	MA2411B	1339353	Mar. 01, 2017	1 Year
Temp. & Humi. Recorder	CLOCK	HTC-1	157248	Jul. 26, 2017	1 Year
Electronic Thermometer	YONGFA	YF-160A	120100323	Sep. 22, 2017	1 Year
Coupler	Woken	0110A056020-10	COM27RW1A3	Sep. 20, 2017	1 Year

FCC SAR Test Report

6. Measurement Uncertainty

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.0	Normal	1	1	1	6.0	6.0	∞
Axial Isotropy	4.7	Rectangular	√3	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.707	0.707	3.9	3.9	∞
Boundary Effect	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Test Sample Related								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.2	Rectangular	√3	1	1	4.2	4.2	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
Combined Standard Uncertainty						± 11.2 %	± 10.4 %	
Expanded Uncertainty (K=2)						± 22.4 %	± 20.8 %	

Uncertainty budget for frequency range 300 MHz to 3 GHz

FCC SAR Test Report

Source of Uncertainty	Tolerance (± %)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (± %, 1g)	Standard Uncertainty (± %, 10g)	Vi
Measurement System								
Probe Calibration	6.55	Normal	1	1	1	6.55	6.55	∞
Axial Isotropy	4.7	Rectangular	√3	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	0.707	0.707	3.9	3.9	∞
Boundary Effect	2.0	Rectangular	√3	1	1	1.2	1.2	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limits	0.25	Rectangular	√3	1	1	0.14	0.14	∞
Readout Electronics	0.3	Normal	1	1	1	0.3	0.3	∞
Response Time	0.0	Rectangular	√3	1	1	0.0	0.0	∞
Integration Time	1.7	Rectangular	√3	1	1	1.0	1.0	∞
RF Ambient Conditions - Noise	3.0	Rectangular	√3	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Probe Positioning with Respect to Phantom Shell	6.7	Rectangular	√3	1	1	3.9	3.9	∞
Extrapolation, interpolation, and integration algorithms for max. SAR evaluation	4.0	Rectangular	√3	1	1	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	1.5 / 0.7	Normal	1	1	1	1.5	0.7	32
Device Holder Uncertainty	4.2 / 1.8	Normal	1	1	1	4.2	1.8	32
Output Power Variation - SAR Drift Measurement	5.0	Rectangular	√3	1	1	2.9	2.9	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and Thickness Tolerances)	7.6	Rectangular	√3	1	1	4.4	4.4	∞
Liquid Conductivity - Deviation from Target Values	5.0	Rectangular	√3	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - Measurement Uncertainty	1.0	Normal	1	0.64	0.43	0.6	0.4	25
Liquid Permittivity - Deviation from Target Values	5.0	Rectangular	√3	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - Measurement Uncertainty	0.5	Normal	1	0.60	0.49	0.3	0.2	25
Combined Standard Uncertainty						± 12.3 %	± 11.5 %	
Expanded Uncertainty (K=2)						± 24.6 %	± 23.0 %	

Uncertainty budget for frequency range 3 GHz to 6 GHz

FCC SAR Test Report

7. Information on the Testing Laboratories

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Add: No. B102, Dazhu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industry Park, Nanshan District, Shenzhen, Guangdong, China

Tel: 86-755-8869-6566

Fax: 86-755-8869-6577

Email: customerservice.dg@cn.bureauveritas.com

Web Site: www.bureauveritas.com

The road map of all our labs can be found in our web site also.

---END---

Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.



System Check_H835_180121**DUT: Dipole:835 MHz;Type:D835V2; SN;4d139**

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium: H835_0121 Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.925 \text{ S/m}$; $\epsilon_r = 42.855$; $\rho = 1000 \text{ kg/m}^3$ Ambient Temperature : $23.2 \text{ }^\circ\text{C}$; Liquid Temperature : $22.2 \text{ }^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.74, 9.74, 9.74); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x121x1): Interpolated grid: $dx=1.500 \text{ mm}$, $dy=1.500 \text{ mm}$ Maximum value of SAR (interpolated) = 3.26 W/kg **Pin=250mW/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$ Reference Value = 59.44 V/m ; Power Drift = 0.05 dB Peak SAR (extrapolated) = 3.73 W/kg **SAR(1 g) = 2.52 W/kg ; SAR(10 g) = 1.65 W/kg** Maximum value of SAR (measured) = 3.35 W/kg 

System Check_H1750_180119**DUT: Dipole:1750 MHz;Type:D1750V2; SN:1071**

Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1

Medium: H1750_0119 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.346$ S/m; $\epsilon_r = 39.504$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.62, 8.62, 8.62); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.6 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.52 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 9.27 W/kg; SAR(10 g) = 4.93 W/kg

Maximum value of SAR (measured) = 14.2 W/kg



System Check_H1900_180118**DUT: Dipole:1900MHz;Type:D1900V2; SN:5d159**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: H1900_0118 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.425$ S/m; $\epsilon_r = 41.401$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.37, 8.37, 8.37); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.7 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 100.7 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 19.1 W/kg

SAR(1 g) = 10.2 W/kg; SAR(10 g) = 5.23 W/kg

Maximum value of SAR (measured) = 15.9 W/kg



System Check_H2450_180224**DUT: Dipole:2450 MHz;Type:D2450V2; SN:893**

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1

Medium: H2450_0224 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.845$ S/m; $\epsilon_r = 39.401$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.36, 7.36, 7.36); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 22.7 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 105.7 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 28.3 W/kg

SAR(1 g) = 13.5 W/kg; SAR(10 g) = 6.17 W/kg

Maximum value of SAR (measured) = 22.6 W/kg



System Check_H2600_180114**DUT: Dipole:2600 MHz;Type:D2600V2; SN:1110**

Communication System: CW; Frequency: 2600 MHz;Duty Cycle: 1:1

Medium: H2600_0114 Medium parameters used: $f = 2600$ MHz; $\sigma = 2.039$ S/m; $\epsilon_r = 38.932$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.8 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.17, 7.17, 7.17); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 26.2 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 106.4 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 32.7 W/kg

SAR(1 g) = 14.8 W/kg; SAR(10 g) = 6.5 W/kg

Maximum value of SAR (measured) = 26.0 W/kg



System Check_H5250_180225**DUT: Dipole:5GHzV2;Type:D5GHzV2; SN:1133**

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: H5G_0225 Medium parameters used: $f = 5250$ MHz; $\sigma = 4.691$ S/m; $\epsilon_r = 35.327$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(5.04, 5.04, 5.04); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 19.2 W/kg


Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 55.12 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 33.5 W/kg

SAR(1 g) = 7.98 W/kg; SAR(10 g) = 2.25 W/kg

Maximum value of SAR (measured) = 20.3 W/kg



System Check_H5600_180225**DUT: Dipole:5GHzV2;Type:D5GHzV2; SN:1133**

Communication System: CW; Frequency: 5600 MHz;Duty Cycle: 1:1

Medium: H5G_0225 Medium parameters used: $f = 5600$ MHz; $\sigma = 5.041$ S/m; $\epsilon_r = 34.826$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.66, 4.66, 4.66); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 19.1 W/kg


Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 56.49 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 34.3 W/kg

SAR(1 g) = 7.86 W/kg; SAR(10 g) = 2.2 W/kg

Maximum value of SAR (measured) = 20.4 W/kg



System Check_H5800_180225**DUT: Dipole:5GHzV2;Type:D5GHzV2; SN:1133**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: H5G_0225 Medium parameters used: $f = 5800$ MHz; $\sigma = 5.249$ S/m; $\epsilon_r = 34.537$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.7, 4.7, 4.7); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 18.6 W/kg



Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 55.03 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 34.5 W/kg

SAR(1 g) = 7.51 W/kg; SAR(10 g) = 2.1 W/kg

Maximum value of SAR (measured) = 19.9 W/kg



System Check_B835_180120**DUT: Dipole:835 MHz;Type:D835V2; SN:4d139**

Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1

Medium: B835_0120 Medium parameters used: $f = 835$ MHz; $\sigma = 0.976$ S/m; $\epsilon_r = 54.382$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.62, 9.62, 9.62); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x101x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 2.92 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 56.50 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 3.40 W/kg

SAR(1 g) = 2.32 W/kg; SAR(10 g) = 1.55 W/kg

Maximum value of SAR (measured) = 2.92 W/kg



System Check_B1750_180122**DUT: Dipole:1750 MHz;Type:D1750V2; SN:1071**

Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1

Medium: B1750_0122 Medium parameters used: $f = 1750$ MHz; $\sigma = 1.471$ S/m; $\epsilon_r = 53.784$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 13.9 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 93.56 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 16.9 W/kg

SAR(1 g) = 9.64 W/kg; SAR(10 g) = 5.19 W/kg

Maximum value of SAR (measured) = 14.6 W/kg



System Check_B1900_180123**DUT: Dipole:1900MHz;Type:D1900V2; SN:5d159**

Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1

Medium: B1900_0123 Medium parameters used: $f = 1900$ MHz; $\sigma = 1.571$ S/m; $\epsilon_r = 53.584$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.77, 7.77, 7.77); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 15.9 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 97.98 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 10.7 W/kg; SAR(10 g) = 5.55 W/kg

Maximum value of SAR (measured) = 16.5 W/kg



System Check_B2450_180224**DUT: Dipole:2450 MHz;Type:D2450V2; SN:893**

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1

Medium: B2450_0224 Medium parameters used: $f = 2450$ MHz; $\sigma = 1.963$ S/m; $\epsilon_r = 50.972$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.45, 7.45, 7.45); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 21.5 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 98.62 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 25.9 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.18 W/kg

Maximum value of SAR (measured) = 21.3 W/kg



System Check_B2600_180117**DUT: Dipole:2600 MHz;Type:D2600V2; SN:1110**

Communication System: CW; Frequency: 2600 MHz;Duty Cycle: 1:1

Medium: B2600_0117 Medium parameters used: $f = 2600$ MHz; $\sigma = 2.096$ S/m; $\epsilon_r = 50.743$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.9 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.19, 7.19, 7.19); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (71x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 23.2 W/kg



Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 97.87 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 28.3 W/kg

SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.22 W/kg

Maximum value of SAR (measured) = 22.7 W/kg



System Check_B5250_180226**DUT: Dipole:D5GHzV2;Type:D5GHzV2; SN:1133**

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5250$ MHz; $\sigma = 5.379$ S/m; $\epsilon_r = 48.856$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.61, 4.61, 4.61); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 16.1 W/kg


Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 44.94 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 28.6 W/kg

SAR(1 g) = 7.53 W/kg; SAR(10 g) = 2.11 W/kg

Maximum value of SAR (measured) = 16.9 W/kg



System Check_B5600_180226**DUT: Dipole:D5GHzV2;Type:D5GHzV2; SN:1133**

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5600$ MHz; $\sigma = 5.871$ S/m; $\epsilon_r = 48.168$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(3.9, 3.9, 3.9); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 19.6 W/kg


Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 48.86 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 33.1 W/kg

SAR(1 g) = 7.9 W/kg; SAR(10 g) = 2.22 W/kg

Maximum value of SAR (measured) = 20.6 W/kg



System Check_B5800_180226**DUT: Dipole:D5GHzV2;Type:D5GHzV2; SN:1133**

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5800$ MHz; $\sigma = 6.123$ S/m; $\epsilon_r = 47.668$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.16, 4.16, 4.16); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=100mW/Area Scan (91x91x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 16.2 W/kg


Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 46.77 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 29.9 W/kg

SAR(1 g) = 7.59 W/kg; SAR(10 g) = 2.11 W/kg

Maximum value of SAR (measured) = 17.6 W/kg



Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

P01 GSM850_GPRS12_Left Cheek_Ch128_Antenna 0**DUT: 171229W006**

Communication System: GPRS12; Frequency: 824.2 MHz; Duty Cycle: 1:2

Medium: H835_0121 Medium parameters used: $f = 824.2$ MHz; $\sigma = 0.915$ S/m; $\epsilon_r = 42.988$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.74, 9.74, 9.74); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.76 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.72 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 0.989 W/kg; SAR(10 g) = 0.563 W/kg

Maximum value of SAR (measured) = 1.50 W/kg



P02 GSM1900_GPRS12_Left Cheek_Ch661_Antenna 1**DUT: 171229W006**

Communication System: GPRS12; Frequency: 1880 MHz; Duty Cycle: 1:2

Medium: H1900_0118 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.387$ S/m; $\epsilon_r = 39.605$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.37, 8.37, 8.37); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (51x91x1): Interpolated grid: dx=2.000 mm, dy=2.000 mm

Maximum value of SAR (interpolated) = 0.622 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.355 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.697 W/kg

SAR(1 g) = 0.444 W/kg; SAR(10 g) = 0.274 W/kg

Maximum value of SAR (measured) = 0.610 W/kg



P03 WCDMA II_RMC12.2K_Left Cheek_Ch9262_Antenna 1**DUT: 171229W006**

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: H1900_0118 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.4$ S/m; $\epsilon_r = 39.363$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.37, 8.37, 8.37); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (51x91x1): Interpolated grid: dx=2.000 mm, dy=2.000 mm

Maximum value of SAR (interpolated) = 0.416 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.743 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.442 W/kg

SAR(1 g) = 0.287 W/kg; SAR(10 g) = 0.180 W/kg

Maximum value of SAR (measured) = 0.386 W/kg



P04 WCDMA V_RMC12.2K_Left Cheek_Ch4233_Antenna 0**DUT: 171229W006**

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: H835_0121 Medium parameters used: $f = 847$ MHz; $\sigma = 0.936$ S/m; $\epsilon_r = 42.714$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.74, 9.74, 9.74); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.377 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.375 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.424 W/kg

SAR(1 g) = 0.198 W/kg; SAR(10 g) = 0.111 W/kg

Maximum value of SAR (measured) = 0.324 W/kg



P05 CDMA BC0_RC3+SO55_Left Cheek_Ch384_Antenna 0**DUT: 171229W006**

Communication System: CDMA2000; Frequency: 835.52 MHz; Duty Cycle: 1:1

Medium: H835_0121 Medium parameters used: $f = 836$ MHz; $\sigma = 0.926$ S/m; $\epsilon_r = 42.841$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.74, 9.74, 9.74); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.785 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.78 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.879 W/kg

SAR(1 g) = 0.235 W/kg; SAR(10 g) = 0.129 W/kg

Maximum value of SAR (measured) = 0.687 W/kg



P06 LTE 4_QPSK20M_Left Cheek_Ch20175_1RB_OS0_Antenna 0**DUT: 171229W006**

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: H1750_0119 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.326$ S/m; $\epsilon_r = 41.877$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C; Liquid Temperature : 22.1 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.62, 8.62, 8.62); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.866 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.66 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.22 W/kg

SAR(1 g) = 0.535 W/kg; SAR(10 g) = 0.265 W/kg

Maximum value of SAR (measured) = 0.953 W/kg



P07 LTE 5_QPSK10M_Left Cheek_Ch20600_1RB_OS0_Antenna 0**DUT: 171229W006**

Communication System: LTE; Frequency: 844 MHz; Duty Cycle: 1:1

Medium: H835_0121 Medium parameters used: $f = 844$ MHz; $\sigma = 0.934$ S/m; $\epsilon_r = 42.746$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.74, 9.74, 9.74); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.298 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.737 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.361 W/kg

SAR(1 g) = 0.177 W/kg; SAR(10 g) = 0.102 W/kg

Maximum value of SAR (measured) = 0.268 W/kg



P08 LTE 7_QPSK20M_Left Cheek_Ch21350_1RB_OS0_Antenna 1**DUT: 171229W006**

Communication System: LTE; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium: H2600_0114 Medium parameters used: $f = 2560$ MHz; $\sigma = 1.995$ S/m; $\epsilon_r = 39.075$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.8 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.17, 7.17, 7.17); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.806 W/kg



- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.642 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.03 W/kg

SAR(1 g) = 0.545 W/kg; SAR(10 g) = 0.288 W/kg

Maximum value of SAR (measured) = 0.832 W/kg



P09 LTE 41_QPSK20M_Left Cheek_Ch40340_1RB_OS0_Antenna 1**DUT: 171229W006**

Communication System: LTE; Frequency: 2565 MHz; Duty Cycle: 1:1.58

Medium: H2600_0114 Medium parameters used: $f = 2565$ MHz; $\sigma = 2.001$ S/m; $\epsilon_r = 39.057$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.8 °C; Liquid Temperature : 21.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.17, 7.17, 7.17); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.402 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.358 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.520 W/kg

SAR(1 g) = 0.278 W/kg; SAR(10 g) = 0.148 W/kg

Maximum value of SAR (measured) = 0.404 W/kg



P10 802.11b_Right Cheek_Ch1**DUT: 171229W006**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: H2450_0224 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.804$ S/m; $\epsilon_r = 39.56$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.36, 7.36, 7.36); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.410 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.789 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.438 W/kg

SAR(1 g) = 0.173 W/kg; SAR(10 g) = 0.086 W/kg

Maximum value of SAR (measured) = 0.305 W/kg



P11 802.11a_Right Cheek_Ch52**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: H5G_0225 Medium parameters used: $f = 5260$ MHz; $\sigma = 4.7$ S/m; $\epsilon_r = 35.315$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(5.04, 5.04, 5.04); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (111x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.824 W/kg


- Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.327 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 1.03 W/kg

SAR(1 g) = 0.206 W/kg; SAR(10 g) = 0.067 W/kg

Maximum value of SAR (measured) = 0.585 W/kg



P12 802.11a_Right Cheek_Ch100**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: H5G_0225 Medium parameters used: $f = 5500$ MHz; $\sigma = 4.934$ S/m; $\epsilon_r = 34.971$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.66, 4.66, 4.66); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (111x181x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.595 W/kg

- Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 1.477 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.930 W/kg

SAR(1 g) = 0.193 W/kg; SAR(10 g) = 0.058 W/kg

Maximum value of SAR (measured) = 0.507 W/kg



P13 802.11a_Right Cheek_Ch157**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: H5G_0225 Medium parameters used: $f = 5785$ MHz; $\sigma = 5.23$ S/m; $\epsilon_r = 34.56$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.5 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.7, 4.7, 4.7); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (111x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.06 W/kg

- Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.288 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.75 W/kg

SAR(1 g) = 0.344 W/kg; SAR(10 g) = 0.107 W/kg

Maximum value of SAR (measured) = 0.892 W/kg



P14 GSM1900_GPRS12_Front Face_1cm_Ch661_Antenna 1**DUT: 171229W006**

Communication System: GPRS12; Frequency: 1880 MHz; Duty Cycle: 1:2

Medium: B1900_0123 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.549$ S/m; $\epsilon_r = 53.665$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.77, 7.77, 7.77); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.945 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.572 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 1.21 W/kg

SAR(1 g) = 0.624 W/kg; SAR(10 g) = 0.314 W/kg

Maximum value of SAR (measured) = 1.02 W/kg



P15 WCDMA II_RMC12.2K_Front Face_1cm_Ch9662_Antenna 1**DUT: 171229W006**

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: B1900_0123 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.526$ S/m; $\epsilon_r = 53.742$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.77, 7.77, 7.77); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.688 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.531 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.887 W/kg

SAR(1 g) = 0.460 W/kg; SAR(10 g) = 0.235 W/kg

Maximum value of SAR (measured) = 0.746 W/kg



P16 LTE 4_QPSK20M_Front Face_1cm_Ch20175_1RB_OS0_Antenna 1**DUT: 171229W006**

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: B1750_0122 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.453$ S/m; $\epsilon_r = 53.825$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.116 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 3.080 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.146 W/kg

SAR(1 g) = 0.084 W/kg; SAR(10 g) = 0.048 W/kg

Maximum value of SAR (measured) = 0.126 W/kg



P17 802.11a_Front Face_1cm_Ch52**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5260$ MHz; $\sigma = 5.28$ S/m; $\epsilon_r = 50.997$; $\rho =$

1000 kg/m^3

Ambient Temperature : 23.4°C ; Liquid Temperature : 22.3°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.61, 4.61, 4.61); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- **Area Scan (111x181x1):** Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.0504 W/kg


- **Zoom Scan (7x7x12)/Cube 0:** Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 0.4700 V/m ; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.0110 W/kg

SAR(1 g) = 0.008 W/kg ; SAR(10 g) = 0.00131 W/kg

Maximum value of SAR (measured) = 0.0144 W/kg



P18 802.11a_Front Face_1cm_Ch100**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5500$ MHz; $\sigma = 5.69$ S/m; $\epsilon_r = 50.618$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(3.9, 3.9, 3.9); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (111x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.0151 W/kg


- Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.3420 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.0570 W/kg

SAR(1 g) = 0.00137 W/kg; SAR(10 g) = 0.00017 W/kg

Maximum value of SAR (measured) = 0.0566 W/kg



P19 802.11a_Front Face_1cm_Ch157**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5785$ MHz; $\sigma = 6.128$ S/m; $\epsilon_r = 49.918$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.16, 4.16, 4.16); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (111x181x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 0.016 W/kg


- Zoom Scan (7x7x12)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 0.3460 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.0590 W/kg

SAR(1 g) = 0.023 W/kg; SAR(10 g) = 0.00693 W/kg

Maximum value of SAR (measured) = 0.0598 W/kg



P20 GSM850_GPRS12_Rear Face_1cm_Ch251_Antenna 1**DUT: 171229W006**

Communication System: GPRS12; Frequency: 848.8 MHz; Duty Cycle: 1:2

Medium: B835_0120 Medium parameters used: $f = 849$ MHz; $\sigma = 1.006$ S/m; $\epsilon_r = 55.43$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.62, 9.62, 9.62); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.370 W/kg

- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.01 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.881 W/kg; SAR(10 g) = 0.484 W/kg

Maximum value of SAR (measured) = 0.380 W/kg


- Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.01 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.60 W/kg

SAR(1 g) = 0.874 W/kg; SAR(10 g) = 0.469 W/kg

Maximum value of SAR (measured) = 0.299 W/kg



P21 GSM1900_GPRS12_Bottom Side_1cm_Ch512_Antenna 1**DUT: 171229W006**

Communication System: GPRS12; Frequency: 1850.2 MHz; Duty Cycle: 1:2

Medium: B1900_0123 Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.524$ S/m; $\epsilon_r = 53.747$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.77, 7.77, 7.77); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (41x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.98 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.28 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 2.40 W/kg

SAR(1 g) = 1.25 W/kg; SAR(10 g) = 0.623 W/kg

Maximum value of SAR (measured) = 1.97 W/kg



P22 WCDMA II_RMC12.2K_Bottom Side_1cm_Ch9662_Antenna 1**DUT: 171229W006**

Communication System: WCDMA; Frequency: 1852.4 MHz; Duty Cycle: 1:1

Medium: B1900_0123 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.526$ S/m; $\epsilon_r = 53.742$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.4 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.77, 7.77, 7.77); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (41x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.16 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.82 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.739 W/kg; SAR(10 g) = 0.367 W/kg

Maximum value of SAR (measured) = 1.16 W/kg



P23 WCDMA V_RMC12.2K_Rear Face_1cm_Ch4233_Antenna 1**DUT: 171229W006**

Communication System: WCDMA; Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: B835_0120 Medium parameters used: $f = 847$ MHz; $\sigma = 1.004$ S/m; $\epsilon_r = 55.449$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.62, 9.62, 9.62); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.395 W/kg

- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.80 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.528 W/kg

SAR(1 g) = 0.279 W/kg; SAR(10 g) = 0.154 W/kg

Maximum value of SAR (measured) = 0.399 W/kg


- Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.80 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.534 W/kg

SAR(1 g) = 0.281 W/kg; SAR(10 g) = 0.147 W/kg

Maximum value of SAR (measured) = 0.420 W/kg



P24 CDMA BC0_RC3+SO32_Rear Face_1cm_Ch384_Antenna 1**DUT: 171229W006**

Communication System: CDMA2000; Frequency: 835.52 MHz; Duty Cycle: 1:1

Medium: B835_0120 Medium parameters used: $f = 836$ MHz; $\sigma = 0.993$ S/m; $\epsilon_r = 55.563$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.62, 9.62, 9.62); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.389 W/kg

- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.78 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.520 W/kg

SAR(1 g) = 0.341 W/kg; SAR(10 g) = 0.188 W/kg

Maximum value of SAR (measured) = 0.394 W/kg


- Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.78 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.527 W/kg

SAR(1 g) = 0.315 W/kg; SAR(10 g) = 0.175 W/kg

Maximum value of SAR (measured) = 0.414 W/kg



P25 LTE 4_QPSK20M_Bottom Side_1cm_Ch20175_1RB_OS0_Antenna 1**DUT: 171229W006**

Communication System: LTE; Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: B1750_0122 Medium parameters used: $f = 1732.5$ MHz; $\sigma = 1.453$ S/m; $\epsilon_r = 53.825$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.2 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(8.04, 8.04, 8.04); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Front Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1695
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (41x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.214 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.870 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.253 W/kg

SAR(1 g) = 0.135 W/kg; SAR(10 g) = 0.066 W/kg

Maximum value of SAR (measured) = 0.215 W/kg



P26 LTE 5_QPSK10M_Rear Face_1cm_Ch20600_1RB_OS0_Antenna 1**DUT: 171229W006**

Communication System: LTE; Frequency: 844 MHz; Duty Cycle: 1:1

Medium: B835_0120 Medium parameters used: $f = 844$ MHz; $\sigma = 1.001$ S/m; $\epsilon_r = 55.479$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(9.62, 9.62, 9.62); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (71x121x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.364 W/kg

- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.73 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.450 W/kg

SAR(1 g) = 0.243 W/kg; SAR(10 g) = 0.134 W/kg

Maximum value of SAR (measured) = 0.374 W/kg


- Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.73 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.353 W/kg

SAR(1 g) = 0.182 W/kg; SAR(10 g) = 0.128 W/kg

Maximum value of SAR (measured) = 0.295 W/kg



P27 LTE 7_QPSK20M_Rear Face_0.5cm_Ch21350_1RB_OS0_Antenna 1**DUT: 171229W006**

Communication System: LTE; Frequency: 2560 MHz; Duty Cycle: 1:1

Medium: B2600_0117 Medium parameters used: $f = 2560$ MHz; $\sigma = 2.046$ S/m; $\epsilon_r = 50.875$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.9 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.19, 7.19, 7.19); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.909 W/kg


- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.819 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.13 W/kg

SAR(1 g) = 0.622 W/kg; SAR(10 g) = 0.337 W/kg

Maximum value of SAR (measured) = 0.942 W/kg



P28 LTE 41_QPSK20M_Rear Face_0.5cm_Ch40340_1RB_OS0_Antenna 1**DUT: 171229W006**

Communication System: LTE; Frequency: 2565 MHz; Duty Cycle: 1:1.58

Medium: B2600_0117 Medium parameters used: $f = 2565$ MHz; $\sigma = 2.053$ S/m; $\epsilon_r = 50.856$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.9 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.19, 7.19, 7.19); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.529 W/kg



- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.426 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.664 W/kg

SAR(1 g) = 0.366 W/kg; SAR(10 g) = 0.198 W/kg

Maximum value of SAR (measured) = 0.553 W/kg



P29 802.11b_Rear Face_1cm_Ch1**DUT: 171229W006**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: B2450_0224 Medium parameters used: $f = 2412$ MHz; $\sigma = 1.881$ S/m; $\epsilon_r = 51.734$; $\rho = 1000$ kg/m³

Ambient Temperature : 22.7 °C; Liquid Temperature : 21.9 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(7.45, 7.45, 7.45); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1205
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- **Area Scan (91x151x1):** Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.0599 W/kg


- **Zoom Scan (5x5x7)/Cube 0:** Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 2.003 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 0.0710 W/kg

SAR(1 g) = 0.036 W/kg; SAR(10 g) = 0.019 W/kg

Maximum value of SAR (measured) = 0.0568 W/kg



P30 802.11a_Left Side_1cm_Ch36**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5180 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5180$ MHz; $\sigma = 5.152$ S/m; $\epsilon_r = 51.079$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.61, 4.61, 4.61); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (81x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.0997 W/kg


- Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.2280 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.143 W/kg

SAR(1 g) = 0.025 W/kg; SAR(10 g) = 0.00847 W/kg

Maximum value of SAR (measured) = 0.0760 W/kg



P31 802.11a_Left Side_1cm_Ch157**DUT: 171229W006**

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: B5G_0226 Medium parameters used: $f = 5785$ MHz; $\sigma = 6.128$ S/m; $\epsilon_r = 49.918$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C; Liquid Temperature : 22.3 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3873; ConvF(4.16, 4.16, 4.16); Calibrated: 2017/08/25;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1341; Calibrated: 2017/08/23
- Phantom: Left Phantom with CRP v5.0; Type: QD000P40CD; Serial: TP:1722
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

- Area Scan (81x181x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.126 W/kg

- Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.2420 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.032 W/kg; SAR(10 g) = 0.011 W/kg

Maximum value of SAR (measured) = 0.0961 W/kg

