

### FCC REPORT

**Applicant:** YANSHAN YONGSHENGJIE TECHNOLOGY CO.,LTD  
**Address of Applicant:** BUBIAO INDUSTRIAL TRANSFER PARK,YANSHAN COUNTY,WENSHAN CITY,YUNNAN PROVINCE,CHINA  
**Manufacturer/Factory:** YANSHAN YONGSHENGJIE TECHNOLOGY CO.,LTD  
**Address of Manufacturer/Factory:** BUBIAO INDUSTRIAL TRANSFER PARK,YANSHAN COUNTY,WENSHAN CITY,YUNNAN PROVINCE,CHINA  
**Equipment Under Test (EUT)**

**Product Name:** Car Audio Palyer(with CD)

**Model No.:** CX-50BT, YSJ-3250C, VCD-61BA, YSJ-3248C, PVCD-91B, YSJ-3242C, PCD-81B, YSJ-3252C

**FCC ID:** 2ANS2-YSJ01SPC

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.249:2017

**Date of sample receipt:** July 03, 2017

**Date of Test:** July 04-09, 2017

**Date of report issued:** July 10, 2017

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue ink stamp from GTS Global United Technology Services Co., Ltd. is visible. The stamp contains the text 'GTS', 'GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD.', and 'TVS015'. Overlaid on the stamp is a handwritten signature in black ink, which appears to be 'Robinson Lo'.

Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

| Version No. | Date          | Description |
|-------------|---------------|-------------|
| 00          | July 10, 2017 | Original    |
|             |               |             |
|             |               |             |
|             |               |             |
|             |               |             |

Prepared By:




Date:

July 10, 2017

Project Engineer

Check By:



Date:

July 10, 2017

Reviewer

## 3 Contents

|                                                       | Page |
|-------------------------------------------------------|------|
| 1 COVER PAGE.....                                     | 1    |
| 2 VERSION .....                                       | 2    |
| 3 CONTENTS .....                                      | 3    |
| 4 TEST SUMMARY .....                                  | 4    |
| 4.1 MEASUREMENT UNCERTAINTY .....                     | 4    |
| 5 GENERAL INFORMATION .....                           | 5    |
| 5.1 GENERAL DESCRIPTION OF EUT .....                  | 5    |
| 5.2 TEST MODE .....                                   | 7    |
| 5.3 DESCRIPTION OF SUPPORT UNITS .....                | 7    |
| 5.4 TEST FACILITY .....                               | 7    |
| 5.5 TEST LOCATION .....                               | 7    |
| 5.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER ..... | 7    |
| 6 TEST INSTRUMENTS LIST .....                         | 8    |
| 7 TEST RESULTS AND MEASUREMENT DATA.....              | 9    |
| 7.1 ANTENNA REQUIREMENT .....                         | 9    |
| 7.2 RADIATED EMISSION METHOD .....                    | 10   |
| 7.2.1 Field Strength of The Fundamental Signal .....  | 12   |
| 7.2.2 Spurious emissions.....                         | 13   |
| 7.2.3 Bandedge emissions.....                         | 17   |
| 7.3 20dB OCCUPY BANDWIDTH .....                       | 21   |
| 8 TEST SETUP PHOTO .....                              | 23   |
| 9 EUT CONSTRUCTIONAL DETAILS .....                    | 24   |

## 4 Test Summary

| Test Item                                | Section in CFR 47     | Result |
|------------------------------------------|-----------------------|--------|
| Antenna requirement                      | 15.203                | Pass   |
| AC Power Line Conducted Emission         | 15.207                | N/A    |
| Field strength of the fundamental signal | 15.249 (a)            | Pass   |
| Spurious emissions                       | 15.249 (a) (d)/15.209 | Pass   |
| Band edge                                | 15.249 (d)/15.205     | Pass   |
| 20dB Occupied Bandwidth                  | 15.215 (c)            | Pass   |

*Pass: The EUT complies with the essential requirements in the standard.*

*Remark: Test according to ANSI C63.4:2014 and ANSI C63.10:2013.*

### 4.1 Measurement Uncertainty

| Test Item                        | Frequency Range | Measurement Uncertainty | Notes |
|----------------------------------|-----------------|-------------------------|-------|
| Radiated Emission                | 9kHz ~ 30MHz    | $\pm 4.34\text{dB}$     | (1)   |
| Radiated Emission                | 30MHz ~ 1000MHz | $\pm 4.24\text{dB}$     | (1)   |
| Radiated Emission                | 1GHz ~ 26.5GHz  | $\pm 4.68\text{dB}$     | (1)   |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | $\pm 3.45\text{dB}$     | (1)   |

Note (1): The measurement uncertainty is for coverage factor of  $k=2$  and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

|                                                                                                                                                                                  |                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| Product Name:                                                                                                                                                                    | Car Audio Palyer(with CD)                                                        |
| Model No.:                                                                                                                                                                       | CX-50BT, YSJ-3250C, VCD-61BA, YSJ-3248C, PVCD-91B, YSJ-3242C, PCD-81B, YSJ-3252C |
| Test Model No:                                                                                                                                                                   | PCD-81B                                                                          |
| <i>Remark:All above models are identical in the same PCB layout, interior structure and electrical circuits. Th differences are color and model name for commercial purpose.</i> |                                                                                  |
| Operation Frequency:                                                                                                                                                             | 2402MHz~2480MHz                                                                  |
| Channel numbers:                                                                                                                                                                 | 79                                                                               |
| Channel separation:                                                                                                                                                              | 1MHz                                                                             |
| Modulation type:                                                                                                                                                                 | GFSK, Pi/4QPSK, 8DPSK                                                            |
| Antenna Type:                                                                                                                                                                    | PCB antenna                                                                      |
| Antenna gain:                                                                                                                                                                    | 0dBi (Declared by Applicant)                                                     |
| Power supply:                                                                                                                                                                    | DC 12V                                                                           |

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                   | 2402MHz   | 21      | 2422MHz   | 41      | 2442MHz   | 61      | 2462MHz   |
| 2                                   | 2403MHz   | 22      | 2423MHz   | 42      | 2443MHz   | 62      | 2463MHz   |
| ⋮                                   | ⋮         | ⋮       | ⋮         | ⋮       | ⋮         | ⋮       | ⋮         |
| 19                                  | 2420MHz   | 39      | 2440MHz   | 59      | 2460MHz   | 79      | 2480MHz   |
| 20                                  | 2421MHz   | 40      | 2441MHz   | 60      | 2461MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel             | Frequency |
|---------------------|-----------|
| The lowest channel  | 2402MHz   |
| The middle channel  | 2441MHz   |
| The Highest channel | 2480MHz   |

## 5.2 Test mode

|                                                                                                                                                                                                                                                                     |                                                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| Transmitting mode                                                                                                                                                                                                                                                   | Keep the EUT in continuously transmitting mode |
| <i>Remark: During the test, the dutycycle &gt;98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i> |                                                |

### Pre-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

| Axis                   | X     | Y     | Z     |
|------------------------|-------|-------|-------|
| Field Strength(dBuV/m) | 93.62 | 94.63 | 92.78 |

### Final Test Mode:

The EUT was tested in GFSK,  $\pi/4$ QPSK, 8DPSK modulation, and found the GFSK modulation is the worst case.

According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup”:

Y axis (see the test setup photo)

## 5.3 Description of Support Units

| Manufacturer | Description       | Model      | Serial Number |
|--------------|-------------------|------------|---------------|
| GS           | Lead-Acid battery | S5D26R-MFZ | 9442804454    |

## 5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

## 5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

## 5.6 Other Information Requested by the Customer


None.

## 6 Test Instruments list


| Radiated Emission: |                               |                                |                             |               |                     |                         |
|--------------------|-------------------------------|--------------------------------|-----------------------------|---------------|---------------------|-------------------------|
| Item               | Test Equipment                | Manufacturer                   | Model No.                   | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | 3m Semi- Anechoic Chamber     | ZhongYu Electron               | 9.2(L)*6.2(W)* 6.4(H)       | GTS250        | July 03 2015        | July 02 2020            |
| 2                  | Control Room                  | ZhongYu Electron               | 6.2(L)*2.5(W)* 2.4(H)       | GTS251        | N/A                 | N/A                     |
| 3                  | Spectrum Analyzer             | Agilent                        | E4440A                      | GTS533        | June 29 2017        | June 28 2018            |
| 4                  | EMI Test Receiver             | Rohde & Schwarz                | ESU26                       | GTS203        | June 29 2017        | June 28 2018            |
| 5                  | BiConiLog Antenna             | SCHWARZBECK<br>MESS-ELEKTRONIK | VULB9163                    | GTS214        | June 29 2017        | June 28 2018            |
| 6                  | Double -ridged waveguide horn | SCHWARZBECK<br>MESS-ELEKTRONIK | 9120D-829                   | GTS208        | June 29 2017        | June 28 2018            |
| 7                  | Horn Antenna                  | ETS-LINDGREN                   | 3160                        | GTS217        | June 29 2017        | June 28 2018            |
| 8                  | EMI Test Software             | AUDIX                          | E3                          | N/A           | N/A                 | N/A                     |
| 9                  | Coaxial Cable                 | GTS                            | N/A                         | GTS213        | June 29 2017        | June 28 2018            |
| 10                 | Coaxial Cable                 | GTS                            | N/A                         | GTS211        | June 29 2017        | June 28 2018            |
| 11                 | Coaxial cable                 | GTS                            | N/A                         | GTS210        | June 29 2017        | June 28 2018            |
| 12                 | Coaxial Cable                 | GTS                            | N/A                         | GTS212        | June 29 2017        | June 28 2018            |
| 13                 | Amplifier(100kHz-3GHz)        | HP                             | 8347A                       | GTS204        | June 29 2017        | June 28 2018            |
| 14                 | Amplifier(2GHz-20GHz)         | HP                             | 8349B                       | GTS206        | June 29 2017        | June 28 2018            |
| 15                 | Amplifier (18-26GHz)          | Rohde & Schwarz                | AFS33-18002<br>650-30-8P-44 | GTS218        | June 29 2017        | June 28 2018            |
| 16                 | Band filter                   | Amindeon                       | 82346                       | GTS219        | June 29 2017        | June 28 2018            |
| 17                 | Power Meter                   | Anritsu                        | ML2495A                     | GTS540        | June 29 2017        | June 28 2018            |
| 18                 | Power Sensor                  | Anritsu                        | MA2411B                     | GTS541        | June 29 2017        | June 28 2018            |


## 7 Test results and Measurement Data

### 7.1 Antenna requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                     | FCC Part15 C Section 15.203 |
| <b>15.203 requirement:</b><br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |                             |
| <b>EUT Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                             |
| <p><i>The antenna is PCB antenna, the best case gain of the antenna is 0dBi</i></p>                                                                                                                                                                                                                                                                                                           |                             |

## 7.2 Radiated Emission Method

|                                                      |                                                                                                                                                                                                                                                                |            |                    |        |                  |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------------------|--------|------------------|
| Test Requirement:                                    | FCC Part15 C Section 15.209                                                                                                                                                                                                                                    |            |                    |        |                  |
| Test Method:                                         | ANSI C63.10:2013                                                                                                                                                                                                                                               |            |                    |        |                  |
| Test Frequency Range:                                | 30MHz to 25GHz                                                                                                                                                                                                                                                 |            |                    |        |                  |
| Test site:                                           | Measurement Distance: 3m                                                                                                                                                                                                                                       |            |                    |        |                  |
| Receiver setup:                                      | Frequency                                                                                                                                                                                                                                                      | Detector   | RBW                | VBW    | Remark           |
|                                                      | 30MHz-1GHz                                                                                                                                                                                                                                                     | Quasi-peak | 120KHz             | 300KHz | Quasi-peak Value |
|                                                      | Above 1GHz                                                                                                                                                                                                                                                     | Peak       | 1MHz               | 3MHz   | Peak Value       |
|                                                      |                                                                                                                                                                                                                                                                | Peak       | 1MHz               | 10Hz   | Average Value    |
| Limit:<br>(Field strength of the fundamental signal) | Frequency                                                                                                                                                                                                                                                      |            | Limit (dBuV/m @3m) |        | Remark           |
|                                                      | 2400MHz-2483.5MHz                                                                                                                                                                                                                                              |            | 94.00              |        | Average Value    |
|                                                      |                                                                                                                                                                                                                                                                |            | 114.00             |        | Peak Value       |
| Limit:<br>(Spurious Emissions)                       | Frequency                                                                                                                                                                                                                                                      |            | Limit (dBuV/m @3m) |        | Remark           |
|                                                      | 30MHz-88MHz                                                                                                                                                                                                                                                    |            | 40.00              |        | Quasi-peak Value |
|                                                      | 88MHz-216MHz                                                                                                                                                                                                                                                   |            | 43.50              |        | Quasi-peak Value |
|                                                      | 216MHz-960MHz                                                                                                                                                                                                                                                  |            | 46.00              |        | Quasi-peak Value |
|                                                      | 960MHz-1GHz                                                                                                                                                                                                                                                    |            | 54.00              |        | Quasi-peak Value |
|                                                      | Above 1GHz                                                                                                                                                                                                                                                     |            | 54.00              |        | Average Value    |
|                                                      |                                                                                                                                                                                                                                                                |            | 74.00              |        | Peak Value       |
| Limit:<br>(band edge)                                | Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation. |            |                    |        |                  |
| Test setup:                                          | <div>Below 1GHz</div> <div></div> <div>Above 1GHz</div>                                                                                                                    |            |                    |        |                  |

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Test Procedure:   | <ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

## Measurement data:

## 7.2.1 Field Strength of The Fundamental Signal

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2402.00         | 95.67             | 27.58                 | 5.39            | 34.01                    | 94.63          | 114.00              | -19.37          | Vertical     |
| 2402.00         | 93.63             | 27.58                 | 5.39            | 34.01                    | 92.59          | 114.00              | -21.41          | Horizontal   |
| 2441.00         | 95.80             | 27.48                 | 5.43            | 33.96                    | 94.75          | 114.00              | -19.25          | Vertical     |
| 2441.00         | 93.64             | 27.48                 | 5.43            | 33.96                    | 92.59          | 114.00              | -21.41          | Horizontal   |
| 2480.00         | 95.32             | 27.52                 | 5.47            | 33.92                    | 94.39          | 114.00              | -19.61          | Vertical     |
| 2480.00         | 93.23             | 27.52                 | 5.47            | 33.92                    | 92.30          | 114.00              | -21.70          | Horizontal   |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2402.00         | 85.67             | 27.58                 | 5.39            | 34.01                    | 84.63          | 94.00               | -9.37           | Vertical     |
| 2402.00         | 83.71             | 27.58                 | 5.39            | 34.01                    | 82.67          | 94.00               | -11.33          | Horizontal   |
| 2441.00         | 85.76             | 27.48                 | 5.43            | 33.96                    | 84.71          | 94.00               | -9.29           | Vertical     |
| 2441.00         | 83.48             | 27.48                 | 5.43            | 33.96                    | 82.43          | 94.00               | -11.57          | Horizontal   |
| 2480.00         | 85.38             | 27.52                 | 5.47            | 33.92                    | 84.45          | 94.00               | -9.55           | Vertical     |
| 2480.00         | 82.88             | 27.52                 | 5.47            | 33.92                    | 81.95          | 94.00               | -12.05          | Horizontal   |

Remark: RBW 3MHz, VBW 10MHz , peak detector for PK value, RBW 3MHz, VBW 10MHz AV detector for AV value

## 7.2.2 Spurious emissions

### ■ Below 1GHz

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 119.86          | 45.29             | 12.48                 | 1.36            | 29.57                    | 29.56          | 43.50               | -13.94          | Vertical     |
| 239.99          | 43.27             | 14.09                 | 2.07            | 29.56                    | 29.87          | 46.00               | -16.13          | Vertical     |
| 360.45          | 41.65             | 16.43                 | 2.67            | 29.69                    | 31.06          | 46.00               | -14.94          | Vertical     |
| 480.53          | 36.43             | 18.07                 | 3.22            | 29.34                    | 28.38          | 46.00               | -17.62          | Vertical     |
| 601.43          | 32.05             | 20.46                 | 3.73            | 29.30                    | 26.94          | 46.00               | -19.06          | Vertical     |
| 842.13          | 27.50             | 22.51                 | 4.63            | 29.16                    | 25.48          | 46.00               | -20.52          | Vertical     |
| 59.23           | 33.88             | 14.74                 | 0.85            | 29.93                    | 19.54          | 40.00               | -20.46          | Horizontal   |
| 88.03           | 36.89             | 13.32                 | 1.09            | 29.76                    | 21.54          | 43.50               | -21.96          | Horizontal   |
| 119.86          | 50.24             | 12.48                 | 1.36            | 29.57                    | 34.51          | 43.50               | -8.99           | Horizontal   |
| 239.99          | 52.94             | 14.09                 | 2.07            | 29.56                    | 39.54          | 46.00               | -6.46           | Horizontal   |
| 360.45          | 45.38             | 16.43                 | 2.67            | 29.69                    | 34.79          | 46.00               | -11.21          | Horizontal   |
| 480.53          | 38.65             | 18.07                 | 3.22            | 29.34                    | 30.60          | 46.00               | -15.40          | Horizontal   |

## ■ Above 1GHz

|               |                |
|---------------|----------------|
| Test channel: | Lowest channel |
|---------------|----------------|

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4804.00         | 37.64             | 31.78                 | 8.60            | 32.09              | 45.93          | 74.00               | -28.07          | Vertical     |
| 7206.00         | 32.05             | 36.15                 | 11.65           | 32.00              | 47.85          | 74.00               | -26.15          | Vertical     |
| 9608.00         | 31.67             | 37.95                 | 14.14           | 31.62              | 52.14          | 74.00               | -21.86          | Vertical     |
| 12010.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14412.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4804.00         | 41.99             | 31.78                 | 8.60            | 32.09              | 50.28          | 74.00               | -23.72          | Horizontal   |
| 7206.00         | 33.84             | 36.15                 | 11.65           | 32.00              | 49.64          | 74.00               | -24.36          | Horizontal   |
| 9608.00         | 31.12             | 37.95                 | 14.14           | 31.62              | 51.59          | 74.00               | -22.41          | Horizontal   |
| 12010.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14412.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4804.00         | 26.39             | 31.78                 | 8.60            | 32.09              | 34.68          | 54.00               | -19.32          | Vertical     |
| 7206.00         | 20.70             | 36.15                 | 11.65           | 32.00              | 36.50          | 54.00               | -17.50          | Vertical     |
| 9608.00         | 19.76             | 37.95                 | 14.14           | 31.62              | 40.23          | 54.00               | -13.77          | Vertical     |
| 12010.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14412.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4804.00         | 30.65             | 31.78                 | 8.60            | 32.09              | 38.94          | 54.00               | -15.06          | Horizontal   |
| 7206.00         | 22.89             | 36.15                 | 11.65           | 32.00              | 38.69          | 54.00               | -15.31          | Horizontal   |
| 9608.00         | 19.51             | 37.95                 | 14.14           | 31.62              | 39.98          | 54.00               | -14.02          | Horizontal   |
| 12010.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14412.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

### Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “\*”, means this data is the too weak instrument of signal is unable to test.

|               |                |
|---------------|----------------|
| Test channel: | Middle channel |
|---------------|----------------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4882.00         | 36.65             | 31.85                 | 8.67            | 32.12                    | 45.05          | 74.00               | -28.95          | Vertical     |
| 7323.00         | 31.40             | 36.37                 | 11.72           | 31.89                    | 47.60          | 74.00               | -26.40          | Vertical     |
| 9764.00         | 31.08             | 38.35                 | 14.25           | 31.62                    | 52.06          | 74.00               | -21.94          | Vertical     |
| 12205.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 14646.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 4882.00         | 40.81             | 31.85                 | 8.67            | 32.12                    | 49.21          | 74.00               | -24.79          | Horizontal   |
| 7323.00         | 33.10             | 36.37                 | 11.72           | 31.89                    | 49.30          | 74.00               | -24.70          | Horizontal   |
| 9764.00         | 30.45             | 38.35                 | 14.25           | 31.62                    | 51.43          | 74.00               | -22.57          | Horizontal   |
| 12205.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 14646.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4882.00         | 25.60             | 31.85                 | 8.67            | 32.12                    | 34.00          | 54.00               | -20.00          | Vertical     |
| 7323.00         | 20.17             | 36.37                 | 11.72           | 31.89                    | 36.37          | 54.00               | -17.63          | Vertical     |
| 9764.00         | 19.28             | 38.35                 | 14.25           | 31.62                    | 40.26          | 54.00               | -13.74          | Vertical     |
| 12205.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 14646.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 4882.00         | 29.76             | 31.85                 | 8.67            | 32.12                    | 38.16          | 54.00               | -15.84          | Horizontal   |
| 7323.00         | 22.30             | 36.37                 | 11.72           | 31.89                    | 38.50          | 54.00               | -15.50          | Horizontal   |
| 9764.00         | 18.96             | 38.35                 | 14.25           | 31.62                    | 39.94          | 54.00               | -14.06          | Horizontal   |
| 12205.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 14646.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “\*”, means this data is the too weak instrument of signal is unable to test.

|               |                 |
|---------------|-----------------|
| Test channel: | Highest channel |
|---------------|-----------------|

## Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4960.00         | 35.97             | 31.93                 | 8.73            | 32.16                    | 44.47          | 74.00               | -29.53          | Vertical     |
| 7440.00         | 30.94             | 36.59                 | 11.79           | 31.78                    | 47.54          | 74.00               | -26.46          | Vertical     |
| 9920.00         | 30.68             | 38.81                 | 14.38           | 31.88                    | 51.99          | 74.00               | -22.01          | Vertical     |
| 12400.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 14880.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 4960.00         | 39.98             | 31.93                 | 8.73            | 32.16                    | 48.48          | 74.00               | -25.52          | Horizontal   |
| 7440.00         | 32.58             | 36.59                 | 11.79           | 31.78                    | 49.18          | 74.00               | -24.82          | Horizontal   |
| 9920.00         | 29.97             | 38.81                 | 14.38           | 31.88                    | 51.28          | 74.00               | -22.72          | Horizontal   |
| 12400.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 14880.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |

## Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4960.00         | 25.08             | 31.93                 | 8.73            | 32.16                    | 33.58          | 54.00               | -20.42          | Vertical     |
| 7440.00         | 19.81             | 36.59                 | 11.79           | 31.78                    | 36.41          | 54.00               | -17.59          | Vertical     |
| 9920.00         | 18.97             | 38.81                 | 14.38           | 31.88                    | 40.28          | 54.00               | -13.72          | Vertical     |
| 12400.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 14880.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 4960.00         | 29.17             | 31.93                 | 8.73            | 32.16                    | 37.67          | 54.00               | -16.33          | Horizontal   |
| 7440.00         | 21.90             | 36.59                 | 11.79           | 31.78                    | 38.50          | 54.00               | -15.50          | Horizontal   |
| 9920.00         | 18.59             | 38.81                 | 14.38           | 31.88                    | 39.90          | 54.00               | -14.10          | Horizontal   |
| 12400.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 14880.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |

## Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “\*”, means this data is the too weak instrument of signal is unable to test.

## 7.2.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

GFSK mode


|               |                |
|---------------|----------------|
| Test channel: | Lowest channel |
| Polarization  | Horizontal     |



Site : 3m chamber  
Condition: FCC PART 15 (PK) 3m HORIZONTAL  
Remark : GFSK 2402MHz

|   | Freq     | Read<br>Level | Antenna<br>Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit<br>Line | Over<br>Limit | Remark  |
|---|----------|---------------|-------------------|---------------|------------------|--------|---------------|---------------|---------|
|   | MHz      | dBuV          | dB/m              | dB            | dB               | dBuV/m | dBuV/m        | dB            |         |
| 1 | 2310.000 | 25.58         | 27.91             | 5.30          | 36.64            | 22.15  | 54.00         | -31.85        | Average |
| 2 | 2310.000 | 34.37         | 27.91             | 5.30          | 36.64            | 30.94  | 74.00         | -43.06        | Peak    |
| 3 | 2390.000 | 25.71         | 27.59             | 5.38          | 36.71            | 21.97  | 54.00         | -32.03        | Average |
| 4 | 2390.000 | 33.55         | 27.59             | 5.38          | 36.71            | 29.81  | 74.00         | -44.19        | Peak    |
| 5 | 2400.000 | 35.99         | 27.58             | 5.39          | 36.71            | 32.25  | 54.00         | -21.75        | Average |
| 6 | 2400.000 | 44.10         | 27.58             | 5.39          | 36.71            | 40.36  | 74.00         | -33.64        | Peak    |


|               |                |
|---------------|----------------|
| Test channel: | Lowest channel |
| Polarization  | Vertical       |



Site : 3m chamber  
Condition: FCC PART 15 (PK) 3m VERTICAL  
Remark : GFSK 2402MHz

|   | Freq     | ReadAntenna<br>Level | Antenna<br>Factor | Cable<br>Loss | Preamp<br>Factor | Level  | Limit  | Over   | Remark  |
|---|----------|----------------------|-------------------|---------------|------------------|--------|--------|--------|---------|
|   | MHz      | dBuV                 | dB/m              | dB            | dB               | dBuV/m | dBuV/m | dB     |         |
| 1 | 2310.000 | 25.00                | 27.91             | 5.30          | 36.64            | 21.57  | 54.00  | -32.43 | Average |
| 2 | 2310.000 | 34.45                | 27.91             | 5.30          | 36.64            | 31.02  | 74.00  | -42.98 | Peak    |
| 3 | 2390.000 | 25.72                | 27.59             | 5.38          | 36.71            | 21.98  | 54.00  | -32.02 | Average |
| 4 | 2390.000 | 34.83                | 27.59             | 5.38          | 36.71            | 31.09  | 74.00  | -42.91 | Peak    |
| 5 | 2400.000 | 30.46                | 27.58             | 5.39          | 36.71            | 26.72  | 54.00  | -27.28 | Average |
| 6 | 2400.000 | 38.19                | 27.58             | 5.39          | 36.71            | 34.45  | 74.00  | -39.55 | Peak    |


|               |                 |
|---------------|-----------------|
| Test channel: | Highest channel |
| Polarization  | Horizontal      |



Site : 3m chamber  
Condition: FCC PART 15 (PK) 3m HORIZONTAL  
Remark : 2480MHz

|      | Read     | Antenna | Cable | Preamp | Limit  | Over   |                      |
|------|----------|---------|-------|--------|--------|--------|----------------------|
| Freq | Level    | Factor  | Loss  | Factor | Line   | Limit  | Remark               |
| MHz  | dBuV     | dB/m    | dB    | dB     | dBuV/m | dBuV/m | dB                   |
| 1    | 2483.500 | 25.86   | 27.53 | 5.47   | 36.78  | 22.08  | 54.00 -31.92 Average |
| 2    | 2483.500 | 34.61   | 27.53 | 5.47   | 36.78  | 30.83  | 74.00 -43.17 Peak    |
| 3    | 2500.000 | 25.55   | 27.55 | 5.49   | 36.79  | 21.80  | 54.00 -32.20 Average |
| 4    | 2500.000 | 33.69   | 27.55 | 5.49   | 36.79  | 29.94  | 74.00 -44.06 Peak    |

|               |                 |
|---------------|-----------------|
| Test channel: | Highest channel |
| Polarization  | Vertical        |




Site : 3m chamber  
Condition: FCC PART 15 (PK) 3m VERTICAL  
Remark : 2480MHz

|   | Freq     | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Level  | Limit  | Over Limit | Remark  |
|---|----------|------------|----------------|------------|---------------|--------|--------|------------|---------|
|   | MHz      | dBuV       | dB/m           | dB         | dB            | dBuV/m | dBuV/m | dB         |         |
| 1 | 2483.500 | 23.75      | 27.53          | 5.47       | 36.78         | 19.97  | 54.00  | -34.03     | Average |
| 2 | 2483.500 | 32.35      | 27.53          | 5.47       | 36.78         | 28.57  | 74.00  | -45.43     | Peak    |
| 3 | 2500.000 | 23.98      | 27.55          | 5.49       | 36.79         | 20.23  | 54.00  | -33.77     | Average |
| 4 | 2500.000 | 32.83      | 27.55          | 5.49       | 36.79         | 29.08  | 74.00  | -44.92     | Peak    |

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor  
RBW 1MHz, VBW 3MHz, peak detector for PK value, RBW 1MHz, VBW 10Hz AV detector for AV value


## 7.3 20dB Occupy Bandwidth

|                   |                                                                                                                                                                                                                                                                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.249/15.215                                                                                                                                                                                                                                                                                                                         |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                           |
| Limit:            | Operation Frequency range 2400MHz~2483.5MHz                                                                                                                                                                                                                                                                                                                |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                           |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                           |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                       |


### Measurement Data

| Test channel | 20dB bandwidth(MHz) | Result |
|--------------|---------------------|--------|
| Lowest       | 0.872               | Pass   |
| Middle       | 0.863               | Pass   |
| Highest      | 0.861               | Pass   |


Test plot as follows:



Lowest channel




Middle channel



Highest channel


## 8 Test Setup Photo


Radiated Emission






## 9 EUT Constructional Details




































-----End-----