

RF EXPOSURE REPORT



Report No.: 17021528-FCC-H1

Supersede Report No.: N/A

Applicant	Zhejiang VALUE Mechanical & Electrical Products CO.,LTD	
Product Name	Handheld device	
Model No.	H2	
Serial Model	H50, H1, H100, H3, H120	
Test Standard	FCC 2.1093	
Test Date	November 08 to November 13, 2017	
Issue Date	November 15, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Trety Lu Test Engineer	Deon Dai Engineer Reviewer	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:
SIEMIC (Nanjing-China) Laboratories
2-1 Longcang Avenue Yuhua Economic and
Technology Development Park, Nanjing, China
Tel:+86(25)86730128/86730129 Fax:+86(25)86730127 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17021528-FCC-H1
Page	3 of 7

This page has been left blank intentionally.

CONTENTS

1	REPORT REVISION HISTORY.....	5
2	CUSTOMER INFORMATION	5
3	TEST SITE INFORMATION.....	5
4	EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.....	7
5.1	RF EXPOSURE.....	7

1 Report Revision History

Report No.	Report Version	Description	Issue Date
17021528-FCC-H1	NONE	Original	November 15, 2017

2 Customer information

Applicant Name	Zhejiang VALUE Mechanical & Electrical Products CO.,LTD
Applicant Add	jiulong Avenue,Western Industrial District,Wenling,Zhejiang,China
Manufacturer	Zhejiang VALUE Mechanical & Electrical Products CO.,LTD
Manufacturer Add	jiulong Avenue,Western Industrial District,Wenling,Zhejiang,China

3 Test site information

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG

4 Equipment under Test (EUT) Information

Description of EUT:	Handheld device
Main Model:	H2
Serial Model:	H50, H1, H100, H3, H120
Date EUT received:	November 06, 2017
Test Date(s):	November 08 to November 13, 2017
Output power	BLE:0.702dBm
Antenna Gain:	BLE:0.5dBi
Type of Modulation:	BLE:GFSK
RF Operating Frequency (ies):	BLE:2402-2480 MHz
Number of Channels:	BLE:40CH
Port:	N/A
Input Power:	4*AAA(4*1.5V)
Trade Name :	N/A
FCC ID:	2ANTN0002

5 FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{GHz}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- f_{GHz} is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

2.4G Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-4.877	-5.5±1	-4.5	0.355	0.110	3
	Mid	2440	-2.560	-3.5±1	-2.5	0.562	0.176	3
	High	2480	-0.702	-1.5±1	-0.5	0.891	0.281	3

Result: Pass