



Radio Test Report

Report No.: STS2601074W07

Issued for

Stanley Black & Decker, Inc.

New Britain Design Center, 600 Myrtle Street, New Britain, CT
06053 USA

Product Name: ADV2 DIAGNOSTIC SCAN TOOL

Brand Name:



Model Name: ET9150

Series Model(s): N/A

FCC ID: 2ANWFET9150

Test Standards: FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name: Stanley Black & Decker, Inc.
Address: New Britain Design Center, 600 Myrtle Street, New Britain, CT 06053
USA
Manufacturer's Name: Stanley Black & Decker, Inc.
Address: New Britain Design Center, 600 Myrtle Street, New Britain, CT 06053
USA

Product Description

Product Name: ADV2 DIAGNOSTIC SCAN TOOL

Brand Name:



Model Name: ET9150

Series Model(s): N/A

Test Standards: FCC Part 15.247

Test Procedure: ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item: 09 Jan. 2026

Date (s) of performance of tests: 09 Jan. 2026 ~ 29 Jan. 2026

Date of Issue: 29 Jan. 2026

Test Result: **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)



**Table of Contents****Page**

1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	10
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 RADIATED EMISSION MEASUREMENT	18
4. DUTY CYCLE	41
4.1 TEST STANDARD	41
4.2 TEST PROCEDURE	41
4.3 DEVIATION FROM STANDARD	41
4.4 TEST SETUP	41
4.6 TEST RESULTS	41
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION	42
5.1 LIMIT	42
5.2 TEST PROCEDURE	42
5.3 DEVIATION FROM STANDARD	42
5.4 TEST SETUP	42
5.5 EUT OPERATION CONDITIONS	42
5.6 TEST RESULTS	42
6. POWER SPECTRAL DENSITY TEST	43
6.1 LIMIT	43
6.2 TEST PROCEDURE	43
6.3 DEVIATION FROM STANDARD	43
6.4 TEST SETUP	43
6.5 EUT OPERATION CONDITIONS	43
6.6 TEST RESULTS	43



Table of Contents	Page
7. BANDWIDTH TEST	44
6.1 LIMIT	44
7.2 TEST PROCEDURE	44
7.3 DEVIATION FROM STANDARD	44
7.4 TEST SETUP	44
7.5 EUT OPERATION CONDITIONS	44
7.6 TEST RESULTS	44
8. PEAK OUTPUT POWER TEST	45
8.1 LIMIT	45
8.2 TEST PROCEDURE	45
8.3 DEVIATION FROM STANDARD	45
8.4 TEST SETUP	45
8.5 EUT OPERATION CONDITIONS	45
8.6 TEST RESULTS	45
9. ANTENNA REQUIREMENT	46
9.1 STANDARD REQUIREMENT	46
9.2 EUT ANTENNA	46
APPENDIX 1-TEST DATA	47
DUTY CYCLE	47
MAXIMUM PEAK CONDUCTED OUTPUT POWER	54
-6DB BANDWIDTH	55
MAXIMUM POWER SPECTRAL DENSITY LEVEL	62
BAND EDGE	69
CONDUCTED RF SPURIOUS EMISSION	78
APPENDIX 2-PHOTOS OF TEST SETUP	91



Rev.	Issue Date	Report No.	Effect Page	Contents
00	29 Jan. 2026	STS2601074W07	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/ part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.751\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.888\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.48\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 2.52\text{dB}$
5	All emissions, radiated 1G-18GHz	$\pm 3.48\text{dB}$
6	All emissions, radiated >18GHz	$\pm 4.18\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.48\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.52\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.6\%$
10	Power Spectral Density, conducted	$\pm 1.214\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	ADV2 DIAGNOSTIC SCAN TOOL	
Brand Name		
Model Name	ET9150	
Series Model(s)	N/A	
Model Difference	N/A	
Product Description	The EUT is a ADV2 DIAGNOSTIC SCAN TOOL	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz 802.11n 40:2422~2452MHz
	Modulation Type:	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz): 65/58.5/52/39/26/19.5/13/6.5Mbps 802.11n(40MHz): 135/121.5/108/81/54/40.5/37/13.5Mbps
	Number of Channel:	802.11b/g/n 20: 11CH 802.11n 40: 7CH
	Antenna Type:	FPC
	Antenna Gain (dBi):	3.28
Channel List	Please refer to the Note 3.	
Power Rating	Input: 15VDC, 3A	
Adapter	Model: XDJ481R-PDG Brand: N/A Input: 100-240V~, 50/60Hz, 1.8A Output: 15Vdc, 3A, 45W	
Battery	Model: CLP606070-2S2P Brand: N/A Rated Voltage: 7.6V Charge Limit Voltage: 8.7V Capacity: 7000mAh	
Hardware version number	N/A	
Software version number	N/A	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.



2. The antenna details in this report are based on the manufacturer provided antenna specification documents and apply only to the tested sample identified herein.
Any discrepancies in the antenna information may affect the accuracy of the test results, and the customer assumes responsibility for any related issues.

3.

Operation Frequency of channel			
802.11b/g/n(20MHz)		Channel List for 802.11n(40MHz)	
Channel	Frequency	Channel	Frequency
01	2412	03	2422
02	2417	04	2427
03	2422	05	2432
04	2427	06	2437
05	2432	07	2442
06	2437	08	2447
07	2442	09	2452
08	2447		
09	2452		
10	2457		
11	2462		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n (HT20)		For 802.11n (HT40)	
Channel	Freq.(MHz)	Channel	Freq.(MHz)
01	2412	03	2422
06	2437	06	2437
11	2462	09	2452



2.2 DESCRIPTION OF THE TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0
Mode 10	TX IEEE 802.11n HT40 CH3	MCS 0
Mode 11	TX IEEE 802.11n HT40 CH6	MCS 0
Mode 12	TX IEEE 802.11n HT40 CH9	MCS 0

Note:

- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
- (2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V /60Hz is shown in the report.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode13: Keeping WIFI TX

2.3 TEST SOFTWARE AND POWER LEVEL


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(2.4G)	2.4G WIFI	802.11b	3.28	14	Engineering mode
		802.11g		13	
		802.11n(HT20)		13.5	
		802.11n(HT40)		13	




2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiation Test Set



Conduction Test Set



RF Conduction Test Set





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Adapter	N/A	XDJ481R-PDG	N/A

Item	Equipment	Mfr/Brand	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Pre-Amplifier(0.1M-3 GHz)	EM	EM330	060665	2025.02.22	2026.02.21
Pre-Amplifier(1G-18G Hz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18G-40 GHz)	SKET	LNPA_1840-50	SK2018101801	2025.02.22	2026.02.21
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2027.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBEC K	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Band 2.4G-2.5G Filter	HX MICROWAVE	HXLBQ-DZA61	N/A	2025.09.23	2026.09.22
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENG FENG	DPS-305AF	17064939	2025.09.22	2026.09.21
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2025.09.25	2026.09.24
Limiter	CYBERTEK	EM5010	N/A	2025.09.25	2026.09.24
LISN	R&S	ENV216	101242	2025.09.25	2026.09.24
LISN	EMCO	3810/2NM	23625	2025.09.25	2026.09.24
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2025.02.22	2026.02.21
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
Pulse Power Sensor	Anritsu	MA2411B	917389	2025.09.23	2026.09.22
Power Meter	Anritsu	ML2480	1005127	2025.09.23	2026.09.22
Temperature& Humidity test chamber	Safety test	AG80L	171200018	2025.02.22	2026.02.21
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	MW	MTS 8310_2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.5 TEST RESULT

Temperature:	25.1°C	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.9020	24.01	19.40	43.41	56.00	-12.59	QP
2	0.9020	11.43	19.40	30.83	46.00	-15.17	AVG
3	1.1860	24.06	19.39	43.45	56.00	-12.55	QP
4	1.1860	10.97	19.39	30.36	46.00	-15.64	AVG
5	1.8820	23.42	19.38	42.80	56.00	-13.20	QP
6	1.8820	10.67	19.38	30.05	46.00	-15.95	AVG
7	3.2580	24.35	19.46	43.81	56.00	-12.19	QP
8	3.2580	14.02	19.46	33.48	46.00	-12.52	AVG
9	9.0580	27.17	19.61	46.78	60.00	-13.22	QP
10	9.0580	18.23	19.61	37.84	50.00	-12.16	AVG
11	18.2140	27.82	19.90	47.72	60.00	-12.28	QP
12	18.2140	17.74	19.90	37.64	50.00	-12.36	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)






Temperature:	25.1℃	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 13		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2140	23.31	19.37	42.68	63.05	-20.37	QP
2	0.2140	14.08	19.37	33.45	53.05	-19.60	AVG
3	0.4980	18.31	19.34	37.65	56.03	-18.38	QP
4	0.4980	6.20	19.34	25.54	46.03	-20.49	AVG
5	0.9100	19.97	19.40	39.37	56.00	-16.63	QP
6	0.9100	7.19	19.40	26.59	46.00	-19.41	AVG
7	1.2220	19.71	19.39	39.10	56.00	-16.90	QP
8	1.2220	5.86	19.39	25.25	46.00	-20.75	AVG
9	2.0660	19.25	19.38	38.63	56.00	-17.37	QP
10	2.0660	6.10	19.38	25.48	46.00	-20.52	AVG
11	7.9780	28.72	19.52	48.24	60.00	-11.76	QP
12	7.9780	22.38	19.52	41.90	50.00	-8.10	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2430 MHz Upper Band Edge: 2445 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested with a band-stop filter and performed pretest to three orthogonal axis. The worst-case emissions were reported.

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.



3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



3.2.6 TEST RESULT

9KHz-30MHz

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Polarization:	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



(30MHz - 1000MHz)


n20

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	182.2900	47.90	-20.19	27.71	43.50	-15.79	peak
2	261.8300	40.62	-14.77	25.85	46.00	-20.15	peak
3	327.7900	39.25	-13.77	25.48	46.00	-20.52	peak
4	472.3200	35.06	-8.92	26.14	46.00	-19.86	peak
5	733.2500	32.00	-2.35	29.65	46.00	-16.35	peak
6	901.0600	31.60	-0.43	31.17	46.00	-14.83	peak

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.






Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.6380	45.86	-13.18	32.68	40.00	-7.32	peak
2	131.8500	47.38	-18.20	29.18	43.50	-14.32	peak
3	154.1600	47.14	-18.60	28.54	43.50	-14.96	peak
4	246.3100	39.29	-16.76	22.53	46.00	-23.47	peak
5	589.6900	30.67	-5.83	24.84	46.00	-21.16	peak
6	980.6000	27.96	2.63	30.59	54.00	-23.41	peak

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.





n40

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	180.3500	48.41	-20.04	28.37	43.50	-15.13	peak
2	261.8300	41.46	-14.77	26.69	46.00	-19.31	peak
3	327.7900	41.44	-13.77	27.67	46.00	-18.33	peak
4	472.3200	34.75	-8.92	25.83	46.00	-20.17	peak
5	733.2500	30.98	-2.35	28.63	46.00	-17.37	peak
6	901.0600	40.43	-0.43	40.00	46.00	-6.00	peak


Remark:

4. Margin = Result (Result =Reading + Factor)-Limit

5. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain

6. All modes have been tested,only show the worst case.

80.0 dBuV/m






Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.5306	43.42	-13.12	30.30	40.00	-9.70	peak
2	133.7900	46.02	-18.14	27.88	43.50	-15.62	peak
3	154.1600	47.46	-18.60	28.86	43.50	-14.64	peak
4	260.8600	38.71	-14.78	23.93	46.00	-22.07	peak
5	576.1100	29.57	-5.70	23.87	46.00	-22.13	peak
6	897.1800	39.37	-0.52	38.85	46.00	-7.15	peak

Remark:

- Margin = Result (Result = Reading + Factor) - Limit
- Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain
- All modes have been tested, only show the worst case.

80.0 dBuV/m





(1GHz-25GHz) Spurious emission Requirements

Horizontal


Low Channel (802.11n20/2412 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1777.00	41.13	-0.65	74	-32.87	Peak	249.5	Horizontal	Pass
1777.00	35.71	-0.65	54	-18.29	AV	249.5	Horizontal	Pass
2492.50	51.56	3.16	74	-22.44	Peak	171.8	Horizontal	Pass
2492.50	37.18	3.16	54	-16.82	AV	171.8	Horizontal	Pass
6977.00	50.71	1.13	74	-23.29	Peak	147.5	Horizontal	Pass
6977.00	39.99	1.13	54	-14.01	AV	147.5	Horizontal	Pass
10660.25	52.11	1.42	74	-21.89	Peak	75.5	Horizontal	Pass
10660.25	41.52	1.42	54	-12.48	AV	75.5	Horizontal	Pass
14191.25	56.40	6.95	74	-17.60	Peak	358.7	Horizontal	Pass
14191.25	45.54	6.95	54	-8.46	AV	358.7	Horizontal	Pass
17337.25	55.66	6.45	74	-18.34	Peak	261.7	Horizontal	Pass
17337.25	44.40	6.45	54	-9.60	AV	261.7	Horizontal	Pass
Middle Channel (802.11n20/2437 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1776.68	40.36	-0.72	74.00	-33.64	Peak	264.25	Horizontal	Pass
1776.68	34.13	-0.72	54.00	-19.87	AV	264.25	Horizontal	Pass
2492.29	50.87	3.12	74.00	-23.13	Peak	180.38	Horizontal	Pass
2492.29	35.43	3.12	54.00	-18.57	AV	180.38	Horizontal	Pass
6976.73	49.24	1.10	74.00	-24.76	Peak	153.61	Horizontal	Pass
6976.73	38.95	1.10	54.00	-15.05	AV	153.61	Horizontal	Pass
10659.94	51.24	1.39	74.00	-22.76	Peak	92.63	Horizontal	Pass
10659.94	40.21	1.39	54.00	-13.79	AV	92.63	Horizontal	Pass
14190.79	55.80	6.91	74.00	-18.20	Peak	380.41	Horizontal	Pass
14190.79	43.93	6.91	54.00	-10.07	AV	380.41	Horizontal	Pass
17336.93	55.13	6.42	74.00	-18.87	Peak	277.15	Horizontal	Pass
17336.93	43.00	6.42	54.00	-11.00	AV	277.15	Horizontal	Pass



High Channel (802.11n20/2462 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1776.47	39.56	-0.79	74.00	-34.44	Peak	276.50	Horizontal	Pass
1776.47	32.78	-0.79	54.00	-21.22	AV	276.50	Horizontal	Pass
2492.00	49.67	3.07	74.00	-24.33	Peak	193.83	Horizontal	Pass
2492.00	34.33	3.07	54.00	-19.67	AV	193.83	Horizontal	Pass
6976.41	47.91	1.08	74.00	-26.09	Peak	171.16	Horizontal	Pass
6976.41	38.01	1.08	54.00	-15.99	AV	171.16	Horizontal	Pass
10659.45	49.83	1.37	74.00	-24.17	Peak	111.53	Horizontal	Pass
10659.45	38.38	1.37	54.00	-15.62	AV	111.53	Horizontal	Pass
14190.31	54.31	6.87	74.00	-19.69	Peak	396.45	Horizontal	Pass
14190.31	42.89	6.87	54.00	-11.11	AV	396.45	Horizontal	Pass
17336.64	53.64	6.38	74.00	-20.36	Peak	300.38	Horizontal	Pass
17336.64	41.23	6.38	54.00	-12.77	AV	300.38	Horizontal	Pass


n20
RSE-1G-18G-H

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G






RSE-18G-26G-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19392.000	50.60	1.54	52.14	74.00	-21.86	peak
2	20304.000	50.14	2.06	52.20	74.00	-21.80	peak
3	21576.000	49.81	3.01	52.82	74.00	-21.18	peak
4	23280.000	48.51	3.92	52.43	74.00	-21.57	peak
5	24304.000	46.86	4.69	51.55	74.00	-22.45	peak
6	25264.000	47.31	5.48	52.79	74.00	-21.21	peak




RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G



RSE-18G-26G-H

100.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18928.000	50.56	1.82	52.38	74.00	-21.62	peak
2	20088.000	50.77	1.88	52.65	74.00	-21.35	peak
3	21040.000	49.14	2.69	51.83	74.00	-22.17	peak
4	22584.000	47.87	3.87	51.74	74.00	-22.26	peak
5	24080.000	47.18	4.65	51.83	74.00	-22.17	peak
6	25144.000	46.78	5.41	52.19	74.00	-21.81	peak




Low Channel (802.11n20/2412 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1760.00	41.17	-0.57	74	-32.83	Peak	51.6	Vertical	Pass
1760.00	29.87	-0.57	54	-24.13	AV	51.6	Vertical	Pass
2493.50	51.98	3.15	74	-22.02	Peak	33.3	Vertical	Pass
2493.50	37.52	3.15	54	-16.48	AV	33.3	Vertical	Pass
6998.00	51.30	1.30	74	-22.70	Peak	150.1	Vertical	Pass
6998.00	40.28	1.30	54	-13.72	AV	150.1	Vertical	Pass
10982.00	52.93	1.77	74	-21.07	Peak	353.2	Vertical	Pass
10982.00	41.48	1.77	54	-12.52	AV	353.2	Vertical	Pass
14191.25	57.18	6.95	74	-16.82	Peak	273.3	Vertical	Pass
14191.25	45.80	6.95	54	-8.20	AV	273.3	Vertical	Pass
17879.00	55.97	7.06	74	-18.03	Peak	5.4	Vertical	Pass
17879.00	45.22	7.06	54	-8.78	AV	5.4	Vertical	Pass
Middle Channel (802.11n20/2437 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1759.65	39.22	-0.63	74.00	-34.78	Peak	63.63	Vertical	Pass
1759.65	29.32	-0.63	54.00	-24.68	AV	63.63	Vertical	Pass
2493.14	50.49	3.10	74.00	-23.51	Peak	40.44	Vertical	Pass
2493.14	36.49	3.10	54.00	-17.51	AV	40.44	Vertical	Pass
6997.51	50.25	1.27	74.00	-23.75	Peak	169.57	Vertical	Pass
6997.51	38.34	1.27	54.00	-15.66	AV	169.57	Vertical	Pass
10981.64	51.55	1.75	74.00	-22.45	Peak	370.55	Vertical	Pass
10981.64	40.91	1.75	54.00	-13.09	AV	370.55	Vertical	Pass
14190.87	55.29	6.91	74.00	-18.71	Peak	287.11	Vertical	Pass
14190.87	44.50	6.91	54.00	-9.50	AV	287.11	Vertical	Pass
17878.73	55.36	7.03	74.00	-18.64	Peak	27.59	Vertical	Pass
17878.73	44.11	7.03	54.00	-9.89	AV	27.59	Vertical	Pass



High Channel (802.11n20/2462 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1759.18	37.88	-0.69	74.00	-36.12	Peak	78.93	Vertical	Pass
1759.18	28.57	-0.69	54.00	-25.43	AV	78.93	Vertical	Pass
2492.75	48.63	3.07	74.00	-25.37	Peak	58.97	Vertical	Pass
2492.75	35.88	3.07	54.00	-18.12	AV	58.97	Vertical	Pass
6997.20	48.91	1.24	74.00	-25.09	Peak	183.78	Vertical	Pass
6997.20	36.65	1.24	54.00	-17.35	AV	183.78	Vertical	Pass
10981.28	50.55	1.70	74.00	-23.45	Peak	387.85	Vertical	Pass
10981.28	39.73	1.70	54.00	-14.27	AV	387.85	Vertical	Pass
14190.50	54.17	6.87	74.00	-19.83	Peak	299.45	Vertical	Pass
14190.50	43.37	6.87	54.00	-10.63	AV	299.45	Vertical	Pass
17878.46	53.81	6.98	74.00	-20.19	Peak	57.07	Vertical	Pass
17878.46	42.91	6.98	54.00	-11.09	AV	57.07	Vertical	Pass


n20
RSE-1G-18G-V

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





RSE-18G-26G-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18936.000	50.28	1.81	52.09	74.00	-21.91	peak
2	20752.000	50.05	2.44	52.49	74.00	-21.51	peak
3	21576.000	49.29	3.01	52.30	74.00	-21.70	peak
4	22912.000	48.52	3.68	52.20	74.00	-21.80	peak
5	24224.000	47.44	4.66	52.10	74.00	-21.90	peak
6	25264.000	46.48	5.48	51.96	74.00	-22.04	peak




N40

RSE-1G-18G-V

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19120.000	50.45	1.68	52.13	74.00	-21.87	peak
2	19872.000	50.62	1.72	52.34	74.00	-21.66	peak
3	21040.000	49.44	2.69	52.13	74.00	-21.87	peak
4	22056.000	48.84	3.47	52.31	74.00	-21.69	peak
5	23936.000	46.81	4.57	51.38	74.00	-22.62	peak
6	24944.000	46.22	5.23	51.45	74.00	-22.55	peak

Note:


- 1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor.
- 2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



3.2.6 TEST RESULTS(Band edge Requirements)


802.11 n20-Low Channel

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.120	50.82	0.79	51.61	54.00	-2.39	peak
2	2390.000	51.87	0.81	52.68	54.00	-1.32	peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.480	49.91	0.80	50.71	54.00	-3.29	peak
2	2390.000	51.14	0.81	51.95	54.00	-2.05	peak




High Channel

Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	54.33	1.02	55.35	74.00	-18.65	peak
2	2483.500	46.91	1.02	47.93	54.00	-6.07	AVG
3	2485.470	54.88	1.02	55.90	74.00	-18.10	peak
4	2485.470	45.21	1.02	46.23	54.00	-7.77	AVG

Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	59.11	1.02	60.13	74.00	-13.87	peak
2	2483.500	47.05	1.02	48.07	54.00	-5.93	AVG
3	2484.995	56.94	1.03	57.97	74.00	-16.03	peak
4	2484.995	45.69	1.03	46.72	54.00	-7.28	AVG




802.11 n40-Low Channel

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.840	59.06	0.79	59.85	74.00	-14.15	peak
2	2387.840	36.04	0.79	36.83	54.00	-17.17	AVG
3	2390.000	59.07	0.81	59.88	74.00	-14.12	peak
4	2390.000	36.63	0.81	37.44	54.00	-16.56	AVG

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2386.860	57.35	0.79	58.14	74.00	-15.86	peak
2	2386.860	32.97	0.79	33.76	54.00	-20.24	AVG
3	2390.000	57.91	0.81	58.72	74.00	-15.28	peak
4	2390.000	34.88	0.81	35.69	54.00	-18.31	AVG



High Channel

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	65.37	1.02	66.39	74.00	-7.61	peak
2	2483.500	37.39	1.02	38.41	54.00	-15.59	AVG
3	2486.250	64.11	1.02	65.13	74.00	-8.87	peak
4	2486.250	36.34	1.02	37.36	54.00	-16.64	AVG

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	64.71	1.02	65.73	74.00	-8.27	peak
2	2483.500	38.92	1.02	39.94	54.00	-14.06	AVG
3	2485.375	64.46	1.02	65.48	74.00	-8.52	peak
4	2485.375	37.29	1.02	38.31	54.00	-15.69	AVG

Note: All modes have been measurement, only worst mode was reported.



4. DUTY CYCLE

4.1 TEST STANDARD

Please refer to ANSI C63.10-2020 Section 11.6

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Zero
RB	set RBW to the largest available value
VB	$VBW \geq RBW$.
Detector	Peak
Trace	Clear Write
Sweep Time	Auto

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

4.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

5.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

5.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



6. POWER SPECTRAL DENSITY TEST

6.1 LIMIT

FCC Part15.247 , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

6.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



7. BANDWIDTH TEST

6.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW =1% to 5% of the OBW but not less than 100 kHz., VBW $\geq$ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

7.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



8. PEAK OUTPUT POWER TEST

8.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE


PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

8.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA


The EUT antenna is FPC Antenna. It comply with the standard requirement.



APPENDIX 1-TEST DATA

Duty Cycle

Condition	Mode	Frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	8.384	8.408	99.71	0.01	0.12
NVNT	b	2437	8.384	8.416	99.62	0.02	0.12
NVNT	b	2462	8.384	8.416	99.62	0.02	0.12
NVNT	g	2412	1.395	1.428	97.69	0.1	0.72
NVNT	g	2437	1.392	1.428	97.48	0.11	0.72
NVNT	g	2462	1.392	1.428	97.48	0.11	0.72
NVNT	n20	2412	1.3	1.336	97.31	0.12	0.77
NVNT	n20	2437	1.302	1.336	97.46	0.11	0.77
NVNT	n20	2462	1.3	1.336	97.31	0.12	0.77
NVNT	n40	2422	0.648	0.683	94.88	0.23	1.54
NVNT	n40	2437	0.648	0.683	94.88	0.23	1.54
NVNT	n40	2452	0.648	0.683	94.88	0.23	1.54


Test Graphs
Duty Cycle NVNT b 2412MHz

Duty Cycle NVNT b 2437MHz






Duty Cycle NVNT b 2462MHz




Duty Cycle NVNT g 2412MHz






Duty Cycle NVNT g 2437MHz




Duty Cycle NVNT g 2462MHz






Duty Cycle NVNT n20 2412MHz




Duty Cycle NVNT n20 2437MHz






Duty Cycle NVNT n20 2462MHz




Duty Cycle NVNT n40 2422MHz






Duty Cycle NVNT n40 2437MHz



Duty Cycle NVNT n40 2452MHz





Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	17.62	<=30	Pass
NVNT	b	2437	17.7	<=30	Pass
NVNT	b	2462	17.49	<=30	Pass
NVNT	g	2412	17.6	<=30	Pass
NVNT	g	2437	17.81	<=30	Pass
NVNT	g	2462	17.59	<=30	Pass
NVNT	n20	2412	18.18	<=30	Pass
NVNT	n20	2437	18.17	<=30	Pass
NVNT	n20	2462	17.91	<=30	Pass
NVNT	n40	2422	17.96	<=30	Pass
NVNT	n40	2437	17.84	<=30	Pass
NVNT	n40	2452	17.77	<=30	Pass

**-6dB Bandwidth**

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	8.118	≥ 0.5	Pass
NVNT	b	2437	8.105	≥ 0.5	Pass
NVNT	b	2462	8.071	≥ 0.5	Pass
NVNT	g	2412	15.94	≥ 0.5	Pass
NVNT	g	2437	16.13	≥ 0.5	Pass
NVNT	g	2462	15.99	≥ 0.5	Pass
NVNT	n20	2412	17.17	≥ 0.5	Pass
NVNT	n20	2437	17.09	≥ 0.5	Pass
NVNT	n20	2462	17.14	≥ 0.5	Pass
NVNT	n40	2422	35.8	≥ 0.5	Pass
NVNT	n40	2437	35.62	≥ 0.5	Pass
NVNT	n40	2452	36.08	≥ 0.5	Pass



Test Graphs

-6dB Bandwidth NVNT b 2412MHz




-6dB Bandwidth NVNT b 2437MHz





-6dB Bandwidth NVNT b 2462MHz



-6dB Bandwidth NVNT g 2412MHz





-6dB Bandwidth NVNT g 2437MHz



-6dB Bandwidth NVNT g 2462MHz





-6dB Bandwidth NVNT n20 2412MHz



-6dB Bandwidth NVNT n20 2437MHz





-6dB Bandwidth NVNT n20 2462MHz



-6dB Bandwidth NVNT n40 2422MHz





-6dB Bandwidth NVNT n40 2437MHz



-6dB Bandwidth NVNT n40 2452MHz





Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	-9.39	≤ -8	Pass
NVNT	b	2437	-9.81	≤ -8	Pass
NVNT	b	2462	-9.36	≤ -8	Pass
NVNT	g	2412	-12.12	≤ -8	Pass
NVNT	g	2437	-13.22	≤ -8	Pass
NVNT	g	2462	-13.05	≤ -8	Pass
NVNT	n20	2412	-11.07	≤ -8	Pass
NVNT	n20	2437	-11.74	≤ -8	Pass
NVNT	n20	2462	-11.65	≤ -8	Pass
NVNT	n40	2422	-14.67	≤ -8	Pass
NVNT	n40	2437	-14.86	≤ -8	Pass
NVNT	n40	2452	-14.98	≤ -8	Pass

Test Graphs
PSD NVNT b 2412MHz

PSD NVNT b 2437MHz





PSD NVNT b 2462MHz




PSD NVNT g 2412MHz





PSD NVNT g 2437MHz



PSD NVNT g 2462MHz





PSD NVNT n20 2412MHz




PSD NVNT n20 2437MHz





PSD NVNT n20 2462MHz



PSD NVNT n40 2422MHz






PSD NVNT n40 2437MHz



PSD NVNT n40 2452MHz





Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-53.2	<=-20	Pass
NVNT	b	2462	-58.57	<=-20	Pass
NVNT	g	2412	-41.6	<=-20	Pass
NVNT	g	2462	-52.9	<=-20	Pass
NVNT	n20	2412	-39.79	<=-20	Pass
NVNT	n20	2462	-50.11	<=-20	Pass
NVNT	n40	2422	-40.08	<=-20	Pass
NVNT	n40	2452	-39.96	<=-20	Pass



Test Graphs

Band Edge NVNT b 2412MHz Ref



Band Edge NVNT b 2412MHz Emission





Band Edge NVNT b 2462MHz Ref



Band Edge NVNT b 2462MHz Emission





Band Edge NVNT g 2412MHz Ref



Band Edge NVNT g 2412MHz Emission





Band Edge NVNT g 2462MHz Ref



Band Edge NVNT g 2462MHz Emission





Band Edge NVNT n20 2412MHz Ref




Band Edge NVNT n20 2412MHz Emission





Band Edge NVNT n20 2462MHz Ref




Band Edge NVNT n20 2462MHz Emission






Band Edge NVNT n40 2422MHz Ref




Band Edge NVNT n40 2422MHz Emission






Band Edge NVNT n40 2452MHz Ref



Band Edge NVNT n40 2452MHz Emission





Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	-47.12	<=-20	Pass
NVNT	b	2437	-48.45	<=-20	Pass
NVNT	b	2462	-47.85	<=-20	Pass
NVNT	g	2412	-44.42	<=-20	Pass
NVNT	g	2437	-43.57	<=-20	Pass
NVNT	g	2462	-43.1	<=-20	Pass
NVNT	n20	2412	-44.03	<=-20	Pass
NVNT	n20	2437	-44.17	<=-20	Pass
NVNT	n20	2462	-44.77	<=-20	Pass
NVNT	n40	2422	-41.56	<=-20	Pass
NVNT	n40	2437	-42.15	<=-20	Pass
NVNT	n40	2452	-41.74	<=-20	Pass




Test Graphs

Tx. Spurious NVNT b 2412MHz Ref




Tx. Spurious NVNT b 2412MHz Emission






Tx. Spurious NVNT b 2437MHz Ref




Tx. Spurious NVNT b 2437MHz Emission






Tx. Spurious NVNT b 2462MHz Ref




Tx. Spurious NVNT b 2462MHz Emission






Tx. Spurious NVNT g 2412MHz Ref




Tx. Spurious NVNT g 2412MHz Emission






Tx. Spurious NVNT g 2437MHz Ref




Tx. Spurious NVNT g 2437MHz Emission






Tx. Spurious NVNT g 2462MHz Ref




Tx. Spurious NVNT g 2462MHz Emission






Tx. Spurious NVNT n20 2412MHz Ref




Tx. Spurious NVNT n20 2412MHz Emission






Tx. Spurious NVNT n20 2437MHz Ref




Tx. Spurious NVNT n20 2437MHz Emission






Tx. Spurious NVNT n20 2462MHz Ref




Tx. Spurious NVNT n20 2462MHz Emission






Tx. Spurious NVNT n40 2422MHz Ref




Tx. Spurious NVNT n40 2422MHz Emission






Tx. Spurious NVNT n40 2437MHz Ref




Tx. Spurious NVNT n40 2437MHz Emission






Tx. Spurious NVNT n40 2452MHz Ref



Tx. Spurious NVNT n40 2452MHz Emission





APPENDIX 2-PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※