



Radio Test Report

Report No.: STS2601074W06

Issued for

Stanley Black & Decker, Inc.

New Britain Design Center, 600 Myrtle Street, New Britain, CT
06053 USA

Product Name: ADV2 DIAGNOSTIC SCAN TOOL

Brand Name:



Model Name: ET9150

Series Model(s): N/A

FCC ID: 2ANWFET9150

Test Standards: FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name..... : Stanley Black & Decker, Inc.
Address : New Britain Design Center, 600 Myrtle Street, New Britain, CT 06053
USA
Manufacturer's Name : Stanley Black & Decker, Inc.
Address : New Britain Design Center, 600 Myrtle Street, New Britain, CT 06053
USA

Product Description

Product Name : ADV2 DIAGNOSTIC SCAN TOOL
Brand Name : 
Model Name : ET9150
Series Model(s) : N/A

Test Standards..... : FCC Part15.247

Test Procedure : ANSI C63.10-2020

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the IC requirements. And it is applicable only to the tested sample identified in the report.

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

Date of Test..... :


Date of receipt of test item : 09 Jan. 2026

Date (s) of performance of tests..... : 09 Jan. 2026 ~ 29 Jan. 2026

Date of Issue..... : 29 Jan. 2026

Test Result..... : **Pass**

Testing Engineer :




(Aaron Bu)

Technical Manager :



(Skylar Li)

Authorized Signatory :



(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	7
1.1 TEST FACTORY	8
1.2 MEASUREMENT UNCERTAINTY	8
2. GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF THE EUT	9
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	11
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	12
2.6 EQUIPMENTS LIST	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 TEST PROCEDURE	15
3.3 TEST SETUP	15
3.4 EUT OPERATING CONDITIONS	15
3.5 TEST RESULTS	16
4. RADIATED EMISSION MEASUREMENT	18
4.1 RADIATED EMISSION LIMITS	18
4.2 TEST PROCEDURE	20
4.3 TEST SETUP	21
4.4 EUT OPERATING CONDITIONS	22
4.5 FIELD STRENGTH CALCULATION	22
4.6 TEST RESULTS	23
5. DUTY CYCLE	47
5.1 TEST STANDARD	47
5.2 TEST PROCEDURE	47
5.3 DEVIATION FROM STANDARD	47
5.4 TEST SETUP	47
5.6 TEST RESULTS	47
6. CONDUCTED SPURIOUS & BAND EDGE EMISSION	48
6.1 LIMIT	48
6.2 TEST PROCEDURE	48



Table of Contents	Page
6.3 TEST SETUP	48
6.4 EUT OPERATION CONDITIONS	48
6.5 TEST RESULTS	48
7. POWER SPECTRAL DENSITY TEST	49
7.1 LIMIT	49
7.2 TEST PROCEDURE	49
7.3 TEST SETUP	49
7.4 EUT OPERATION CONDITIONS	49
7.5 TEST RESULTS	49
8. BANDWIDTH TEST	50
8.1 LIMIT	50
8.2 TEST PROCEDURE	50
8.3 TEST SETUP	50
8.4 EUT OPERATION CONDITIONS	50
8.5 TEST RESULTS	50
9. PEAK OUTPUT POWER TEST	51
9.1 LIMIT	51
9.2 TEST PROCEDURE	51
9.3 TEST SETUP	51
9.4 EUT OPERATION CONDITIONS	51
9.5 TEST RESULTS	51
10. ANTENNA REQUIREMENT	52
10.1 STANDARD REQUIREMENT	52
10.2 EUT ANTENNA	52
APPENDIX 1-TEST DATA	53
DUTY CYCLE	53
MAXIMUM PEAK CONDUCTED OUTPUT POWER	57
-6DB BANDWIDTH	61
MAXIMUM POWER SPECTRAL DENSITY LEVEL	65
BAND EDGE	69
CONDUCTED RF SPURIOUS EMISSION	74



Table of Contents

Page

APPENDIX 2- EUT TEST PHOTO

81

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	29 Jan. 2026	STS2601074W06	ALL	Initial Issue



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

Note:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2020.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.751\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.888\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.48\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 2.52\text{dB}$
5	All emissions, radiated 1G-18GHz	$\pm 3.48\text{dB}$
6	All emissions, radiated >18GHz	$\pm 4.18\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.48\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.52\text{dB}$
9	Occupied Channel Bandwidth	$\pm 3.6\%$
10	Power Spectral Density, conducted	$\pm 1.214\text{dB}$
11	Duty Cycle	$\pm 3.2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	ADV2 DIAGNOSTIC SCAN TOOL	
Brand Name		
Model Name	ET9150	
Series Model(s)	N/A	
Model Difference	N/A	
Product Description	The EUT is a ADV2 DIAGNOSTIC SCAN TOOL	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Configuration:	LE(Support 1M PHY, 2M PHY)
	Number Of Channel:	40
	Antenna Type:	FPC
	Antenna Gain (dBi)	3.28
Channel List	Please refer to the Note 3.	
Power Rating	Input: 15VDC, 3A	
Adapter	Model: XDJ481R-PDG Brand: N/A Input: 100-240V~, 50/60Hz, 1.8A Output: 15Vdc, 3A, 45W	
Battery	Model: CLP606070-2S2P Brand: N/A Rated Voltage: 7.6V Charge Limit Voltage: 8.7V Capacity: 7000mAh	
Hardware version number	N/A	
Software version number	N/A	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480

2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Worst Mode	Description	Data/Modulation
Mode 1	TX CH00(2402MHz)	1M PHY /GFSK
Mode 2	TX CH19(2440MHz)	1M PHY /GFSK
Mode 3	TX CH39(2480MHz)	1M PHY /GFSK

Worst Mode	Description	Data/Modulation
Mode 4	TX CH00(2402MHz)	2M PHY /GFSK
Mode 5	TX CH19(2440MHz)	2M PHY /GFSK
Mode 6	TX CH39(2480MHz)	2M PHY /GFSK

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

(2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/60Hz is shown in the report.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 7 : Keeping BT TX




2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
BLE	BLE-1M	GFSK	3.28	5	Engineering mode
	BLE-2M			5	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test



RF Conducted Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Note
E-1	Adapter	N/A	XDJ481R-PDG	N/A

Item	Equipment	Mfr/Brand	Length	Note

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Pre-Amplifier(0.1M-3GHz)	EM	EM330	060665	2025.02.22	2026.02.21
Pre-Amplifier(1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2025.09.25	2026.09.24
Pre-Amplifier(18G-40GHz)	SKET	LNPA_1840-50	SK2018101801	2025.02.22	2026.02.21
Active loop Antenna	ZHINAN	ZN30900C	16035	2025.02.25	2027.02.24
Bilog Antenna	TESEQ	CBL6111D	34678	2025.09.27	2027.09.26
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2025.09.27	2027.09.26
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2025.09.27	2027.09.26
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2025.09.26	2026.09.25
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Band 2.4G-2.5G Filter	HX MICROWAVE	HXLBQ-DZA61	N/A	2025.09.23	2026.09.22
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC power supply	HONGSHENGFE NG	DPS-305AF	17064939	2025.09.22	2026.09.21
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2025.09.25	2026.09.24
Limiter	CYBERTEK	EM5010	N/A	2025.09.25	2026.09.24
LISN	R&S	ENV216	101242	2025.09.25	2026.09.24
LISN	EMCO	3810/2NM	23625	2025.09.25	2026.09.24
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2025.02.22	2026.02.21
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
Temperature& Humidity test chamber	Safety test	AG80L	171200018	2025.02.22	2026.02.21
Temperature & Humidity	SW-108	SuWei	N/A	2025.02.24	2026.02.23
Test SW	MW	MTS 8310_2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “*” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.5 TEST RESULTS

Temperature:	25.1°C	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 7		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.7660	24.09	19.41	43.50	56.00	-12.50	QP
2	0.7660	11.57	19.41	30.98	46.00	-15.02	AVG
3	1.0820	24.70	19.39	44.09	56.00	-11.91	QP
4	1.0820	11.10	19.39	30.49	46.00	-15.51	AVG
5	1.9540	23.39	19.38	42.77	56.00	-13.23	QP
6	1.9540	9.45	19.38	28.83	46.00	-17.17	AVG
7	3.9900	24.44	19.46	43.90	56.00	-12.10	QP
8	3.9900	14.22	19.46	33.68	46.00	-12.32	AVG
9	9.3980	27.40	19.63	47.03	60.00	-12.97	QP
10	9.3980	18.21	19.63	37.84	50.00	-12.16	AVG
11	18.0100	27.56	19.89	47.45	60.00	-12.55	QP
12	18.0100	17.63	19.89	37.52	50.00	-12.48	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor)-Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)






Temperature:	25.1°C	Relative Humidity:	59%
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 7		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2100	24.43	19.37	43.80	63.21	-19.41	QP
2	0.2100	15.01	19.37	34.38	53.21	-18.83	AVG
3	0.4660	19.39	19.35	38.74	56.58	-17.84	QP
4	0.4660	7.09	19.35	26.44	46.58	-20.14	AVG
5	0.9620	19.87	19.39	39.26	56.00	-16.74	QP
6	0.9620	7.52	19.39	26.91	46.00	-19.09	AVG
7	1.1740	20.13	19.39	39.52	56.00	-16.48	QP
8	1.1740	6.74	19.39	26.13	46.00	-19.87	AVG
9	2.1900	19.92	19.39	39.31	56.00	-16.69	QP
10	2.1900	7.63	19.39	27.02	46.00	-18.98	AVG
11	7.7580	28.03	19.51	47.54	60.00	-12.46	QP
12	7.7580	21.84	19.51	41.35	50.00	-8.65	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

100.0 dBuV





4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2020 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2475 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested with a band-stop filter and performed pretest to three orthogonal axis. The worst-case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





4.4 EUT OPERATING CONDITIONS

Please refer to section 3.4 of this report.

4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$



4.6 TEST RESULTS

(Between 9KHz – 30 MHz)

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Polarization:	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



(30MHz -1000MHz)


1M PHY

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Horizontal
Test Mode:	Mode 1/2/3 (Mode 2 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.2111	32.17	-12.95	19.22	40.00	-20.78	peak
2	134.7600	43.18	-18.11	25.07	43.50	-18.43	peak
3	180.3500	49.20	-20.04	29.16	43.50	-14.34	peak
4	324.8800	40.11	-13.85	26.26	46.00	-19.74	peak
5	472.3200	35.59	-8.92	26.67	46.00	-19.33	peak
6	910.7600	39.29	-0.17	39.12	46.00	-6.88	peak

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain
3. All modes have been tested,only show the worst case.






Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Vertical
Test Mode:	Mode 1/2/3 (Mode 2 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.3173	44.87	-13.01	31.86	40.00	-8.14	peak
2	134.7600	46.41	-18.11	28.30	43.50	-15.20	peak
3	158.0400	44.67	-18.74	25.93	43.50	-17.57	peak
4	257.9500	36.57	-15.02	21.55	46.00	-24.45	peak
5	589.6900	31.88	-5.83	26.05	46.00	-19.95	peak
6	869.0500	36.17	-0.52	35.65	46.00	-10.35	peak

Remark:

1. $\text{Margin} = \text{Result} - (\text{Reading} + \text{Factor}) - \text{Limit}$
2. $\text{Factor} = \text{Antenna factor} + \text{Cable attenuation factor (cable loss)} - \text{Amplifier gain}$
3. All modes have been tested, only show the worst case.






2M PHY

Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Horizontal
Test Mode:	Mode 4/5/6 (Mode5 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	131.8500	41.52	-18.20	23.32	43.50	-20.18	peak
2	181.3200	46.58	-20.11	26.47	43.50	-17.03	peak
3	328.7600	39.41	-13.74	25.67	46.00	-20.33	peak
4	472.3200	34.57	-8.92	25.65	46.00	-20.35	peak
5	705.1200	38.74	-4.01	34.73	46.00	-11.27	peak
6	910.7600	39.59	-0.17	39.42	46.00	-6.58	peak

Remark:

1. Margin = Result (Result = Reading + Factor) - Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain
3. All modes have been tested, only show the worst case.






Temperature:	23.4℃	Relative Humidity:	60%
Test Voltage:	DC 7.6V	Phase:	Vertical
Test Mode:	Mode 4/5/6 (Mode5 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.9100	46.49	-14.33	32.16	40.00	-7.84	peak
2	38.7300	44.86	-17.36	27.50	40.00	-12.50	peak
3	154.1600	46.66	-18.60	28.06	43.50	-15.44	peak
4	589.6900	30.87	-5.83	25.04	46.00	-20.96	peak
5	733.2500	29.38	-2.35	27.03	46.00	-18.97	peak
6	972.8400	28.54	2.19	30.73	54.00	-23.27	peak

Remark:

1. Margin = Result (Result = Reading + Factor) - Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain
3. All modes have been tested, only show the worst case.

80.0 dBuV/m





(1GHz-25GHz) Spurious emission Requirements

1M PHY- GFSK


Low Channel (GFSK/2402 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1923.00	41.77	-0.09	74	-32.23	Peak	292.3	Horizontal	Pass
1923.00	30.73	-0.09	54	-23.27	AV	292.3	Horizontal	Pass
2991.50	47.66	5.42	74	-26.34	Peak	204.9	Horizontal	Pass
2991.50	36.12	5.42	54	-17.88	AV	204.9	Horizontal	Pass
6917.00	51.71	0.65	74	-22.29	Peak	157.6	Horizontal	Pass
6917.00	40.14	0.65	54	-13.86	AV	157.6	Horizontal	Pass
9579.50	51.82	0.77	74	-22.18	Peak	210.4	Horizontal	Pass
9579.50	41.39	0.77	54	-12.61	AV	210.4	Horizontal	Pass
14422.25	56.11	6.83	74	-17.89	Peak	157.6	Horizontal	Pass
14422.25	45.87	6.83	54	-8.13	AV	157.6	Horizontal	Pass
17879.00	55.69	7.06	74	-18.31	Peak	171.0	Horizontal	Pass
17879.00	45.38	7.06	54	-8.62	AV	171.0	Horizontal	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1922.57	41.09	-0.14	74.00	-32.91	Peak	307.57	Horizontal	Pass
1922.57	28.90	-0.14	54.00	-25.10	AV	307.57	Horizontal	Pass
2991.00	45.82	5.39	74.00	-28.18	Peak	224.99	Horizontal	Pass
2991.00	34.51	5.39	54.00	-19.49	AV	224.99	Horizontal	Pass
6916.69	50.38	0.63	74.00	-23.62	Peak	191.40	Horizontal	Pass
6916.69	39.40	0.63	54.00	-14.60	AV	191.40	Horizontal	Pass
9579.08	51.19	0.74	74.00	-22.81	Peak	223.95	Horizontal	Pass
9579.08	40.78	0.74	54.00	-13.22	AV	223.95	Horizontal	Pass
14421.82	55.22	6.80	74.00	-18.78	Peak	176.56	Horizontal	Pass
14421.82	44.21	6.80	54.00	-9.79	AV	176.56	Horizontal	Pass
17878.58	54.32	7.04	74.00	-19.68	Peak	186.56	Horizontal	Pass
17878.58	43.69	7.04	54.00	-10.31	AV	186.56	Horizontal	Pass



High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1922.47	39.13	-0.21	74.00	-34.87	Peak	322.76	Horizontal	Pass
1922.47	27.78	-0.21	54.00	-26.22	AV	322.76	Horizontal	Pass
2990.71	46.01	5.36	74.00	-27.99	Peak	245.62	Horizontal	Pass
2990.71	33.76	5.36	54.00	-20.24	AV	245.62	Horizontal	Pass
6916.03	49.96	0.59	74.00	-24.04	Peak	206.02	Horizontal	Pass
6916.03	37.08	0.59	54.00	-16.92	AV	206.02	Horizontal	Pass
9579.04	49.66	0.71	74.00	-24.34	Peak	217.37	Horizontal	Pass
9579.04	39.79	0.71	54.00	-14.21	AV	217.37	Horizontal	Pass
14421.70	54.01	6.77	74.00	-19.99	Peak	195.51	Horizontal	Pass
14421.70	43.41	6.77	54.00	-10.59	AV	195.51	Horizontal	Pass
17878.39	52.36	7.00	74.00	-21.64	Peak	172.97	Horizontal	Pass
17878.39	44.06	7.00	54.00	-9.94	AV	172.97	Horizontal	Pass


RSE-1G-18G-H

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





RSE-18G-26G-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19056.000	50.38	1.72	52.10	74.00	-21.90	peak
2	20424.000	49.81	2.16	51.97	74.00	-22.03	peak
3	21040.000	49.64	2.69	52.33	74.00	-21.67	peak
4	22560.000	48.09	3.89	51.98	74.00	-22.02	peak
5	23920.000	47.91	4.54	52.45	74.00	-21.55	peak
6	25144.000	47.28	5.41	52.69	74.00	-21.31	peak




Low Channel (GFSK/2402 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1693.00	40.69	-0.98	74.00	-33.31	Peak	318.0	Vertical	Pass
1693.00	28.97	-0.98	54.00	-25.03	AV	318.0	Vertical	Pass
2986.00	46.83	5.39	74.00	-27.17	Peak	197.4	Vertical	Pass
2986.00	36.41	5.39	54.00	-17.59	AV	197.4	Vertical	Pass
6969.00	51.96	1.07	74.00	-22.04	Peak	78.8	Vertical	Pass
6969.00	39.99	1.07	54.00	-14.01	AV	78.8	Vertical	Pass
10792.25	53.12	1.97	74.00	-20.88	Peak	246.2	Vertical	Pass
10792.25	42.16	1.97	54.00	-11.84	AV	246.2	Vertical	Pass
14414.00	55.94	6.89	74.00	-18.06	Peak	275.9	Vertical	Pass
14414.00	45.77	6.89	54.00	-8.23	AV	275.9	Vertical	Pass
17785.50	55.83	6.31	74.00	-18.17	Peak	260.7	Vertical	Pass
17785.50	45.08	6.31	54.00	-8.92	AV	260.7	Vertical	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1692.52	39.01	-1.03	74.00	-34.99	Peak	333.33	Vertical	Pass
1692.52	28.40	-1.03	54.00	-25.60	AV	333.33	Vertical	Pass
2985.72	45.42	5.34	74.00	-28.58	Peak	217.48	Vertical	Pass
2985.72	35.33	5.34	54.00	-18.67	AV	217.48	Vertical	Pass
6968.59	50.52	1.04	74.00	-23.48	Peak	97.80	Vertical	Pass
6968.59	38.20	1.04	54.00	-15.80	AV	97.80	Vertical	Pass
10791.96	51.16	1.93	74.00	-22.84	Peak	240.09	Vertical	Pass
10791.96	40.99	1.93	54.00	-13.01	AV	240.09	Vertical	Pass
14413.80	54.65	6.85	74.00	-19.35	Peak	292.01	Vertical	Pass
14413.80	44.78	6.85	54.00	-9.22	AV	292.01	Vertical	Pass
17785.16	54.59	6.28	74.00	-19.41	Peak	258.12	Vertical	Pass
17785.16	43.30	6.28	54.00	-10.70	AV	258.12	Vertical	Pass



High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1692.05	37.92	-1.11	74.00	-36.08	Peak	348.65	Vertical	Pass
1692.05	26.60	-1.11	54.00	-27.40	AV	348.65	Vertical	Pass
2985.47	44.45	5.31	74.00	-29.55	Peak	237.50	Vertical	Pass
2985.47	34.71	5.31	54.00	-19.29	AV	237.50	Vertical	Pass
6968.23	49.05	1.01	74.00	-24.95	Peak	127.77	Vertical	Pass
6968.23	36.83	1.01	54.00	-17.17	AV	127.77	Vertical	Pass
10791.75	49.54	1.88	74.00	-24.46	Peak	255.94	Vertical	Pass
10791.75	39.88	1.88	54.00	-14.12	AV	255.94	Vertical	Pass
14413.59	53.25	6.81	74.00	-20.75	Peak	318.68	Vertical	Pass
14413.59	43.26	6.81	54.00	-10.74	AV	318.68	Vertical	Pass
17784.81	52.68	6.24	74.00	-21.32	Peak	270.59	Vertical	Pass
17784.81	42.64	6.24	54.00	-11.36	AV	270.59	Vertical	Pass


RSE-1G-18G-V

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





RSE-18G-26G-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19216.000	50.57	1.63	52.20	74.00	-21.80	peak
2	20752.000	49.55	2.44	51.99	74.00	-22.01	peak
3	22016.000	48.57	3.42	51.99	74.00	-22.01	peak
4	23232.000	48.36	3.87	52.23	74.00	-21.77	peak
5	24216.000	47.33	4.67	52.00	74.00	-22.00	peak
6	25560.000	46.72	5.67	52.39	74.00	-21.61	peak

Note:

- 1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor.
- 2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



2M PHY


Low Channel (GFSK/2402 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1328.00	46.84	-1.29	74	-27.16	Peak	137.5	Horizontal	Pass
1328.00	35.07	-1.29	54	-18.93	AV	137.5	Horizontal	Pass
2825.50	46.84	4.87	74	-27.16	Peak	358.1	Horizontal	Pass
2825.50	35.94	4.87	54	-18.06	AV	358.1	Horizontal	Pass
8914.00	51.32	1.40	74	-22.68	Peak	209.7	Horizontal	Pass
8914.00	41.21	1.40	54	-12.79	AV	209.7	Horizontal	Pass
10797.75	52.78	2.02	74	-21.22	Peak	346.2	Horizontal	Pass
10797.75	41.90	2.02	54	-12.10	AV	346.2	Horizontal	Pass
13985.00	55.14	8.26	74	-18.86	Peak	153.1	Horizontal	Pass
13985.00	44.85	8.26	54	-9.15	AV	153.1	Horizontal	Pass
17887.25	55.15	7.13	74	-18.85	Peak	26.2	Horizontal	Pass
17887.25	45.00	7.13	54	-9.00	AV	26.2	Horizontal	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1327.58	46.17	-1.36	74.00	-27.83	Peak	152.87	Horizontal	Pass
1327.58	34.07	-1.36	54.00	-19.93	AV	152.87	Horizontal	Pass
2825.26	45.05	4.83	74.00	-28.95	Peak	378.49	Horizontal	Pass
2825.26	35.16	4.83	54.00	-18.84	AV	378.49	Horizontal	Pass
8913.74	50.07	1.37	74.00	-23.93	Peak	241.12	Horizontal	Pass
8913.74	40.15	1.37	54.00	-13.85	AV	241.12	Horizontal	Pass
10797.52	50.89	1.99	74.00	-23.11	Peak	341.19	Horizontal	Pass
10797.52	40.86	1.99	54.00	-13.14	AV	341.19	Horizontal	Pass
13984.75	53.40	8.23	74.00	-20.60	Peak	165.44	Horizontal	Pass
13984.75	43.66	8.23	54.00	-10.34	AV	165.44	Horizontal	Pass
17886.97	53.86	7.08	74.00	-20.14	Peak	22.05	Horizontal	Pass
17886.97	43.10	7.08	54.00	-10.90	AV	22.05	Horizontal	Pass



High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1327.17	44.25	-1.43	74.00	-29.75	Peak	168.22	Horizontal	Pass
1327.17	32.18	-1.43	54.00	-21.82	AV	168.22	Horizontal	Pass
2824.76	43.76	4.78	74.00	-30.24	Peak	398.51	Horizontal	Pass
2824.76	33.62	4.78	54.00	-20.38	AV	398.51	Horizontal	Pass
8913.41	48.23	1.34	74.00	-25.77	Peak	261.05	Horizontal	Pass
8913.41	38.77	1.34	54.00	-15.23	AV	261.05	Horizontal	Pass
10797.19	49.79	1.96	74.00	-24.21	Peak	353.02	Horizontal	Pass
10797.19	40.11	1.96	54.00	-13.89	AV	353.02	Horizontal	Pass
13984.36	51.99	8.20	74.00	-22.01	Peak	193.83	Horizontal	Pass
13984.36	41.95	8.20	54.00	-12.05	AV	193.83	Horizontal	Pass
17886.55	53.01	7.06	74.00	-20.99	Peak	20.17	Horizontal	Pass
17886.55	41.61	7.06	54.00	-12.39	AV	20.17	Horizontal	Pass


RSE-1G-18G-H

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





RSE-18G-26G-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19056.000	50.38	1.72	52.10	74.00	-21.90	peak
2	20184.000	50.31	1.96	52.27	74.00	-21.73	peak
3	20968.000	50.05	2.63	52.68	74.00	-21.32	peak
4	22864.000	48.49	3.71	52.20	74.00	-21.80	peak
5	24272.000	47.58	4.68	52.26	74.00	-21.74	peak
6	25544.000	46.17	5.67	51.84	74.00	-22.16	peak




Low Channel (GFSK/2402 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1328.00	46.84	-1.29	74	-27.16	Peak	137.5	Vertical	Pass
1328.00	35.07	-1.29	54	-18.93	AV	137.5	Vertical	Pass
2825.50	46.84	4.87	74	-27.16	Peak	358.1	Vertical	Pass
2825.50	35.94	4.87	54	-18.06	AV	358.1	Vertical	Pass
8914.00	51.32	1.40	74	-22.68	Peak	209.7	Vertical	Pass
8914.00	41.21	1.40	54	-12.79	AV	209.7	Vertical	Pass
10797.75	52.78	2.02	74	-21.22	Peak	346.2	Vertical	Pass
10797.75	41.90	2.02	54	-12.10	AV	346.2	Vertical	Pass
13985.00	55.14	8.26	74	-18.86	Peak	153.1	Vertical	Pass
13985.00	44.85	8.26	54	-9.15	AV	153.1	Vertical	Pass
17887.25	55.15	7.13	74	-18.85	Peak	26.2	Vertical	Pass
17887.25	45.00	7.13	54	-9.00	AV	26.2	Vertical	Pass
Middle Channel (GFSK/2440 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1327.62	45.51	-1.34	74.00	-28.49	Peak	152.82	Vertical	Pass
1327.62	34.41	-1.34	54.00	-19.59	AV	152.82	Vertical	Pass
2825.14	45.74	4.83	74.00	-28.26	Peak	378.15	Vertical	Pass
2825.14	35.09	4.83	54.00	-18.91	AV	378.15	Vertical	Pass
8913.79	49.71	1.35	74.00	-24.29	Peak	231.71	Vertical	Pass
8913.79	40.69	1.35	54.00	-13.31	AV	231.71	Vertical	Pass
10797.34	52.13	1.98	74.00	-21.87	Peak	362.32	Vertical	Pass
10797.34	40.49	1.98	54.00	-13.51	AV	362.32	Vertical	Pass
13984.68	53.43	8.22	74.00	-20.57	Peak	176.94	Vertical	Pass
13984.68	42.86	8.22	54.00	-11.14	AV	176.94	Vertical	Pass
17886.98	54.25	7.10	74.00	-19.75	Peak	40.34	Vertical	Pass
17886.98	43.36	7.10	54.00	-10.64	AV	40.34	Vertical	Pass



High Channel (GFSK/2480 MHz)								
Frequency (MHz)	Results (dBuV/m)	Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Antenna	Verdict
1327.19	44.19	-1.40	74.00	-29.81	Peak	168.06	Vertical	Pass
1327.19	32.77	-1.40	54.00	-21.23	AV	168.06	Vertical	Pass
2824.72	44.77	4.81	74.00	-29.23	Peak	398.15	Vertical	Pass
2824.72	34.25	4.81	54.00	-19.75	AV	398.15	Vertical	Pass
8913.39	49.12	1.33	74.00	-24.88	Peak	248.57	Vertical	Pass
8913.39	38.70	1.33	54.00	-15.30	AV	248.57	Vertical	Pass
10797.02	50.18	1.94	74.00	-23.82	Peak	367.69	Vertical	Pass
10797.02	39.89	1.94	54.00	-14.11	AV	367.69	Vertical	Pass
13984.31	51.58	8.18	74.00	-22.42	Peak	190.33	Vertical	Pass
13984.31	40.95	8.18	54.00	-13.05	AV	190.33	Vertical	Pass
17886.75	53.72	7.05	74.00	-20.28	Peak	37.52	Vertical	Pass
17886.75	42.48	7.05	54.00	-11.52	AV	37.52	Vertical	Pass


RSE-1G-18G-V

RE_FCC Test Case_FCC 15C 1GHz-18GHz - 2.4G





RSE-18G-26G-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19184.000	50.70	1.64	52.34	74.00	-21.66	peak
2	20088.000	50.73	1.88	52.61	74.00	-21.39	peak
3	21416.000	49.31	2.89	52.20	74.00	-21.80	peak
4	23040.000	49.30	3.67	52.97	74.00	-21.03	peak
5	24496.000	47.97	4.72	52.69	74.00	-21.31	peak
6	25144.000	46.68	5.41	52.09	74.00	-21.91	peak

Note:

- 1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor.
- 2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.




4.6 TEST RESULTS (Restricted Bands Requirements)
1M PHY-LOW
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2382.100	39.46	0.75	40.21	74.00	-33.79	peak
2	2390.000	37.92	0.81	38.73	74.00	-35.27	peak

Vertical






No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2375.200	39.79	0.70	40.49	74.00	-33.51	peak
2	2390.000	37.22	0.81	38.03	74.00	-35.97	peak

1M PHY-HIGH
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.92	1.02	40.94	74.00	-33.06	peak
2	2491.500	39.81	1.03	40.84	74.00	-33.16	peak

Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.26	1.02	40.28	74.00	-33.72	peak
2	2489.075	39.87	1.03	40.90	74.00	-33.10	peak



2M PHY-LOW
Horizontal


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2365.000	39.68	0.62	40.30	74.00	-33.70	peak
2	2390.000	37.56	0.81	38.37	74.00	-35.63	peak

Vertical






No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2365.200	40.26	0.62	40.88	74.00	-33.12	peak
2	2390.000	38.61	0.81	39.42	74.00	-34.58	peak

2M PHY-HIGH
Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	38.26	1.02	39.28	74.00	-34.72	peak
2	2486.068	39.48	1.02	40.50	74.00	-33.50	peak

Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	2483.500	37.90	1.02	38.92	74.00	-35.08	peak
2	2485.609	39.70	1.02	40.72	74.00	-33.28	peak



5. DUTY CYCLE

5.1 TEST STANDARD

Please refer to ANSI C63.10-2020 Section 11.6

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Zero
RB	set RBW to the largest available value
VB	$VBW \geq RBW$.
Detector	Peak
Trace	Clear Write
Sweep Time	Auto

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



6. CONDUCTED SPURIOUS & BAND EDGE EMISSION

6.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

6.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

6.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminals is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

6.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

6.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



7. POWER SPECTRAL DENSITY TEST

7.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

7.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



8. BANDWIDTH TEST

8.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

8.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq 3\text{RBW}$, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

8.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



9. PEAK OUTPUT POWER TEST

9.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

9.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW $\geq$ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq$ [3 $\times$ RBW].
- Set span $\geq$ [3 $\times$ RBW].
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

9.3 TEST SETUP



9.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

9.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA


The EUT antenna is FPC Antenna. It comply with the standard requirement.

**APPENDIX 1-TEST DATA****Duty Cycle**


Condition	Mode	Frequency (MHz)	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	0.384	0.626	61.34	2.12	2.6
NVNT	BLE 1M	2440	0.382	0.624	61.22	2.13	2.62
NVNT	BLE 1M	2480	0.384	0.626	61.34	2.12	2.6
NVNT	BLE 2M	2404	0.2	0.626	31.95	4.96	5
NVNT	BLE 2M	2440	0.2	0.626	31.95	4.96	5
NVNT	BLE 2M	2478	0.198	0.624	31.73	4.99	5.05



Test Graphs
Duty Cycle NVNT BLE 1M 2402MHz




Duty Cycle NVNT BLE 1M 2440MHz






Duty Cycle NVNT BLE 1M 2480MHz




Duty Cycle NVNT BLE 2M 2404MHz






Duty Cycle NVNT BLE 2M 2440MHz



Duty Cycle NVNT BLE 2M 2478MHz





Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	-1.79	<=30	Pass
NVNT	BLE 1M	2440	-1.56	<=30	Pass
NVNT	BLE 1M	2480	-1.61	<=30	Pass
NVNT	BLE 2M	2404	-1.79	<=30	Pass
NVNT	BLE 2M	2440	-1.55	<=30	Pass
NVNT	BLE 2M	2478	-1.58	<=30	Pass



Test Graphs
Peak Power NVNT BLE 1M 2402MHz



Peak Power NVNT BLE 1M 2440MHz





Peak Power NVNT BLE 1M 2480MHz



Peak Power NVNT BLE 2M 2404MHz





Peak Power NVNT BLE 2M 2440MHz



Peak Power NVNT BLE 2M 2478MHz





-6dB Bandwidth

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	0.684	≥ 0.5	Pass
NVNT	BLE 1M	2440	0.6863	≥ 0.5	Pass
NVNT	BLE 1M	2480	0.6914	≥ 0.5	Pass
NVNT	BLE 2M	2404	1.136	≥ 0.5	Pass
NVNT	BLE 2M	2440	1.172	≥ 0.5	Pass
NVNT	BLE 2M	2478	1.153	≥ 0.5	Pass



Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz



-6dB Bandwidth NVNT BLE 1M 2440MHz






-6dB Bandwidth NVNT BLE 1M 2480MHz



-6dB Bandwidth NVNT BLE 2M 2404MHz





-6dB Bandwidth NVNT BLE 2M 2440MHz



-6dB Bandwidth NVNT BLE 2M 2478MHz






Maximum Power Spectral Density Level


Condition	Mode	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	-16.86	≤ -8	Pass
NVNT	BLE 1M	2440	-16.6	≤ -8	Pass
NVNT	BLE 1M	2480	-16.66	≤ -8	Pass
NVNT	BLE 2M	2404	-19.02	≤ -8	Pass
NVNT	BLE 2M	2440	-18.84	≤ -8	Pass
NVNT	BLE 2M	2478	-18.8	≤ -8	Pass



Test Graphs
PSD NVNT BLE 1M 2402MHz



PSD NVNT BLE 1M 2440MHz






PSD NVNT BLE 1M 2480MHz




PSD NVNT BLE 2M 2404MHz






PSD NVNT BLE 2M 2440MHz



PSD NVNT BLE 2M 2478MHz





Band Edge

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-52.87	≤ -20	Pass
NVNT	BLE 1M	2480	-53.41	≤ -20	Pass
NVNT	BLE 2M	2404	-50.85	≤ -20	Pass
NVNT	BLE 2M	2478	-53.19	≤ -20	Pass



Test Graphs
Band Edge NVNT BLE 1M 2402MHz Ref



Band Edge NVNT BLE 1M 2402MHz Emission





Band Edge NVNT BLE 1M 2480MHz Ref



Band Edge NVNT BLE 1M 2480MHz Emission





Band Edge NVNT BLE 2M 2404MHz Ref



Band Edge NVNT BLE 2M 2404MHz Emission





Band Edge NVNT BLE 2M 2478MHz Ref



Band Edge NVNT BLE 2M 2478MHz Emission





Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-40.58	≤ -20	Pass
NVNT	BLE 1M	2440	-40.84	≤ -20	Pass
NVNT	BLE 1M	2480	-40.66	≤ -20	Pass
NVNT	BLE 2M	2404	-49.23	≤ -20	Pass
NVNT	BLE 2M	2440	-34.6	≤ -20	Pass
NVNT	BLE 2M	2478	-49.5	≤ -20	Pass




Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ref




Tx. Spurious NVNT BLE 1M 2402MHz Emission






Tx. Spurious NVNT BLE 1M 2440MHz Ref




Tx. Spurious NVNT BLE 1M 2440MHz Emission






Tx. Spurious NVNT BLE 1M 2480MHz Ref



Tx. Spurious NVNT BLE 1M 2480MHz Emission






Tx. Spurious NVNT BLE 2M 2404MHz Ref



Tx. Spurious NVNT BLE 2M 2404MHz Emission






Tx. Spurious NVNT BLE 2M 2440MHz Ref



Tx. Spurious NVNT BLE 2M 2440MHz Emission






Tx. Spurious NVNT BLE 2M 2478MHz Ref



Tx. Spurious NVNT BLE 2M 2478MHz Emission





APPENDIX 2- EUT TEST PHOTO

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

*****END OF THE REPORT*****