

RF exposure Estimation for WPTT

1. Introduction

Product:	PowerWatch Series 2
Model no.:	PW07
FCC ID:	2ANY2MPW07
Options and accessories:	Wireless Charger
Rating:	3.85Vdc 340mAh Li-ion Rechargeable battery
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	40
Modulation:	GFSK
Antenna Type:	Integrated antenna
Antenna Gain:	-10.1dBi
Description of the EUT:	The Equipment Under Test (EUT) is a watch which support Bluetooth function operated at 2.4GHz.

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right]$$

$$[\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3. Calculation method

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Conducted Power + tune up tolerance = 1.47mW (1.66dBm)

Distance = 5 mm

$f = 2.402$ GHz

$[1.47/5] \cdot \text{SQRT}(2.402) = 0.46$

$0.46 \leq 3.0$

Therefore, excluded from SAR testing.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch


Reviewed by:



John Zhi/ Project Manager

Date: 2019-08-08

Prepared By:



Alan Xiong/ Project Engineer

Date: 2019-08-08