



# FCC TEST REPORT

## FCC ID: 2ANYX-RF-R-LCD-B4V2

|                                                                               |   |                      |
|-------------------------------------------------------------------------------|---|----------------------|
| Product                                                                       | : | L-Wireless Receiver  |
| Model Name                                                                    | : | RF-R-LCD-B4V2        |
| Additional Model                                                              | : | RF-R-LED-B4V2        |
| Brand                                                                         | : | Lian Li              |
| Report No.                                                                    | : | PTC25091116103E-FC01 |
| <b>Prepared for</b>                                                           |   |                      |
| LIAN LI INDUSTRIAL CO.,LTD.                                                   |   |                      |
| 11-1, KONG-CHIEN N.RD; LIU-TU INDUSTRIAL PARK Keelung Taiwan                  |   |                      |
| <b>Prepared by</b>                                                            |   |                      |
| Precise Testing & Certification Co., Ltd.                                     |   |                      |
| Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China |   |                      |



## 1 TEST RESULT CERTIFICATION

Applicant's name : LIAN LI INDUSTRIAL CO.,LTD.  
Address : 11-1, KONG-CHIEN N.RD; LIU-TU INDUSTRIAL PARK Keelung Taiwan  
Manufacture's name : LIAN LI INDUSTRIAL CO.,LTD.  
Address : 11-1, KONG-CHIEN N.RD; LIU-TU INDUSTRIAL PARK Keelung Taiwan  
Product name : L-Wireless Receiver  
Model Name : RF-R-LCD-B4V2  
Additional Model : RF-R-LED-B4V2  
Standards : FCC Part15 Subpart C, Paragraph 15.249  
Test procedure : ANSI C63.10-2020  
Test Date : October 29, 2025 to November 14, 2025  
Date of Issue : November 14, 2025  
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



## Contents

|                                                        | Page      |
|--------------------------------------------------------|-----------|
| <b>1 TEST RESULT CERTIFICATION .....</b>               | <b>2</b>  |
| <b>2 TEST SUMMARY .....</b>                            | <b>5</b>  |
| 2.1 TEST SITE .....                                    | 6         |
| <b>3 GENERAL INFORMATION .....</b>                     | <b>7</b>  |
| 3.1 GENERAL DESCRIPTION OF E.U.T. ....                 | 7         |
| 3.2 CHANNEL LIST .....                                 | 8         |
| <b>4 EQUIPMENT DURING TEST .....</b>                   | <b>9</b>  |
| 4.1 EQUIPMENTS LIST .....                              | 9         |
| 4.2 MEASUREMENT UNCERTAINTY .....                      | 11        |
| 4.3 DESCRIPTION OF SUPPORT UNITS .....                 | 11        |
| <b>5 CONDUCTED EMISSION .....</b>                      | <b>12</b> |
| 5.1 E.U.T. OPERATION .....                             | 12        |
| 5.2 EUT SETUP .....                                    | 12        |
| 5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) ..... | 13        |
| 5.4 MEASUREMENT PROCEDURE .....                        | 13        |
| 5.5 CONDUCTED EMISSION LIMIT .....                     | 13        |
| 5.6 MEASUREMENT DESCRIPTION .....                      | 13        |
| 5.7 CONDUCTED EMISSION TEST RESULT .....               | 13        |
| <b>6 RADIATED EMISSION AND BAND EDGE .....</b>         | <b>16</b> |
| 6.1 TEST STANDARD AND LIMIT .....                      | 16        |
| 6.2 TEST SETUP .....                                   | 17        |
| 6.3 TEST PROCEDURE .....                               | 18        |
| 6.4 TEST DATA .....                                    | 19        |
| <b>7 20DB BANDWIDTH TEST .....</b>                     | <b>26</b> |
| 7.1 TEST STANDARD AND LIMIT .....                      | 26        |
| 7.2 TEST SETUP .....                                   | 26        |
| 7.3 TEST PROCEDURE .....                               | 26        |
| 7.4 TEST DATA .....                                    | 27        |
| <b>8 ANTENNA REQUIREMENT .....</b>                     | <b>31</b> |
| 8.1 TEST STANDARD AND REQUIREMENT .....                | 31        |



Report No.: PTC25091116103E-FC01

|                                                    |           |
|----------------------------------------------------|-----------|
| 8.2 ANTENNA CONNECTED CONSTRUCTION .....           | 31        |
| <b>9 APPENDIX I -- TEST SETUP PHOTOGRAPH .....</b> | <b>32</b> |
| <b>10 APPENDIX II -- EUT PHOTOGRAPH .....</b>      | <b>34</b> |



## 2 Test Summary

| Standard Section                                            | Test Item           | Result |
|-------------------------------------------------------------|---------------------|--------|
| 15.203                                                      | Antenna Requirement | PASS   |
| 15.207                                                      | Conducted Emission  | N/A    |
| 15.249                                                      | Radiated Emission   | PASS   |
| 15.215(c)                                                   | 20dB Bandwidth      | PASS   |
| 15.249(d)                                                   | Band Edge           | PASS   |
| <b>Remark:</b> "N/A" is an abbreviation for Not Applicable. |                     |        |

Remark:N/A



Report No.: PTC25091116103E-FC01

## 2.1 Test Site

Precise Testing & Certification Co., Ltd.

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A



### 3 General Information

#### 3.1 General Description of E.U.T.

|                       |   |                     |
|-----------------------|---|---------------------|
| Product Name          | : | L-Wireless Receiver |
| Model Name            | : | RF-R-LCD-B4V2       |
| Additional Model      | : | RF-R-LED-B4V2       |
| Operating frequency   | : | 2402MHz-2480MHz     |
| Channels              | : | 40 Channels         |
| Antenna installation: | : | PCB antenna         |
| Type of Modulation    | : | GFSK                |
| Antenna Gain          | : | 2.1 dBi             |
| Power supply          | : | DC12V(USB HUB DC5V) |
| Hardware version      | : | MY0003M29C V7.0     |
| Software version      | : | 1.1                 |

#### Models Difference:

The RF-R-LED-B4V2 model features reduced USB HUB functionality and LED indicator light (the HUB is used to power the fan's display).



### 3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2020 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

| Channel | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) | Channel | Frequency<br>(MHz) |
|---------|--------------------|---------|--------------------|---------|--------------------|
| 00      | <b>2402</b>        | 14      | 2430               | 28      | 2458               |
| 01      | 2404               | 15      | 2432               | 29      | 2460               |
| 02      | 2406               | 16      | 2434               | 30      | 2462               |
| 03      | 2408               | 17      | 2436               | 31      | 2464               |
| 04      | 2410               | 18      | 2438               | 32      | 2466               |
| 05      | 2412               | 19      | <b>2440</b>        | 33      | 2468               |
| 06      | 2414               | 20      | 2442               | 34      | 2470               |
| 07      | 2416               | 21      | 2444               | 35      | 2472               |
| 08      | 2418               | 22      | 2446               | 36      | 2474               |
| 09      | 2420               | 23      | 2448               | 37      | 2476               |
| 10      | 2422               | 24      | 2450               | 38      | 2478               |
| 11      | 2424               | 25      | 2452               | 39      | <b>2480</b>        |
| 12      | 2426               | 26      | 2454               |         |                    |
| 13      | 2428               | 27      | 2456               |         |                    |

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.
2. EUT used the new batteries during test.



## 4 Equipment During Test

### 4.1 Equipments List

RF Conducted Test

| Name of Equipment   | Manufacturer | Model    | Serial No.    | Characteristics | Last Calibration | Calibration Interval |
|---------------------|--------------|----------|---------------|-----------------|------------------|----------------------|
| MXG Signal Analyzer | Agilent      | N9020A   | SER MY5111038 | 10Hz-26.5GHz    | Aug.14, 2025     | 1 Year               |
| Coaxial Cable       | CDS          | 79254    | 46107086      | 10Hz-30GHz      | Aug.14, 2025     | 1 Year               |
| Power Meter         | Anritsu      | ML2495A  | 0949003       | 300MHz-40GHz    | Aug.14, 2025     | 1 Year               |
| Power Sensor        | Anritsu      | MA2411B  | 0917017       | 300MHz-40GHz    | Aug.14, 2025     | 1 Year               |
| Test S/W            | Tonscend     | JS1120-3 | /             | /               | /                | /                    |

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

| Name of Equipment            | Manufacturer  | Model        | Serial No.       | Characteristics | Last Calibration | Calibration Interval |
|------------------------------|---------------|--------------|------------------|-----------------|------------------|----------------------|
| EMI Test Receiver            | Rohde&Schwarz | ESPI7        | 101671           | 9KHz-7GHz       | Aug.14, 2025     | 1 Year               |
| Loop Antenna                 | Schwarzbeck   | FMZB 1519    | 192              | 9 KHz -30MHz    | Aug.14, 2025     | 1 Year               |
| Bilog Antenna                | SCHWARZBECK   | VULB9160     | 9160-3355        | 25MHz-2GHz      | Sep.09, 2025     | 1 Year               |
| Preamplifier (low frequency) | SCHWARZBECK   | BBV 9475     | 9745-0013        | 1MHz-1GHz       | Aug.14, 2025     | 1 Year               |
| Cable                        | IMRO          | AK-9515E(9m) | Cable-L          | 9KHz-3GHz       | Aug.14, 2025     | 1 Year               |
| Spectrum Analyzer            | Rohde&Schwarz | FSV40        | 6625-01-588-5515 | 9KHz-40GHz      | Aug.14, 2025     | 1 Year               |
| Horn Antenna                 | SCHWARZBECK   | 9120D        | 9120D-1246       | 1GHz-18GHz      | Aug.14, 2025     | 1 Year               |
| Power Amplifier              | ZHINAN        | ZN3380C      | 15002            | 1GHz-26.5GHz    | Aug.14, 2025     | 1 Year               |
| Horn Antenna                 | SCHWARZBECK   | BBHA 9170    | 9170-1066        | 15GHz-40GHz     | Jul. 18, 2025    | 1 Year               |



Report No.: PTC25091116103E-FC01

|           |             |          |          |              |               |        |
|-----------|-------------|----------|----------|--------------|---------------|--------|
| Amplifier | SCHWARZBECK | BBV 9721 | 9721-205 | 18GHz-40GHz  | Jul. 18, 2025 | 1 Year |
| Cable     | H+S         | CBL-26   | N/A      | 1GHz-26.5GHz | Aug.14, 2025  | 1 Year |
| RF Cable  | R&S         | R204     | R21X     | 1GHz-40GHz   | Aug.14, 2025  | 1 Year |
| Test S/W  | Tonscend    | TS+      | /        | /            | /             | /      |

Conducted Emissions

| Name of Equipment        | Manufacturer    | Model   | Serial No.             | Characteristics | Calibration Date | Calibration Interval |
|--------------------------|-----------------|---------|------------------------|-----------------|------------------|----------------------|
| EMI Test Receiver        | Rohde&Schwarz   | ESCI    | 101417                 | 9KHz-3GHz       | Aug.14, 2025     | 1 Year               |
| Artificial Mains Network | Rohde&Schwarz   | ENV216  | 102453                 | 9KHz-300MHz     | Aug.14, 2025     | 1 Year               |
| Artificial Mains Network | Rohde&Schwarz   | ENV216  | 101342                 | 9KHz-300MHz     | Aug.14, 2025     | 1 Year               |
| Limiter                  | R&S             | ESH3-Z2 | 0357.8810.54-102808-NB | 0Hz-30MHz       | Aug.14, 2025     | 1 Year               |
| RF Switch                | DIAMOND ANTENNA | CX-210  | /                      | 0.09MHz-6GHz    | Mar. 22,2025     | 1 Year               |
| Test S/W                 | Tonscend        | JS32-CE | /                      | /               | /                | /                    |



## 4.2 Measurement Uncertainty

| Parameter                          | Uncertainty              |
|------------------------------------|--------------------------|
| RF output power, conducted         | $\pm 1.0\text{dB}$       |
| Power Spectral Density, conducted  | $\pm 2.2\text{dB}$       |
| Radio Frequency                    | $\pm 1 \times 10^{-6}$   |
| Bandwidth                          | $\pm 1.5 \times 10^{-6}$ |
| Time                               | $\pm 2\%$                |
| Duty Cycle                         | $\pm 2\%$                |
| Temperature                        | $\pm 1^\circ\text{C}$    |
| Humidity                           | $\pm 5\%$                |
| DC and low frequency voltages      | $\pm 3\%$                |
| Conducted Emissions (150kHz~30MHz) | $\pm 3.64\text{dB}$      |
| Radiated Emission(30MHz~1GHz)      | $\pm 5.03\text{dB}$      |
| Radiated Emission(1GHz~25GHz)      | $\pm 4.74\text{dB}$      |
| Radiated Emission(9KHz~30MHz)      | $\pm 3.15\text{dB}$      |

## 4.3 Description of Support Units

| Equipment | Model No. | Series No. |
|-----------|-----------|------------|
| FAN       | N/A       | N/A        |

## 5 Conducted Emission

|                  |                                     |
|------------------|-------------------------------------|
| Test Requirement | : FCC CFR 47 Part 15 Section 15.207 |
| Test Method      | : ANSI C63.10-2020                  |
| Test Result      | : PASS                              |
| Frequency Range  | : 150kHz to 30MHz                   |
| Class/Severity   | : Class B                           |


### 5.1 E.U.T. Operation

Operating Environment :


|                      |            |
|----------------------|------------|
| Temperature          | : 25.5 °C  |
| Humidity             | : 51 % RH  |
| Atmospheric Pressure | : 101.2kPa |

### 5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10-2020.



### 5.3 Test SET-UP (Block Diagram of Configuration)



### 5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

### 5.5 Conducted Emission Limit

#### Conducted Emission

##### Frequency(MHz)

0.15-0.5

0.5-5.0

5.0-30.0

##### Quasi-peak

66-56

56

60

##### Average

56-46

46

50

#### Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.6 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


### 5.7 Conducted Emission Test Result

All the modulation modes were tested the data of the worst mode ( GFSK TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.



Line-AC 120V/60Hz

Report No.: PTC25091116103E-FC01




## Final Data List

| NO. | Freq.<br>[MHz] | QP<br>Reading | Factor<br>[dB] | QP<br>Value | QP<br>Limit | QP<br>Margin | AV<br>Reading | AV<br>Value | AV<br>Limit | AV<br>Margin | Verdict |
|-----|----------------|---------------|----------------|-------------|-------------|--------------|---------------|-------------|-------------|--------------|---------|
| 1   | 0.555          | 32.87         | 9.96           | 42.83       | 56.00       | 13.17        | 18.34         | 28.30       | 46.00       | 17.70        | PASS    |
| 2   | 0.884          | 33.51         | 10.01          | 43.52       | 56.00       | 12.48        | 20.94         | 30.95       | 46.00       | 15.05        | PASS    |
| 3   | 4.794          | 31.15         | 10.25          | 41.40       | 56.00       | 14.60        | 13.82         | 24.07       | 46.00       | 21.93        | PASS    |
| 4   | 12.642         | 38.32         | 10.32          | 48.64       | 60.00       | 11.36        | 18.43         | 28.75       | 50.00       | 21.25        | PASS    |
| 5   | 13.641         | 43.56         | 10.36          | 53.92       | 60.00       | 6.08         | 21.39         | 31.75       | 50.00       | 18.25        | PASS    |
| 6   | 15.581         | 38.06         | 10.42          | 48.48       | 60.00       | 11.52        | 20.79         | 31.21       | 50.00       | 18.79        | PASS    |



Neutral-AC 120V/60Hz

Report No.: PTC25091116103E-FC01



## Final Data List

| NO. | Freq.<br>[MHz] | QP<br>Reading | Factor<br>[dB] | QP<br>Value | QP<br>Limit | QP<br>Margin | AV<br>Reading | AV<br>Value | AV<br>Limit | AV<br>Margin | Verdict |
|-----|----------------|---------------|----------------|-------------|-------------|--------------|---------------|-------------|-------------|--------------|---------|
| 1   | 1.023          | 32.24         | 9.96           | 42.20       | 56.00       | 13.80        | 17.94         | 27.90       | 46.00       | 18.10        | PASS    |
| 2   | 1.289          | 31.91         | 9.96           | 41.87       | 56.00       | 14.13        | 17.72         | 27.68       | 46.00       | 18.32        | PASS    |
| 3   | 4.992          | 31.13         | 10.31          | 41.44       | 56.00       | 14.56        | 13.40         | 23.71       | 46.00       | 22.29        | PASS    |
| 4   | 12.633         | 38.31         | 10.30          | 48.61       | 60.00       | 11.39        | 18.01         | 28.31       | 50.00       | 21.69        | PASS    |
| 5   | 13.794         | 42.59         | 10.33          | 52.92       | 60.00       | 7.08         | 21.19         | 31.52       | 50.00       | 18.48        | PASS    |
| 6   | 15.500         | 38.31         | 10.38          | 48.69       | 60.00       | 11.31        | 20.78         | 31.16       | 50.00       | 18.84        | PASS    |

Note: QP Margin[dB]= QP Limit[dBμV]- QP Value[dBμV], AV Margin[dB]= AV Limit[dBμV]- AV Value[dBμV].

## 6 Radiated Emission and Band Edge

### 6.1 Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 |                                     |                   |            |                             |
|---------------|----------------------------------------|-------------------------------------|-------------------|------------|-----------------------------|
| Test Limit    | Frequency<br>(MHz)                     | Field strength<br>(microvolt/meter) | Limit<br>(dBuV/m) | Remark     | Measurement<br>distance (m) |
|               | 0.009MHz~0.490MHz                      | 2400/F(kHz)                         | -                 | -          | 300                         |
|               | 0.490MHz~1.705MHz                      | 24000/F(kHz)                        | -                 | -          | 30                          |
|               | 1.705MHz~30MHz                         | 30                                  | -                 | -          | 30                          |
|               | 30MHz~88MHz                            | 100                                 | 40.0              | Quasi-peak | 3                           |
|               | 88MHz~216MHz                           | 150                                 | 43.5              | Quasi-peak | 3                           |
|               | 216MHz~960MHz                          | 200                                 | 46.0              | Quasi-peak | 3                           |
|               | 960MHz~1000MHz                         | 500                                 | 54.0              | Quasi-peak | 3                           |
|               | Above 1000MHz                          | 500                                 | 54.0              | Average    | 3                           |
|               |                                        | -                                   | 74.0              | Peak       | 3                           |

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

| Test Standard | FCC Part15 C Section 15.249 |                                                         |                                                      |                   |         |                             |
|---------------|-----------------------------|---------------------------------------------------------|------------------------------------------------------|-------------------|---------|-----------------------------|
| Test Limit    | Frequency<br>(MHz)          | Field Strength of<br>fundamental<br>(millivolts /meter) | Field Strength of<br>Harmonics<br>(microvolts/meter) | Limit<br>(dBuV/m) | Remark  | Measurement<br>distance (m) |
|               | 2400~2483.5                 | 50                                                      | -                                                    | 114.0             | Peak    | 3                           |
|               | 2400~2483.5                 | 50                                                      | -                                                    | 94.0              | Average | 3                           |
|               | 2400~2483.5                 | -                                                       | 500                                                  | 74.0              | Peak    | 3                           |
|               | 2400~2483.5                 | -                                                       | 500                                                  | 54.0              | Average | 3                           |

**Remark:**

(1) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

## 6.2 Test Setup

Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz



### 6.3 Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.



For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz,Set the spectrum analyzer as:

RBW =1MHz, VBW =1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW =1MHz, VBW =10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

## 6.4 Test Data

### PASS


During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, and found the Middle channel which is the worst case, only the worst case is recorded in the report



# Test plot for Horizontal



## Final Data List[QP]


| NO. | Freq.<br>[MHz] | QP<br>Reading<br>[dBμV/m] | Factor<br>[dB] | QP Value<br>[dBμV/m] | QP Limit<br>[dBμV/m] | QP Margin<br>[dB] | Polarity   | Verdict |
|-----|----------------|---------------------------|----------------|----------------------|----------------------|-------------------|------------|---------|
| 1   | 194.66         | 51                        | -11.32         | 39.68                | 43.50                | 3.82              | Horizontal | PASS    |
| 2   | 271.05         | 41.21                     | -8.00          | 33.21                | 46.00                | 12.79             | Horizontal | PASS    |
| 3   | 402.72         | 39.12                     | -4.55          | 34.57                | 46.00                | 11.43             | Horizontal | PASS    |
| 4   | 482.26         | 33.25                     | -2.61          | 30.64                | 46.00                | 15.36             | Horizontal | PASS    |
| 5   | 784.66         | 28.56                     | 3.66           | 32.22                | 46.00                | 13.78             | Horizontal | PASS    |
| 6   | 943.01         | 27.09                     | 6.26           | 33.35                | 46.00                | 12.65             | Horizontal | PASS    |

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



# Test plot for Vertical

Report No.: PTC25091116103E-FC01



## Final Data List[QP]

| NO. | Freq.<br>[MHz] | QP<br>Reading<br>[dBμV/m] | Factor<br>[dB] | QP Value<br>[dBμV/m] | QP Limit<br>[dBμV/m] | QP Margin<br>[dB] | Polarity | Verdict |
|-----|----------------|---------------------------|----------------|----------------------|----------------------|-------------------|----------|---------|
| 1   | 126.76         | 33.97                     | -9.17          | 24.80                | 43.50                | 18.70             | Vertical | PASS    |
| 2   | 200.48         | 42.92                     | -11.01         | 31.91                | 43.50                | 11.59             | Vertical | PASS    |
| 3   | 477.90         | 35.51                     | -2.68          | 32.83                | 46.00                | 13.17             | Vertical | PASS    |
| 4   | 644.98         | 32.39                     | 1.25           | 33.64                | 46.00                | 12.36             | Vertical | PASS    |
| 5   | 868.08         | 27.21                     | 5.31           | 32.52                | 46.00                | 13.48             | Vertical | PASS    |
| 6   | 916.34         | 27.27                     | 5.90           | 33.17                | 46.00                | 12.83             | Vertical | PASS    |

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor



# Test Frequency 1GHz-25GHz

| Test Mode: CH00 (Low channel) |                   |                       |                 |                          |                |                |                 |      |          |
|-------------------------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|------|----------|
| Frequency (MHz)               | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector |
| 2402.00                       | 94.79             | 31.12                 | 2.18            | 35.33                    | 92.76          | 114            | -21.24          | V    | Peak     |
| 2402.00                       | 82.10             | 31.12                 | 2.18            | 35.33                    | 80.07          | 94             | -13.93          | V    | AVG      |
| 4804.00                       | 48.87             | 34.01                 | 2.58            | 34.65                    | 50.81          | 74             | -23.19          | V    | Peak     |
| 4804.00                       | 36.97             | 34.01                 | 2.58            | 34.65                    | 38.91          | 54             | -15.09          | V    | AVG      |
| 7206.00                       | 46.61             | 36.16                 | 2.97            | 35.07                    | 50.67          | 74             | -23.33          | V    | Peak     |
| 7206.00                       | 36.76             | 36.16                 | 2.97            | 35.07                    | 40.82          | 54             | -13.18          | V    | AVG      |
|                               |                   |                       |                 |                          |                |                |                 |      |          |
| 2402.00                       | 95.82             | 31.12                 | 2.18            | 35.33                    | 93.79          | 114            | -20.21          | H    | Peak     |
| 2402.00                       | 81.99             | 31.12                 | 2.18            | 35.33                    | 79.96          | 94             | -14.04          | H    | AVG      |
| 4804.00                       | 48.80             | 34.01                 | 2.58            | 34.65                    | 50.74          | 74             | -23.26          | H    | Peak     |
| 4804.00                       | 36.46             | 34.01                 | 2.58            | 34.65                    | 38.40          | 54             | -15.60          | H    | AVG      |
| 7206.00                       | 47.40             | 36.16                 | 2.97            | 35.07                    | 51.46          | 74             | -22.54          | H    | Peak     |
| 7206.00                       | 35.56             | 36.16                 | 2.97            | 35.07                    | 39.62          | 54             | -14.38          | H    | AVG      |



| Test Mode: CH19 (Middle channel) |                   |                       |                 |                          |                |                |                 |      |          |
|----------------------------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|------|----------|
| Frequency (MHz)                  | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector |
| 2440.00                          | 95.08             | 31.12                 | 2.2             | 34.51                    | 93.89          | 114            | -20.11          | V    | Peak     |
| 2440.00                          | 81.63             | 31.22                 | 2.2             | 34.51                    | 80.54          | 94             | -13.46          | V    | AVG      |
| 4880.00                          | 48.06             | 34.98                 | 2.49            | 34.14                    | 51.39          | 74             | -22.61          | V    | Peak     |
| 4880.00                          | 36.22             | 34.98                 | 2.49            | 34.14                    | 39.55          | 54             | -14.45          | V    | AVG      |
| 7320.00                          | 47.74             | 36.01                 | 3.01            | 34.56                    | 52.20          | 74             | -21.80          | V    | Peak     |
| 7320.00                          | 35.00             | 36.01                 | 3.01            | 34.56                    | 39.46          | 54             | -14.54          | V    | AVG      |
|                                  |                   |                       |                 |                          |                |                |                 |      |          |
| 2440.00                          | 94.93             | 31.12                 | 2.2             | 34.51                    | 93.74          | 114            | -20.26          | H    | Peak     |
| 2440.00                          | 81.68             | 31.12                 | 2.2             | 34.51                    | 80.49          | 94             | -13.51          | H    | AVG      |
| 4880.00                          | 48.62             | 34.98                 | 2.49            | 34.14                    | 51.95          | 74             | -22.05          | H    | Peak     |
| 4880.00                          | 36.28             | 34.98                 | 2.49            | 34.14                    | 39.61          | 54             | -14.39          | H    | AVG      |
| 7320.00                          | 47.82             | 36.01                 | 3.01            | 34.56                    | 52.28          | 74             | -21.72          | H    | Peak     |
| 7320.00                          | 37.00             | 36.01                 | 3.01            | 34.56                    | 41.46          | 54             | -12.54          | H    | AVG      |



| Test Mode: CH39(High channel) |                   |                       |                 |                          |                |                |                 |      |          |
|-------------------------------|-------------------|-----------------------|-----------------|--------------------------|----------------|----------------|-----------------|------|----------|
| Frequency (MHz)               | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Pol. | Detector |
| 2480.00                       | 93.99             | 31.65                 | 2.23            | 36.07                    | 91.80          | 114            | -22.20          | V    | Peak     |
| 2480.00                       | 84.90             | 31.65                 | 2.23            | 36.07                    | 82.71          | 94             | -11.29          | V    | AVG      |
| 4960.00                       | 49.66             | 35.06                 | 2.6             | 34.93                    | 52.39          | 74             | -21.61          | V    | Peak     |
| 4960.00                       | 36.21             | 35.06                 | 2.6             | 34.93                    | 38.94          | 54             | -15.06          | V    | AVG      |
| 7440.00                       | 47.20             | 36.19                 | 3.12            | 35.11                    | 51.40          | 74             | -22.60          | V    | Peak     |
| 7440.00                       | 35.40             | 36.19                 | 3.12            | 35.11                    | 39.60          | 54             | -14.40          | V    | AVG      |
|                               |                   |                       |                 |                          |                |                |                 |      |          |
| 2480.00                       | 94.36             | 31.65                 | 2.23            | 36.07                    | 92.17          | 114            | -21.83          | H    | Peak     |
| 2480.00                       | 83.44             | 31.65                 | 2.23            | 36.07                    | 81.25          | 94             | -12.75          | H    | AVG      |
| 4960.00                       | 48.04             | 35.06                 | 2.6             | 34.93                    | 50.77          | 74             | -23.23          | H    | Peak     |
| 4960.00                       | 37.04             | 35.06                 | 2.6             | 34.93                    | 39.77          | 54             | -14.23          | H    | AVG      |
| 7440.00                       | 47.40             | 36.19                 | 3.12            | 35.11                    | 51.60          | 74             | -22.40          | H    | Peak     |
| 7440.00                       | 35.95             | 36.19                 | 3.12            | 35.11                    | 40.15          | 54             | -13.85          | H    | AVG      |

Note: 1. The testing has been conformed to 10\*2402MHz=24020MHz. 10\*2440MHz=24400MHz.  
10\*2480MHz=24800MHz.

2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
Emission Level = Reading + Factor  
Margin=Emission Level-Limit



### Spurious Emission in Restricted Band 2310-2400MHz and 2483.5-2500MHz

| Test Mode: Low Channel 2402MHz |                   |                       |                 |                    |                |                |                 |              |            |
|--------------------------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------------|--------------|------------|
| Frequency (MHz)                | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Polarity H/V | Test Value |
| 2310.00                        | 40.07             | 29.15                 | 3.41            | 34.01              | 38.62          | 74             | -35.38          | H            | Peak       |
| 2400.00                        | 57.76             | 29.16                 | 3.43            | 34.01              | 56.34          | 74             | -17.66          | H            | Peak       |
| 2310.00                        | 40.04             | 29.15                 | 3.41            | 34.01              | 38.59          | 74             | -35.41          | V            | Peak       |
| 2400.00                        | 56.26             | 29.16                 | 3.43            | 34.01              | 54.84          | 74             | -19.16          | V            | Peak       |
| 2310.00                        | 35.07             | 29.15                 | 3.41            | 34.01              | 33.62          | 54             | -20.38          | H            | AV         |
| 2400.00                        | 40.42             | 29.16                 | 3.43            | 34.01              | 39.00          | 54             | -15.00          | H            | AV         |
| 2310.00                        | 36.36             | 29.15                 | 3.41            | 34.01              | 34.91          | 54             | -19.09          | V            | AV         |
| 2400.00                        | 43.91             | 29.16                 | 3.43            | 34.01              | 42.49          | 54             | -11.51          | V            | AV         |

| Test Mode: High Channel 2480MHz |                   |                       |                 |                    |                |                |                 |              |            |
|---------------------------------|-------------------|-----------------------|-----------------|--------------------|----------------|----------------|-----------------|--------------|------------|
| Frequency (MHz)                 | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Polarity H/V | Test Value |
| 2483.50                         | 46.81             | 29.28                 | 3.53            | 34.03              | 45.59          | 74             | -28.41          | H            | Peak       |
| 2500.00                         | 40.16             | 29.30                 | 3.56            | 34.03              | 38.99          | 74             | -35.01          | H            | Peak       |
| 2483.50                         | 48.00             | 29.28                 | 3.53            | 34.03              | 46.78          | 74             | -27.22          | V            | Peak       |
| 2500.00                         | 41.96             | 29.30                 | 3.56            | 34.03              | 40.79          | 74             | -33.21          | V            | Peak       |
| 2483.50                         | 39.68             | 29.28                 | 3.53            | 34.03              | 38.46          | 54             | -15.54          | H            | AV         |
| 2500.00                         | 33.06             | 29.30                 | 3.56            | 34.03              | 31.89          | 54             | -22.11          | H            | AV         |
| 2483.50                         | 39.59             | 29.28                 | 3.53            | 34.03              | 38.37          | 54             | -15.63          | V            | AV         |
| 2500.00                         | 32.94             | 29.30                 | 3.56            | 34.03              | 31.77          | 54             | -22.23          | V            | AV         |




## 7 20dB Bandwidth Test

### 7.1 Test Standard and Limit

|               |                                |
|---------------|--------------------------------|
| Test Standard | FCC Part15 C Section 15.215(c) |
|---------------|--------------------------------|

### 7.2 Test Setup



### 7.3 Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:  
RBW = 1% to 5% of the OBW,  $VBW \geq 3 \times RBW$ ,  
Detector= Average  
Trace mode= Max hold.  
Sweep- auto couple.
4. Mark the peak frequency and  $-20\text{dB}$  (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.



## 7.4 Test Data

Test Item : 20dB Bandwidth  
Test Voltage : DC 12V  
Test Result : PASS

Test Mode : TX  
Temperature : 22.4°C  
Humidity : 55%RH

|        | Frequency<br>(MHz) | Bandwidth<br>(MHz) | Result |
|--------|--------------------|--------------------|--------|
| SRD_1M | 2402               | 1.290              | PASS   |
| SRD_1M | 2440               | 1.301              | PASS   |
| SRD_1M | 2480               | 1.368              | PASS   |
| SRD_2M | 2402               | 2.290              | PASS   |
| SRD_2M | 2440               | 2.404              | PASS   |
| SRD_2M | 2480               | 2.173              | PASS   |



Report No.: PTC25091116103E-FC01



Test Mode:SRD\_1M Low



Test Mode: SRD\_1M Middle



Report No.: PTC25091116103E-FC01



Test Mode: SRD\_1M High



Test Mode:SRD\_2M Low



Report No.: PTC25091116103E-FC01



Test Mode: SRD\_2M Middle



Test Mode: SRD\_2M High



## 8 Antenna Requirement

### 8.1 Test Standard and Requirement

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard | FCC Part15 Section 15.203                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Requirement   | 1) 15.203 requirement:<br><br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |

### 8.2 Antenna Connected Construction


The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is 2.1 dBi. It complies with the standard requirement.

## 9 APPENDIX I -- TEST SETUP PHOTOGRAPH

### CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST









## 10 APPENDIX II -- EUT PHOTOGRAPH











\*\*\*\*\*THE END REPORT\*\*\*\*\*