

§1.1310& §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:**5G Wi-Fi(worst case):**

Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11a	5150~5250	19.0	79.43	17.00	50.12	20	0.7919	1.0
	5725~5850	19.0	79.43	17.00	50.12	20	0.7919	1.0
802.11ac20	5150~5250	19.0	79.43	14.00	25.12	20	0.3969	1.0
	5725~5850	19.0	79.43	14.00	25.12	20	0.3969	1.0
802.11n20	5150~5250	19.0	79.43	14.00	25.12	20	0.3969	1.0
	5725~5850	19.0	79.43	14.00	25.12	20	0.3969	1.0
802.11ac40	5150~5250	19.0	79.43	14.00	25.12	20	0.3969	1.0
	5725~5850	19.0	79.43	14.00	25.12	20	0.3969	1.0
802.11n40	5150~5250	19.0	79.43	14.00	25.12	20	0.3969	1.0
	5725~5850	19.0	79.43	14.00	25.12	20	0.3969	1.0
802.11ac80	5150~5250	19.0	79.43	14.00	25.12	20	0.3969	1.0
	5725~5850	19.0	79.43	13.50	22.39	20	0.3538	1.0

Note: For the above tune up power were declared by the manufacturer.

Conclusion: The device meets MPE at distance 20cm.