FCC TEST REPORT

Product Name:	kids wireless ANC headphones
Trade Mark:	heyday, deal worthy, Chug Inc., Gems
Model No.:	ANC3
Report Number:	25051417865RFC-1
Test Standards:	FCC 47 CFR Part 15 Subpart C
FCC ID:	2AO23-ANC3
Test Result:	PASS
Date of Issue:	May 30, 2025

Prepared for:

Chug, Inc.
7157 Shady Oak Rd, Eden Prairie MN 55344, United States

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6th, Baoneng Science and Technology Park,
Longhua Street, Longhua District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by: David Chen
David Chen
Senior Project Engineer

Reviewed by: Henry Lu
Henry Lu
Team Leader

Approved by: Billy Li
Technical Director

Date: May 30, 2025

UnionTrust Laboratories UnionTrust *Certified*

Version

Version No.	Date	Description
V1.0	May 30, 2025	Original

CONTENTS

1. GENERAL INFORMATION 4
   1.1 CLIENT INFORMATION 4
   1.2 EUT INFORMATION 4
      1.2.1 GENERAL DESCRIPTION OF EUT 4
      1.2.2 DESCRIPTION OF ACCESSORIES 4
   1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 5
   1.4 OTHER INFORMATION 5
   1.5 DESCRIPTION OF SUPPORT UNITS 6
   1.6 TEST LOCATION 6
   1.7 TEST FACILITY 6
   1.8 DEVIATION FROM STANDARDS 6
   1.9 ABNORMALITIES FROM STANDARD CONDITIONS 6
   1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER 7
   1.11 MEASUREMENT UNCERTAINTY 7
2. TEST SUMMARY 8
3. EQUIPMENT LIST 9
4. TEST CONFIGURATION 10
   4.1 ENVIRONMENTAL CONDITIONS FOR TESTING 10
      4.1.1 NORMAL OR EXTREME TEST CONDITIONS 10
      4.1.2 RECORD OF NORMAL ENVIRONMENT AND TEST SAMPLE 10
   4.2 TEST CHANNELS 10
   4.3 EUT TEST STATUS 10
   4.4 PRE-SCAN 11
      4.4.1 WORST-CASE DATA PACKETS 11
      4.4.2 TESTED CHANNEL DETAIL 11
   4.5 TEST SETUP 12
      4.5.1 FOR RADIATED EMISSIONS TEST SETUP 12
      4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP 13
      4.5.3 FOR CONDUCTED RF TEST SETUP 14
   4.6 SYSTEM TEST CONFIGURATION 14
   4.7 DUTY CYCLE 15
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION 16
   5.1 REFERENCE DOCUMENTS FOR TESTING 16
   5.2 ANTENNA REQUIREMENT 16
   5.3 CONDUCTED PEAK OUTPUT POWER 17
   5.4 20 DB BANDWIDTH 18
   5.5 CARRIER FREQUENCIES SEPARATION 19
   5.6 NUMBER OF HOPPING CHANNEL 20
   5.7 DWELL TIME 21
   5.8 CONDUCTED OUT OF BAND EMISSION 22
   5.9 RADIATED SPURIOUS EMISSIONS 23
   5.10 BAND EDGE MEASUREMENTS (RADIATED) 27

APPENDIX A RF TEST DATA 30
   A.1 20DB EMISSION BANDWIDTH 30
   A.2 OCCUPIED CHANNEL BANDWIDTH 35
   A.3 CARRIER FREQUENCY SEPARATION 40
   A.4 TIME OF OCCUPANCY 42
   A.5 NUMBER OF HOPPING CHANNELS 52
   A.6 BAND EDGE MEASUREMENTS 54
   A.7 CONDUCTED SPURIOUS EMISSION 61

APPENDIX 1 PHOTOS OF TEST SETUP 76
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS 76

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Chug, Inc.
Address of Applicant:	7157 Shady Oak Rd, Eden Prairie MN 55344, United States
Manufacturer 1:	Hunan XuanTong Technology Co., Ltd
Address of Manufacturer 1:	B2 Building, Standard Factory, Caojiapeng Four Phases, Baofeng Street, Shimen County, Changde City, Hunan Province, China
Manufacturer 2:	Rocker Technology Co., Ltd
Address of Manufacturer 2:	Building S3, 2nd Floor, Area A, Star Maiya Innovation Science and Technology Park, Prey Roka Village, Chok Chheu Neang Commune, Ang Snoul District, National Road 4, Kandal Province, Phnom Penh, Cambodia

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	kids wireless ANC headphones	
Model No.:	ANC3	
Trade Mark:	heyday, deal worthy, Chug Inc., Gems	
DUT Stage:	Identical Prototype	
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	Bluetooth 5.4
Sample Received Date:	May 14, 2025	
Sample Tested Date:	May 15, 2025 to May 22, 2025	

Remark:
The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

USB Cable	
Connector:	USB Cable
Cable Type:	Unshielded without ferrite
Length:	0.8 Meter

AUX Cable	
Connector:	3.5mm AUX Cable
Cable Type:	Unshielded without ferrite
Length:	1.2 Meter

Battery	
Model No.:	602030
Battery Type:	Lithium-ion Polymer Rechargeable Battery
Rated Voltage:	3.7 Vdc
Rated Capacity:	300 mAh

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth BR + EDR
Modulation Technique:	Frequency Hopping Spread Spectrum (FHSS)
Type of Modulation:	GFSK, π/4DQPSK, 8DPSK
Number of Channels:	79
Channel Separation:	1 MHz
Hopping Channel Type:	Adaptive Frequency Hopping Systems
Antenna Type: (Provided by the customer)	PCB Antenna
Antenna Gain: (Provided by the customer)	2.73 dBi
Maximum Peak Power:	-14.16 dBm
Normal Test Voltage:	3.7 Vdc

1.4 OTHER INFORMATION

Operation Frequency Each of Channel
f = 2402 + k MHz, k = 0,…,78
Note: **f** is the operating frequency (MHz); **k** is the operating channel.

Modulation Configure			
Modulation	**Packet**	**Packet Type**	**Packet Size**
GFSK	1-DH1	4	27
	1-DH3	11	183
	1-DH5	15	339
π/4 DQPSK	2-DH1	20	54
	2-DH3	26	367
	2-DH5	30	679
8DPSK	3-DH1	24	83
	3-DH3	27	552
	3-DH5	31	1021

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	DELL	Latitude 3400	16238087894	UnionTrust
Mouse	DELL	MS111	CN-011D3V-738	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.1 Meter	Applicant

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6th, Baoneng Science and Technology Park, Longhua Street, Longhua District, Shenzhen, China
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069
The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories
CAB identifier: CN0032

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9kHz-150kHz	±3.2 dB
2	Conducted emission 150kHz-30MHz	±2.7 dB
3	Radiated emission 9kHz-30MHz	± 4.7 dB
4	Radiated emission 30MHz-1GHz	± 4.9 dB
5	Radiated emission 1GHz-18GHz	± 4.8 dB
6	Radiated emission 18GHz-26GHz	± 5.1 dB
7	Radiated emission 26GHz-40GHz	± 5.1 dB
8	Conducted spurious emissions	± 2.7 dB
9	RF Power, Conducted	± 0.68 dB
10	Occupied Bandwidth	± 1.86 %
11	Radio Frequency	2.4 GHz: ± 6.5 x 10^{-8}
12	Transmission Time	± 0.19 %

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart C Test Cases			
Test Item	**Test Requirement**	**Test Method**	**Result**
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (b)	N/A	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013 Section 6.2	N/A(Note2)
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(1)	ANSI C63.10-2013 Section 7.8.5	PASS
20 dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 6.9.2	PASS
Carrier Frequencies Separation	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 7.8.2	PASS
Number of Hopping Channel	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)(iii)	ANSI C63.10-2013 Section 7.8.3	PASS
Dwell Time	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013 Section 7.8.4	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013 Section 6.10.4 & Section 7.8.8	PASS
Radiated Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Section 6.3 & 6.5 & 6.6	PASS
Band Edge Measurement	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013 Section 6.10.5	PASS

Note:

1) N/A: In this whole report not applicable.
2) During the EUT charging process, they will turn off automatically, and the Bluetooth does not work.

Disclaimer and Explanations:

The declared of product specification and data (e.g., antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date**	**Cal. Due date**
☒	3m SAC	ETS-LINDGREN	3M	Euroshiedpn-CT001270-1317	11-Nov-2023	10-Nov-2026
☒	Receiver	R&S	ESIB26	100114	25-Oct-2024	24-Oct-2025
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	28-Mar-2025	27-Mar-2026
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	28-Oct-2024	27-Oct-2025
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	29-Oct-2024	28-Oct-2025
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	29-Oct-2024	28-Oct-2025
☒	Preamplifier	HP	8447F	2805A02960	25-Oct-2024	24-Oct-2025
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201541	29-Mar-2025	28-Mar-2026
☒	Pre-amplifier	ETS-Lindgren	00118385	00201874	28-Mar-2025	27-Mar-2026
☒	Double-Ridged Waveguide Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	28-Oct-2024	27-Oct-2025
☒	Pre-amplifier	ETS-Lindgren	00118384	00202652	28-Oct-2024	27-Oct-2025
☒	Band Reject Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G590	21-Feb-2025	20-Feb-2026
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☒	Test Software	Audix	e3	Software Version: 9.160323		

RF Conducted Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date**	**Cal. Due date**
☒	EXA Spectrum Analyzer	KEYSIGHT	N9020A	MY51286807	25-Oct-2024	24-Oct-2025
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	25-Oct-2024	24-Oct-2025

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage(V)	Relative Humidity (%)
NT/NV	+15 to +35	3.7	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment and Test Sample

Test Item	Temp. (°C)	Relative Humidity (%)	Pressure (kPa)	Sample No.	Tested by
Conducted Peak Output Power	22.9	46.6	99.6	S202505146004-ZJA02/6	David Du
20 dB Bandwidth					
Carrier Frequencies Separation					
Number of Hopping Channel					
Dwell Time					
Conducted Out of Band Emission					
Radiated Emissions	24.5	49.7	99.7	S202505146004-ZJA01/6	Jackson Wu
Band Edge Measurement	25.2	50.9	99.8		

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
GFSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
π/4DQPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz
8DPSK (DH1, DH3, DH5)	2402 MHz to 2480 MHz	Channel 0	Channel 39	Channel 78
		2402 MHz	2441 MHz	2480 MHz

4.3 EUT TEST STATUS

Type of Modulation	Tx Function	Description
GFSK/π/4DQPSK/ 8DPSK	1Tx	1. Keep the EUT in continuously transmitting with Modulation test single 2. Keep the EUT in continuously transmitting with Modulation test Hopping Frequency.

Power Setting (Provided by the customer)
Power Setting: 1

Test Software (Provided by the customer)
FCC Assist 1.0.2.2

4.4 PRE-SCAN

4.4.1 Worst-case data packets

Type of Modulation	Worst-case data rates
GFSK	1-DH5
π/4DQPSK	2-DH5
8DPSK	3-DH5

4.4.2 Tested channel detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data packets and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Type of Modulation	GFSK			π/4DQPSK			8DPSK		
Data Packets	1-DH 1	1-DH 3	1-DH 5	2-DH 1	2-DH 3	2-DH 5	3-DH 1	3-DH 3	3-DH 5
Available Channel	0 to 78								
Test Item	**Test channel and choose of data packets**								
Conducted Peak Output Power	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
20 dB Bandwidth	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Carrier Frequencies Separation	Frequency Hopping Channel 0 to 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Number of Hopping Channel	Frequency Hopping Channel 0 to 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Dwell Time	Channel 39								
	☒	☒	☒	☒	☒	☒	☒	☒	☒
Conducted Out of Band Emission	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☒	☐	☐	☒
Radiated Emissions	Channel 0 & 39 & 78								
	☐	☐	☒	☐	☐	☐	☐	☐	☐
Band Edge Measurements (Radiated)	Channel 0 & 78								
	☐	☐	☒	☐	☐	☐	☐	☐	☐

Remark:
1. The mark "☒" means is chosen for testing;
2. The mark "☐" means is not chosen for testing.

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup

Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz



4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in orientation.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 11.6.

Test Results

Modulation	Packets	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T Minimum VBW (kHz)
GFSK	1-DH5	2.880	3.740	0.77	77.01	1.13	0.35

Remark:

1) Duty cycle= On Time/ Period;

2) Duty Cycle factor = 10 * log(1/ Duty cycle);

The test plots as follows

DH5-2402



5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicesed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(b) (4) requirement:** The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:
Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 2.73 dBi.

5.3 CONDUCTED PEAK OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C Section15.247 (b)(1)

Test Method: ANSI C63.10-2013 Section 7.8.5

Limit: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.
Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

a) Use the following spectrum analyzer settings:
   1) Span: Approximately 5 x 20 dB bandwidth, centered on a hopping channel.
   2) RBW > 20 dB bandwidth of the emission being measured.
   3) VBW ≥ RBW.
   4) Sweep: Auto.
   5) Detector function: Peak.
   6) Trace: Max hold.

b) Allow trace to stabilize.
c) Use the marker-to-peak function to set the marker to the peak of the emission.
d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
e) A plot of the test results and setup description shall be included in the test report.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Results: Pass

Test Mode	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Avg Power [dBm]	Conducted Limit [dBm]	Verdict
DH5	2402	-14.41	-17.66	≤20.97	PASS
DH5	2441	-14.26	-17.76	≤20.97	PASS
DH5	2480	-14.93	-18.26	≤20.97	PASS
2DH5	2402	-14.36	-19.02	≤20.97	PASS
2DH5	2441	-14.16	-19.12	≤20.97	PASS
2DH5	2480	-14.95	-19.65	≤20.97	PASS
3DH5	2402	-14.35	-19.03	≤20.97	PASS
3DH5	2441	-14.26	-19.13	≤20.97	PASS
3DH5	2480	-14.60	-19.66	≤20.97	PASS

Note: The antenna gain of 2.73 dBi less than 6dBi maximum permission antenna gain value based on 125 mW peak output power limit.

5.4 20 DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)

Test Method: ANSI C63.10-2013 Section 6.9.2

Limit: None; for reporting purposes only.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span = approximately 2 to 5 times the OBW, centered on a hopping channel.
b) RBW = 1% to 5% of the OBW.
c) VBW ≥ 3 x RBW
d) Sweep = auto;
e) Detector function = peak
f) Trace = max hold
g) All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down bandwidth of the emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.5 CARRIER FREQUENCIES SEPARATION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(1)

Test Method: ANSI C63.10-2013 Section 7.8.2

Limit: Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.
Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span: Wide enough to capture the peaks of two adjacent channels.
b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c) Video (or average) bandwidth (VBW) ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.
h) Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.6 NUMBER OF HOPPING CHANNEL

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(a)(1)(iii)

Test Method: ANSI C63.10-2013 Section 7.8.3

Limit: Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b) RBW < 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
c) VBW ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.7 DWELL TIME

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(a)(1)

Test Method: ANSI C63.10-2013 Section 7.8.4

Limit: Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Span = zero span, centered on a hopping channel
b) RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
c) Sweep = As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d) Detector function = peak
e) Trace = max hold
f) Use the marker-delta function to determine the dwell time

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.8 CONDUCTED OUT OF BAND EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(d)

Test Method: ANSI C63.10-2013 Section 6.10.4 & Section 7.8.8

Limit: In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

Step 1: Measurement Procedure REF

a) Set instrument center frequency to 2400 MHz or 2483.5 MHz.
b) Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
c) Set the RBW = 100 kHz.
d) Set the VBW ≥ 3 x RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Sweep points ≥ 2 x Span/RBW
h) Trace mode = max hold.
i) Allow the trace to stabilize.
j) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

Step 2: Measurement Procedure OOBE

a) Set RBW = 100 kHz.
b) Set VBW ≥ 300 kHz.
c) Detector = peak.
d) Sweep = auto couple.
e) Trace Mode = max hold.
f) Allow trace to fully stabilize.
g) Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Hopping Frequencies Transmitter mode

Test Results: **Please refer to Appendix A**

5.9 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Section 6.3 & 6.5 & 6.6

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter (Above 18GHz the distance is 1 meter and table is 1.5 meter).

2) Test the EUT in the lowest channel, middle channel, the Highest channel
3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Y axis positioning which it is worse case.
4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:

Radiated Emission Test Data (9 kHz ~ 30 MHz):
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):
Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37.830	28.09	-7.66	20.43	40.00	-19.57	QP
2	47.703	35.77	-13.58	22.19	40.00	-17.81	QP
3	62.304	35.21	-17.64	17.57	40.00	-22.43	QP
4	102.612	32.15	-15.94	16.21	43.50	-27.29	QP
5	436.396	27.60	-3.42	24.18	46.00	-21.82	QP
6	919.132	26.72	4.56	31.28	46.00	-14.72	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.425	26.82	-5.37	21.45	40.00	-18.55	QP
2	47.703	31.97	-13.58	18.39	40.00	-21.61	QP
3	104.798	27.59	-15.67	11.92	43.50	-31.58	QP
4	176.275	26.63	-11.79	14.84	43.50	-28.66	QP
5	204.305	26.54	-11.32	15.22	43.50	-28.28	QP
6	558.079	26.44	-1.61	24.83	46.00	-21.17	QP

Radiated Emission Test Data (Above 1GHz):

No.	Frequency (MHz)	Reading (dBμV)	Correction factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Antenna Polaxis
Lowest Channel:								
1	4777.554	50.56	-2.09	48.47	54.00	-5.53	Average	Horizontal
2	4777.554	55.56	-2.09	53.47	74.00	-20.53	Peak	Horizontal
3	7207.945	48.64	1.30	49.94	54.00	-4.06	Average	Horizontal
4	7207.945	53.64	1.30	54.94	74.00	-19.06	Peak	Horizontal
5	9573.587	49.84	3.09	52.93	54.00	-1.07	Average	Horizontal
6	9573.587	54.79	3.09	57.88	74.00	-16.12	Peak	Horizontal
7	4777.554	44.06	-2.09	41.97	54.00	-12.03	Average	Vertical
8	4777.554	49.06	-2.09	46.97	74.00	-27.03	Peak	Vertical
9	7207.945	42.72	1.30	44.02	54.00	-9.98	Average	Vertical
10	7207.945	47.72	1.30	49.02	74.00	-24.98	Peak	Vertical
11	9573.587	45.96	3.09	49.05	54.00	-4.95	Average	Vertical
12	9573.587	49.96	3.09	53.05	74.00	-20.95	Peak	Vertical
Middle Channel:								
1	4861.298	49.24	-2.05	47.19	54.00	-6.81	Average	Horizontal
2	4861.298	54.24	-2.05	52.19	74.00	-21.81	Peak	Horizontal
3	7334.292	49.64	1.31	50.95	54.00	-3.05	Average	Horizontal
4	7334.292	54.64	1.31	55.95	74.00	-18.05	Peak	Horizontal
5	9741.401	49.59	3.18	52.77	54.00	-1.23	Average	Horizontal
6	9741.401	53.89	3.18	57.07	74.00	-16.93	Peak	Horizontal
7	4861.298	44.23	-2.05	42.18	54.00	-11.82	Average	Vertical
8	4861.298	49.23	-2.05	47.18	74.00	-26.82	Peak	Vertical
9	7334.292	44.51	1.31	45.82	54.00	-8.18	Average	Vertical
10	7334.292	48.51	1.31	49.82	74.00	-24.18	Peak	Vertical
11	9741.401	45.11	3.18	48.29	54.00	-5.71	Average	Vertical
12	9741.401	50.11	3.18	53.29	74.00	-20.71	Peak	Vertical
Highest Channel:								
1	4946.511	49.16	-2.02	47.14	54.00	-6.86	Average	Horizontal
2	4946.511	53.16	-2.02	51.14	74.00	-22.86	Peak	Horizontal
3	7419.751	46.70	1.32	48.02	54.00	-5.98	Average	Horizontal
4	7419.751	51.70	1.32	53.02	74.00	-20.98	Peak	Horizontal
5	9912.156	49.61	3.28	52.89	54.00	-1.11	Average	Horizontal
6	9912.156	52.33	3.28	55.61	74.00	-18.39	Peak	Horizontal
7	4946.511	45.29	-2.02	43.27	54.00	-10.73	Average	Vertical
8	4946.511	50.29	-2.02	48.27	74.00	-25.73	Peak	Vertical
9	7440	41.55	1.32	42.87	54.00	-11.13	Average	Vertical
10	7440	46.55	1.32	47.87	74.00	-26.13	Peak	Vertical
11	9912.156	43.46	3.28	46.74	54.00	-7.26	Average	Vertical
12	9912.156	48.46	3.28	51.74	74.00	-22.26	Peak	Vertical

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result – Limit

5.10 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

Test Method: ANSI C63.10-2013 Section 6.10.5

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dBμV/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.5.1 for details.

Test Procedures:

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).

1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:

Test Channel:	Lowest Channel	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2390.000	53.72	74.00	41.18	54.00	PASS

Test Channel:	Lowest Channel	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2390.000	53.30	74.00	40.97	54.00	PASS

Test Channel:	Highest Channel	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBuv/m)	Pe Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.500	55.35	74.00	45.61	54.00	PASS

Test Channel:	Highest Channel	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.500	54.10	74.00	42.58	54.00	PASS

APPENDIX A RF TEST DATA

A.1 20DB EMISSION BANDWIDTH

Test Mode	Antenna	Frequency [MHz]	20db EBW [MHz]
DH5	Ant1	2402	0.9515
DH5	Ant1	2441	0.9230
DH5	Ant1	2480	0.9507
2DH5	Ant1	2402	1.284
2DH5	Ant1	2441	1.317
2DH5	Ant1	2480	1.350
3DH5	Ant1	2402	1.310
3DH5	Ant1	2441	1.298
3DH5	Ant1	2480	1.302

Test Graphs



DH5-Ant1-2402



DH5-Ant1-2441



DH5-Ant1-2480



2DH5-Ant1-2402



2DH5-Ant1-2441



2DH5-Ant1-2480



3DH5-Ant1-2402



3DH5-Ant1-2441



3DH5-Ant1-2480

A.2 OCCUPIED CHANNEL BANDWIDTH

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]
DH5	Ant1	2402	0.86901	2401.5610	2402.4301
DH5	Ant1	2441	0.89032	2440.5584	2441.4487
DH5	Ant1	2480	0.86575	2479.5630	2480.4287
2DH5	Ant1	2402	1.1976	2401.3993	2402.5969
2DH5	Ant1	2441	1.2093	2440.3971	2441.6064
2DH5	Ant1	2480	1.1792	2479.4056	2480.5848
3DH5	Ant1	2402	1.1923	2401.3991	2402.5914
3DH5	Ant1	2441	1.1911	2440.4009	2441.5920
3DH5	Ant1	2480	1.1999	2479.3977	2480.5976

Test Graphs



DH5-Ant1-2402



DH5-Ant1-2441



DH5-Ant1-2480



2DH5-Ant1-2402



2DH5-Ant1-2441



2DH5-Ant1-2480



3DH5-Ant1-2402



3DH5-Ant1-2441



3DH5-Ant1-2480

A.3 CARRIER FREQUENCY SEPARATION

Test Mode	Antenna	Frequency [MHz]	Result [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	1.136	≥0.594	PASS
2DH5	Ant1	Hop	1.178	≥0.900	PASS
3DH5	Ant1	Hop	1.014	≥0.873	PASS

Test Graphs

DH5-Ant1-Hop-PASS

2DH5-Ant1-Hop-PASS

3DH5-Ant1-Hop-FAIL

A.4 TIME OF OCCUPANCY

Test Mode	Antenna	Frequency [MHz]	Burst Width [ms]	Tota lHops [Num]	Result [s]	Limit [s]	Verdict
DH1	Ant1	Hop	0.381	317	0.121	≤0.4	PASS
DH3	Ant1	Hop	1.638	160	0.262	≤0.4	PASS
DH5	Ant1	Hop	2.885	112	0.323	≤0.4	PASS
2DH1	Ant1	Hop	0.391	318	0.124	≤0.4	PASS
2DH3	Ant1	Hop	1.643	157	0.258	≤0.4	PASS
2DH5	Ant1	Hop	2.891	99	0.286	≤0.4	PASS
3DH1	Ant1	Hop	0.390	317	0.124	≤0.4	PASS
3DH3	Ant1	Hop	1.642	160	0.263	≤0.4	PASS
3DH5	Ant1	Hop	2.892	114	0.33	≤0.4	PASS

Test Graphs



DH1-Ant1-Hop-PASS





DH3-Ant1-Hop-PASS





DH5-Ant1-Hop-PASS





2DH1-Ant1-Hop-PASS





2DH3-Ant1-Hop-PASS





2DH5-Ant1-Hop-PASS





3DH1-Ant1-Hop-PASS





3DH3-Ant1-Hop-PASS





3DH5-Ant1-Hop-PASS


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Fast
IFGain:Low
Trig Delay0.000 s
Trig: Video
#Atten: 20 dB
#Avg Type: RMS
02:40:11 PM May 22, 2025
Ref Offset 11.88 dB
10 dB/div
Ref 21.88 dBm
Log
11.9
1.88
-8.12
-18.1
-28.1
-38.1
-48.1
-58.1
-68.1
Center 2.441000000 GHz
Res BW 510 kHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 31.60 s (30000 pts)
Frequency
Auto Tune
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
510.000 kHz
Auto
Man
Freq Offset
0 Hz

A.5 NUMBER OF HOPPING CHANNELS

Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS

Test Graphs



DH5-Ant1-Hop-PASS



2DH5-Ant1-Hop-PASS



3DH5-Ant1-Hop-PASS

A.6 BAND EDGE MEASUREMENTS

Test Mode	Antenna	Ch Name	Frequency [MHz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	-18.39	-56.79	≤-38.39	PASS
DH5	Ant1	High	2480	-18.58	-56.19	≤-38.58	PASS
DH5	Ant1	Low	Hop_2402	-18.31	-56.76	≤-38.31	PASS
DH5	Ant1	High	Hop_2480	-18.65	-41.98	≤-38.65	PASS
2DH5	Ant1	Low	2402	-18.73	-56.66	≤-38.73	PASS
2DH5	Ant1	High	2480	-18.59	-56.06	≤-38.59	PASS
2DH5	Ant1	Low	Hop_2402	-18.35	-56.29	≤-38.35	PASS
2DH5	Ant1	High	Hop_2480	-18.49	-55.8	≤-38.49	PASS
3DH5	Ant1	Low	2402	-18.23	-56.57	≤-38.23	PASS
3DH5	Ant1	High	2480	-18.58	-56.41	≤-38.58	PASS
3DH5	Ant1	Low	Hop_2402	-18.22	-56.48	≤-38.22	PASS
3DH5	Ant1	High	Hop_2480	-18.48	-55.37	≤-38.48	PASS

Test Graphs



DH5-Ant1-2402-PASS



DH5-Ant1-2480-PASS



DH5-Ant1-Hop_2402-PASS



DH5-Ant1-Hop_2480-PASS



2DH5-Ant1-2402-PASS



2DH5-Ant1-2480-PASS



2DH5-Ant1-Hop_2402-PASS



2DH5-Ant1-Hop_2480-PASS



3DH5-Ant1-2402-PASS



3DH5-Ant1-2480-PASS



3DH5-Ant1-Hop_2402-PASS



3DH5-Ant1-Hop_2480-PASS

A.7 CONDUCTED SPURIOUS EMISSION

Test Mode	Antenna	Frequency [MHz]	Freq Range [MHz]	Ref Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	0~Reference	-18.97	-18.97	---	PASS
DH5	Ant1	2402	30~1000	-18.97	-58.78	≤-38.97	PASS
DH5	Ant1	2402	1000~26500	-18.97	-46.16	≤-38.97	PASS
DH5	Ant1	2441	0~Reference	-18.62	-18.62	---	PASS
DH5	Ant1	2441	30~1000	-18.62	-58.72	≤-38.62	PASS
DH5	Ant1	2441	1000~26500	-18.62	-45.49	≤-38.62	PASS
DH5	Ant1	2480	0~Reference	-19.37	-19.37	---	PASS
DH5	Ant1	2480	30~1000	-19.37	-58.82	≤-39.37	PASS
DH5	Ant1	2480	1000~26500	-19.37	-46.2	≤-39.37	PASS
2DH5	Ant1	2402	0~Reference	-21.44	-21.44	---	PASS
2DH5	Ant1	2402	30~1000	-21.44	-59.13	≤-41.44	PASS
2DH5	Ant1	2402	1000~26500	-21.44	-45.88	≤-41.44	PASS
2DH5	Ant1	2441	0~Reference	-22.22	-22.22	---	PASS
2DH5	Ant1	2441	30~1000	-22.22	-58.32	≤-42.22	PASS
2DH5	Ant1	2441	1000~26500	-22.22	-45.62	≤-42.22	PASS
2DH5	Ant1	2480	0~Reference	-19.79	-19.79	---	PASS
2DH5	Ant1	2480	30~1000	-19.79	-58.83	≤-39.79	PASS
2DH5	Ant1	2480	1000~26500	-19.79	-46.19	≤-39.79	PASS
3DH5	Ant1	2402	0~Reference	-18.68	-18.68	---	PASS
3DH5	Ant1	2402	30~1000	-18.68	-58.62	≤-38.68	PASS
3DH5	Ant1	2402	1000~26500	-18.68	-46.15	≤-38.68	PASS
3DH5	Ant1	2441	0~Reference	-18.82	-18.82	---	PASS
3DH5	Ant1	2441	30~1000	-18.82	-58.68	≤-38.82	PASS
3DH5	Ant1	2441	1000~26500	-18.82	-46.5	≤-38.82	PASS
3DH5	Ant1	2480	0~Reference	-19.36	-19.36	---	PASS
3DH5	Ant1	2480	30~1000	-19.36	-59.21	≤-39.36	PASS
3DH5	Ant1	2480	1000~26500	-19.36	-46.02	≤-39.36	PASS

Test Graphs

DH5-Ant1-2402-0~Reference-PASS



DH5-Ant1-2402-30~1000-PASS



DH5-Ant1-2402-1000~26500-PASS

DH5-Ant1-2441-0~Reference-PASS



DH5-Ant1-2441-30~1000-PASS



DH5-Ant1-2441-1000~26500-PASS

DH5-Ant1-2480-0~Reference-PASS



DH5-Ant1-2480-30~1000-PASS



DH5-Ant1-2480-1000~26500-PASS

2DH5-Ant1-2402-0~Reference-PASS



2DH5-Ant1-2402-30~1000-PASS



2DH5-Ant1-2402-1000~26500-PASS



2DH5-Ant1-2441-0~Reference-PASS



2DH5-Ant1-2441-30~1000-PASS



2DH5-Ant1-2441-1000~26500-PASS

2DH5-Ant1-2480-0~Reference-PASS



2DH5-Ant1-2480-30~1000-PASS



2DH5-Ant1-2480-1000~26500-PASS



3DH5-Ant1-2402-0~Reference-PASS



3DH5-Ant1-2402-30~1000-PASS



3DH5-Ant1-2402-1000~26500-PASS

3DH5-Ant1-2441-0~Reference-PASS



3DH5-Ant1-2441-30~1000-PASS



3DH5-Ant1-2441-1000~26500-PASS

3DH5-Ant1-2480-0~Reference-PASS



3DH5-Ant1-2480-30~1000-PASS



3DH5-Ant1-2480-1000~26500-PASS

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.