



FCC RF Test Report

APPLICANT : Innowi Inc.
EQUIPMENT : ChecOut M
BRAND NAME : Innowi
MODEL NAME : IWCHT-M101
FCC ID : 2AO2Y-IWCHTM101
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Dec. 01, 2017 and testing was completed on Feb. 04, 2018. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

Sporton International (Shenzhen) Inc.

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Applicable Standards.....	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode	10
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 TEST RESULT	13
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	13
3.2 Maximum Conducted Output Power Measurement	16
3.3 Power Spectral Density Measurement	17
3.4 Unwanted Emissions Measurement.....	20
3.5 AC Conducted Emission Measurement.....	26
3.6 Automatically Discontinue Transmission	30
3.7 Antenna Requirements.....	31
4 LIST OF MEASURING EQUIPMENT	32
5 UNCERTAINTY OF EVALUATION	33
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR7D0101F	Rev. 01	Initial issue of report	Apr. 23, 2018



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) & 15.209(a)	Pass	Under limit 3.70 dB at 84.320 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 14.00 dB at 0.530 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Innowi Inc.

3240 Scott Blvd. Santa Clara CA 95054 USA

1.2 Manufacturer

Innowi Inc.

3240 Scott Blvd. Santa Clara CA 95054 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	ChecOut M
Brand Name	Innowi
Model Name	IWCHT-M101
FCC ID	2AO2Y-IWCHTM101
EUT supports Radios application	NFC/ WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT80 Bluetooth v2.0+EDR/ Bluetooth v4.1 LE
HW Version	Rev.4
SW Version	Android 6.0, Microsoft Windows 10, Payment Firmware 1.10.1
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification			
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz		
Maximum Output Power	<5745 MHz ~ 5825 MHz> <Ant. 1> 802.11a : 15.95 dBm / 0.0394 W 802.11n HT20 : 13.83 dBm / 0.0242 W 802.11n HT40 : 14.61 dBm / 0.0289 W 802.11ac VHT80: 12.19 dBm / 0.0166 W <Ant. 2> 802.11a : 12.78 dBm / 0.0190 W 802.11n HT20 : 10.91 dBm / 0.0123 W 802.11n HT40 : 11.60 dBm / 0.0145 W 802.11ac VHT80: 9.06 dBm / 0.0081 W MIMO <Ant. 1 + 2> 802.11a : 17.43 dBm / 0.0553 W 802.11n HT20 : 15.45 dBm / 0.0351 W 802.11n HT40 : 16.12 dBm / 0.0409 W 802.11ac VHT80: 13.82 dBm / 0.0241 W		
99% Occupied Bandwidth	802.11a : 18.93 MHz 802.11n HT20 : 19.33 MHz 802.11n HT40 : 36.86 MHz 802.11ac VHT80 : 75.76 MHz		
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)		
Antenna Type	Ant. 1 : Internal Inverted-L (PCB) Antenna Ant. 2 : Internal Inverted-F (Top Bezel) Antenna		
Antenna Gain	Ant. 1 : -0.78 dBi Ant. 2 : 0.05 dBi		
Antenna Function Description		Ant. 1	Ant. 2
	802.11 a/n/ac SISO	V	V
	802.11 a/n/ac MIMO	V	V

Note:

1. MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.
2. For SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to their higher conducted power.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019.

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	TH01-SZ	CO01-SZ	251365

Test Site	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	03CH01-SZ		577730

Note: The test site complies with ANSI C63.4 2014 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151 [*]	5755	159 [*]	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "^{*}" were 802.11n HT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0


Test Cases	
AC Conducted	Mode 1 : Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 1)
Emission	Mode 2 : Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 2)
Remark: The worst case of conducted emission is mode 1; only the test data of it was reported.	

Ch. #		Band IV : 5745-5825 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159


Ch. #		Band IV : 5745-5825 MHz	
		802.11ac VHT80	
L	Low	-	
M	Middle	155	
H	High	-	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	E450	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Samsung	EO-MG900	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 6.3 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 6.3 + 10 = 16.3 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.



3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.





Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:
15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part 15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

(3) KDB789033 D02 v01r04 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold


(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.4.7 Duty Cycle

Please refer to Appendix C.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.5.4 Test Setup





3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	24~25℃
Test Engineer :	Peng Wang	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 1)		




Site : C001-SZ
Condition: FCC 15E_QP LISN_20170907_L LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.46	29.70	-17.06	46.76	19.60	0.02	10.08	Average
2	0.46	42.50	-14.26	56.76	32.40	0.02	10.08	QP
3	0.53	31.50	-14.50	46.00	21.40	0.02	10.08	Average
4 *	0.53	42.00	-14.00	56.00	31.90	0.02	10.08	QP
5	0.69	21.40	-24.60	46.00	11.30	0.02	10.08	Average
6	0.69	34.90	-21.10	56.00	24.80	0.02	10.08	QP
7	0.96	23.55	-22.45	46.00	13.40	0.06	10.09	Average
8	0.96	35.25	-20.75	56.00	25.10	0.06	10.09	QP
9	1.15	23.77	-22.23	46.00	13.60	0.08	10.09	Average
10	1.15	35.67	-20.33	56.00	25.50	0.08	10.09	QP
11	1.31	24.18	-21.82	46.00	13.99	0.09	10.10	Average
12	1.31	36.58	-19.42	56.00	26.39	0.09	10.10	QP



Test Mode :	Mode 1	Temperature :	24~25°C
Test Engineer :	Peng Wang	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 1)		



Site : CO01-SZ
Condition: FCC 15E_QP LISN_20170907_N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.46	27.80	-18.91	46.71	17.70	0.02	10.08	Average
2	0.46	38.90	-17.81	56.71	28.80	0.02	10.08	QP
3 *	0.53	29.00	-17.00	46.00	18.90	0.02	10.08	Average
4	0.53	37.90	-18.10	56.00	27.80	0.02	10.08	QP
5	0.67	22.00	-24.00	46.00	11.90	0.02	10.08	Average
6	0.67	31.60	-24.40	56.00	21.50	0.02	10.08	QP
7	0.93	21.43	-24.57	46.00	11.30	0.04	10.09	Average
8	0.93	31.53	-24.47	56.00	21.40	0.04	10.09	QP
9	1.07	21.54	-24.46	46.00	11.40	0.05	10.09	Average
10	1.07	31.24	-24.76	56.00	21.10	0.05	10.09	QP
11	1.34	21.35	-24.65	46.00	11.20	0.05	10.10	Average
12	1.34	30.85	-25.15	56.00	20.70	0.05	10.10	QP

3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.7 Antenna Requirements

3.7.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	-0.78	0.05	0.05	2.66	0.00	0.00

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 20, 2017	Jan. 28, 2018~ Feb. 04, 2018	Apr. 19, 2018	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 26, 2017	Jan. 28, 2018~ Feb. 04, 2018	Dec. 25, 2018	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 26, 2017	Jan. 28, 2018~ Feb. 04, 2018	Dec. 25, 2018	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Apr. 20, 2017	Feb. 01, 2018	Apr. 19, 2018	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May 14, 2017	Feb. 01, 2018	May 13, 2018	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz-2GHz	Apr. 25, 2017	Feb. 01, 2018	Apr. 24, 2018	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	119436	1GHz~18GHz	Jul. 28, 2017	Feb. 01, 2018	Jul. 27, 2018	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz-40GHz	Jun. 16, 2017	Feb. 01, 2018	Jun. 15, 2018	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 20, 2017	Feb. 01, 2018	Apr. 19, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1707137	1GHz~18GHz	Oct. 19, 2017	Feb. 01, 2018	Oct. 18, 2018	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5GHz	Oct. 19, 2017	Feb. 01, 2018	Oct. 18, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 18, 2017	Feb. 01, 2018	Jul. 17, 2018	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Feb. 01, 2018	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Feb. 01, 2018	NCR	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 26, 2017	Jan. 30, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Dec. 26, 2017	Jan. 30, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Dec. 26, 2017	Jan. 30, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 19, 2017	Jan. 30, 2018	Jul. 18, 2018	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6 dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3 dB
--	--------



Appendix A. Conducted Test Results

Report Number : FR7D0101F

Test Engineer:	Bruce Huang	Temperature:	21~25	°C
Test Date:	2018/1/28~2018/2/4	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	17.43	17.53	20.43	21.18	16.34	16.38	0.5		Pass
11a	6Mbps	2	157	5785	18.38	18.93	22.88	22.88	16.32	16.38	0.5		Pass
11a	6Mbps	2	165	5825	18.63	18.88	22.78	22.68	16.32	16.34	0.5		Pass
HT20	MCS0	2	149	5745	17.78	17.23	20.38	20.28	17.16	17.08	0.5		Pass
HT20	MCS0	2	157	5785	19.33	18.53	23.03	23.03	17.60	17.58	0.5		Pass
HT20	MCS0	2	165	5825	19.28	18.53	22.88	22.88	17.58	17.58	0.5		Pass
HT40	MCS0	2	151	5755	36.86	36.86	41.45	41.36	36.32	36.32	0.5		Pass
HT40	MCS0	2	159	5795	36.86	36.86	41.18	41.54	36.32	36.32	0.5		Pass
VHT80	MCS0	2	155	5775	75.76	75.76	82.00	82.32	76.08	76.32	0.5		Pass

TEST RESULTS DATA
Average Power Table

Band IV														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.05	0.03	15.95	12.78		30.00	30.00	-0.78	0.05	Pass
11a	6Mbps	1	157	5785	0.05	0.03	15.67	12.48		30.00	30.00	-0.78	0.05	Pass
11a	6Mbps	1	165	5825	0.05	0.03	15.81	12.65		30.00	30.00	-0.78	0.05	Pass
HT20	MCS0	1	149	5745	0.05	0.05	13.77	10.91		30.00	30.00	-0.78	0.05	Pass
HT20	MCS0	1	157	5785	0.05	0.05	13.75	10.81		30.00	30.00	-0.78	0.05	Pass
HT20	MCS0	1	165	5825	0.05	0.05	13.83	10.84		30.00	30.00	-0.78	0.05	Pass
HT40	MCS0	1	151	5755	0.09	0.09	14.61	11.60		30.00	30.00	-0.78	0.05	Pass
HT40	MCS0	1	159	5795	0.09	0.09	14.49	11.51		30.00	30.00	-0.78	0.05	Pass
VHT80	MCS0	1	155	5775	0.19	0.19	12.19	9.06		30.00	30.00	-0.78	0.05	Pass
11a	6Mbps	2	149	5745	0.03	0.06	15.65	12.69	17.43	30.00		0.05		Pass
11a	6Mbps	2	157	5785	0.03	0.06	15.53	12.39	17.25	30.00		0.05		Pass
11a	6Mbps	2	165	5825	0.03	0.06	15.58	12.10	17.19	30.00		0.05		Pass
HT20	MCS0	2	149	5745	0.08	0.11	13.70	10.64	15.45	30.00		0.05		Pass
HT20	MCS0	2	157	5785	0.08	0.11	13.58	10.53	15.33	30.00		0.05		Pass
HT20	MCS0	2	165	5825	0.08	0.11	13.74	10.57	15.45	30.00		0.05		Pass
HT40	MCS0	2	151	5755	0.19	0.16	14.38	11.32	16.12	30.00		0.05		Pass
HT40	MCS0	2	159	5795	0.19	0.16	14.32	11.25	16.06	30.00		0.05		Pass
VHT80	MCS0	2	155	5775	0.33	0.33	12.09	8.99	13.82	30.00		0.05		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	0.03	0.06	2.22					3.55	30.00	2.66		Pass
11a	6Mbps	2	157	5785	0.03	0.06	2.22					3.10	30.00	2.66		Pass
11a	6Mbps	2	165	5825	0.03	0.06	2.22					2.89	30.00	2.66		Pass
HT20	MCS0	2	149	5745	0.08	0.11	2.22					0.95	30.00	2.66		Pass
HT20	MCS0	2	157	5785	0.08	0.11	2.22					0.90	30.00	2.66		Pass
HT20	MCS0	2	165	5825	0.08	0.11	2.22					1.27	30.00	2.66		Pass
HT40	MCS0	2	151	5755	0.19	0.16	2.22					-1.21	30.00	2.66		Pass
HT40	MCS0	2	159	5795	0.19	0.16	2.22					-1.05	30.00	2.66		Pass
VHT80	MCS0	2	155	5775	0.33	0.33	2.22					-5.99	30.00	2.66		Pass



Appendix B. Radiated Spurious Emission

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5632.2	53.92	-14.28	68.2	40.31	34.48	12.23	33.1	100	175	P	H
		5696.6	56.64	-46.05	102.69	42.89	34.48	12.37	33.1	100	175	P	H
		5717	68.29	-41.67	109.96	54.41	34.47	12.51	33.1	100	175	P	H
		5722.4	71.26	-45.01	116.27	57.39	34.46	12.51	33.1	100	175	P	H
	*	5745	103.49	-	-	89.49	34.45	12.65	33.1	100	175	P	H
	*	5745	95.59	-	-	81.59	34.45	12.65	33.1	100	175	A	H
		5608.2	53.23	-14.97	68.2	39.78	34.46	12.09	33.1	100	345	P	V
		5693.2	57.79	-42.4	100.19	44.04	34.48	12.37	33.1	100	345	P	V
		5718	69.32	-40.92	110.24	55.45	34.46	12.51	33.1	100	345	P	V
		5723.2	73.58	-44.52	118.1	59.71	34.46	12.51	33.1	100	345	P	V
	*	5745	103.46	-	-	89.46	34.45	12.65	33.1	100	345	P	V
	*	5745	96.68	-	-	82.68	34.45	12.65	33.1	100	345	A	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5628.6	53.08	-15.12	68.2	39.47	34.48	12.23	33.1	229	108	P	H
		5671	52.92	-30.86	83.78	39.17	34.48	12.37	33.1	229	108	P	H
		5718.6	55.32	-55.09	110.41	41.45	34.46	12.51	33.1	229	108	P	H
		5724.4	53.1	-67.73	120.83	39.23	34.46	12.51	33.1	229	108	P	H
	*	5785	106.91	-	-	92.78	34.44	12.79	33.1	229	108	P	H
	*	5785	99.34	-	-	85.21	34.44	12.79	33.1	229	108	A	H
		5854	52.62	-60.46	113.08	38.44	34.4	12.88	33.1	229	108	P	H
		5870.8	53.97	-52.4	106.37	39.69	34.41	12.97	33.1	229	108	P	H
		5877.6	53.74	-49.53	103.27	39.46	34.41	12.97	33.1	229	108	P	H
		5930.6	53.99	-14.21	68.2	39.59	34.45	13.05	33.1	229	108	P	H
		5641.6	53.52	-14.68	68.2	39.89	34.5	12.23	33.1	286	346	P	V
		5682.2	54.18	-37.89	92.07	40.43	34.48	12.37	33.1	286	346	P	V
		5718.6	53.56	-56.85	110.41	39.69	34.46	12.51	33.1	286	346	P	V
		5720.8	52.83	-59.79	112.62	38.96	34.46	12.51	33.1	286	346	P	V
	*	5785	102.42	-	-	88.29	34.44	12.79	33.1	286	346	P	V
	*	5785	94.56	-	-	80.43	34.44	12.79	33.1	286	346	A	V
		5852.6	52.55	-63.72	116.27	38.36	34.41	12.88	33.1	286	346	P	V
		5855.4	52.54	-58.15	110.69	38.36	34.4	12.88	33.1	286	346	P	V
		5876.6	53.48	-50.53	104.01	39.2	34.41	12.97	33.1	286	346	P	V
		5943.8	54.94	-13.26	68.2	40.44	34.46	13.14	33.1	286	346	P	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	107.48	-	-	93.28	34.42	12.88	33.1	249	112	P	H
	*	5825	98.97	-	-	84.77	34.42	12.88	33.1	249	112	A	H
		5852	61.36	-56.28	117.64	47.17	34.41	12.88	33.1	249	112	P	H
		5856.2	57.88	-52.58	110.46	43.61	34.4	12.97	33.1	249	112	P	H
		5875.6	54.49	-50.26	104.75	40.21	34.41	12.97	33.1	249	112	P	H
		5936.8	54.1	-14.1	68.2	39.61	34.45	13.14	33.1	249	112	P	H
	*	5825	102.56	-	-	88.36	34.42	12.88	33.1	280	347	P	V
	*	5825	94.92	-	-	80.72	34.42	12.88	33.1	280	347	A	V
		5850	57.21	-64.99	122.2	43.02	34.41	12.88	33.1	280	347	P	V
		5871	54.26	-52.06	106.32	39.98	34.41	12.97	33.1	280	347	P	V
		5907	54.56	-26.92	81.48	40.17	34.44	13.05	33.1	280	347	P	V
		5941	53.37	-14.83	68.2	38.87	34.46	13.14	33.1	280	347	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	46.21	-27.79	74	49	37.69	14.88	55.36	160	360	P	H
		17235	50.2	-18	68.2	44.76	43.89	18.04	56.49	170	360	P	H
		11490	46.29	-27.71	74	49.08	37.69	14.88	55.36	160	360	P	V
		17235	50.69	-17.51	68.2	45.25	43.89	18.04	56.49	170	360	P	V
802.11a CH 157 5785MHz		11570	46.29	-27.71	74	48.82	37.81	14.9	55.24	175	198	P	H
		17355	50.07	-18.13	68.2	44.94	43.53	18.18	56.58	189	185	P	H
		11570	46.84	-27.16	74	49.37	37.81	14.9	55.24	175	198	P	V
		17355	50.84	-17.36	68.2	45.71	43.53	18.18	56.58	189	185	P	V
802.11a CH 165 5825MHz		11650	46.76	-27.24	74	49.05	37.92	14.92	55.13	156	347	P	H
		17475	50.81	-17.39	68.2	46	43.18	18.31	56.68	150	360	P	H
		11650	47.38	-26.62	74	49.67	37.92	14.92	55.13	156	347	P	V
		17475	50.32	-17.88	68.2	45.51	43.18	18.31	56.68	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5613.4	52.42	-15.78	68.2	38.97	34.46	12.09	33.1	247	126	P	H
		5699.4	52.68	-52.08	104.76	38.93	34.48	12.37	33.1	247	126	P	H
		5720	55.23	-55.57	110.8	41.36	34.46	12.51	33.1	247	126	P	H
		5723.6	59.14	-59.87	119.01	45.27	34.46	12.51	33.1	247	126	P	H
	*	5745	101.79	-	-	87.79	34.45	12.65	33.1	247	126	P	H
	*	5745	94.13	-	-	80.13	34.45	12.65	33.1	247	126	A	H
		5636	52.18	-16.02	68.2	38.55	34.5	12.23	33.1	271	345	P	V
		5698.8	52.54	-51.78	104.32	38.79	34.48	12.37	33.1	271	345	P	V
		5719.6	54.59	-56.1	110.69	40.72	34.46	12.51	33.1	271	345	P	V
		5724.8	56.49	-65.25	121.74	42.62	34.46	12.51	33.1	271	345	P	V
	*	5745	99.2	-	-	85.2	34.45	12.65	33.1	271	345	P	V
	*	5745	94.1	-	-	80.1	34.45	12.65	33.1	271	345	A	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5647.6	51.93	-16.27	68.2	38.3	34.5	12.23	33.1	219	142	P	H
		5664.2	52.24	-26.5	78.74	38.48	34.49	12.37	33.1	219	142	P	H
		5701.4	52.26	-53.33	105.59	38.38	34.47	12.51	33.1	219	142	P	H
		5725	52.21	-69.99	122.2	38.34	34.46	12.51	33.1	219	142	P	H
	*	5785	99.36	-	-	85.23	34.44	12.79	33.1	219	142	P	H
	*	5785	91.56	-	-	77.43	34.44	12.79	33.1	219	142	A	H
		5851.2	51.79	-67.67	119.46	37.6	34.41	12.88	33.1	219	142	P	H
		5868	52.48	-54.68	107.16	38.21	34.4	12.97	33.1	219	142	P	H
		5922	52.14	-18.27	70.41	37.74	34.45	13.05	33.1	219	142	P	H
		5932.8	52.78	-15.42	68.2	38.38	34.45	13.05	33.1	219	142	P	H
		5644.4	52.19	-16.01	68.2	38.56	34.5	12.23	33.1	270	348	P	V
		5656.8	53.17	-20.08	73.25	39.55	34.49	12.23	33.1	270	348	P	V
		5705.6	51.63	-55.14	106.77	37.75	34.47	12.51	33.1	270	348	P	V
		5724.4	50.98	-69.85	120.83	37.11	34.46	12.51	33.1	270	348	P	V
	*	5785	98.55	-	-	84.42	34.44	12.79	33.1	270	348	P	V
	*	5785	90.88	-	-	76.75	34.44	12.79	33.1	270	348	A	V
		5854.4	51.05	-61.12	112.17	36.87	34.4	12.88	33.1	270	348	P	V
		5857	51.65	-58.59	110.24	37.38	34.4	12.97	33.1	270	348	P	V
		5912.8	52	-25.2	77.2	37.61	34.44	13.05	33.1	270	348	P	V
		5940.2	52.06	-16.14	68.2	37.56	34.46	13.14	33.1	270	348	P	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz	*	5825	100.03	-	-	85.83	34.42	12.88	33.1	216	114	P	H
	*	5825	92.33	-	-	78.13	34.42	12.88	33.1	216	114	A	H
		5854	52.33	-60.75	113.08	38.15	34.4	12.88	33.1	216	114	P	H
		5859	54.38	-55.3	109.68	40.11	34.4	12.97	33.1	216	114	P	H
		5912	52.8	-24.99	77.79	38.41	34.44	13.05	33.1	216	114	P	H
		5943.4	53.21	-14.99	68.2	38.71	34.46	13.14	33.1	216	114	P	H
	*	5825	99.48	-	-	85.28	34.42	12.88	33.1	241	346	P	V
	*	5825	91.75	-	-	77.55	34.42	12.88	33.1	241	346	A	V
		5851.2	53.26	-66.2	119.46	39.07	34.41	12.88	33.1	241	346	P	V
		5855.2	53.64	-57.1	110.74	39.46	34.4	12.88	33.1	241	346	P	V
		5923.8	51.72	-17.36	69.08	37.32	34.45	13.05	33.1	241	346	P	V
		5948.2	51.51	-16.69	68.2	37.01	34.46	13.14	33.1	241	346	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	46.96	-27.04	74	49.75	37.69	14.88	55.36	160	360	P	H
		17235	50.34	-17.86	68.2	44.9	43.89	18.04	56.49	170	360	P	H
		11490	46.55	-27.45	74	49.34	37.69	14.88	55.36	160	360	P	V
		17235	50.47	-17.73	68.2	45.03	43.89	18.04	56.49	170	360	P	V
802.11n HT20 CH 157 5785MHz		11570	46.01	-27.99	74	48.54	37.81	14.9	55.24	175	198	P	H
		17355	50.11	-18.09	68.2	44.98	43.53	18.18	56.58	189	185	P	H
		11570	46.02	-27.98	74	48.55	37.81	14.9	55.24	175	198	P	V
		17355	50.9	-17.3	68.2	45.77	43.53	18.18	56.58	189	185	P	V
802.11n HT20 CH 165 5825MHz		11650	47.57	-26.43	74	49.86	37.92	14.92	55.13	156	347	P	H
		17475	50.69	-17.51	68.2	45.88	43.18	18.31	56.68	150	360	P	H
		11650	46.87	-27.13	74	49.16	37.92	14.92	55.13	156	347	P	V
		17475	50.17	-18.03	68.2	45.36	43.18	18.31	56.68	150	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5633.6	51.57	-16.63	68.2	37.94	34.5	12.23	33.1	229	104	P	H
		5698.6	56.51	-47.66	104.17	42.76	34.48	12.37	33.1	229	104	P	H
		5719	67.39	-43.13	110.52	53.52	34.46	12.51	33.1	229	104	P	H
		5724.4	69.45	-51.38	120.83	55.58	34.46	12.51	33.1	229	104	P	H
	*	5755	97.73	-	-	83.73	34.45	12.65	33.1	229	104	P	H
	*	5755	90.86	-	-	76.86	34.45	12.65	33.1	229	104	A	H
		5850.4	52.58	-68.71	121.29	38.39	34.41	12.88	33.1	229	104	P	H
		5864.2	52.23	-55.99	108.22	37.96	34.4	12.97	33.1	229	104	P	H
		5901.6	52.01	-33.47	85.48	37.64	34.42	13.05	33.1	229	104	P	H
		5936	52.56	-15.64	68.2	38.07	34.45	13.14	33.1	229	104	P	H
		5633.2	51.4	-16.8	68.2	37.77	34.5	12.23	33.1	128	109	P	V
		5700	54.26	-50.94	105.2	40.37	34.48	12.51	33.1	128	109	P	V
		5716.2	60.87	-48.87	109.74	46.99	34.47	12.51	33.1	128	109	P	V
		5720.8	61.46	-51.16	112.62	47.59	34.46	12.51	33.1	128	109	P	V
	*	5755	91.56	-	-	77.56	34.45	12.65	33.1	128	109	P	V
	*	5755	84.56	-	-	70.56	34.45	12.65	33.1	128	109	A	V
		5851	50.68	-69.24	119.92	36.49	34.41	12.88	33.1	128	109	P	V
		5871.4	51.24	-54.97	106.21	36.96	34.41	12.97	33.1	128	109	P	V
		5899.8	52.63	-34.18	86.81	38.26	34.42	13.05	33.1	128	109	P	V
		5938.4	52.21	-15.99	68.2	37.72	34.45	13.14	33.1	128	109	P	V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5639.4	50.86	-17.34	68.2	37.23	34.5	12.23	33.1	236	105	P	H
		5663.2	52.73	-25.27	78	38.97	34.49	12.37	33.1	236	105	P	H
		5713	52.85	-55.99	108.84	38.97	34.47	12.51	33.1	236	105	P	H
		5720.8	54.75	-57.87	112.62	40.88	34.46	12.51	33.1	236	105	P	H
	*	5795	97.31	-	-	83.19	34.43	12.79	33.1	236	105	P	H
	*	5795	90.33	-	-	76.21	34.43	12.79	33.1	236	105	A	H
		5850.8	53.01	-67.37	120.38	38.82	34.41	12.88	33.1	236	105	P	H
		5872.8	55.67	-50.15	105.82	41.39	34.41	12.97	33.1	236	105	P	H
		5887.6	53.95	-41.9	95.85	39.66	34.42	12.97	33.1	236	105	P	H
		5926.4	53.44	-14.76	68.2	39.04	34.45	13.05	33.1	236	105	P	H
		5634	50.96	-17.24	68.2	37.33	34.5	12.23	33.1	114	109	P	V
		5692.2	51.39	-48.06	99.45	37.64	34.48	12.37	33.1	114	109	P	V
		5704	51.68	-54.64	106.32	37.8	34.47	12.51	33.1	114	109	P	V
		5724.6	51.12	-70.17	121.29	37.25	34.46	12.51	33.1	114	109	P	V
	*	5795	92.33	-	-	78.21	34.43	12.79	33.1	114	109	P	V
	*	5795	85.46	-	-	71.34	34.43	12.79	33.1	114	109	A	V
		5854.4	51.31	-60.86	112.17	37.13	34.4	12.88	33.1	114	109	P	V
		5870.8	52	-54.37	106.37	37.72	34.41	12.97	33.1	114	109	P	V
		5908.2	51.8	-28.8	80.6	37.41	34.44	13.05	33.1	114	109	P	V
		5934.8	51.87	-16.33	68.2	37.38	34.45	13.14	33.1	114	109	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	45.78	-28.22	74	48.54	37.7	14.88	55.34	160	360	P	H
		17265	50.86	-17.34	68.2	45.5	43.79	18.09	56.52	170	360	P	H
		11510	46.47	-27.53	74	49.23	37.7	14.88	55.34	160	360	P	V
		17265	50.27	-17.93	68.2	44.91	43.79	18.09	56.52	170	360	P	V
802.11n HT40 CH 159 5795MHz		11590	46.2	-27.8	74	48.66	37.84	14.91	55.21	170	300	P	H
		17385	50.95	-17.25	68.2	45.91	43.43	18.22	56.61	150	200	P	H
		11590	46.5	-27.5	74	48.96	37.84	14.91	55.21	170	300	P	V
		17385	50.54	-17.66	68.2	45.5	43.43	18.22	56.61	150	200	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5644.6	53.28	-14.92	68.2	39.65	34.5	12.23	33.1	273	114	P	H
		5692.4	57.73	-41.87	99.6	43.98	34.48	12.37	33.1	273	114	P	H
		5711.4	58.26	-50.13	108.39	44.38	34.47	12.51	33.1	273	114	P	H
		5722.2	57.8	-58.02	115.82	43.93	34.46	12.51	33.1	273	114	P	H
	*	5775	93.49	-	-	79.5	34.44	12.65	33.1	273	114	P	H
	*	5775	84.36	-	-	70.37	34.44	12.65	33.1	273	114	A	H
		5853.8	57.65	-55.89	113.54	43.47	34.4	12.88	33.1	273	114	P	H
		5866.8	57.54	-49.95	107.49	43.27	34.4	12.97	33.1	273	114	P	H
		5876.6	54.75	-49.26	104.01	40.47	34.41	12.97	33.1	273	114	P	H
		5946.2	52.23	-15.97	68.2	37.73	34.46	13.14	33.1	273	114	P	H
		5649.6	51.65	-16.55	68.2	38.03	34.49	12.23	33.1	100	32	P	V
		5681.6	54.75	-36.87	91.62	41	34.48	12.37	33.1	100	32	P	V
		5714.4	54.56	-54.67	109.23	40.68	34.47	12.51	33.1	100	32	P	V
		5722.8	54.64	-62.54	117.18	40.77	34.46	12.51	33.1	100	32	P	V
	*	5775	90.14	-	-	76.15	34.44	12.65	33.1	100	32	P	V
	*	5775	81.53	-	-	67.54	34.44	12.65	33.1	100	32	A	V
		5851.8	51.78	-66.32	118.1	37.59	34.41	12.88	33.1	100	32	P	V
		5859.6	52.56	-56.95	109.51	38.29	34.4	12.97	33.1	100	32	P	V
		5916	52.23	-22.61	74.84	37.84	34.44	13.05	33.1	100	32	P	V
		5942.4	52.27	-15.93	68.2	37.77	34.46	13.14	33.1	100	32	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac		11550	47.46	-26.54	74	50.04	37.78	14.9	55.26	160	360	P	H
VHT80		17325	50.21	-17.99	68.2	44.96	43.63	18.18	56.56	170	360	P	H
CH 155		11550	47.85	-26.15	74	50.43	37.78	14.9	55.26	160	360	P	V
5775MHz		17325	50.4	-17.8	68.2	45.15	43.63	18.18	56.56	170	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11a LF		31.94	26.96	-13.04	40	31.15	27.14	0.27	31.6			P	H
		85.29	30.7	-9.3	40	46.78	14.7	0.72	31.5	100	0	P	H
		156.1	31.93	-11.57	43.5	43.92	18.04	1.35	31.38			P	H
		266.68	31.75	-14.25	46	40.74	20.13	1.92	31.04			P	H
		653.71	32.17	-13.83	46	32.79	27.42	3.16	31.2			P	H
		988.36	34.68	-19.32	54	31.43	30.55	4.15	31.45			P	H
		32.91	33.7	-6.3	40	38.16	26.86	0.28	31.6			P	V
		84.32	36.3	-3.7	40	52.08	15	0.72	31.5	100	0	P	V
		156.1	28.74	-14.76	43.5	40.73	18.04	1.35	31.38			P	V
		450.01	28.92	-17.08	46	30.75	26.7	2.57	31.1			P	V
		595.51	29.09	-16.91	46	30.61	26.69	2.99	31.2			P	V
		999.03	33.78	-20.22	54	30.29	30.78	4.2	31.49			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.


Appendix C. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
1+2	802.11a	99.30	-	-	10Hz
1+2	802.11n HT20	98.12	-	-	10Hz
1+2	802.11n HT40	96.36	0.499	2.004	3KHz
1+2	802.11ac VHT80	92.67	0.257	3.891	10KHZ


802.11a



802.11n HT20



802.11n HT40



802.11ac VHT80

